

---

## FCC §2.1093 - RF EXPOSURE INFORMATION

---

### Applicable Standard

According to KDB 447498 D01 General RF Exposure Guidance v06, clause 4.3. General SAR test exclusion guidance:

- c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):
- 1) For test separation distances  $> 50$  mm and  $< 200$  mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$
  - 2) For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$
  - 3) SAR measurement procedures are not established below 100 MHz.

### Test Result

$$P_{th} = [474 * (1 + \log(100/f_{(MHz)}))] / 2 = 443 \text{mW}.$$

$$E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] + 95.2$$

$$E[\text{dB}\mu\text{V}/\text{m}] = 70.56 \text{ dB}\mu\text{V}/\text{m}@3\text{m},$$

$$\text{EIRP} = 70.56 \text{ dB}\mu\text{V}/\text{m} - 95.2 = -24.64 \text{dBm} = 0.0034 \text{mW} < 443 \text{mW}$$

So the NFC SAR evaluation can be compliance.