

FCC Part 15C Measurement and Test Report

For

Shenzhen Inrico Electronics Co.,LTD

3/F, Building NO.118, High Tech Industrial Park,72 Guowei Road, Luohu

District, Shenzhen, China

FCC ID: 2AIV6-T522A

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>Intelligent Two Way Radio</u>
Tested Model:	<u>T522A</u>
Report No.:	<u>WTX19X03011771W-5</u>
Sample Receipt Date:	<u>2019-03-05</u>
Tested Date:	<u>2019-03-05 to 2019-04-23</u>
Issued Date:	<u>2019-04-24</u>
Tested By:	<u>Jason Su / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Jason Su
Silin Chen
Jandy So

Shenzhen SEM Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. POWER SPECTRAL DENSITY.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	10
6. DTS BANDWIDTH.....	12
6.1 STANDARD APPLICABLE.....	12
6.2 TEST PROCEDURE.....	12
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	12
7. RF OUTPUT POWER.....	14
7.1 STANDARD APPLICABLE.....	14
7.2 TEST PROCEDURE.....	14
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	14
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	16
8.1 STANDARD APPLICABLE.....	16
8.2 TEST PROCEDURE.....	16
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
9. OUT OF BAND EMISSIONS.....	25
9.1 STANDARD APPLICABLE.....	25
9.2 TEST PROCEDURE.....	25
9.3 SUMMARY OF TEST RESULTS/PLOTS.....	26
10. CONDUCTED EMISSIONS.....	32
10.1 TEST PROCEDURE.....	32
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	32
10.3 TEST RECEIVER SETUP.....	32
10.4 SUMMARY OF TEST RESULTS/PLOTS.....	32

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Inrico Electronics Co.,LTD
Address of applicant: 3/F, Building NO.118, High Tech Industrial Park,72 Guowei Road, Luohu District, Shenzhen, China

Manufacturer: Shenzhen Inrico Electronics Co.,LTD
Address of manufacturer: 3/F, Building NO.118, High Tech Industrial Park,72 Guowei Road, Luohu District, Shenzhen, China

General Description of EUT	
Product Name:	Intelligent Two Way Radio
Brand Name:	Inrico
Model No.:	T522A
Adding Model(s):	/
Rated Voltage:	DC 3.7V
Battery:	4000mAh
Power Adapter:	Model: HJ-0501000E1-US Input: AC100-240V 50/60Hz 0.2A; Output:DC5V 1000mA
Software Version:	011019 release-keys
Hardware Version:	TVH30_MB_V2.0_20180704
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V4.0 (BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	5.711dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	1.92dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance For Compliance Measurements On Digital Transmission System, Frequency Hopping Spread Spectrum System, And Hybrid System Devices Operating Under Section 15.247 Of The Fcc Rules

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low	2402MHz
TM2	Middle	2440MHz
TM3	High	2480MHz

Test Conditions	
Temperature:	22~25 °C
Relative humidity	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	0.9	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2019-03-18	2020-03-17
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2019-03-18	2020-03-17
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2019-03-18	2020-03-17
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2019-03-18	2020-03-17
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2019-03-18	2020-03-17
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	DTS Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an Integral antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.2, the test method of power spectral density as below:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Summary of Test Results/Plots

Test Mode	Test Channel	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	Low	-9.769	8
	Middle	-8.885	8
	High	-9.283	8

Please refer to the following test plots:

<p style="text-align: center;">Low</p>	 <p>Agilent R T Peak Search Ref 15 dBm Atten 25 dB Mkr1 2.401902 GHz -9.769 dBm #Peak Log 10 dB/ Offst 1 dB M1 S2 S3 FC AA Marker 2.401902000 GHz -9.769 dBm Center 2.402 GHz Span 2 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 228.7 ms (1001 pts) More 1 of 2</p>
<p style="text-align: center;">Middle</p>	 <p>Agilent R T Peak Search Ref 15 dBm Atten 25 dB Mkr1 2.439902 GHz -8.885 dBm #Peak Log 10 dB/ Offst 1 dB M1 S2 S3 FC AA Marker 2.439902000 GHz -8.885 dBm Center 2.44 GHz Span 2 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 228.7 ms (1001 pts) More 1 of 2</p>
<p style="text-align: center;">High</p>	 <p>Agilent R T Peak Search Ref 15 dBm Atten 25 dB Mkr1 2.479902 GHz -9.283 dBm #Peak Log 10 dB/ Offst 1 dB M1 S2 S3 FC AA Marker 2.479902000 GHz -9.283 dBm Center 2.48 GHz Span 2 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 228.7 ms (1001 pts) More 1 of 2</p>

6. DTS Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure




According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Summary of Test Results/Plots

Test Mode	Test Channel	6 dB Bandwidth kHz	Limit kHz
GFSK(BLE)	Low	727.289	≥ 500
	Middle	724.285	≥ 500
	High	717.459	≥ 500

Please refer to the following test plots:

<p style="text-align: center;">Low</p>	 <p>Agilent R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Center 2.40200000 GHz</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.402 GHz Span 3 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 % 1.0501 MHz x dB -6.00 dB</p> <p>Transmit Freq Error 3.427 kHz x dB Bandwidth 727.289 kHz</p> <p>Freq/Channel Center Freq 2.40200000 GHz Start Freq 2.40050000 GHz Stop Freq 2.40350000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>
<p style="text-align: center;">Middle</p>	 <p>Agilent R T</p> <p>Ch Freq 2.44 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Center 2.44 GHz</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.44 GHz Span 3 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 % 1.0510 MHz x dB -6.00 dB</p> <p>Transmit Freq Error 751.913 Hz x dB Bandwidth 724.285 kHz</p> <p>Freq/Channel Center Freq 2.44000000 GHz Start Freq 2.43850000 GHz Stop Freq 2.44150000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>
<p style="text-align: center;">High</p>	 <p>Agilent R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Center 2.48000000 GHz</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.48 GHz Span 3 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 10 ms (1001 pts)</p> <p>Occupied Bandwidth Occ BW % Pwr 99.00 % 1.0472 MHz x dB -6.00 dB</p> <p>Transmit Freq Error 1.564 kHz x dB Bandwidth 717.459 kHz</p> <p>Freq/Channel Center Freq 2.48000000 GHz Start Freq 2.47850000 GHz Stop Freq 2.48150000 GHz CF Step 300.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>

7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.




7.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.1.1 and ANSI C63.10-2013 Subclause 11.9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

7.3 Summary of Test Results/Plots

Test Mode	Test Channel	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	Low	5.028	3.183	1000
	Middle	5.711	3.725	1000
	High	5.394	3.463	1000

<p>Low</p>	 <p>Agilent R T Peak Search Ref 15 dBm Atten 25 dB Mkr1 2.402180 GHz 5.028 dBm #Peak Log 10 dB/Offst 1 dB Marker 2.402180000 GHz 5.028 dBm Center 2.402 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 10 ms (1001 pts)</p>
<p>Middle</p>	 <p>Agilent R T Peak Search Ref 15 dBm Atten 25 dB Mkr1 2.440175 GHz 5.711 dBm #Peak Log 10 dB/Offst 1 dB Marker 2.440175000 GHz 5.711 dBm Center 2.44 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 10 ms (1001 pts)</p>
<p>High</p>	 <p>Agilent R T Freq/Channel Ref 15 dBm Atten 25 dB Mkr1 2.480175 GHz 5.394 dBm #Peak Log 10 dB/Offst 1 dB Center 2.480000000 GHz Center 2.48 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 10 ms (1001 pts)</p> <p>Center Freq 2.48000000 GHz Start Freq 2.47750000 GHz Stop Freq 2.48250000 GHz CF Step 500.000000 kHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin</p>

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of $-6\text{dB}\mu\text{V}$ means the emission is $6\text{dB}\mu\text{V}$ below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.5860	27.96	-11.60	16.36	40.00	-23.64	122	100	peak
2	108.2667	27.45	-13.70	13.75	43.50	-29.75	56	100	peak
3	273.2341	26.48	-9.03	17.45	46.00	-28.55	126	100	peak
4	701.7610	27.59	-1.77	25.82	46.00	-20.18	79	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	90.5374	27.78	-13.51	14.27	43.50	-29.23	243	100	peak
2	105.6415	26.33	-13.44	12.89	43.50	-30.61	135	100	peak
3	375.9385	27.04	-7.11	19.93	46.00	-26.07	79	100	peak
4	658.8362	27.74	-2.60	25.14	46.00	-20.86	249	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.3005	26.54	-11.59	14.95	40.00	-25.05	97	100	peak
2	90.2205	26.66	-13.44	13.22	43.50	-30.28	119	100	peak
3	243.3772	26.13	-10.09	16.04	46.00	-29.96	98	100	peak
4	441.7426	27.45	-6.11	21.34	46.00	-24.66	112	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.7600	27.79	-11.69	16.10	40.00	-23.90	161	100	peak
2	90.5374	29.10	-13.51	15.59	43.50	-27.91	124	100	peak
3	128.1130	28.00	-16.78	11.22	43.50	-32.28	147	100	peak
4	274.1939	26.91	-9.00	17.91	46.00	-28.09	56	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.0566	27.71	-11.60	16.11	40.00	-23.89	297	100	peak
2	92.7872	27.14	-13.96	13.18	43.50	-30.32	113	100	peak
3	203.5228	27.46	-13.10	14.36	43.50	-29.14	76	100	peak
4	437.1199	27.94	-6.08	21.86	46.00	-24.14	193	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	90.5374	27.96	-13.51	14.45	43.50	-29.05	351	100	peak
2	291.0360	28.09	-8.44	19.65	46.00	-26.35	90	100	peak
3	654.2318	28.79	-2.51	26.28	46.00	-19.72	73	100	peak
4	827.4934	30.39	-0.29	30.10	46.00	-15.90	92	100	peak

➤ Spurious Emissions Below 1GHz

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804	58.37	-3.59	54.78	74	-19.22	H	PK
4804	40.51	-3.59	36.92	54	-17.08	H	AV
7206	59.58	-0.52	59.06	74	-14.94	H	PK
7206	38.16	-0.52	37.64	54	-16.36	H	AV
4804	61.21	-3.59	57.62	74	-16.38	V	PK
4804	40.36	-3.59	36.77	54	-17.23	V	AV
7206	58.64	-0.52	58.12	74	-15.88	V	PK
7206	41.79	-0.52	41.27	54	-12.73	V	AV
Middle Channel-2440MHz							
4880	60.37	-3.49	56.88	74	-17.12	H	PK
4880	40.22	-3.49	36.73	54	-17.27	H	AV
7320	60.72	-0.47	60.25	74	-13.75	H	PK
7320	41.38	-0.47	40.91	54	-13.09	H	AV
4880	60.84	-3.49	57.35	74	-16.65	V	PK
4880	38.29	-3.49	34.8	54	-19.2	V	AV
7320	60.46	-0.47	59.99	74	-14.01	V	PK
7320	39.8	-0.47	39.33	54	-14.67	V	AV
High Channel-2480MHz							
4960	60.22	-3.41	56.81	74	-17.19	H	PK
4960	41.28	-3.41	37.87	54	-16.13	H	AV
7440	59.42	-0.42	59	74	-15	H	PK
7440	38.11	-0.42	37.69	54	-16.31	H	AV
4960	60.55	-3.41	57.14	74	-16.86	V	PK
4960	41.2	-3.41	37.79	54	-16.21	V	AV
7440	59.24	-0.42	58.82	74	-15.18	V	PK
7440	40.55	-0.42	40.13	54	-13.87	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9/
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Summary of Test Results/Plots


➤ Radiated test

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.97	-7.78	34.19	54.00	-19.81	Average Detector
	2310.000	52.27	-7.78	44.49	74.00	-29.51	Peak Detector
2	2390.000	42.05	-7.32	34.73	54.00	-19.27	Average Detector
	2390.000	53.20	-7.32	45.88	74.00	-28.12	Peak Detector
3	2401.494	107.72	-7.25	100.47	/	/	Average Detector
	2401.738	112.78	-7.25	105.53	/	/	Peak Detector



Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------





No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.955	99.56	-6.79	92.77	/	/	Average Detector
	2479.681	107.20	-6.79	100.41	/	/	Peak Detector
2	2483.500	58.51	-6.77	51.74	54.00	-2.26	Average Detector
	2483.500	68.30	-6.77	61.53	74.00	-12.47	Peak Detector
3	2500.000	40.86	-6.67	34.19	54.00	-19.81	Average Detector
	2500.000	52.10	-6.67	45.43	74.00	-28.57	Peak Detector

➤ Conducted test



Low



Middle



High




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
 Stop Frequency 30 MHz
 Sweep Speed Auto
 IF Bandwidth..... 10 kHz
 Quasi-Peak Adapter Bandwidth 9 kHz
 Quasi-Peak Adapter Mode Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2060	40.18	10.12	50.30	63.36	-13.06	QP
2	0.2100	25.84	10.13	35.97	53.20	-17.23	AVG
3	1.1100	35.20	10.51	45.71	56.00	-10.29	QP
4	1.1180	23.78	10.51	34.29	46.00	-11.71	AVG
5	4.1540	22.66	10.72	33.38	46.00	-12.62	AVG
6*	4.3780	37.73	10.74	48.47	56.00	-7.53	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	39.97	10.13	50.10	63.20	-13.10	QP
2	0.2100	25.80	10.13	35.93	53.20	-17.27	AVG
3	0.9140	21.88	10.47	32.35	46.00	-13.65	AVG
4	1.1220	29.30	10.51	39.81	56.00	-16.19	QP
5*	4.1540	34.77	10.72	45.49	56.00	-10.51	QP
6	4.1620	21.39	10.72	32.11	46.00	-13.89	AVG

***** END OF REPORT *****