




# TEST REPORT

**Report No.** ..... : **CHTEW20040096** Report Verification: 

**Project No.**..... : **SHT2002002907EW**

**FCC ID**..... : **2AIV9-AP1C**

**Applicant's name**..... : **Beijing Visual World Technology Co.,Ltd.**

Address..... : 501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing

Manufacturer..... : Beijing Visual World Technology Co.,Ltd.

Address..... : 501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing

**Test item description** ..... : **360 Smart Camera Pan-Tilt AI Version**

Trade Mark ..... : +360

Model/Type reference..... : AP1C

Listed Model(s) ..... : AP1L


**Standard** ..... : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**


Date of receipt of test sample..... : Mar.03, 2020


Date of testing..... : Mar.03, 2020- Apr.10, 2020

Date of issue..... : Apr.13, 2020

**Result**..... : **PASS**

Compiled by  
 ( Position+Printed name+Signature): File administrator Echo Wei 

Supervised by  
 (Position+Printed name+Signature): Project Engineer Edward Pan 

Approved by  
 (Position+Printed name+Signature): RF Manager Hans Hu 

**Testing Laboratory Name** ..... : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

## Contents

<b>1.</b>	<b><u>TEST STANDARDS AND REPORT VERSION</u></b>	<b>3</b>
1.1.	Test Standards	3
1.2.	Report version	3
<b>2.</b>	<b><u>TEST DESCRIPTION</u></b>	<b>4</b>
<b>3.</b>	<b><u>SUMMARY</u></b>	<b>5</b>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<b>4.</b>	<b><u>TEST CONFIGURATION</u></b>	<b>7</b>
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Support unit used in test configuration and system	8
4.5.	Testing environmental condition	8
4.6.	Measurement uncertainty	8
4.7.	Equipment Used during the Test	9
<b>5.</b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b>11</b>
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Peak Output Power	17
5.4.	Power Spectral Density	18
5.5.	6dB bandwidth	19
5.6.	99% Occupied Bandwidth	20
5.7.	Duty Cycle	21
5.8.	Conducted Band edge and Spurious Emission	22
5.9.	Radiated Band edge Emission	24
5.10.	Radiated Spurious Emission	29
<b>6.</b>	<b><u>TEST SETUP PHOTOS</u></b>	<b>38</b>
<b>7.</b>	<b><u>EXTERANAL AND INTERNAL PHOTOS</u></b>	<b>39</b>
<b>8.</b>	<b><u>APPENDIX REPORT</u></b>	<b>44</b>

# 1. TEST STANDARDS AND REPORT VERSION

## 1.1. Test Standards

The tests were performed according to following standards:

- [FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

## 1.2. Report version

Revision No.	Date of issue	Description
N/A	2020-04-13	Original

## 2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247(c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Peak Output Power	15.247(b)(3)	PASS
5.4	Power Spectral Density	15.247(e)	PASS
5.5	6dB Bandwidth	15.247(a)(2)	PASS
5.6	99% Occupied Bandwidth	-	PASS <sup>*1</sup>
5.7	Duty cycle	-	PASS <sup>*1</sup>
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.9	Radiated Band Edge Emission	15.205/15.209	PASS
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

- The measurement uncertainty is not included in the test result.
- \*1: No requirement on standard, only report these test data.

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	Beijing Visual World Technology Co.,Ltd.
Address:	501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing
Manufacturer:	Beijing Visual World Technology Co.,Ltd.
Address:	501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing

#### 3.2. Product Description

Name of EUT:	360 Smart Camera Pan-Tilt AI Version
Trade Mark:	+360
Model No.:	AP1C
Listed Model(s):	AP1L
Power supply:	DC 5V from adapter
Adapter Information 1:	Model: A18A-050100U-US2 Input: 100-240Va.c.,50/60Hz MAX 0.2A Output: 5Vd.c.,1.0A
Adapter Information 2:	Model: TEKA006-0501000UK Input: 100-240Va.c.,50/60Hz 0.2A MAX Output: 5Vd.c.,1000mA
Hardware version:	SJ-C399-V1.04
Software version:	D916_A_20190930.7.0.277

#### 3.3. Radio Specification Description

Support type <sup>*2</sup> :	802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 9 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	PIFA
Antenna gain:	2.9dBi

Note:

\*2: only show the RF function associated with this report.

### 3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Qualifications	Type	Accreditation Number
	CNAS	L1225
	A2LA	3902.01
	FCC	762235
	Canada	5377A

## 4. TEST CONFIGURATION

### 4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

802.11b/802.11g/802.11n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
<b>01</b>	<b>2412</b>	<b>03</b>	<b>2422</b>
02	2417	04	2427
· :	· :	· :	· :
<b>06</b>	<b>2437</b>	<b>06</b>	<b>2437</b>
· :	· :	· :	· :
10	2457	08	2447
<b>11</b>	<b>2462</b>	<b>09</b>	<b>2452</b>

### 4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0

### 4.3. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

#### 4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?					
✓ No					
Item	Equipment	Trade Name	Model No.	FCC ID	Power cord
1					
2					

#### 4.5. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

#### 4.6. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.02 dB
Radiated Emission (30MHz~1000MHz)	4.90 dB
Radiated Emissions (1GHz~25GHz)	4.96 dB
Peak Output Power	0.51 dB
Power Spectral Density	0.51 dB
Conducted Spurious Emission	0.51 dB
6dB Bandwidth	70 Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .



## 4.7. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLE X_142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2020/04/05	2023/04/04
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/08/21	2020/08/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX 104	501184/4	2019/05/27	2020/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2018/10/11	2021/10/10
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/10
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2019/10/26	2020/10/25
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2019/10/26	2020/10/25
●	Power Meter	Anritsu	ML249A	N/A	2019/10/26	2020/10/25
○	Radio communication tester	R&S	CMW500	137688-Lv	2019/10/26	2020/10/25

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna Requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### TEST RESULT

**Passed**       **Not Applicable**

The antenna type is a PCB antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



## 5.2. AC Conducted Emission

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST MODE:

Please refer to the clause 4.2


### TEST RESULT

Passed       Not Applicable

**Adapter 1:**

Test Line:

L



**MEASUREMENT RESULT: "GM2003115072\_fin"**

3/11/2020 7:53PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.172500	37.80	10.1	65	27.0	QP	L1	GND
0.582000	47.50	10.1	56	8.5	QP	L1	GND
1.167000	39.80	10.1	56	16.2	QP	L1	GND
4.915500	33.00	10.1	56	23.0	QP	L1	GND
5.986500	33.80	10.2	60	26.2	QP	L1	GND
22.942500	34.50	10.2	60	25.5	QP	L1	GND


**MEASUREMENT RESULT: "GM2003115072\_fin2"**

3/11/2020 7:53PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.235500	28.00	10.1	52	24.3	AV	L1	GND
0.586500	39.20	10.1	46	6.8	AV	L1	GND
1.167000	30.20	10.1	46	15.8	AV	L1	GND
2.850000	27.10	10.1	46	18.9	AV	L1	GND
5.734500	24.60	10.2	50	25.4	AV	L1	GND
22.807500	25.90	10.2	50	24.1	AV	L1	GND

Test Line:

N



**MEASUREMENT RESULT: "GM2003115071\_fin"**

3/11/2020 7:50PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.186000	36.50	10.1	64	27.7	QP	N	GND
0.595500	37.20	10.1	56	18.8	QP	N	GND
1.662000	27.20	10.1	56	28.8	QP	N	GND
3.561000	26.90	10.1	56	29.1	QP	N	GND
5.518500	28.00	10.2	60	32.0	QP	N	GND
22.479000	29.60	10.2	60	30.4	QP	N	GND

**MEASUREMENT RESULT: "GM2003115071\_fin2"**


3/11/2020 7:50PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	22.30	10.1	55	32.8	AV	N	GND
0.586500	30.60	10.1	46	15.4	AV	N	GND
1.099500	22.50	10.1	46	23.5	AV	N	GND
2.566500	15.20	10.1	46	30.8	AV	N	GND
5.455500	19.40	10.2	50	30.6	AV	N	GND
21.867000	21.60	10.2	50	28.4	AV	N	GND

**Adapter 2:**

Test Line:

L



**MEASUREMENT RESULT: "GM2003115098\_fin"**

3/11/2020 10:32PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.163500	40.70	10.1	65	24.6	QP	L1	GND
0.433500	38.60	10.1	57	18.6	QP	L1	GND
0.870000	27.80	10.1	56	28.2	QP	L1	GND
2.323500	22.30	10.1	56	33.7	QP	L1	GND
11.283000	21.00	10.2	60	39.0	QP	L1	GND
15.855000	27.80	10.2	60	32.2	QP	L1	GND


**MEASUREMENT RESULT: "GM2003115098\_fin2"**

3/11/2020 10:32PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	23.70	10.1	55	31.4	AV	L1	GND
0.393000	25.60	10.1	48	22.4	AV	L1	GND
0.424500	22.30	10.1	47	25.1	AV	L1	GND
1.360500	14.40	10.1	46	31.6	AV	L1	GND
2.112000	14.10	10.1	46	31.9	AV	L1	GND
15.864000	16.50	10.2	50	33.5	AV	L1	GND

Test Line:

N



**MEASUREMENT RESULT: "GM2003115099\_fin"**

3/11/2020 10:34PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154500	42.00	10.1	66	23.8	QP	N	GND
0.451500	32.40	10.1	57	24.4	QP	N	GND
0.874500	29.20	10.1	56	26.8	QP	N	GND
2.422500	22.00	10.1	56	34.0	QP	N	GND
5.289000	20.30	10.2	60	39.7	QP	N	GND
15.751500	28.50	10.2	60	31.5	QP	N	GND

**MEASUREMENT RESULT: "GM2003115099\_fin2"**

3/11/2020 10:34PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.402000	18.40	10.1	48	29.4	AV	N	GND
0.424500	28.40	10.1	47	19.0	AV	N	GND
0.897000	17.90	10.1	46	28.1	AV	N	GND
3.070500	11.90	10.1	46	34.1	AV	N	GND
12.025500	10.60	10.2	50	39.4	AV	N	GND
15.675000	15.50	10.2	50	34.5	AV	N	GND




### 5.3. Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

#### TEST MODE:

Please refer to the clause 4.2

#### TEST RESULT

Passed       Not Applicable

#### TEST Data

Please refer to appendix A on the appendix report


## 5.4. Power Spectral Density

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:  
Center frequency=DTS channel center frequency  
Span =1.5 times the DTS bandwidth  
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW  
Sweep time = auto couple  
Detector = peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST MODE:

Please refer to the clause 4.2

### TEST RESULT

Passed       Not Applicable

### TEST Data

Please refer to appendix B on the appendix report


## 5.5. 6dB bandwidth

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
Center Frequency =DTS channel center frequency  
Span=2 x DTS bandwidth  
RBW = 100 kHz, VBW  $\geq$  3 x RBW  
Sweep time= auto couple  
Detector = Peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

### TEST MODE:

Please refer to the clause 4.2

### TEST RESULT

Passed       Not Applicable

### TEST Data


Please refer to appendix C on the appendix report

## 5.6. 99% Occupied Bandwidth

### LIMIT

N/A

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
Center Frequency = channel center frequency  
Span  $\geq 1.5 \times \text{OBW}$   
RBW = 1%~5%OBW  
VBW  $\geq 3 \times \text{RBW}$   
Sweep time = auto couple  
Detector = Peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

### TEST MODE:

Please refer to the clause 4.2

### TEST RESULT

Passed       Not Applicable

### TEST Data


Please refer to appendix D on the appendix report

## 5.7. Duty Cycle

### LIMIT

N/A

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW  $\geq$  RBW  
Sweep=as necessary to capture the entire dwell time,  
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

### TEST MODE:

Please refer to the clause 4.2

### TEST Data


Please refer to appendix E on the appendix report

## 5.8. Conducted Band edge and Spurious Emission

### LIMIT

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure  
Center frequency=DTS channel center frequency  
The span = 1.5 times the DTS bandwidth.  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

3. Emission level measurement  
Set the center frequency and span to encompass frequency range to be measured  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

### TEST MODE:

Please refer to the clause 4.2

**TEST RESULT**

**Passed**       **Not Applicable**

**TEST Data**

Please refer to appendix F on the appendix report


## 5.9. Radiated Band edge Emission

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
  - a) Span shall wide enough to fully capture the emission being measured
  - b) Set RBW=100kHz for <1GHz, VBW=3\*RBW, Sweep time=auto, Detector=peak, Trace=max hold
  - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

  - VBW=10Hz, When duty cycle is no less than 98 percent
  - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

### TEST MODE:

Please refer to the clause 4.2

### TEST RESULT

Passed       Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).



Type	802.11b	Test channel	CH01	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	28.61	17.66	46.27	74.00	27.73	Horizontal	PK
2	2310.000	25.08	17.66	42.74	54.00	11.26	Horizontal	AV
3	2390.000	28.95	17.59	46.54	74.00	27.46	Horizontal	PK
4	2390.000	25.18	17.59	42.77	54.00	11.23	Horizontal	AV

Type	802.11b	Test channel	CH01	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	26.82	17.66	44.48	74.00	29.52	Vertical	PK
2	2310.000	23.20	17.66	40.86	54.00	13.14	Vertical	AV
3	2390.000	27.83	17.59	45.42	74.00	28.58	Vertical	PK
4	2390.000	24.00	17.59	41.59	54.00	12.41	Vertical	AV

Type	802.11b	Test channel	CH11	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	30.50	17.85	48.35	74.00	25.65	Horizontal	PK
2	2483.500	25.22	17.85	43.07	54.00	10.93	Horizontal	AV
3	2500.000	28.52	17.90	46.42	74.00	27.58	Horizontal	PK
4	2500.000	26.01	17.90	43.91	54.00	10.09	Horizontal	AV

Type	802.11b	Test channel	CH11	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	27.15	17.85	45.00	74.00	29.00	Vertical	PK
2	2483.500	23.80	17.85	41.65	54.00	12.35	Vertical	AV
3	2500.000	26.69	17.90	44.59	74.00	29.41	Vertical	PK
4	2500.000	23.70	17.90	41.60	54.00	12.40	Vertical	AV

Type	802.11g	Test channel	CH01	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	30.22	17.66	47.88	74.00	26.12	Horizontal	PK
2	2310.000	26.28	17.66	43.94	54.00	10.06	Horizontal	AV
3	2390.000	33.02	17.59	50.61	74.00	23.39	Horizontal	PK
4	2390.000	27.70	17.59	45.29	54.00	8.71	Horizontal	AV

Type	802.11g	Test channel	CH01	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	27.88	17.66	45.54	74.00	28.46	Vertical	PK
2	2310.000	24.49	17.66	42.15	54.00	11.85	Vertical	AV
3	2390.000	31.04	17.59	48.63	74.00	25.37	Vertical	PK
4	2390.000	26.96	17.59	44.55	54.00	9.45	Vertical	AV

Type	802.11g	Test channel	CH11	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	29.63	17.85	47.48	74.00	26.52	Horizontal	PK
2	2483.500	26.22	17.85	44.07	54.00	9.93	Horizontal	AV
3	2500.000	29.47	17.90	47.37	74.00	26.63	Horizontal	PK
4	2500.000	25.29	17.90	43.19	54.00	10.81	Horizontal	AV

Type	802.11g	Test channel	CH11	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	30.47	17.85	48.32	74.00	25.68	Vertical	PK
2	2483.500	25.52	17.85	43.37	54.00	10.63	Vertical	AV
3	2500.000	27.74	17.90	45.64	74.00	28.36	Vertical	PK
4	2500.000	23.86	17.90	41.76	54.00	12.24	Vertical	AV

Type	802.11n(HT20)	Test channel	CH01	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	29.37	17.66	47.03	74.00	26.97	Horizontal	PK
2	2310.000	25.48	17.66	43.14	54.00	10.86	Horizontal	AV
3	2390.000	32.21	17.59	49.80	74.00	24.20	Horizontal	PK
4	2390.000	26.51	17.59	44.10	54.00	9.90	Horizontal	AV

Type	802.11n(HT20)	Test channel	CH01	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	28.37	17.66	46.03	74.00	27.97	Vertical	PK
2	2310.000	25.31	17.66	42.97	54.00	11.03	Vertical	AV
3	2390.000	38.66	17.59	56.25	74.00	17.75	Vertical	PK
4	2390.000	32.92	17.59	50.51	54.00	3.49	Vertical	AV

Type	802.11n(HT20)	Test channel	CH11	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	31.14	17.85	48.99	74.00	25.01	Horizontal	PK
2	2483.500	28.41	17.85	46.26	54.00	7.74	Horizontal	AV
3	2500.000	28.79	17.90	46.69	74.00	27.31	Horizontal	PK
4	2500.000	26.27	17.90	44.17	54.00	9.83	Horizontal	AV

Type	802.11n(HT20)	Test channel	CH11	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	28.54	17.85	46.39	74.00	27.61	Vertical	PK
2	2483.500	24.28	17.85	42.13	54.00	11.87	Vertical	AV
3	2500.000	27.29	17.90	45.19	74.00	28.81	Vertical	PK
4	2500.000	23.86	17.90	41.76	54.00	12.24	Vertical	AV

Type	802.11n(HT40)	Test channel	CH01	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	29.57	17.66	47.23	74.00	26.77	Horizontal	PK
2	2310.000	24.40	17.66	42.06	54.00	11.94	Horizontal	AV
3	2390.000	32.49	17.59	50.08	74.00	23.92	Horizontal	PK
4	2390.000	27.73	17.59	45.32	54.00	8.68	Horizontal	AV

Type	802.11n(HT40)	Test channel	CH01	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2310.000	26.76	17.66	44.42	74.00	29.58	Vertical	PK
2	2310.000	24.16	17.66	41.82	54.00	12.18	Vertical	AV
3	2390.000	31.68	17.59	49.27	74.00	24.73	Vertical	PK
4	2390.000	27.61	17.59	45.20	54.00	8.80	Vertical	AV

Type	802.11n(HT40)	Test channel	CH11	Polarity	Horizontal			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	32.19	17.85	50.04	74.00	23.96	Horizontal	PK
2	2483.500	27.61	17.85	45.46	54.00	8.54	Horizontal	AV
3	2500.000	29.32	17.90	47.22	74.00	26.78	Horizontal	PK
4	2500.000	25.19	17.90	43.09	54.00	10.91	Horizontal	AV

Type	802.11n(HT40)	Test channel	CH11	Polarity	Vertical			
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	2483.500	34.33	17.85	52.18	74.00	21.82	Vertical	PK
2	2483.500	29.34	17.85	47.19	54.00	6.81	Vertical	AV
3	2500.000	28.74	17.90	46.64	74.00	27.36	Vertical	PK
4	2500.000	26.26	17.90	44.16	54.00	9.84	Vertical	AV

### 5.10. Radiated Spurious Emission

**LIMIT**

**FCC CFR Title 47 Part 15 Subpart C Section 15.209**

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40\*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40\*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

**TEST CONFIGURATION**


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



### **TEST PROCEDURE**

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - a) Span shall wide enough to fully capture the emission being measured;
  - b) Below 1 GHz:
    - RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
    - If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
    - For average measurement:
      - VBW=10Hz, When duty cycle is no less than 98 percent
      - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

### **TEST MODE:**

Please refer to the clause 4.2

### **TEST RESULT**

**Passed**       **Not Applicable**

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

**TEST DATA FOR 9 kHz ~ 30 MHz**

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.


**TEST DATA FOR 30 MHz ~ 1000 MHz**

Have pre-scan all test channel and both adapter, found CH11 of 802.11B which it was worst case, so only show the worst case's data on this report.

**Adapter 1:**

Polarization:

Horizontal




**MEASUREMENT RESULT: "GM2003116109\_red"**

3/11/2020 8:53PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
350.100000	38.20	-4.9	46.0	7.8	QP	100.0	279.00	HORIZONTAL
400.540000	29.50	-3.5	46.0	16.5	QP	100.0	40.00	HORIZONTAL
450.980000	37.80	-2.4	46.0	8.2	QP	100.0	360.00	HORIZONTAL
499.480000	31.20	-1.5	46.0	14.8	QP	100.0	28.00	HORIZONTAL
549.920000	35.80	0.2	46.0	10.2	QP	100.0	268.00	HORIZONTAL
947.620000	36.20	8.1	46.0	9.8	QP	100.0	348.00	HORIZONTAL

Polarization:

Vertical



**MEASUREMENT RESULT: "GM2003116110\_red"**

3/11/2020 8:57PM


Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	36.70	-12.8	40.0	3.3	QP	100.0	119.00	VERTICAL
249.220000	27.80	-8.2	46.0	18.2	QP	100.0	38.00	VERTICAL
350.100000	40.60	-4.9	46.0	5.4	QP	100.0	182.00	VERTICAL
450.980000	36.20	-2.4	46.0	9.8	QP	100.0	245.00	VERTICAL
549.920000	36.00	0.2	46.0	10.0	QP	100.0	221.00	VERTICAL
951.500000	38.00	8.2	46.0	8.0	QP	100.0	182.00	VERTICAL



**Adapter 2:**

Polarization:

Horizontal




**MEASUREMENT RESULT: "GM2003116114\_red"**

3/11/2020 9:23PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
350.100000	38.10	-4.9	46.0	7.9	QP	100.0	301.00	HORIZONTAL
400.540000	30.60	-3.5	46.0	15.4	QP	100.0	0.00	HORIZONTAL
450.980000	40.20	-2.4	46.0	5.8	QP	100.0	7.00	HORIZONTAL
499.480000	32.00	-1.5	46.0	14.0	QP	100.0	34.00	HORIZONTAL
549.920000	35.20	0.2	46.0	10.8	QP	100.0	251.00	HORIZONTAL
949.560000	36.40	8.1	46.0	9.6	QP	100.0	105.00	HORIZONTAL

Polarization:

Vertical



**MEASUREMENT RESULT: "GM2003116113\_red"**

3/11/2020 9:19PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
249.220000	29.10	-8.2	46.0	16.9	QP	100.0	15.00	VERTICAL
350.100000	40.30	-4.9	46.0	5.7	QP	100.0	175.00	VERTICAL
450.980000	35.00	-2.4	46.0	11.0	QP	100.0	201.00	VERTICAL
549.920000	35.40	0.2	46.0	10.6	QP	100.0	90.00	VERTICAL
650.800000	34.10	2.5	46.0	11.9	QP	100.0	201.00	VERTICAL
951.500000	39.00	8.2	46.0	7.0	QP	100.0	175.00	VERTICAL

**TEST DATA FOR 1 GHz ~ 25 GHz**

Type	802.11b	Test channel	CH00					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1246.750	34.23	-5.71	28.52	74.00	45.48	Horizontal	PK
2	4823.156	40.48	7.08	47.56	74.00	26.44	Horizontal	PK
3	7237.781	33.57	15.01	48.58	74.00	25.42	Horizontal	PK
4	9606.875	31.05	17.11	48.16	74.00	25.84	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1218.843	33.67	-5.78	27.89	74.00	46.11	Vertical	PK
2	4823.156	42.34	7.08	49.42	74.00	24.58	Vertical	PK
3	7236.312	35.27	15.01	50.28	74.00	23.72	Vertical	PK
4	9285.218	30.02	17.74	47.76	74.00	26.24	Vertical	PK
Type	802.11b	Test channel	CH07					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1240.875	33.06	-5.72	27.34	74.00	46.66	Horizontal	PK
2	4874.562	38.03	7.15	45.18	74.00	28.82	Horizontal	PK
3	7894.312	31.46	16.25	47.71	74.00	26.29	Horizontal	PK
4	10351.53	30.20	17.49	47.69	74.00	26.31	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1142.468	34.92	-6.44	28.48	74.00	45.52	Vertical	PK
2	4873.093	40.10	7.15	47.25	74.00	26.75	Vertical	PK
3	7311.218	32.61	15.09	47.70	74.00	26.30	Vertical	PK
4	9818.375	30.90	17.24	48.14	74.00	25.86	Vertical	PK
Type	802.11b	Test channel	CH11					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1132.187	34.61	-6.55	28.06	74.00	45.94	Horizontal	PK
2	3184.031	31.95	0.76	32.71	74.00	41.29	Horizontal	PK
3	4924.500	35.65	7.34	42.99	74.00	31.01	Horizontal	PK
4	7453.687	31.65	15.39	47.04	74.00	26.96	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1177.718	33.33	-6.07	27.26	74.00	46.74	Vertical	PK
2	4924.500	37.61	7.34	44.95	74.00	29.05	Vertical	PK
3	7383.187	33.34	15.32	48.66	74.00	25.34	Vertical	PK
4	9351.312	31.45	17.63	49.08	74.00	24.92	Vertical	PK

Type	802.11g	Test channel	CH00					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1217.375	33.90	-5.78	28.12	74.00	45.88	Horizontal	PK
2	4826.093	37.51	7.08	44.59	74.00	29.41	Horizontal	PK
3	7231.906	35.44	15.01	50.45	74.00	23.55	Horizontal	PK
4	9330.750	30.39	17.74	48.13	74.00	25.87	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1198.281	33.89	-5.85	28.04	74.00	45.96	Vertical	PK
2	4827.562	37.62	7.09	44.71	74.00	29.29	Vertical	PK
3	7239.250	35.46	15.01	50.47	74.00	23.53	Vertical	PK
4	9852.156	30.95	17.25	48.20	74.00	25.80	Vertical	PK
Type	802.11g	Test channel	CH07					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	3188.437	32.74	0.78	33.52	74.00	40.48	Horizontal	PK
2	4874.562	36.07	7.15	43.22	74.00	30.78	Horizontal	PK
3	7308.281	32.21	15.08	47.29	74.00	26.71	Horizontal	PK
4	9840.406	30.65	17.25	47.90	74.00	26.10	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1321.656	32.55	-5.57	26.98	74.00	47.02	Vertical	PK
2	4874.562	36.42	7.15	43.57	74.00	30.43	Vertical	PK
3	7314.156	33.84	15.10	48.94	74.00	25.06	Vertical	PK
4	9577.500	30.46	17.30	47.76	74.00	26.24	Vertical	PK
Type	802.11g	Test channel	CH11					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1170.375	34.61	-6.14	28.47	74.00	45.53	Horizontal	PK
2	4924.500	33.03	7.34	40.37	74.00	33.63	Horizontal	PK
3	7387.593	32.35	15.33	47.68	74.00	26.32	Horizontal	PK
4	9474.687	30.67	17.84	48.51	74.00	25.49	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1254.093	33.00	-5.69	27.31	74.00	46.69	Vertical	PK
2	3188.437	32.85	0.78	33.63	74.00	40.37	Vertical	PK
3	4927.437	35.67	7.36	43.03	74.00	30.97	Vertical	PK
4	7389.062	34.39	15.34	49.73	74.00	24.27	Vertical	PK




Type	802.11n(HT20)	Test channel	CH00					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1171.843	33.91	-6.13	27.78	74.00	46.22	Horizontal	PK
2	4823.156	36.35	7.08	43.43	74.00	30.57	Horizontal	PK
3	7230.437	33.20	15.01	48.21	74.00	25.79	Horizontal	PK
4	9241.156	31.74	17.20	48.94	74.00	25.06	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1270.250	33.93	-5.65	28.28	74.00	45.72	Vertical	PK
2	4824.625	38.98	7.08	46.06	74.00	27.94	Vertical	PK
3	7226.031	35.12	15.01	50.13	74.00	23.87	Vertical	PK
4	9502.593	29.93	17.99	47.92	74.00	26.08	Vertical	PK
Type	802.11n(HT20)	Test channel	CH07					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1171.843	33.51	-6.13	27.38	74.00	46.62	Horizontal	PK
2	3142.906	32.35	0.54	32.89	74.00	41.11	Horizontal	PK
3	4873.093	36.24	7.15	43.39	74.00	30.61	Horizontal	PK
4	8008.875	30.29	16.20	46.49	74.00	27.51	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1255.562	33.02	-5.69	27.33	74.00	46.67	Vertical	PK
2	4874.562	37.08	7.15	44.23	74.00	29.77	Vertical	PK
3	7309.750	32.34	15.08	47.42	74.00	26.58	Vertical	PK
4	9324.875	30.78	17.78	48.56	74.00	25.44	Vertical	PK
Type	802.11n(HT20)	Test channel	CH11					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1268.781	33.60	-5.65	27.95	74.00	46.05	Horizontal	PK
2	4920.093	33.66	7.31	40.97	74.00	33.03	Horizontal	PK
3	7384.656	32.67	15.32	47.99	74.00	26.01	Horizontal	PK
4	9213.250	30.94	16.85	47.79	74.00	26.21	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1252.625	33.32	-5.69	27.63	74.00	46.37	Vertical	PK
2	4921.562	35.75	7.32	43.07	74.00	30.93	Vertical	PK
3	7381.718	33.97	15.31	49.28	74.00	24.72	Vertical	PK
4	9280.812	30.25	17.68	47.93	74.00	26.07	Vertical	PK

Type	802.11n(HT40)	Test channel	CH03					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1177.718	34.01	-6.07	27.94	74.00	46.06	Horizontal	PK
2	4845.187	34.66	7.11	41.77	74.00	32.23	Horizontal	PK
3	8058.812	29.79	16.28	46.07	74.00	27.93	Horizontal	PK
4	9502.593	29.83	17.99	47.82	74.00	26.18	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1182.125	33.38	-6.02	27.36	74.00	46.64	Vertical	PK
2	3157.593	33.00	0.62	33.62	74.00	40.38	Vertical	PK
3	4843.718	34.70	7.11	41.81	74.00	32.19	Vertical	PK
4	9601.000	30.84	17.10	47.94	74.00	26.06	Vertical	PK
Type	802.11n(HT40)	Test channel	CH07					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1267.312	32.68	-5.65	27.03	74.00	46.97	Horizontal	PK
2	4870.156	32.28	7.14	39.42	74.00	34.58	Horizontal	PK
3	7327.375	30.39	15.14	45.53	74.00	28.47	Horizontal	PK
4	9273.468	31.14	17.59	48.73	74.00	25.27	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1198.281	33.66	-5.85	27.81	74.00	46.19	Vertical	PK
2	3198.718	34.97	0.83	35.80	74.00	38.20	Vertical	PK
3	4868.687	33.74	7.14	40.88	74.00	33.12	Vertical	PK
4	8055.875	31.55	16.27	47.82	74.00	26.18	Vertical	PK
Type	802.11n(HT40)	Test channel	CH09					
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1188.000	33.90	-5.96	27.94	74.00	46.06	Horizontal	PK
2	4903.937	31.69	7.21	38.90	74.00	35.10	Horizontal	PK
3	7597.625	29.89	15.86	45.75	74.00	28.25	Horizontal	PK
4	9311.656	30.25	17.85	48.10	74.00	25.90	Horizontal	PK
<b>Suspected Data List</b>								
NO.	Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1	1199.750	33.44	-5.83	27.61	74.00	46.39	Vertical	PK
2	4903.937	33.31	7.21	40.52	74.00	33.48	Vertical	PK
3	7337.656	31.80	15.17	46.97	74.00	27.03	Vertical	PK
4	9515.812	30.52	17.87	48.39	74.00	25.61	Vertical	PK





## 6. TEST SETUP PHOTOS



Radiated Emission




## 7. EXTERANAL AND INTERNAL PHOTOS

### External Photos











Adapter 1:





Adapter 2:




**Internal Photos**









## 8. APPENDIX REPORT