




TEST REPORT

Report No.: **CHTEW20040097** Report verification : 

Project No.: **SHT2002002907EW**

FCC ID.....: **2AIV9-AP1C**

Applicant's name.....: **Beijing Visual World Technology Co.,Ltd.**

Address.....: 501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing

Manufacturer.....: Beijing Visual World Technology Co.,Ltd.

Address.....: 501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing

Test item description: **360 Smart Camera Pan-Tilt AI Version**

Trade Mark: +360

Model/Type reference.....: AP1C

Listed Model(s): AP1L

Standard: **47 CFR FCC Part 15 Subpart B**

Date of receipt of test sample.....: Mar.03, 2020

Date of testing.....: Mar.03, 2020- Apr.10, 2020

Date of issue.....: Apr.13, 2020

Result.....: **Pass**

Compiled by
 (position+printed name+signature)...: File administrators Echo Wei

Supervised by
 (position+printed name+signature)...: Project Engineer Edward Pan

Approved by
 (position+printed name+signature)...: RF Manager Hans Hu

Echo Wei

Edward Pan

Hans Hu

Testing Laboratory Name: **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address.....: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely corresponds to the test sample.

Contents

1.	<u>TEST STANDARDS AND REPORT VERSION.....</u>	3
1.1.	Test Standards	3
1.2.	Report version information	3
2.	<u>TEST DESCRIPTION.....</u>	4
3.	<u>SUMMARY.....</u>	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	EUT operation mode	5
3.4.	Configuration of Tested System	5
3.5.	Support unit used in test configuration	5
4.	<u>TEST ENVIRONMENT.....</u>	6
4.1.	Address of the test laboratory	6
4.2.	Test Facility	6
4.3.	Environmental conditions	7
4.4.	Statement of the measurement uncertainty	7
4.5.	Equipments Used during the Test	8
5.	<u>TEST CONDITIONS AND RESULTS.....</u>	9
5.1.	Conducted Emissions Test	9
5.2.	Radiated Emissions Test	14
6.	<u>TEST SETUP PHOTOS OF THE EUT.....</u>	20
7.	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....</u>	21

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[47 CFR FCC Part 15 Subpart B](#) - Unintentional Radiators

[ANSI C63.4: 2014](#) – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2020-04-13	Original

2. TEST DESCRIPTION

Test Item	Section in CFR 47	Result	Test Engineer
Conducted Emissions	15.107(a)	PASS	Jianquan Wu
Radiated Emissions	15.109(a)	PASS	Pan Xie

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	Beijing Visual World Technology Co.,Ltd.
Address:	501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing
Manufacturer:	Beijing Visual World Technology Co.,Ltd.
Address:	501 & 5F,102 No, Building No. 2, No 6 Jiuxianqiao Rd, Chaoyang District, Beijing

3.2. Product Description

Name of EUT:	360 Smart Camera Pan-Tilt AI Version
Trade Mark:	+360
Model No.:	AP1C
Listed Model(s)	AP1L
Power supply:	DC 5V from adapter
Adapter Information 1:	Model: A18A-050100U-US2 Input: 100-240Va.c.,50/60Hz MAX 0.2A Output: 5Vd.c.,1.0A
Adapter Information 2:	Model: TEKA006-0501000UK Input: 100-240Va.c.,50/60Hz 0.2A MAX Output: 5Vd.c.,1000mA
Hardware version:	SJ-C399-V1.04
Software version:	D916_A_20190930.7.0.277

3.3. EUT operation mode

Test mode	Describe
Camera recording mode	The EUT works at video recording status

3.4. Configuration of Tested System

N/A.

3.5. Support unit used in test configuration

N/A.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

4.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 762235.

IC-Registration No.: 5377A

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emissions	30~1000MHz	4.90 dB	(1)
Radiated Emissions	1~18GHz	4.96 dB	(1)
Conducted Disturbance	0.15~30MHz	3.02 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2019/10/26	2020/10/25
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2019/10/23	2020/10/22
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2019/10/23	2020/10/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLE X_142	EF-NM-BNCM-2M	2019/10/23	2020/10/22
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2019/10/26	2020/10/25
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2018/04/02	2021/04/01
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2020/04/05	2023/04/04
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2019/11/14	2020/11/13
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2019/08/21	2020/08/20
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX 104	501184/4	2019/05/27	2020/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2019/10/26	2020/10/25
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	25841	2018/10/11	2021/10/10
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2018/10/11	2021/10/11
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2019/11/14	2020/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2019/05/23	2020/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-03	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2019/05/10	2020/05/09
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2019/05/10	2020/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.107:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4:2014
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

Adapter 1:

Test Line: L



MEASUREMENT RESULT: "GM2003115069_fin"

3/11/2020 7:43PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.213000	36.60	10.1	63	26.5	QP	L1	GND
0.586500	47.80	10.1	56	8.2	QP	L1	GND
1.131000	35.60	10.1	56	20.4	QP	L1	GND
3.066000	35.50	10.1	56	20.5	QP	L1	GND
6.063000	35.20	10.2	60	24.8	QP	L1	GND
22.875000	34.30	10.2	60	25.7	QP	L1	GND


MEASUREMENT RESULT: "GM2003115069_fin2"

3/11/2020 7:43PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.226500	23.90	10.1	53	28.7	AV	L1	GND
0.582000	38.40	10.1	46	7.6	AV	L1	GND
0.942000	26.70	10.1	46	19.3	AV	L1	GND
2.868000	23.90	10.1	46	22.1	AV	L1	GND
5.208000	22.70	10.2	50	27.3	AV	L1	GND
23.064000	25.90	10.2	50	24.1	AV	L1	GND

Test Line:

N



MEASUREMENT RESULT: "GM2003115070_fin"

3/11/2020 7:47PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.168000	38.10	10.1	65	27.0	QP	N	GND
0.582000	39.90	10.1	56	16.1	QP	N	GND
1.032000	32.40	10.1	56	23.6	QP	N	GND
4.744500	28.00	10.1	56	28.0	QP	N	GND
6.144000	25.70	10.2	60	34.3	QP	N	GND
22.825500	29.80	10.2	60	30.2	QP	N	GND

MEASUREMENT RESULT: "GM2003115070_fin2"


3/11/2020 7:47PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.213000	19.50	10.1	53	33.6	AV	N	GND
0.582000	29.50	10.1	46	16.5	AV	N	GND
1.072500	22.90	10.1	46	23.1	AV	N	GND
4.803000	18.70	10.1	46	27.3	AV	N	GND
6.027000	16.60	10.2	50	33.4	AV	N	GND
23.109000	22.10	10.2	50	27.9	AV	N	GND

Adapter 2:

Test Line:

L



MEASUREMENT RESULT: "GM2003115097_fin"

3/11/2020 10:27PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.154500	42.60	10.1	66	23.2	QP	L1	GND
0.429000	36.60	10.1	57	20.7	QP	L1	GND
1.203000	23.90	10.1	56	32.1	QP	L1	GND
2.107500	21.50	10.1	56	34.5	QP	L1	GND
11.436000	21.20	10.2	60	38.8	QP	L1	GND
16.179000	27.50	10.2	60	32.5	QP	L1	GND


MEASUREMENT RESULT: "GM2003115097_fin2"

3/11/2020 10:27PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.361500	20.50	10.1	49	28.2	AV	L1	GND
0.433500	33.30	10.1	47	13.9	AV	L1	GND
1.329000	15.50	10.1	46	30.5	AV	L1	GND
2.395500	14.20	10.1	46	31.8	AV	L1	GND
5.347500	12.70	10.2	50	37.3	AV	L1	GND
15.846000	16.90	10.2	50	33.1	AV	L1	GND

Test Line:

N



MEASUREMENT RESULT: "GM2003115096_fin"

3/11/2020 10:24PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	47.70	10.1	66	18.3	QP	N	GND
0.451500	34.60	10.1	57	22.2	QP	N	GND
1.063500	25.30	10.1	56	30.7	QP	N	GND
2.134500	25.10	10.1	56	30.9	QP	N	GND
7.039500	19.90	10.2	60	40.1	QP	N	GND
16.327500	28.40	10.2	60	31.6	QP	N	GND

MEASUREMENT RESULT: "GM2003115096_fin2"

3/11/2020 10:24PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.177000	26.40	10.1	55	28.2	AV	N	GND
0.429000	28.50	10.1	47	18.8	AV	N	GND
0.906000	18.50	10.1	46	27.5	AV	N	GND
2.346000	13.30	10.1	46	32.7	AV	N	GND
5.248500	10.80	10.2	50	39.2	AV	N	GND
15.607500	15.90	10.2	50	34.1	AV	N	GND

5.2. Radiated Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.109


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

- The EUT was tested according to ANSI C63.4:2014.
- The EUT is placed on a turn table which is 0.8 meter above ground.
- The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
- Use the following spectrum analyzer settings
 - Span shall wide enough to fully capture the emission being measured;
 - Below 1GHz,
 RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;
 If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - From 1GHz to 5th harmonic, RBW=1MHz, VBW=3MHz

TEST MODE:

Please refer to the clause 3.3


TEST RESULTS

Passed **Not Applicable**

Note: Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
The emission levels of frequency above 6GHz are very lower than limit and not show in test report.

Adapter 1:


Polarization: Horizontal



MEASUREMENT RESULT: "GM2003116112_red"

3/11/2020 9:11PM


Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
249.220000	26.90	-8.2	46.0	19.1	QP	100.0	238.00	HORIZONTAL
350.100000	38.00	-4.9	46.0	8.0	QP	100.0	290.00	HORIZONTAL
400.540000	30.50	-3.5	46.0	15.5	QP	100.0	33.00	HORIZONTAL
450.980000	38.30	-2.4	46.0	7.7	QP	100.0	315.00	HORIZONTAL
549.920000	35.80	0.2	46.0	10.2	QP	300.0	228.00	HORIZONTAL
883.600000	36.80	6.9	46.0	9.2	QP	300.0	359.00	HORIZONTAL



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Polarity	Detector
1	1199.375	40.24	-5.84	34.40	74.00	39.60	Horizontal	PK
2	1761.250	33.56	-5.92	27.64	74.00	46.36	Horizontal	PK
3	2676.250	32.22	0.13	32.35	74.00	41.65	Horizontal	PK
4	3203.750	33.35	0.80	34.15	74.00	39.85	Horizontal	PK
5	4231.250	32.65	3.80	36.45	74.00	37.55	Horizontal	PK
6	5146.875	31.79	8.88	40.67	74.00	33.33	Horizontal	PK

Polarization:


Vertical



MEASUREMENT RESULT: "GM2003116111_red"

3/11/2020 9:07PM


Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	36.50	-12.8	40.0	3.5	QP	100.0	307.00	VERTICAL
249.220000	27.70	-8.2	46.0	18.3	QP	100.0	25.00	VERTICAL
350.100000	40.70	-4.9	46.0	5.3	QP	100.0	191.00	VERTICAL
450.980000	36.50	-2.4	46.0	9.5	QP	100.0	244.00	VERTICAL
549.920000	35.80	0.2	46.0	10.2	QP	100.0	202.00	VERTICAL
951.500000	39.10	8.2	46.0	6.9	QP	100.0	191.00	VERTICAL



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1200.000	39.81	-5.83	33.98	74.00	40.02	Vertical	PK
2	1700.625	34.97	-6.10	28.87	74.00	45.13	Vertical	PK
3	2416.875	34.20	-2.37	31.83	74.00	42.17	Vertical	PK
4	3110.625	35.57	0.38	35.95	74.00	38.05	Vertical	PK
5	4045.625	33.87	3.12	36.99	74.00	37.01	Vertical	PK
6	5161.875	32.31	8.91	41.22	74.00	32.78	Vertical	PK

Adapter 2:


Polarization: Horizontal



MEASUREMENT RESULT: "GM2003116115_red"

3/11/2020 9:26PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
350.100000	38.10	-4.9	46.0	7.9	QP	100.0	299.00	HORIZONTAL
400.540000	31.00	-3.5	46.0	15.0	QP	100.0	197.00	HORIZONTAL
450.980000	39.70	-2.4	46.0	6.3	QP	100.0	360.00	HORIZONTAL
499.480000	31.00	-1.5	46.0	15.0	QP	100.0	38.00	HORIZONTAL
549.920000	35.90	0.2	46.0	10.1	QP	100.0	299.00	HORIZONTAL
957.320000	36.70	8.3	46.0	9.3	QP	300.0	195.00	HORIZONTAL




Suspected Data List

NO.	Freq. [MHz]	Reading [dBuV/m]	Factor [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Polarity	Detector
1	1200.000	40.48	-5.83	34.65	74.00	39.35	Horizontal	PK
2	1776.250	34.01	-5.87	28.14	74.00	45.86	Horizontal	PK
3	2293.125	31.45	-2.37	29.08	74.00	44.92	Horizontal	PK
4	2805.000	31.20	2.01	33.21	74.00	40.79	Horizontal	PK
5	3631.250	33.39	1.49	34.88	74.00	39.12	Horizontal	PK
6	5214.375	31.47	8.90	40.37	74.00	33.63	Horizontal	PK

Polarization:


Vertical



MEASUREMENT RESULT: "GM2003116116_red"

3/11/2020 9:29PM


Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	19.90	-12.1	40.0	20.1	QP	100.0	26.00	VERTICAL
249.220000	29.30	-8.2	46.0	16.7	QP	100.0	26.00	VERTICAL
350.100000	40.40	-4.9	46.0	5.6	QP	100.0	191.00	VERTICAL
450.980000	34.60	-2.4	46.0	11.4	QP	100.0	277.00	VERTICAL
549.920000	35.70	0.2	46.0	10.3	QP	100.0	213.00	VERTICAL
951.500000	38.20	8.2	46.0	7.8	QP	100.0	88.00	VERTICAL



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity	Detector
1	1200.000	39.64	-5.83	33.81	74.00	40.19	Vertical	PK
2	1900.000	36.52	-5.83	30.69	74.00	43.31	Vertical	PK
3	2278.750	33.99	-2.47	31.52	74.00	42.48	Vertical	PK
4	2767.500	31.98	1.60	33.58	74.00	40.42	Vertical	PK
5	4086.875	33.21	3.22	36.43	74.00	37.57	Vertical	PK
6	5116.875	32.15	8.83	40.98	74.00	33.02	Vertical	PK


6. TEST SETUP PHOTOS OF THE EUT

Conducted Emissions (AC Mains)



Radiated Emissions





7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No.: CHTEW20040096

-----End of Report-----