

Maximum Permissible Exposure Report

1. Product Information

FCC ID	2AIV9-J635
Product name	360 Dash Cam
Model number	J635
Model Declaration	/
Test Model	J635
Power supply	DC 3.7V by Rechargeable Li-ion Battery (470mAh) Recharge Voltage: DC 5V 1A
2.4G WLAN	Supports IEEE 802.11b/802.11g/802.11n (Not support 802.11n-HT40)
Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz
Modulation Type	IEEE 802.11b: DSSS (CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM,QPSK,BPSK)
Channel Number	11 Channels for WIFI 20MHz Bandwidth (IEEE 802.11b/g/n HT20)
Antenna Type	Internal antenna
Antenna Gain	1.77dBi (Max.)
Hardware version	J635-MB-V1.1
Software version	J635-0.1.118-S
Extreme temp. Tolerance	-5°C to +45°C
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer evaluation method

ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

f=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

The EUT can only use antennas certificated as follows provided by manufacturer;

External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	Internal Antenna	600 MHz – 2500 MHz	1.77dBi (max.) For 2.4G WLAN

6. Conducted Power

General Note:

- Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing, further SAR test reduction and MPE.

<2.4GWLAN Max Conducted Peak Power>

Test Mode		Channel	Frequency (MHz)	Max Conducted Power (dBm)
2.4GWLAN	IEEE 802.11b	LCH	2412	17.11
		MCH	2437	17.70
		HCH	2462	17.82
	IEEE 802.11g	LCH	2412	16.13
		MCH	2437	16.97
		HCH	2462	16.87
	IEEE 802.11n HT20	LCH	2412	16.14
		MCH	2437	16.21
		HCH	2462	16.66

7. Manufacturing Tolerance

<2.4GWLAN>

Test Mode		Channel	Max Conducted Power (dBm)	ANT Max. Tune Up Power (dBm)
2.4GWLAN	IEEE 802.11b	LCH	17.11	17.0±1.0
		MCH	17.70	17.0±1.0
		HCH	17.82	17.0±1.0
	IEEE 802.11g	LCH	16.13	16.0±1.0
		MCH	16.97	16.0±1.0
		HCH	16.87	16.0±1.0
	IEEE 802.11n HT20	LCH	16.14	16.0±1.0
		MCH	16.21	16.0±1.0
		HCH	16.66	16.0±1.0

8. Measurement Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Antenna 0

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
IEEE 802.11b	18.00	63.0957	1.7700	1.5031	0.0189	1.0000
IEEE 802.11g	17.00	50.1187	1.7700	1.5031	0.0150	1.0000
IEEE 802.11n HT20	17.00	50.1187	1.7700	1.5031	0.0150	1.0000

Remark:

- Output power including turn-up tolerance;
- Output power is burst average power;
- MPE evaluate distance is 20cm from user manual provide by manufacturer;
- MPE values = $PG/4\pi R^2$

8.2 Simultaneous Transmission MPE

The sample support only one 2.4GWLAN transmit antenna, so no need to consider simultaneous transmission;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----