

FCC ID: 2AIV9-P4PRO

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT(20/40): 2412-2462MHz,
Power density limited: 1mW/ cm²

Antenna Type: Metal Plate spring Antenna

WIFI antenna gain: 0.75dBi;

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(0.75/10)}=1.19$

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna Gain Numeric	Evaluation result at 20cm Power density(mW/cm2)	Power density Limits (mW/cm2)
				tune-up power				
				(dBm)	(mW)			
2412	802.11b	16.13	16.5±1	17.5	56.23413	1.19	0.01331	1
2437		17.02	16.5±1	17.5	56.23413	1.19	0.01331	1
2462		15.69	16.5±1	17.5	56.23413	1.19	0.01331	1
2412	802.11g	14.04	14±1	15	31.62278	1.19	0.00749	1
2437		14.75	14±1	15	31.62278	1.19	0.00749	1
2462		13.41	14±1	15	31.62278	1.19	0.00749	1
2412	802.11n H20	13.99	14±1	15	31.62278	1.19	0.00749	1
2437		14.49	14±1	15	31.62278	1.19	0.00749	1
2462		13.37	14±1	15	31.62278	1.19	0.00749	1
2422	802.11n(HT 40)	13.05	13±1	14	25.11886	1.19	0.00595	1
2437		12.84	13±1	14	25.11886	1.19	0.00595	1
2452		12.88	13±1	14	25.11886	1.19	0.00595	1

Conclusion:

For the max result : $0.01331 \leq 1.0$ for Max Power Density, No RF exposure evaluation is required.



Signature:

Date: 2021-06-21

NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.