

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Beijing Visual World Technology Co.,Ltd.

360 Smart Camera

Model Number: D503

FCC ID: 2AIV9D503

Prepared for : Beijing Visual World Technology Co.,Ltd.
15th Floor and 17th Floor 1701-10A, Building 3, No. 10,
Jiuxianqiao Road Jia, Chaoyang District, Beijing.

Prepared By : EST Technology Co., Ltd.
San Tun Management Zone, Houjie District, Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1606049
Date of Test : June 01~ 28, 2016
Date of Report : June 28, 2016

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	4
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT).....	5
2. SUMMARY OF TEST.....	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Assistant equipment used for test.....	8
2.4. Block Diagram.....	8
2.5. Test mode.....	9
2.6. Channel List for wifi.....	9
2.7. Test Equipment.....	10
3. POWER LINE CONDUCTED EMISSION TEST.....	11
3.1. Limit.....	11
3.3. Test Procedure.....	11
3.4. Test Result.....	11
3.5. Test data.....	12
4. RADIATED EMISSION TEST.....	16
4.1 Limit.....	16
4.2. Block Diagram of Test setup.....	17
4.3. Test Procedure.....	18
4.4. Test Result.....	18
4.5. Test Data.....	19
5. BAND EDGE COMPLIANCE TEST.....	91
5.1 Limit.....	91
5.2 Test Procedure.....	91
5.3 Test Result.....	91
5.4 Test Data.....	92
6. 6dB & 20dB Bandwidth Test.....	108
6.1 Limit.....	108
6.2 Test Procedure.....	108
6.3 Test Result.....	108
6.4 6dB Test Data.....	110
6.5 20dB Test Data.....	118
7. OUTPUT POWER TEST.....	126
7.1 Limit.....	126
7.2 Test Procedure.....	126
7.3 Test Procedure.....	126
7.4 Test Result.....	127
7.5 Test Data.....	128
8. POWER SPECTRAL DENSITY TEST.....	136
8.1 Limit.....	136
8.2 Test Procedure.....	136

8.3 Test Result..... 137

8.4 Test Data 138

9 ANTENNA REQUIREMENTS 146




9.1 Limit 146


9.2 Result..... 146

10 TEST SETUP PHOTO..... 147

11 PHOTOS OF EUT 149

Test Report Verification

Applicant:	Beijing Visual World Technology Co.,Ltd.		
Address:	15th Floor and 17th Floor 1701-10A, Building 3, No. 10, Jiuxianqiao Road Jia, Chaoyang District, Beijing.		
Manufacturer Address:	Beijing Visual World Technology Co.,Ltd. 15th Floor and 17th Floor 1701-10A, Building 3, No. 10, Jiuxianqiao Road Jia, Chaoyang District, Beijing.		
E.U.T:	360 Smart Camera		
Model Number:	D503		
Power Supply:	DC 5V From Adapter Input AC 100-240V ~ 50/60Hz		
Test Voltage:	AC 120V/60Hz AC 240V/60Hz		
Trade Name:	-----	Serial No.:	-----
Date of Receipt:	June 01, 2016	Date of Test:	June 01~ 28, 2016
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2015 ANSI C63.10:2013		
Test Result:	<p>The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p style="text-align: right;">This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd. Date: June 28, 2016</p>		
Prepared by:	Tested by:	Approved by:	
			
_____ Ada / Assistant	_____ Tony.Tang/ Engineer	_____ IcemanHu / Manager	
Other Aspects:	None.		
<i>Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested</i>			
<i>This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.</i>			



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	360 SMART CAMERA
Model Number	:	D503
FCC ID	:	2AIV9D503
Wi-Fi		
Modulation	:	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT20 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n HT40 MHz mode: OFDM (BPSK/QPSK/16QAM/64QAM)
Operation Frequency	:	IEEE 802.11b/g: 2412 ~ 2472 MHz IEEE 802.11n HT20 : 2412 ~ 2472 MHz IEEE 802.11n HT40 : 2422 ~ 2462 MHz
Number of channel	:	IEEE 802.11b 2412 ~ 2472 MHz: 13 Channels IEEE 802.11g 2412 ~ 2472 MHz: 13 Channels IEEE 802.11n HT20 2412 ~ 2472 MHz: 13 Channels IEEE 802.11n HT40 2422 ~ 2462 MHz: 9 Channels
Antenna and Gain	:	Internal Antenna with 2.73dBi gain (Max)

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10:2013	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10:2013 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Conducted spurious emissions	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: KDB 558074 D01 DTS Meas Guidance v03r05		

2.2. Test Facilities

EMC Lab : Certified by CNAL, CHINA
Registration No.: L5288
Date of registration: December 07, 2015

Certificated by FCC, USA
Registration No.: 989591
Date of registration: November 20, 2013

Certificated by Industry Canada
Registration No.: 9405A-1
Date of registration: December 30, 2015

Certificated by VCCI, Japan
Registration No.: R-3663 & C-4103
Date of registration: July 25, 2011

Certificated by TUV Rheinland, Germany
Registration No.: UA 50195514 0001
Date of registration: January 07, 2011

Certificated by TUV/PS, Shenzhen
Registration No.: SCN1017
Date of registration: January 27, 2011

Certificated by Intertek ETL SEMKO
Registration No.: 2011-RTL-L1-18
Date of registration: April 28, 2011

Certificated by Siemic, Inc.
Registration No.: SLCN021
Date of registration: November 8, 2011

Certificated by Nemko, Hong Kong
Registration No.: 175193
Date of registration: May 4, 2011

Name of Firm : EST Technology Co., Ltd.

Site Location : San Tun Management Zone, Houjie Town, Dongguan,
Guangdong, China


2.3. Assistant equipment used for test

2.3.1. Adapter

M/N : A98A-050100U-US1
Input : AC 100-240V~50/60Hz 0.2A
Output : DC 5V/1.0A

2.4. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 or 1.5 meter high above ground. EUT was be set into Wifi test mode by software before test.



(EUT: 360 Smart Camera)

2.5. Test mode

A special test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode and data rate.

Test mode	Lower channel	Center channel	Upper channel
IEEE 802.11b;IEEE 802.11g;IEEE 802.11n HT20 Transmitting	2412MHz	2442MHz	2472MHz
IEEE 802.11b;IEEE 802.11g;IEEE 802.11n HT20 Receiving	2412MHz	2442MHz	2472MHz
IEEE 802.11n HT40 Transmitting	2422MHz	2442MHz	2462MHz
IEEE 802.11n HT40 Receiving	2422MHz	2442MHz	2462MHz

2.6. Channel List for wifi

IEEE 802.11b;IEEE 802.11g;IEEE 802.11n HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442	12	2467
3	2422	8	2447	13	2472
4	2427	9	2452		
5	2432	10	2457		
IEEE 802.11n HT40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	4	2437	7	2452
2	2427	5	2442	8	2457
3	2432	6	2447	9	2462

2.7. Test Equipment

2.7.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June,28,15	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	June,28,15	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	June,28,15	1 Year

2.7.2. For radiated emission test(30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June,28,15	1 Year
Spectrum Analyzer	Agilent	E4411B	MY5014069 7	June,28,15	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June,28,15	1 Year
Signal Amplifier	Agilent	310N	187037	June,28,15	1 Year

2.7.3. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1 002	June,28,15	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	June,28,15	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June,28,15	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June,28,15	1 Year

3 POWER LINE CONDUCTED EMISSION TEST

3.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.3 Test Procedure

The EUT was placed on a non-metallic table, 80 cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Result


PASS. (All emissions not reported below are too low against the prescribed limits.)

3.5. Test data




Site no : 844 Shield Room Data no. : 41
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.158	9.61	9.81	7.40	26.82	55.56	28.74	Average
2	0.158	9.61	9.81	22.94	42.36	65.56	23.20	QP
3	0.209	9.61	9.80	6.50	25.91	53.23	27.32	Average
4	0.209	9.61	9.80	20.54	39.95	63.23	23.28	QP
5	13.623	9.67	9.92	6.90	26.49	50.00	23.51	Average
6	13.623	9.67	9.92	20.02	39.61	60.00	20.39	QP




Site no : 844 Shield Room Data no. : 43
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBUV)	Emission Level (dBUv)	Limits (dBUv)	Margin (dB)	Remark
1	0.151	9.46	9.81	8.20	27.47	55.96	28.49	Average
2	0.151	9.46	9.81	23.20	42.47	65.96	23.49	QP
3	2.346	9.63	9.84	2.49	21.96	46.00	24.04	Average
4	2.346	9.63	9.84	12.97	32.44	56.00	23.56	QP
5	14.750	9.74	9.93	5.50	25.17	50.00	24.83	Average
6	14.750	9.74	9.93	16.62	36.29	60.00	23.71	QP



Site no : 844 Shield Room Data no. : 45
 Env. / Ins. : Temp:25.3°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 240V/50Hz
 M/N : D503
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.209	9.61	9.80	4.20	23.61	53.23	29.62	Average
2	0.209	9.61	9.80	20.54	39.95	63.23	23.28	QP
3	6.698	9.66	9.85	1.50	21.01	50.00	28.99	Average
4	6.698	9.66	9.85	18.03	37.54	60.00	22.46	QP
5	13.623	9.67	9.92	6.20	25.79	50.00	24.21	Average
6	13.623	9.67	9.92	20.02	39.61	60.00	20.39	QP



Site no : 844 Shield Room Data no. : 47
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 240V/50Hz
 M/N : D503
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.151	9.46	9.81	8.90	28.17	55.96	27.79	Average
2	0.151	9.46	9.81	24.20	43.47	65.96	22.49	QP
3	0.180	9.55	9.80	6.40	25.75	54.50	28.75	Average
4	0.180	9.55	9.80	23.49	42.84	64.50	21.66	QP
5	0.435	9.59	9.81	5.50	24.90	47.15	22.25	Average
6	0.435	9.59	9.81	16.11	35.51	57.15	21.64	QP

4 RADIATED EMISSION TEST

4.1 Limit

4.1.1 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	


- Remark : (1) Emission level dBμV = 20 log Emission level μV/m
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.1.2 15.205 Restricted bands of operation


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.2. Block Diagram of Test setup



Above 1GHz



4.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 30~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,
PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

4.4. Test Result

PASS.


All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

2、 The frequency 2412MHz 、 2422MHz、 2442MHz、 2462MHz and 2472 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

4.5. Test Data


30-1000 MHz



```


Site no       : 966 1# chamber           Data no.    : 65
Env. / Ins.   : Temp:23.6';Humi:56%;Press:101.52kPa  LINE Phase : VERTICAL
Limit         : FCC PART 15 B(3M)
Engineer      : Tony
EUT           : 360 Smart Camera
Power         : DC 5V From Adapter Input AC 120V/60Hz
M/N           : D503
Test Mode     : IEEE 802.11b CH1 2412TX
    
```

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	39.70	12.90	2.12	42.40	26.04	40.00	13.96	QP
2	102.75	9.75	3.12	45.96	27.69	43.50	15.81	QP
3	154.16	10.71	3.82	44.75	28.15	43.50	15.35	QP
4	500.45	17.88	6.73	37.82	31.63	46.00	14.37	QP
5	600.36	19.60	7.35	36.57	32.35	46.00	13.65	QP
6	901.06	23.28	9.14	39.30	41.93	46.00	4.07	QP




Site no : 966 1# chamber Data no. : 66
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH1 2412TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	43.17	24.90	43.50	18.60	QP
2	282.20	12.45	5.10	42.61	28.99	46.00	17.01	QP
3	374.35	14.93	5.76	41.92	31.81	46.00	14.19	QP
4	400.54	16.07	5.98	40.83	32.11	46.00	13.89	QP
5	500.45	17.88	6.73	37.88	31.69	46.00	14.31	QP
6	600.36	19.60	7.35	37.71	33.49	46.00	12.51	QP



Site no : 966 1# chamber Data no. : 67
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH7 2442TX


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	46.96	28.69	43.50	14.81	QP
2	156.10	10.61	3.83	46.44	29.77	43.50	13.73	QP
3	400.54	16.07	5.98	38.01	29.29	46.00	16.71	QP
4	500.45	17.88	6.73	37.82	31.63	46.00	14.37	QP
5	600.36	19.60	7.35	35.57	31.35	46.00	14.65	QP
6	901.06	23.28	9.14	36.45	39.08	46.00	6.92	QP



Date: 2016-06-22


Site no : 966 1# chamber Data no. : 68
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH7 2442TX

	Freq. (MHz)	LISM Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	47.17	28.90	43.50	14.60	QP
2	275.41	12.36	5.04	43.09	29.40	46.00	16.60	QP
3	282.20	12.45	5.10	42.61	28.99	46.00	17.01	QP
4	400.54	16.07	5.98	40.83	32.11	46.00	13.89	QP
5	600.36	19.60	7.35	35.71	31.49	46.00	14.51	QP
6	901.06	23.28	9.14	29.51	32.14	46.00	13.86	QP




Site no : 966 1# chamber Data no. : 69
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	95.96	8.92	3.03	49.66	30.34	43.50	13.16	QP
2	148.34	11.00	3.76	48.90	32.54	43.50	10.96	QP
3	156.10	10.61	3.83	50.44	33.77	43.50	9.73	QP
4	400.54	16.07	5.98	39.01	30.29	46.00	15.71	QP
5	500.45	17.88	6.73	37.82	31.63	46.00	14.37	QP
6	901.06	23.28	9.14	35.45	38.08	46.00	7.92	QP




Site no : 966 1# chamber Data no. : 70
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	47.17	28.90	43.50	14.60	QP
2	282.20	12.45	5.10	45.61	31.99	46.00	14.01	QP
3	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
4	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
5	500.45	17.88	6.73	38.88	32.69	46.00	13.31	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP




Site no : 966 1# chamber Data no. : 71
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	39.70	12.90	2.12	44.40	28.04	40.00	11.96	QP
2	148.34	11.00	3.76	45.90	29.54	43.50	13.96	QP
3	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
4	901.06	23.28	9.14	36.45	39.08	46.00	6.92	QP
5	946.65	24.59	9.18	32.62	36.54	46.00	9.46	QP
6	1000.00	24.60	9.73	31.82	36.66	54.00	17.34	QP




Site no : 966 1# chamber Data no. : 72
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	LISM Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	102.75	9.75	3.12	47.17	28.90	43.50	14.60	QP
2	282.20	12.45	5.10	43.61	29.99	46.00	16.01	QP
3	374.35	14.93	5.76	41.92	31.81	46.00	14.19	QP
4	500.45	17.88	6.73	37.88	31.69	46.00	14.31	QP
5	600.36	19.60	7.35	36.71	32.49	46.00	13.51	QP
6	810.85	22.38	8.46	29.84	30.54	46.00	15.46	QP




Site no : 966 1# chamber Data no. : 73
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH7 2442TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	49.96	31.69	43.50	11.81	QP
2	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
3	400.54	16.07	5.98	40.01	31.29	46.00	14.71	QP
4	500.45	17.88	6.73	38.82	32.63	46.00	13.37	QP
5	801.15	22.07	8.39	32.53	32.74	46.00	13.26	QP
6	849.65	22.95	8.55	31.62	32.58	46.00	13.42	QP




Site no : 966 1# chamber Data no. : 74
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH7 2442TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	30.00	18.51	1.91	30.78	19.74	40.00	20.26	QP
2	146.40	11.15	3.74	40.50	24.27	43.50	19.23	QP
3	277.35	12.36	5.06	45.13	31.40	46.00	14.60	QP
4	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
5	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP




Site no : 966 1# chamber Data no. : 75
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	52.31	6.41	2.40	49.14	26.58	40.00	13.42	QP
2	78.50	6.89	2.83	48.40	26.78	40.00	13.22	QP
3	95.96	8.92	3.03	47.66	28.34	43.50	15.16	QP
4	374.35	14.93	5.76	37.06	26.95	46.00	19.05	QP
5	400.54	16.07	5.98	38.01	29.29	46.00	16.71	QP
6	623.64	20.08	7.53	32.56	29.07	46.00	16.93	QP



Site no : 966 1# chamber Data no. : 76
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	44.17	25.90	43.50	17.60	QP
2	277.35	12.36	5.06	43.13	29.40	46.00	16.60	QP
3	400.54	16.07	5.98	40.83	32.11	46.00	13.89	QP
4	500.45	17.88	6.73	37.88	31.69	46.00	14.31	QP
5	551.86	19.50	7.07	33.14	28.87	46.00	17.13	QP
6	810.85	22.38	8.46	31.84	32.54	46.00	13.46	QP



Date: 2016-06-22


Site no : 966 1# chamber Data no. : 77
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	49.96	31.69	43.50	11.81	QP
2	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
3	400.54	16.07	5.98	40.01	31.29	46.00	14.71	QP
4	500.45	17.88	6.73	38.82	32.63	46.00	13.37	QP
5	801.15	22.07	8.39	32.53	32.74	46.00	13.26	QP
6	849.65	22.95	8.55	31.62	32.58	46.00	13.42	QP




Site no : 966 1# chamber Data no. : 78
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuv)	Limits (dBuv)	Margin (dB)	Remark
1	30.00	18.51	1.91	30.78	19.74	40.00	20.26	QP
2	146.40	11.15	3.74	40.50	24.27	43.50	19.23	QP
3	277.35	12.36	5.06	45.13	31.40	46.00	14.60	QP
4	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
5	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP




Site no : 966 1# chamber Data no. : 79
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH7 2442TX

	Freq. (MHz)	LISM Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuv)	Limits (dBuv)	Margin (dB)	Remark
1	39.70	12.90	2.12	44.40	28.04	40.00	11.96	QP
2	148.34	11.00	3.76	45.90	29.54	43.50	13.96	QP
3	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
4	901.06	23.28	9.14	36.45	39.08	46.00	6.92	QP
5	946.65	24.59	9.18	32.62	36.54	46.00	9.46	QP
6	1000.00	24.60	9.73	31.82	36.66	54.00	17.34	QP




Site no : 966 1# chamber Data no. : 80
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH7 2442TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	47.17	28.90	43.50	14.60	QP
2	282.20	12.45	5.10	43.61	29.99	46.00	16.01	QP
3	374.35	14.93	5.76	41.92	31.81	46.00	14.19	QP
4	500.45	17.88	6.73	37.88	31.69	46.00	14.31	QP
5	600.36	19.60	7.35	36.71	32.49	46.00	13.51	QP
6	810.85	22.38	8.46	29.84	30.54	46.00	15.46	QP




Site no : 966 1# chamber Data no. : 81
 Env. / Ins. : Temp:23.6';Humid:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	102.75	9.75	3.12	49.96	31.69	43.50	11.81	QP
2	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
3	400.54	16.07	5.98	40.01	31.29	46.00	14.71	QP
4	500.45	17.88	6.73	38.82	32.63	46.00	13.37	QP
5	801.15	22.07	8.39	32.53	32.74	46.00	13.26	QP
6	849.65	22.95	8.55	31.62	32.58	46.00	13.42	QP




Site no : 966 1# chamber Data no. : 82
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	30.00	18.51	1.91	30.78	19.74	40.00	20.26	QP
2	146.40	11.15	3.74	40.50	24.27	43.50	19.23	QP
3	277.35	12.36	5.06	45.13	31.40	46.00	14.60	QP
4	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
5	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP




Site no : 966 1# chamber Data no. : 83
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	95.96	8.92	3.03	49.66	30.34	43.50	13.16	QP
2	148.34	11.00	3.76	48.90	32.54	43.50	10.96	QP
3	156.10	10.61	3.83	50.44	33.77	43.50	9.73	QP
4	400.54	16.07	5.98	39.01	30.29	46.00	15.71	QP
5	500.45	17.88	6.73	37.82	31.63	46.00	14.37	QP
6	901.06	23.28	9.14	35.45	38.08	46.00	7.92	QP




Site no : 966 1# chamber Data no. : 84
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	LISM Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	47.17	28.90	43.50	14.60	QP
2	282.20	12.45	5.10	45.61	31.99	46.00	14.01	QP
3	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
4	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
5	500.45	17.88	6.73	38.88	32.69	46.00	13.31	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP




Site no : 966 1# chamber Data no. : 85
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2442TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	49.96	31.69	43.50	11.81	QP
2	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
3	400.54	16.07	5.98	40.01	31.29	46.00	14.71	QP
4	500.45	17.88	6.73	38.82	32.63	46.00	13.37	QP
5	801.15	22.07	8.39	32.53	32.74	46.00	13.26	QP
6	849.65	22.95	8.55	31.62	32.58	46.00	13.42	QP




Site no : 966 1# chamber Data no. : 86
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2442TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	30.00	18.51	1.91	30.78	19.74	40.00	20.26	QP
2	146.40	11.15	3.74	40.50	24.27	43.50	19.23	QP
3	277.35	12.36	5.06	45.13	31.40	46.00	14.60	QP
4	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
5	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP



Site no : 966 1# chamber Data no. : 87
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : VERTICAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2462TX


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	102.75	9.75	3.12	49.96	31.69	43.50	11.81	QP
2	374.35	14.93	5.76	39.06	28.95	46.00	17.05	QP
3	400.54	16.07	5.98	40.01	31.29	46.00	14.71	QP
4	500.45	17.88	6.73	38.82	32.63	46.00	13.37	QP
5	801.15	22.07	8.39	32.53	32.74	46.00	13.26	QP
6	849.65	22.95	8.55	31.62	32.58	46.00	13.42	QP



Site no : 966 1# chamber Data no. : 88
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2462TX

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuv)	Limits (dBuv)	Margin (dB)	Remark
1	30.00	18.51	1.91	30.78	19.74	40.00	20.26	QP
2	146.40	11.15	3.74	40.50	24.27	43.50	19.23	QP
3	277.35	12.36	5.06	45.13	31.40	46.00	14.60	QP
4	374.35	14.93	5.76	43.92	33.81	46.00	12.19	QP
5	400.54	16.07	5.98	42.83	34.11	46.00	11.89	QP
6	600.36	19.60	7.35	38.71	34.49	46.00	11.51	QP

1000-18000 MHz




Date: 2016-06-20

Site no. : 966 1# chamber Data no. : 1
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.60	6.64	34.64	94.81	94.41	74.00	-20.41	Peak
2	4825.00	31.28	11.84	35.66	44.61	52.07	74.00	21.93	Peak
3	7494.00	36.48	11.62	34.18	32.59	46.51	74.00	27.49	Peak
4	10265.00	38.56	11.44	34.49	31.93	47.44	74.00	26.56	Peak
5	11336.00	39.30	11.04	33.44	31.78	48.68	74.00	25.32	Peak
6	13835.00	41.02	11.10	33.06	33.37	52.43	74.00	21.57	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 2
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.60	6.64	34.64	87.26	86.86	74.00	-12.86	Peak
2	4825.00	31.28	11.84	35.66	38.70	46.16	74.00	27.84	Peak
3	7324.00	36.55	11.57	34.14	32.46	46.44	74.00	27.56	Peak
4	8684.00	37.32	11.45	33.66	32.25	47.36	74.00	26.64	Peak
5	11234.00	39.37	11.12	33.25	31.26	48.50	74.00	25.50	Peak
6	14515.00	41.89	10.93	33.57	31.94	51.19	74.00	22.81	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 5
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	92.99	92.41	74.00	-18.41	Peak
2	4893.00	31.40	12.14	35.82	41.93	49.65	74.00	24.35	Peak
3	7460.00	36.52	11.61	34.21	32.61	46.53	74.00	27.47	Peak
4	8684.00	37.32	11.45	33.66	32.32	47.43	74.00	26.57	Peak
5	10945.00	39.46	11.29	34.13	31.67	48.29	74.00	25.71	Peak
6	14804.00	40.89	10.89	33.78	33.40	51.40	74.00	22.60	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 6
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	92.84	92.26	74.00	-18.26	Peak
2	4876.00	31.37	12.07	35.76	44.27	51.95	74.00	22.05	Peak
3	8004.00	37.01	11.40	34.96	32.93	46.38	74.00	27.62	Peak
4	8684.00	37.32	11.45	33.66	32.70	47.81	74.00	26.19	Peak
5	11166.00	39.41	11.17	33.31	31.10	48.37	74.00	25.63	Peak
6	14005.00	41.46	10.90	33.01	32.53	51.88	74.00	22.12	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 7
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2472.00	27.58	6.71	35.11	85.07	84.25	74.00	-10.25	Peak
2	4944.00	31.47	12.37	35.96	44.65	52.53	74.00	21.47	Peak
3	7460.00	36.52	11.61	34.21	32.94	46.86	74.00	27.14	Peak
4	9109.00	37.59	11.51	34.10	32.14	47.14	74.00	26.86	Peak
5	11285.00	39.33	11.08	33.32	30.67	47.76	74.00	26.24	Peak
6	14090.00	41.54	10.91	33.13	31.15	50.47	74.00	23.53	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 8
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2472.00	27.58	6.71	35.11	94.22	93.40	74.00	-19.40	Peak
2	4944.00	31.47	12.37	35.96	42.35	50.23	74.00	23.77	Peak
3	8565.00	37.10	11.45	33.92	31.32	45.95	74.00	28.05	Peak
4	10316.00	38.65	11.41	34.51	31.75	47.30	74.00	26.70	Peak
5	11234.00	39.37	11.12	33.25	30.38	47.62	74.00	26.38	Peak
6	14005.00	41.46	10.90	33.01	28.70	48.05	74.00	25.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Date: 2016-06-20

Site no. : 966 1# chamber Data no. : 11
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.60	6.64	34.64	85.58	85.18	74.00	-11.18	Peak
2	4825.00	31.28	11.84	35.66	37.18	44.64	74.00	29.36	Peak
3	7460.00	36.52	11.61	34.21	32.72	46.64	74.00	27.36	Peak
4	8684.00	37.32	11.45	33.66	33.16	48.27	74.00	25.73	Peak
5	11336.00	39.30	11.04	33.44	32.45	49.35	74.00	24.65	Peak
6	14124.00	41.57	10.91	33.22	30.93	50.19	74.00	23.81	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 12
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.60	6.64	34.64	88.31	87.91	74.00	-13.91	Peak
2	4825.00	31.28	11.84	35.66	40.33	47.79	74.00	26.21	Peak
3	7885.00	36.78	11.45	35.09	33.28	46.42	74.00	27.58	Peak
4	8650.00	37.27	11.45	33.68	30.55	45.59	74.00	28.41	Peak
5	13665.00	40.55	11.30	32.75	28.53	47.63	74.00	26.37	Peak
6	14464.00	41.85	10.93	33.45	28.27	47.60	74.00	26.40	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 15
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	86.98	86.40	74.00	-12.40	Peak
2	4876.00	31.37	12.07	35.76	37.93	45.61	74.00	28.39	Peak
3	7222.00	36.52	11.54	33.95	31.83	45.94	74.00	28.06	Peak
4	8684.00	37.32	11.45	33.66	32.94	48.05	74.00	25.95	Peak
5	11166.00	39.41	11.17	33.31	30.92	48.19	74.00	25.81	Peak
6	14090.00	41.54	10.91	33.13	30.21	49.53	74.00	24.47	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 16
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	90.34	89.76	74.00	-15.76	Peak
2	4876.00	31.37	12.07	35.76	40.85	48.53	74.00	25.47	Peak
3	7426.00	36.56	11.60	34.22	31.39	45.33	74.00	28.67	Peak
4	9194.00	37.75	11.55	34.16	31.29	46.41	74.00	27.59	Peak
5	11200.00	39.39	11.14	33.24	30.58	47.87	74.00	26.13	Peak
6	14124.00	41.57	10.91	33.22	30.65	49.91	74.00	24.09	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 17
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2472.00	27.58	6.71	35.11	91.39	90.57	74.00	-16.57	Peak
2	4944.00	31.47	12.37	35.96	41.81	49.69	74.00	24.31	Peak
3	7426.00	36.56	11.60	34.22	32.96	46.90	74.00	27.10	Peak
4	8684.00	37.32	11.45	33.66	32.32	47.43	74.00	26.57	Peak
5	11200.00	39.39	11.14	33.24	31.25	48.54	74.00	25.46	Peak
6	13274.00	39.54	11.47	32.92	30.50	48.59	74.00	25.41	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 18
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2472.00	27.58	6.71	35.11	86.26	85.44	74.00	-11.44	Peak
2	4944.00	31.47	12.37	35.96	40.17	48.05	74.00	25.95	Peak
3	7290.00	36.54	11.56	34.09	32.51	46.52	74.00	27.48	Peak
4	8684.00	37.32	11.45	33.66	32.38	47.49	74.00	26.51	Peak
5	10996.00	39.52	11.29	34.11	32.35	49.05	74.00	24.95	Peak
6	13546.00	40.21	11.44	32.61	31.57	50.61	74.00	23.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Date: 2016-06-20

Site no. : 966 1# chamber Data no. : 21
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.60	6.64	34.64	89.42	89.02	74.00	-15.02	Peak
2	4825.00	31.28	11.84	35.66	38.60	46.06	74.00	27.94	Peak
3	7375.00	36.57	11.59	34.21	32.91	46.86	74.00	27.14	Peak
4	8650.00	37.27	11.45	33.68	32.15	47.19	74.00	26.81	Peak
5	10996.00	39.52	11.29	34.11	31.97	48.67	74.00	25.33	Peak
6	13580.00	40.31	11.40	32.64	30.26	49.33	74.00	24.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Date: 2016-06-20

Site no. : 966 1# chamber Data no. : 22
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2412.00	27.60	6.64	34.64	86.06	85.66	74.00	-11.66	Peak
2	4825.00	31.28	11.84	35.66	41.94	49.40	74.00	24.60	Peak
3	7324.00	36.55	11.57	34.14	32.25	46.23	74.00	27.77	Peak
4	8684.00	37.32	11.45	33.66	32.18	47.29	74.00	26.71	Peak
5	11064.00	39.48	11.24	33.83	33.25	50.14	74.00	23.86	Peak
6	14090.00	41.54	10.91	33.13	32.40	51.72	74.00	22.28	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 25
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	88.76	88.18	74.00	-14.18	Peak
2	4876.00	31.37	12.07	35.76	39.44	47.12	74.00	26.88	Peak
3	7426.00	36.56	11.60	34.22	32.45	46.39	74.00	27.61	Peak
4	8684.00	37.32	11.45	33.66	32.93	48.04	74.00	25.96	Peak
5	10180.00	38.42	11.49	34.53	32.02	47.40	74.00	26.60	Peak
6	14056.00	41.51	10.90	33.06	30.90	50.25	74.00	23.75	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Date: 2016-06-20

Site no. : 966 1# chamber Data no. : 26
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	88.56	87.98	74.00	-13.98	Peak
2	4876.00	31.37	12.07	35.76	41.78	49.46	74.00	24.54	Peak
3	7375.00	36.57	11.59	34.21	32.76	46.71	74.00	27.29	Peak
4	8684.00	37.32	11.45	33.66	32.64	47.75	74.00	26.25	Peak
5	12560.00	38.77	10.97	33.36	31.33	47.71	74.00	26.29	Peak
6	13835.00	41.02	11.10	33.06	31.03	50.09	74.00	23.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.




Date: 2016-06-20

Site no. : 966 1# chamber Data no. : 27
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2472.00	27.58	6.71	35.11	91.60	90.78	74.00	-16.78	Peak
2	4944.00	31.47	12.37	35.96	40.72	48.60	74.00	25.40	Peak
3	8514.00	36.96	11.45	34.07	32.19	46.53	74.00	27.47	Peak
4	8684.00	37.32	11.45	33.66	33.53	48.64	74.00	25.36	Peak
5	10265.00	38.56	11.44	34.49	32.11	47.62	74.00	26.38	Peak
6	13665.00	40.55	11.30	32.75	30.11	49.21	74.00	24.79	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 28
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2472.00	27.58	6.71	35.11	89.45	88.63	74.00	-14.63	Peak
2	4961.00	31.49	12.44	36.01	42.40	50.32	74.00	23.68	Peak
3	7426.00	36.56	11.60	34.22	32.56	46.50	74.00	27.50	Peak
4	8684.00	37.32	11.45	33.66	32.72	47.83	74.00	26.17	Peak
5	11064.00	39.48	11.24	33.83	30.67	47.56	74.00	26.44	Peak
6	13546.00	40.21	11.44	32.61	30.49	49.53	74.00	24.47	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 l# chamber Data no. : 31
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.00	27.60	6.66	34.74	85.48	85.00	74.00	-11.00	Peak
2	4876.00	31.37	12.07	35.76	43.59	51.27	74.00	22.73	Peak
3	7630.00	36.41	11.56	34.19	32.12	45.90	74.00	28.10	Peak
4	9925.00	38.14	11.61	34.97	31.88	46.66	74.00	27.34	Peak
5	13495.00	40.07	11.50	32.65	30.16	49.08	74.00	24.92	Peak
6	13954.00	41.35	10.96	32.99	29.71	49.03	74.00	24.97	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 32
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.00	27.60	6.66	34.74	90.87	90.39	74.00	-16.39	Peak
2	4842.00	31.31	11.92	35.68	43.23	50.78	74.00	23.22	Peak
3	7256.00	36.53	11.55	34.02	33.21	47.27	74.00	26.73	Peak
4	9126.00	37.62	11.52	34.09	30.65	45.70	74.00	28.30	Peak
5	10214.00	38.48	11.47	34.50	29.21	44.66	74.00	29.34	Peak
6	13665.00	40.55	11.30	32.75	27.73	46.83	74.00	27.17	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 35
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	89.82	89.24	74.00	-15.24	Peak
2	4910.00	31.42	12.22	35.87	42.51	50.28	74.00	23.72	Peak
3	7324.00	36.55	11.57	34.14	32.09	46.07	74.00	27.93	Peak
4	8735.00	37.40	11.45	33.76	31.35	46.44	74.00	27.56	Peak
5	11166.00	39.41	11.17	33.31	28.87	46.14	74.00	27.86	Peak
6	14090.00	41.54	10.91	33.13	29.23	48.55	74.00	25.45	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 36
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2442.00	27.60	6.67	34.85	92.91	92.33	74.00	-18.33	Peak
2	4910.00	31.42	12.22	35.87	42.86	50.63	74.00	23.37	Peak
3	7324.00	36.55	11.57	34.14	36.59	50.57	74.00	23.43	Peak
4	8786.00	37.48	11.46	33.90	31.05	46.09	74.00	27.91	Peak
5	11404.00	39.25	10.99	33.57	27.65	44.32	74.00	29.68	Peak
6	13954.00	41.35	10.96	32.99	28.72	48.04	74.00	25.96	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 38
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH9 2462TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.00	27.58	6.69	34.98	89.55	88.84	74.00	-14.84	Peak
2	4893.00	31.40	12.14	35.82	42.87	50.59	74.00	23.41	Peak
3	7460.00	36.52	11.61	34.21	31.20	45.12	74.00	28.88	Peak
4	8650.00	37.27	11.45	33.68	30.34	45.38	74.00	28.62	Peak
5	10945.00	39.46	11.29	34.13	27.38	44.00	74.00	30.00	Peak
6	13614.00	40.40	11.36	32.68	26.84	45.92	74.00	28.08	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 42
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21066.00	0.00	20.16	35.73	56.79	41.22	74.00	32.78	Peak
2	22606.00	0.00	20.92	34.27	56.93	43.58	74.00	30.42	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 43
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21360.00	0.00	20.28	35.49	56.58	41.37	74.00	32.63	Peak
2	22585.00	0.00	20.90	34.30	56.19	42.79	74.00	31.21	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 44
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21255.00	46.14	20.24	35.58	10.89	41.69	74.00	32.31	Peak
2	23075.00	45.62	21.21	33.77	9.70	42.76	74.00	31.24	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 45
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20695.00	46.11	19.99	36.07	10.61	40.64	74.00	33.36	Peak
2	22564.00	45.78	20.89	34.30	10.68	43.05	74.00	30.95	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 46
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20625.00	0.00	19.96	36.14	56.81	40.63	74.00	33.37	Peak
2	22466.00	0.00	20.83	34.40	55.61	42.04	74.00	31.96	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 l# chamber Data no. : 47
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21066.00	0.00	20.16	35.73	55.80	40.23	74.00	33.77	Peak
2	22445.00	0.00	20.82	34.43	54.79	41.18	74.00	32.82	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 48
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21136.00	46.21	20.19	35.69	9.24	39.95	74.00	34.05	Peak
2	22585.00	45.77	20.90	34.30	10.44	42.81	74.00	31.19	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 49
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21094.00	46.23	20.17	35.71	10.87	41.56	74.00	32.44	Peak
2	23355.00	45.67	21.47	33.48	9.64	43.30	74.00	30.70	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 50
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21724.00	0.00	20.44	35.15	56.74	42.03	74.00	31.97	Peak
2	23446.00	0.00	21.55	33.38	56.20	44.37	74.00	29.63	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 51
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21850.00	45.79	20.50	35.03	10.78	42.04	74.00	31.96	Peak
2	23740.00	45.65	21.81	33.06	10.10	44.50	74.00	29.50	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 52
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	21794.00	0.00	20.47	35.08	54.65	40.04	74.00	33.96	Peak
2	23110.00	0.00	21.25	33.74	54.79	42.30	74.00	31.70	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 53
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21906.00	45.75	20.52	34.99	8.74	40.02	74.00	33.98	Peak
2	23348.00	45.67	21.46	33.48	7.96	41.61	74.00	32.39	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 l# chamber Data no. : 54
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21080.00	0.00	20.16	35.73	54.76	39.19	74.00	34.81	Peak
2	22004.00	0.00	20.57	34.90	54.49	40.16	74.00	33.84	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 55
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20870.00	46.22	20.07	35.91	9.82	40.20	74.00	33.80	Peak
2	22620.00	45.75	20.92	34.24	8.69	41.12	74.00	32.88	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 56
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21185.00	0.00	20.21	35.64	55.92	40.49	74.00	33.51	Peak
2	22655.00	0.00	20.94	34.22	55.24	41.96	74.00	32.04	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 l# chamber Data no. : 57
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21164.00	46.20	20.20	35.64	8.55	39.31	74.00	34.69	Peak
2	23110.00	45.62	21.25	33.74	8.16	41.29	74.00	32.71	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 58
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21444.00	0.00	20.32	35.40	55.91	40.83	74.00	33.17	Peak
2	23257.00	0.00	21.38	33.59	54.11	41.90	74.00	32.10	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 59
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	20660.00	46.10	19.98	36.12	9.53	39.49	74.00	34.51	Peak
2	22270.00	45.75	20.72	34.61	8.59	40.45	74.00	33.55	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 l# chamber Data no. : 60
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21164.00	0.00	20.20	35.64	55.48	40.04	74.00	33.96	Peak
2	22515.00	0.00	20.87	34.35	54.04	40.56	74.00	33.44	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 l# chamber Data no. : 61
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21150.00	46.21	20.20	35.67	9.70	40.44	74.00	33.56	Peak
2	23215.00	45.64	21.34	33.61	9.60	42.97	74.00	31.03	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 62
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH7 2442TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21500.00	0.00	20.35	35.35	55.53	40.53	74.00	33.47	Peak
2	23194.00	0.00	21.32	33.64	54.57	42.25	74.00	31.75	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 63
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH9 2462TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21325.00	46.10	20.27	35.51	8.99	39.85	74.00	34.15	Peak
2	23096.00	45.62	21.23	33.74	7.83	40.94	74.00	33.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 64
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH9 2462TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	21794.00	0.00	20.47	35.08	55.44	40.83	74.00	33.17	Peak
2	22984.00	0.00	21.14	33.88	55.02	42.28	74.00	31.72	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

5 BAND EDGE COMPLIANCE TEST

5.1 Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits

5.2 Test Procedure


1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto
 - (b) AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto

5.3 Test Result

Pass (The testing data was attached in the next pages.)

- Note:
- 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
 - 2、 The frequency 2412MHz. 2422MHz . 2462MHz and 2472 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


5.4 Test Data



Site no. : 966 1# chamber Data no. : 3
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2374.36	27.64	6.60	34.59	33.00	32.65	74.00	41.35	Peak
2	2390.00	27.64	6.62	34.62	32.10	31.74	74.00	42.26	Peak
3	2400.00	27.61	6.62	34.64	41.56	41.15	74.00	32.85	Peak
4	2412.45	27.60	6.64	34.64	87.26	86.86	74.00	-12.86	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 4
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2389.44	27.64	6.62	34.62	36.98	36.62	74.00	37.38	Peak
2	2390.00	27.64	6.62	34.62	34.24	33.88	74.00	40.12	Peak
3	2400.00	27.61	6.62	34.64	45.90	45.49	74.00	28.51	Peak
4	2413.10	27.60	6.64	34.64	93.24	92.84	74.00	-18.84	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 9
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6%;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2472.48	27.58	6.71	35.11	95.27	94.45	74.00	-20.45	Peak
2	2483.52	27.58	6.71	35.11	54.16	53.34	74.00	20.66	Peak
3	2484.00	27.58	6.71	35.11	56.36	55.54	74.00	18.46	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 10
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11b CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2473.00	27.58	6.71	35.11	87.32	86.50	74.00	-12.50	Peak
2	2483.52	27.58	6.71	35.11	45.86	45.04	74.00	28.96	Peak
3	2484.00	27.58	6.71	35.11	47.49	46.67	74.00	27.33	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 13
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2371.50	27.67	6.60	34.59	35.20	34.88	74.00	39.12	Peak
2	2390.00	27.64	6.62	34.62	36.21	35.85	74.00	38.15	Peak
3	2400.00	27.61	6.62	34.64	47.86	47.45	74.00	26.55	Peak
4	2418.95	27.60	6.64	34.74	88.44	87.94	74.00	-13.94	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 19
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2476.40	27.58	6.71	35.11	88.00	87.18	74.00	-13.18	Peak
2	2483.52	27.58	6.71	35.11	51.08	50.26	74.00	23.74	Peak
3	2483.96	27.58	6.71	35.11	49.15	48.33	74.00	25.67	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 20
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11g CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.40	27.58	6.69	34.98	92.98	92.27	74.00	-18.27	Peak
2	2483.52	27.58	6.71	35.11	45.32	44.50	54.00	9.50	Average
3	2483.52	27.58	6.71	35.11	55.80	54.98	74.00	19.02	Peak
4	2483.92	27.58	6.71	35.11	45.72	44.90	54.00	9.10	Average
5	2483.92	27.58	6.71	35.11	56.12	55.30	74.00	18.70	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 23
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2340.30	27.70	6.56	34.59	34.87	34.54	74.00	39.46	Peak
2	2390.00	27.64	6.62	34.62	36.09	35.73	74.00	38.27	Peak
3	2400.00	27.61	6.62	34.64	48.55	48.14	74.00	25.86	Peak
4	2415.44	27.60	6.64	34.64	87.08	86.68	74.00	-12.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 24
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH1 2412TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2349.66	27.70	6.56	34.57	33.76	33.45	74.00	40.55	Peak
2	2390.00	27.64	6.62	34.62	37.87	37.51	74.00	36.49	Peak
3	2400.00	27.61	6.62	34.64	48.68	48.27	74.00	25.73	Peak
4	2412.84	27.60	6.64	34.64	87.91	87.51	74.00	-13.51	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 29
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2469.12	27.58	6.69	34.98	90.96	90.25	74.00	-16.25	Peak
2	2483.52	27.58	6.71	35.11	46.62	45.80	54.00	8.20	Average
3	2483.52	27.58	6.71	35.11	57.49	56.67	74.00	17.33	Peak
4	2484.08	27.58	6.71	35.11	45.22	44.40	54.00	9.60	Average
5	2484.08	27.58	6.71	35.11	56.41	55.59	74.00	18.41	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 30
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT20 CH13 2472TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.60	27.58	6.69	34.98	86.15	85.44	74.00	-11.44	Peak
2	2483.52	27.58	6.71	35.11	51.92	51.10	74.00	22.90	Peak
3	2484.20	27.58	6.71	35.11	50.38	49.56	74.00	24.44	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : site Data no. : 33
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.64	6.62	34.62	43.40	43.04	54.00	10.96	Average
2	2390.00	27.64	6.62	34.62	53.27	52.91	74.00	21.09	Peak
3	2400.05	27.61	6.62	34.64	44.81	44.40	54.00	9.60	Average
4	2400.05	27.61	6.62	34.64	59.66	59.25	74.00	14.75	Peak
5	2426.75	27.60	6.66	34.74	90.79	90.31	74.00	-16.31	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 34
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH3 2422TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2382.20	27.64	6.60	34.62	45.82	45.44	74.00	28.56	Peak
2	2390.00	27.64	6.62	34.62	45.83	45.47	74.00	28.53	Peak
3	2400.05	27.61	6.62	34.64	53.96	53.55	74.00	20.45	Peak
4	2414.30	27.60	6.64	34.64	85.87	85.47	74.00	-11.47	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 39
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH9 2462TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2454.28	27.59	6.69	34.98	89.63	88.93	74.00	-14.93	Peak
2	2483.50	27.58	6.71	35.11	48.42	47.60	54.00	6.40	Average
3	2483.50	27.58	6.71	35.11	65.79	64.97	74.00	9.03	Peak
4	2484.10	27.58	6.71	35.11	50.22	49.40	54.00	4.60	Average
5	2484.10	27.58	6.71	35.11	68.21	67.39	74.00	6.61	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 966 1# chamber Data no. : 40
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : 360 Smart Camera
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : D503
 Test Mode : IEEE 802.11n HT40 CH9 2462TX

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.40	27.58	6.69	34.98	94.36	93.65	74.00	-19.65	Peak
2	2483.50	27.58	6.71	35.11	49.72	48.90	54.00	5.10	Average
3	2483.50	27.58	6.71	35.11	67.12	66.30	74.00	7.70	Peak
4	2483.98	27.58	6.71	35.11	50.22	49.40	54.00	4.60	Average
5	2483.98	27.58	6.71	35.11	69.12	68.30	74.00	5.70	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

6 6dB & 20dB Bandwidth Test

6.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

6.2 Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set resolution bandwidth (RBW) = 100 kHz.
 - (2). Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - (3). Detector = Peak.
 - (4). Trace mode = max hold.
 - (5). Sweep = auto couple.
 - (6). Allow the trace to stabilize.
 - (7). Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


6.3 Test Result

EUT: 360 Smart Camera			
M/N: D503			
Test date: 2016-06-20		Tested by: Tony.Tang	Test site: RF Site
Test Mode	CH	6dB bandwidth (MHz)	Limit (KHz)
IEEE 802.11 b	CH1	10.076	>500
	CH7	10.069	>500
	CH13	10.070	>500
IEEE 802.11 g	CH1	16.614	>500
	CH7	16.617	>500
	CH13	16.584	>500
IEEE 802.11 n HT 20	CH1	17.831	>500
	CH7	17.834	>500
	CH13	17.832	>500
IEEE 802.11 n HT 40	CH1	36.309	>500
	CH5	36.343	>500
	CH9	36.346	>500
Conclusion : PASS			


EUT: 360 Smart Camera			
M/N: D503			
Test date: 2016-06-20		Tested by: Tony.Tang	Test site: RF Site
Test Mode	CH	20dB bandwidth (MHz)	Limit (KHz)
IEEE 802.11 b	CH1	17.297	/
	CH7	17.292	/
	CH13	17.301	/
IEEE 802.11 g	CH1	18.988	/
	CH7	18.908	/
	CH13	19.096	/
IEEE 802.11 n HT 20	CH1	20.259	/
	CH7	20.283	/
	CH13	20.351	/
IEEE 802.11 n HT 40	CH1	40.146	/
	CH5	40.116	/
	CH9	40.214	/
Conclusion : PASS			

6.4 6dB Test Data

Test Mode: IEEE 802.11b 2412MHz



Test Mode: IEEE 802.11b 2442MHz



Test Mode: IEEE 802.11b 2472MHz

Agilent

Ch Freq 2.472 GHz Trig Free

Occupied Bandwidth

Center 2.472 GHz Span 40 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

14.9422 MHz x dB -6.00 dB

Transmit Freq Error -2.591 kHz

x dB Bandwidth 10.070 MHz

Freq/Channel

Center Freq 2.47200000 GHz

Start Freq 2.45200000 GHz

Stop Freq 2.49200000 GHz

CF Step 4.00000000 MHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track
On Off

Test Mode: IEEE 802.11g 2412MHz

Agilent

Freq/Channel
 Center Freq 2.41200000 GHz
 Start Freq 2.39200000 GHz
 Stop Freq 2.43200000 GHz
 CF Step 4.00000000 MHz
 Auto Man
 Freq Offset 0.00000000 Hz
 Signal Track On Off

Ch Freq 2.412 GHz Trig Free

Occupied Bandwidth

Center 2.412 GHz Span 40 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
16.4689 MHz	x dB	-6.00 dB
Transmit Freq Error	-27.166 kHz	
x dB Bandwidth	16.614 MHz	

Test Mode: IEEE 802.11g 2442MHz

Agilent

Freq/Channel
 Center Freq 2.44200000 GHz
 Start Freq 2.42200000 GHz
 Stop Freq 2.46200000 GHz
 CF Step 4.00000000 MHz
 Auto Man
 Freq Offset 0.00000000 Hz
 Signal Track On Off

Ch Freq 2.442 GHz Trig Free

Occupied Bandwidth

Center 2.442 GHz Span 40 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
16.4692 MHz	x dB	-6.00 dB
Transmit Freq Error	-19.188 kHz	
x dB Bandwidth	16.617 MHz	

Test Mode: IEEE 802.11g 2472MHz

Agilent

Ch Freq 2.472 GHz Trig Free

Occupied Bandwidth

Center 2.472 GHz Span 40 MHz
 #Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Freq/Channel

Center Freq 2.47200000 GHz

Start Freq 2.45200000 GHz

Stop Freq 2.49200000 GHz

CF Step 4.00000000 MHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Occupied Bandwidth	Occ BW % Pwr 99.00 %
16.4593 MHz	x dB -6.00 dB
Transmit Freq Error -7.887 kHz	
x dB Bandwidth 16.584 MHz	

Test Mode: IEEE 802.11n HT20 2412MHz

Agilent

Ch Freq 2.412 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak

Log 10 dB

Center 2.412 GHz Span 40 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

17.6343 MHz x dB -6.00 dB

Transmit Freq Error 620.019 Hz

x dB Bandwidth 17.831 MHz

Freq/Channel

Center Freq 2.41200000 GHz

Start Freq 2.39200000 GHz

Stop Freq 2.43200000 GHz

CF Step 4.00000000 MHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Test Mode: IEEE 802.11n HT20 2442MHz

Agilent

Ch Freq 2.442 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak

Log 10 dB

Center 2.442 GHz Span 40 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

17.6371 MHz x dB -6.00 dB

Transmit Freq Error -3.126 kHz

x dB Bandwidth 17.834 MHz

Freq/Channel

Center Freq 2.44200000 GHz

Start Freq 2.42200000 GHz

Stop Freq 2.46200000 GHz

CF Step 4.00000000 MHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Test Mode: IEEE 802.11n HT20 2472MHz

Agilent

Ch Freq 2.472 GHz Trig Free

Occupied Bandwidth

Center 2.472 GHz Span 40 MHz
#Res BW 100 kHz #VBW 300 kHz Sweep 4.144 ms (401 pts)

Freq/Channel

Center Freq 2.47200000 GHz

Start Freq 2.45200000 GHz

Stop Freq 2.49200000 GHz

CF Step 4.00000000 MHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Occupied Bandwidth Occ BW % Pwr 99.00 %
17.6382 MHz x dB -6.00 dB

Transmit Freq Error -117.385 Hz
x dB Bandwidth 17.832 MHz

Test Mode: IEEE 802.11n HT40 2422MHz

Agilent

Freq/Channel

Ch Freq 2.422 GHz
Trig Free

Occupied Bandwidth

Ref 10 dBm
Atten 20 dB

Center 2.422 GHz
Span 50 MHz

#Res BW 100 kHz
#VBW 300 kHz
Sweep 5.18 ms (401 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
35.7609 MHz	x dB	-6.00 dB
Transmit Freq Error	35.912 kHz	
x dB Bandwidth	36.309 MHz	

Signal Track

On Off

Test Mode: IEEE 802.11n HT40 2442MHz

Agilent

Freq/Channel

Ch Freq 2.442 GHz
Trig Free

Occupied Bandwidth

Ref 10 dBm
Atten 20 dB

Center 2.442 GHz
Span 50 MHz

#Res BW 100 kHz
#VBW 300 kHz
Sweep 5.18 ms (401 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
35.8099 MHz	x dB	-6.00 dB
Transmit Freq Error	26.873 kHz	
x dB Bandwidth	36.343 MHz	

Signal Track

On Off

Test Mode: IEEE 802.11n HT40 2462MHz

Agilent

Ch Freq 2.462 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak Log 10 dB/

Center 2.462 GHz Span 50 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 5.18 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

35.8155 MHz

x dB -6.00 dB

Transmit Freq Error 18.202 kHz

x dB Bandwidth 36.346 MHz

Freq/Channel

Center Freq 2.46200000 GHz

Start Freq 2.43700000 GHz

Stop Freq 2.48700000 GHz

CF Step 5.00000000 MHz


Auto Man

Freq Offset 0.00000000 Hz


Signal Track On Off

6.5 20dB Test Data

Test Mode: IEEE 802.11b 2412MHz



Test Mode: IEEE 802.11b 2442MHz



Test Mode: IEEE 802.11b 2472MHz

Agilent

Freq/Channel
 Center Freq
2.47200000 GHz
 Start Freq
2.45200000 GHz
 Stop Freq
2.49200000 GHz
 CF Step
4.00000000 MHz
Auto Man
 Freq Offset
0.00000000 Hz
 Signal Track
On Off

Ch Freq 2.472 GHz
 Trig Free
 Occupied Bandwidth


Ref 10 dBm Atten 20 dB

#Peak
Log
10
dB/


Center 2.472 GHz Span 40 MHz
#Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth	Occ BW % Pwr	99.00 %
14.9965 MHz	x dB	-20.00 dB
Transmit Freq Error	21.659 kHz	
x dB Bandwidth	17.301 MHz	

Test Mode: IEEE 802.11g 2412MHz



Test Mode: IEEE 802.11g 2442MHz



Test Mode: IEEE 802.11g 2472MHz

Agilent

Ch Freq 2.472 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak Log 10 dB/

Center 2.472 GHz Span 40 MHz

#Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

16.7713 MHz x dB -20.00 dB

Transmit Freq Error -33.002 kHz

x dB Bandwidth 19.096 MHz

Freq/Channel

Center Freq 2.47200000 GHz

Start Freq 2.45200000 GHz

Stop Freq 2.49200000 GHz

CF Step 4.00000000 MHz
Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Test Mode: IEEE 802.11n HT20 2412MHz

Agilent

Freq/Channel
 Center Freq 2.41200000 GHz
 Start Freq 2.39200000 GHz
 Stop Freq 2.43200000 GHz
 CF Step 4.00000000 MHz
 Auto Man
 Freq Offset 0.00000000 Hz
 Signal Track On Off

Ch Freq 2.412 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak Log 10 dB/

Center 2.412 GHz Span 40 MHz
 #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %
17.8769 MHz x dB -20.00 dB

Transmit Freq Error -9.600 kHz
 x dB Bandwidth 20.259 MHz

Test Mode: IEEE 802.11n HT20 2442MHz

Agilent

Freq/Channel
 Center Freq 2.44200000 GHz
 Start Freq 2.42200000 GHz
 Stop Freq 2.46200000 GHz
 CF Step 4.00000000 MHz
 Auto Man
 Freq Offset 0.00000000 Hz
 Signal Track On Off

Ch Freq 2.442 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak Log 10 dB/

Center 2.442 GHz Span 40 MHz
 #Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %
17.8653 MHz x dB -20.00 dB

Transmit Freq Error -7.285 kHz
 x dB Bandwidth 20.283 MHz

Test Mode: IEEE 802.11n HT20 2472MHz

Agilent

Ch Freq 2.472 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak Log 10 dB/

Center 2.472 GHz Span 40 MHz

#Res BW 300 kHz #VBW 1 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

17.8676 MHz x dB -20.00 dB

Transmit Freq Error -12.685 kHz

x dB Bandwidth 20.351 MHz

Freq/Channel

Center Freq 2.47200000 GHz

Start Freq 2.45200000 GHz

Stop Freq 2.49200000 GHz

CF Step 4.00000000 MHz

Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Test Mode: IEEE 802.11n HT40 2422MHz

Agilent

Ch Freq 2.422 GHz Trig Free

Occupied Bandwidth

Center 2.422 GHz Span 80 MHz
#Res BW 1 MHz #VBW 3 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth		Occ BW % Pwr	99.00 %
36.1850 MHz		x dB	-20.00 dB
Transmit Freq Error	162.813 kHz		
x dB Bandwidth	40.146 MHz		

Freq/Channel

Center Freq
2.42200000 GHz

Start Freq
2.38200000 GHz

Stop Freq
2.46200000 GHz

CF Step
8.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

Test Mode: IEEE 802.11n HT40 2442MHz

Agilent

Ch Freq 2.442 GHz Trig Free

Occupied Bandwidth

Center 2.442 GHz Span 80 MHz
#Res BW 1 MHz #VBW 3 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth		Occ BW % Pwr	99.00 %
36.2229 MHz		x dB	-20.00 dB
Transmit Freq Error	178.528 kHz		
x dB Bandwidth	40.116 MHz		

Freq/Channel

Center Freq
2.44200000 GHz

Start Freq
2.40200000 GHz

Stop Freq
2.48200000 GHz

CF Step
8.00000000 MHz
Auto Man

Freq Offset
0.00000000 Hz

Signal Track
On Off

Test Mode: IEEE 802.11n HT40 2462MHz

Agilent

Ch Freq 2.462 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak Log 10 dB/

Center 2.462 GHz Span 80 MHz

#Res BW 1 MHz #VBW 3 MHz Sweep 4 ms (401 pts)

Occupied Bandwidth Occ BW % Pwr 99.00 %

36.2135 MHz

x dB -20.00 dB

Transmit Freq Error 154.381 kHz

x dB Bandwidth 40.214 MHz

Freq/Channel

Center Freq 2.46200000 GHz

Start Freq 2.42200000 GHz

Stop Freq 2.50200000 GHz

CF Step 8.00000000 MHz

Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

7 OUTPUT POWER TEST

7.1 Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

7.2 Test Procedure

7.3 Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device.
- 2, Follow the test procedure as described in KDB 558074
 - (1)Set span to at least 1.5 times the OBW.
 - (2)Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
 - (3)Set VBW $\geq 3 \times$ RBW.
 - (4)Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.)
 - (4)Sweep time = auto.
 - (5)Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
 - (6)If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".
 - (7)Trace average at least 100 traces in power averaging (i.e., RMS) mode.
 - (8)Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.


Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

7.4 Test Result


EUT: 360 Smart Camera			
M/N: D503			
Test date: 2016-06-20		Tested by: Tony.Tang	Test site: RF Site
Pass			
Test Mode	CH	Conducted Power (dBm)	Limit (dBm)
IEEE 802.11 b	CH1	11.93	30
	CH7	12.82	30
	CH13	13.52	30
IEEE 802.11 g	CH1	10.62	30
	CH7	11.25	30
	CH13	12.36	30
IEEE 802.11 n HT 20	CH1	10.43	30
	CH7	11.77	30
	CH13	12.30	30
IEEE 802.11 n HT 40	CH1	9.57	30
	CH5	10.09	30
	CH9	11.08	30
Conclusion : PASS			

7.5 Test Data

Test Mode: IEEE 802.11 b 2412MHz




Test Mode: IEEE 802.11 b 2442MHz




Test Mode: IEEE 802.11 b 2472MHz




Test Mode: IEEE 802.11 g 2412MHz




Test Mode: IEEE 802.11 g 2442MHz




Test Mode: IEEE 802.11 g 2472MHz




Test Mode: IEEE 802.11n HT20 2412MHz




Test Mode: IEEE 802.11 n HT20 2442MHz




Test Mode: IEEE 802.11 n HT20 2472MHz




Test Mode: IEEE 802.11 n HT40 2422MHz



Test Mode: IEEE 802.11 n HT40 2442MHz



Test Mode: IEEE 802.11 n HT40 2462MHz



8 POWER SPECTRAL DENSITY TEST

8.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

8.2 Test Procedure

- 1, Connected the EUT's antenna port to spectrum analyzer device.


- 2, Follow the test procedure as described in KDB 558074
 - (1). Set analyzer center frequency to DTS channel center frequency.
 - (2). Set the span to 1.5 times the DTS bandwidth.
 - (3). Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
 - (4). Set the VBW $\geq 3 \text{ RBW}$.
 - (5). Detector = peak.
 - (6). Sweep time = auto couple.
 - (7). Trace mode = max hold.
 - (8). Allow trace to fully stabilize.
 - (9). Use the peak marker function to determine the maximum amplitude level.
 - (10). If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.3 Test Result


EUT: 360 Smart Camera			
M/N: D503			
Test date: 2016-06-20		Tested by: Tony Tang	Test site: RF site
Pass			
Test Mode	CH	Power density (dBm/3kHz)	Limit (dBm/3kHz)
IEEE 802.11 b	CH1	-16.60	8
	CH7	-15.40	8
	CH13	-14.85	8
IEEE 802.11 g	CH1	-16.53	8
	CH7	-15.23	8
	CH13	-14.08	8
IEEE 802.11 n HT 20	CH1	-16.19	8
	CH7	-15.91	8
	CH13	-14.98	8
IEEE 802.11 n HT 40	CH1	-17.00	8
	CH5	-16.40	8
	CH9	-15.69	8
Conclusion: PASS			

8.4 Test Data


Test Mode: IEEE 802.11b 2412MHz




Test Mode: IEEE 802.11b 2442MHz




Test Mode: IEEE 802.11b 2472MHz




Test Mode: IEEE 802.11g 2412MHz




Test Mode: IEEE 802.11g 2442MHz




Test Mode: IEEE 802.11g 2472MHz




Test Mode: IEEE 802.11n HT20 2412MHz




Test Mode: IEEE 802.11n HT20 2442MHz




Test Mode: IEEE 802.11n HT20 2472MHz




Test Mode: IEEE 802.11n HT40 2422MHz



Test Mode: IEEE 802.11n HT40 2442MHz



Test Mode: IEEE 802.11n HT40 2462MHz



9 ANTENNA REQUIREMENTS

9.1 Limit



For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.2 Result

The antennas used for this product are Internal antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 2.73 dBi.

10 TEST SETUP PHOTO

Conducted Test



Radiated Test (30-1000 MHz)



Radiated Test (1000-25000 MHz)




11 PHOTOS OF EUT

External Photos



M/N: D503



External Photos
M/N: D503




External Photos
M/N: D503




External Photos

M/N: D503





Internal Photos

M/N: D503




Internal Photos

M/N: D503




Internal Photos

M/N: D503



Antenna



Internal Photos

M/N: D503

