

Report No.: T3162022004501 Page: 1 of 23

# **FCC Test Report**

Application No.:	T31620220045EM
Applicant: Address:	POTPOURRI GROUP, INC. 101 Billerica Ave., North Billerica, MA 01862 USA.
Product Information:	
Product Description:	RC Bus
Item No.:	Y161138
Country of Origin:	China
Country of Destination:	United States
Age Grading:	6+
Product Class :	Low Power Communication Device – Transmitter (2.4 GHz)
FCC ID:	2AIY3Y161138
Requirement:	CFR 47 FCC PART 15 SUBPART C, 2016 Intentional Radiators (Section 15.249)
Date of Receipt:	2016-06-21
Date of Test:	2016-07-06 to 2016-07-07, 2017-06-01
Date of Issue:	2017-06-01
Test Result :	PASS*

In the configuration tested, the EUT complied with the requirements for the relevant clauses of Federal Communications Commission Rules as specified above.

Authorized Signature:

**TSANG KA TING, Calvin** 

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

results in this report can be traceable to National or International Standards. This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx.and.for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions.aspx.and.for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions.aspx.and.for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions.Terms-e-Document.aspx. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



# 2 Test Summary

Test	Test Requirement	Test Method	Result			
Conducted Emission (150KHz to 30MHz)			N/A <sup>1)</sup>			
Radiated EmissionFCC PART 15,(9kMHz to 1GHz)SUBPART C: 2016		ANSI C63.10:2013	PASS			
Radiated EmissionFCC PART 15,above 1 GHzSUBPART C: 2016		ANSI C63.10:2013	PASS			
Restricted bands around fundamental frequency (Radiated Emission) FCC PART 15, SUBPART C: 2016		ANSI C63.10:2013	PASS			
Remark :						
1) Please refer to section 6.1 of this report for explanation.						

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



Report No.: T3162022004501 Page: 3 of 23

# 3 Contents

		Page
1	COVER PAGE	1
2	TEST SUMMARY	2
3	CONTENTS	
4	GENERAL INFORMATION	4
	4.1 GENERAL DESCRIPTION OF EUT	4
	4.2 DETAILS OF EUT	4
	4.3 CONDITIONS OF EUT	
	4.4 DESCRIPTION OF SUPPORT UNITS	
	4.5 STANDARDS APPLICABLE FOR TESTING	
	4.6 TEST LOCATION	
	4.7 TEST FACILITY	
	4.8 DEVIATION FROM STANDARDS	
	4.9 ABNORMALITIES FROM STANDARD CONDITIONS	
	4.10 DECLARATION OF FAMILY GROUPING	
	4.12 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	
5	EQUIPMENTS USED DURING TEST	7
6	TEST RESULTS	8
	6.1 CONDUCTED EMISSIONS MAINS TERMINALS, 150KHZ TO 30MHZ	
	6.2 RADIATED EMISSIONS, 9KHZ TO 1GHZ	
	6.2.1 EUT Operation	
	6.2.2 Test Setup and Procedure	
	6.2.3 Measurement Data	
	6.3 RADIATED EMISSIONS ABOVE 1 GHZ	
	6.3.1 EUT Operation	
	6.3.2 Test Setup and Procedure 6.3.3 Measurement Data	
	6.4 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	
_	-	
6.	5 20 DB BANDWIDTH	20
7	PHOTOGRAPHS	
	7.1 RADIATD EMISSION TEST SETUP	
	7.2 EUT CONSTRUCTIONAL DETAILS	

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



# 4 General Information

# 4.1 General Description of EUT

Product Description:	RC Bus
Item No.:	Y161138
Serial No.:	

# 4.2 Details of EUT

Power Supply: Operating Frequency Antenna Type: DC 3V (AA battery x 2 pcs) for TX 2405-2480MHz Unreplaceable internal intergral antenna



Modulation Type:

GFSK

Test frequency tested are the lowest channel: 1 channel (2405MHz), middle channel: 2 channel (2440MHz) and highest channel: 3 channel (2480MHz)

Channel configuration method:

1.Press the power switch of engineering samples to enter test mode (2405, 2440 & 2480MHz).

# 4.3 Conditions of EUT

The received sample was under good condition.

# 4.4 Description of Support Units

1. All field strength measures in this test report were done by the sample which set the frequency with continuous transmission

# 4.5 Standards Applicable for Testing

CFR 47, FCC Part 15, 2016 ANSI C63.10:2013

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



Report No.: T3162022004501 Page: 5 of 23

## 4.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

## 4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### • Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

## 4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

## 4.10 Declaration of Family Grouping

None.

## 4.11 Abbreviations

N/A: Not Applicable EUT: Equipment Under Test

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-e-Document.aspx</a> the term of its intervention on an unisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is and/auf and offenders may be prosecuted to the fullest extent of the law.



# 4.12 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Duty cycle	0.37%
2	Occupied Bandwidth	3%
3	RF conducted power	0.75dB
4	Conducted Spurious emissions	0.75dB
_		4.5dB (30MHz-1GHz)
5	Radiated Spurious emission test	4.8dB (1GHz-25GHz)
6	Temperature test	1°C
7	Humidity test	3%
8	Supply voltages	1.5%
9	Time	3%

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



# 5 Equipments Used during Test

	RE in Chamber							
ltem	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)		
1	3m Semi-Anechoic Chamber	ETS- LINDGREN	N/A	SEM001-01	2017-05-13	2018-05-13		
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2016-09-16	2017-09-16		
3	BiConiLog Antenna (26-3000MHz)	ETS- LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01		
4	Double-ridged horn (1-18GHz)	ETS- LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17		
5	Horn Antenna (18-26GHz)	ETS- LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24		
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2017-04-25	2018-04-25		
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A		
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09		
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13		

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



Report No.: T3162022004501 Page: 8 of 23

# 6 Test Results

# 6.1 Conducted Emissions Mains Terminals, 150kHz to 30MHz

Remark:	
Test Date:	Not Applicable
Test Method:	ANSI C63.10
Test Requirement:	FCC Part15 C

This test is not applicable as the EUT is battery operated.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



# 6.2 Radiated Emissions, 9kHz to 1GHz

Test Requirement:	FCC Part15 Subpart C Section 15.209 and 15.249(d)
Test Method:	ANSI C63.10
Test Date:	2016-07-06, 2017-06-01
Frequency Range:	The lowest frequency generated by EUT, 12MHz to 1GHz
Measurement Distance:	3m
Detector:	Peak for pre-scan
	(200Hz resolution bandwidth and 1kHz video bandwidth for measurement between 9kHz – 150kHz)
	(9kHz resolution bandwidth and 100kHz video bandwidth for measurement between 150kHz – 30MHz)
	120kHz resolution bandwidth and 1MHz video bandwidth for measurement between 30MHz to 1GHz)
	Quasi-Peak if maximised peak within 6dB of limit

Quasi-Peak if maximised peak within 6dB of limit

#### Limit :

	Frequency range MHz	Quasi-peak limits dB (μV/m)		
	0.009 - 0.490	-72.4 – 20logF(MHz)		
	0.490 – 1.705	-12.4 – 20logF(MHz)		
	1.705 – 30.0	-10.5		
	30 to 88	40		
	88 to 216	43.5		
	216 to 960	46		
	Above 960	54		
<ul> <li>Note: 1) At transitional frequencies the lower limit applies.</li> <li>2) F is the frequency of the spurious emission measured in MHz.</li> <li>3) Limit from 0.009 – 30 MHz is converted from measuring distance 300m or 30m to 3m with the formulat provided in FCC Part 15, section 15.31(f)(2)</li> </ul>				

#### 6.2.1 EUT Operation

Operating Environment:

Temperature: 27 °C Humidity: 45 %

EUT Operation: Pre-test with Peak detector with the following mode(s):

- 1: Transmission in continous transmitting mode
- 2. Test in lowest, middle and high frequency


Final test with Quasi-Peak detector with the following mode(s):

- 1: Transmission in continous transmitting mode
- 2. Test in lowest, middle and high frequency

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Documenta.spy">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.sgy</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.



#### 6.2.2 Test Setup and Procedure



- 1. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- 7. Test the EUT in the lowest channel, the middle channel, the Highest channel
- 8. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the Y axis positioning which it is worse case.
- 9. Repeat above procedures until all frequencies measured was complete.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



#### 6.2.3 Measurement Data

#### **Test results:**

#### (1) Operation Frequency : 2405 MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over Limit (dB)
30.875	V	19.0	4.5	23.5	40.0	-16.5
46.250	V	13.3	4.8	18.1	40.0	-21.9
87.875	Н	9.5	5.5	15.0	40.0	-25.0
126.375	V	11.6	5.2	16.8	43.5	-26.7
281.625	Н	13.7	5.6	19.3	46.0	-26.7
651.500	V	20.2	5.0	25.2	46.0	-20.8

#### (2) Operation Frequency : 2440 MHz

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over Limit (dB)
30.188	Н	19.3	3.6	22.9	40.0	-17.1
46.500	V	13.2	4.7	17.9	40.0	-22.1
70.688	V	9.3	5.3	14.6	40.0	-25.4
140.625	V	11.8	5.0	16.8	43.5	-26.7
279.188	V	13.7	5.5	19.2	46.0	-26.8
533.188	V	18.9	5.4	24.3	46.0	-21.7

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



Report No.: T3162022004501 Page: 12 of 23

Frequency (MHz)	Antenna Polarization	Correction Factor (dB/m)	Receiver QP Reading (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over Limit (dB)
30.375	V	19.3	3.5	22.7	40.0	-17.3
45.813	V	13.4	4.9	18.3	40.0	-21.7
78.875	V	9.0	5.4	14.4	40.0	-25.6
139.750	Н	11.8	5.1	16.9	43.5	-26.6
297.125	V	14.0	5.5	19.5	46.0	-26.5
656.188	V	20.3	5.0	25.3	46.0	-20.7

#### (3) Operation Frequency : 2480 MHz

#### Note:

- 1) All readings are Quasi-Peak values.
- 2) Correction Factor = Antenna Factor + Cable Loss.
- 3) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.
- 4) Other emissions more than 20dB below the limit are not shown on the above table and only worst six emissions below 1GHz are listed.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T3162022004501 Page: 13 of 23

## 6.3 Radiated Emissions above 1 GHz

Test Requirement:	FCC Part15 Subpart C Section 15.209 & 15.249(a) & (d)
Test Method:	ANSI C63.10
Test Date:	2016-07-07, 2017-06-01
Frequency Range:	1GHz – 26GHz
Measurement Distance:	3m
Detector:	Peak for pre-scan (1MHz resolution bandwidth, 1MHz video bandwidth)
	Average and Peak detector for final test

#### Limit :

#### Fundamental Frequency :

Frequency range	Limits (Peak)	Limits (Average)
MHz	dB (µV/m)	dB (µV/m)
2400 to 2483.5	114	94

#### Spurious Emission :

Frequency range	Limits (Peak)	Limits (Average)
MHz	dB (µV/m)	dB (µV/m)
Over 1000	74	54

#### 6.3.1 EUT Operation

Operating Environment:

Temperature: 27 °C Humidity: 45 %

EUT Operation: Pre-test with Peak detector with the following mode(s):

1: Transmission in continous transmitting mode

2. Test in lowest, middle and high frequency

Final test with Peak and Avearge detector with the following mode(s):


1: Transmission in continous transmitting mode

2. Test in lowest, middle and high frequency

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document dollgations under the transaction documents. This document cannot be reproduced except in full, without prior written approach of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



#### 6.3.2 Test Setup and Procedure




- 1. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- 7. Test the EUT in the lowest channel, the middle channel, the Highest channel
- 8. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the Y axis positioning which it is worse case.
- 9. Repeat above procedures until all frequencies measured was complete.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



Report No.: T3162022004501 Page: 15 of 23



#### 6.3.3 Measurement Data

According to above plot, the duty cycle of the this device is 100%, plused operation according to C63.10 clause 7.5 is not employed and the average correction calculation is not applied on this report.

Hence, the average measurement is used below setting:

Dectector = peak

 $\mathsf{RBW}=\,\geq\!\mathsf{1MHz}$ 

 $VBW = \ge 1Hz$ 

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-eDocument.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-eDocument.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T3162022004501 Page: 16 of 23

#### Test results :

#### (1) Fundmental Frequency

Frequency	Antenna	Emission Lev	vel (dBµV/m)	Limit (c	lBµV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
2405.0	Н	86.02	83.80	114	94	Pass
2405.0	V	83.18	81.04	114	94	Pass
2440.0	Н	82.32	81.09	114	94	Pass
2440.0	V	86.28	84.05	114	94	Pass
2480.0	Н	84.09	83.65	114	94	Pass
2480.0	V	88.79	87.78	114	94	Pass

#### (1) Spurious Emission

#### **Operation Frequency : 2405.0 MHz**

Frequency	Antenna	Emission Le	vel (dBµV/m)	Limit (d	BµV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
4810.000	Н	51.90	46.84	74	54	Pass
6507.000	Н	44.60	26.69	74	54	Pass
7216.000	Н	49.10	43.88	74	54	Pass
8481.000	Н	48.50	33.60	74	54	Pass
9620.000	V	47.30	32.57	74	54	Pass
12025.000	Н	50.30	35.42	74	54	Pass

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



Frequency	Antenna	Emission Lev	/el (dBµV/m)	Limit (d	BµV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
4881.000	Н	44.80	39.53	74	54	Pass
6327.000	V	44.30	29.26	74	54	Pass
7321.000	V	48.90	42.79	74	54	Pass
8681.000	Н	49.40	34.22	74	54	Pass
9759.000	V	48.60	33.32	74	54	Pass
12203.000	Н	50.40	35.56	74	54	Pass

#### **Operation Frequency : 2440.0 MHz**

#### **Operation Frequency : 2480.0 MHz**

Frequency	Antenna	Emission Lev	vel (dBµV/m)	Limit (d	BµV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	Remark
4960.000	Н	50.00	45.83	74	54	Pass
6284.000	Н	44.00	29.45	74	54	Pass
7440.000	V	52.00	47.09	74	54	Pass
8654.000	V	49.60	34.65	74	54	Pass
9919.000	Н	48.50	35.22	74	54	Pass
12404.000	Н	51.80	36.73	74	54	Pass

Note:

- 1) The above results were the worst case results with the EUT positioned in all 3 axis during the test. The EUT was positioned vertically and horizontally on the table for vertical and horizontal measurement respectively.
- 2) Other emissions more than 20dB below the limit are not shown on the above table and only worst six emissions below 1GHz are listed.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all therir rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approach of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



#### 6.4 Restricted bands around fundamental frequency

Test Requirement:	FCC Part15 Subpart C Section 15.215, 15.249(d)		
Test Method:	ANSI C63.10		
Measurement Distance:	3m		
Detector:	(1MHz resolution bandwidth,	3MHz video bandwidth)	
	Average and Peak detector		
Limit:	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in RSS-Gen, whichever is less stringent.		
		54.0	Average Value
	Above 1GHz	74.0	Peak Value
Test Date:	2016-07-07, 2017-06-01		
EUT Operation:	1: Transmission with GFSK		
Result:	Pass		

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an



#### Test results : (Worst case: Transmissin with GFSK)

Operation frequency : 2405.0 MHz

Frequency	Antenna Emission Level (dBµV/m) Limit (dBµV/m)		Emission Level (dBµV/m)		BµV/m)	Remark
(MHz)	Polarization	Peak	Average	Peak	Average	
2400.0	V	53.22	44.31	74	54	Pass

Operation frequency : 2480.0 MHz

Γ	Frequency	Antenna	Emission Level (dBµV/m)		i) Limit (dBµV/m)		Remark
	(MHz)	Polarization	Peak	Average	Peak	Average	
	2483.5	V	53.64	44.56	74	54	Pass

According to above bandedge measurement, emissions radiated outside of the specified frequency bands, (2400-2483.5)MHz except for harmonics, are below general field strength limits under 15.209 It is deemed to comply with section 15.215 and 15.249(d)

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-eDocument.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-eDocument.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T3162022004501 Page: 20 of 23


# 6.5 20 dB Bandwidth

Test Requirement:	FCC Part15 Subpart C Section 15.215
Test Method:	ANSI C63.10:2013
Test Date:	2016-07-07, 2017-06-01
EUT Operation:	1: Transmission with GFSK

Result:

Pass

## **Test results :** (Worst case: Transmissin with GFSK) Operation frequency : 2405.0 MHz




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspy">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspy</a> the limitation of liability, indemnification and urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.



#### Report No.: T3162022004501 Page: 21 of 23

Operation frequency : 2480.0 MHz



According to above plot, 20dB bandwidth falls in assigned band (2400-2483.5)MHz. It is deemed to comply with section 15.215

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-an




Report No.: T3162022004501 Page: 22 of 23

# 7 Photographs

# 7.1 Radiatd Emission Test Setup





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspy">http://www.sgs.com/en/Terms-and-Conditions.aspy</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspy">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspy</a> the limitation of liability, indemnification and urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T3162022004501 Page: 23 of 23

# 

#### 7.2 EUT Constructional Details



#### - END OF REPORT --

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-en/Conditions/Terms-en/Condit