

	Annex A: System Check
SATIMO	Project Name : X555
	Report Number:
	FCC16083918A-6

I. RESULTS

<u>TYPE</u>	BAND	PARAMETERS
Validation	CW835	Measurement 1: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW835	Measurement 2: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW1800	<u>Measurement 3:</u> Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW1800	<u>Measurement 4:</u> Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW1900	<u>Measurement 5:</u> Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW1900	Measurement 6: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW2450	<u>Measurement 7:</u> Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW2450	Measurement 8: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW2600	Measurement 9: Validation Plane with Dipole device position on Middle Channel in CW mode
Validation	CW2600	Measurement 10: Validation Plane with Dipole device position on Middle Channel in CW mode



HEAD

Type: Validation measurement (Complete)

Date of measurement: 19/8/2016

Measurement duration: 11 minutes 48 seconds

A. Experimental conditions.

<u>Area Scan</u>	dx=12mm dy=12mm
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	40.526699
Relative permittivity (imaginary part)	19.965200
Conductivity (S/m)	0.926163



Variation	(%)
-----------	-----

0.920000



Maximum location: X=-1.00, Y=0.00

SAR Peak: 1.37 W/kg

SAR 10g (W/Kg)	6.10478
SAR 1g (W/Kg)	9.69519





3D screen shot	Hot spot position



BODY

Type: Validation measurement (Complete)

Date of measurement: 19/8/2016

Measurement duration: 11 minutes 47 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	53.439098
Relative permittivity (imaginary part)	21.715401
Conductivity (S/m)	1.007353
Variation (%)	0.760000





Maximum location: X=-1.00, Y=0.00

SAR Peak: 1.47 W/kg

SAR 10g (W/Kg)	6.61623
SAR 1g (W/Kg)	9.49474





3D screen shot	Hot spot position



BODY

Type: Validation measurement (Complete)

Date of measurement: 27/8/2016

Measurement duration: 11 minutes 59 seconds

A. Experimental conditions.

<u>Area Scan</u>	dx=12mm dy=12mm
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW1800</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.054001
Relative permittivity (imaginary part)	14.715600
Conductivity (S/m)	1.471560
Variation (%)	0.070000





Maximum location: X=2.00, Y=-2.00

SAR Peak: 6.88 W/kg

SAR 10g (W/Kg)	19.32362
SAR 1g (W/Kg)	38.05405





3D screen shot	Hot spot position



HEAD

Type: Validation measurement (Complete)

Date of measurement: 27/8/2016

Measurement duration: 12 minutes 2 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW1800</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.970501
Relative permittivity (imaginary part)	14.110600
Conductivity (S/m)	1.411060
Variation (%)	0.430000





Maximum location: X=2.00, Y=-2.00

SAR Peak: 6.44 W/kg

SAR 10g (W/Kg)	20.07012
SAR 1g (W/Kg)	38.65479





3D screen shot	Hot spot position



BODY

Type: Validation measurement (Complete)

Date of measurement: 24/8/2016

Measurement duration: 11 minutes 20 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW1900</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	52.238701
Relative permittivity (imaginary part)	14.662300
Conductivity (S/m)	1.547687
Variation (%)	-0.120000





Maximum location: X=0.00, Y=-1.00

SAR Peak: 7.00 W/kg

SAR 10g (W/Kg)	21.16406
SAR 1g (W/Kg)	39.98718





3D screen shot	Hot spot position



HEAD

Type: Validation measurement (Complete)

Date of measurement: 24/8/2016

Measurement duration: 11 minutes 21 seconds

A. Experimental conditions.

<u>Area Scan</u>	dx=12mm dy=12mm
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW1900</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	40.038701
Relative permittivity (imaginary part)	13.562300
Conductivity (S/m)	1.432807
Variation (%)	-0.060000





Maximum location: X=0.00, Y=-1.00

SAR Peak: 6.84 W/kg

SAR 10g (W/Kg)	21.46633
SAR 1g (W/Kg)	41.50148





3D screen shot	Hot spot position



BODY

Type: Validation measurement (Complete)

Date of measurement: 20/8/2016

Measurement duration: 10 minutes 15 seconds

A. Experimental conditions.

<u>Area Scan</u>	dx=12mm dy=12mm
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	54.220600
Relative permittivity (imaginary part)	14.968800
Conductivity (S/m)	2.037420
Variation (%)	0.050000





Maximum location: X=-2.00, Y=-2.00

SAR Peak: 10.27 W/kg

SAR 10g (W/Kg)	23.83320
SAR 1g (W/Kg)	53.34640





3D screen shot	Hot spot position



HEAD

Type: Validation measurement (Complete)

Date of measurement: 20/8/2016

Measurement duration: 10 minutes 16 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW2450</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	39.274300
Relative permittivity (imaginary part)	13.209200
Conductivity (S/m)	1.797919
Variation (%)	-0.070000





Maximum location: X=-2.00, Y=-2.00

SAR Peak: 9.73 W/kg

SAR 10g (W/Kg)	23.89643
SAR 1g (W/Kg)	53.19294





3D screen shot	Hot spot position



BODY

Type: Validation measurement (Complete)

Date of measurement: 29/8/2016

Measurement duration: 10 minutes 30 seconds

A. Experimental conditions.

<u>Area Scan</u>	dx=12mm dy=12mm
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.593700
Relative permittivity (imaginary part)	15.205400
Conductivity (S/m)	2.196336
Variation (%)	-0.080000





Maximum location: X=-1.00, Y=-1.00

SAR Peak: 11.30 W/kg

SAR 10g (W/Kg)	24.74928
SAR 1g (W/Kg)	50.96026





3D screen shot	Hot spot position



HEAD

Type: Validation measurement (Complete)

Date of measurement: 29/8/2016

Measurement duration: 10 minutes 28 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW2600</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.051800
Relative permittivity (imaginary part)	13.905600
Conductivity (S/m)	2.008587
Variation (%)	-0.120000





Maximum location: X=-1.00, Y=-1.00

SAR Peak: 9.72 W/kg

SAR 10g (W/Kg)	23.06832
SAR 1g (W/Kg)	52.61117





3D screen shot	Hot spot position



BODY

Type: Validation measurement (Complete)

Date of measurement: 25/8/2016

Measurement duration: 12 minutes 1 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=8mm dy=8mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Body
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	55.060299
Relative permittivity (imaginary part)	23.031153
Conductivity (S/m)	0.963555
Variation (%)	0.020000





Maximum location: X=0.00, Y=0.00

SAR Peak: 1.55 W/kg

SAR 10g (W/Kg)	5.541224
SAR 1g (W/Kg)	8.330462





3D screen shot	Hot spot position



HEAD

Type: Validation measurement (Complete)

Date of measurement: 25/8/2016

Measurement duration: 11 minutes 35 seconds

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=8mm dy=8mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete</u>
<u>Phantom</u>	Validation plane
Device Position	Dipole
Band	<u>CW750</u>
<u>Channels</u>	Middle
<u>Signal</u>	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	41.913499
Relative permittivity (imaginary part)	21.935699
Conductivity (S/m)	0.914770
Variation (%)	4.680000





Maximum location: X=0.00, Y=0.00

SAR Peak: 6.96 W/kg

SAR 10g (W/Kg)	5.730560
SAR 1g (W/Kg)	8.660687





3D screen shot	Hot spot position