



# TEST REPORT

**FCC ID: 2AIZN-X620B****Product: Mobile phone****Model No.: X620B****Additional Model No.: N/A****Trade Mark: Infinix****Report No.: FCC18070037A-2.4GWi-Fi****Issued Date: July 27, 2018**

Issued for:

**INFINIX MOBILITY LIMITED****RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17  
CANTON RD TST KLN HONG KONG**

Issued By:

**World Standardization Certification & Testing Group Co., Ltd.****Building A-B, Baoshi Science & Technology Park, Baoshi Road,  
Bao'an District, Shenzhen, Guangdong, China****TEL: +86-755-26996192****FAX: +86-755-86376605**

**Note:** The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group Co.,Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.





## Table of Contents

|   |           |
|---|-----------|
| <b>1. GENERAL INFORMATION</b>                     | <b>3</b>  |
| 1.1.GENERAL DESCRIPTION OF EUT                    | 4         |
| 1.2. FACILITIES AND ACCREDITATIONS                | 5         |
| <b>2. TEST DESCRIPTION</b>                        | <b>6</b>  |
| 2.1 MEASUREMENT UNCERTAINTY                       | 6         |
| 2.2 DESCRIPTION OF TEST MODES                     | 7         |
| 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING  | 8         |
| 2.4 CONFIGURATION OF SYSTEM UNDER TEST            | 8         |
| 2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE) | 8         |
| <b>3. SUMMARY OF TEST RESULTS</b>                 | <b>9</b>  |
| <b>4. MEASUREMENT INSTRUMENTS</b>                 | <b>10</b> |
| <b>5. EMC EMISSION TEST</b>                       | <b>11</b> |
| 5.1 CONDUCTED EMISSION MEASUREMENT                | 11        |
| 5.2 RADIATED EMISSION MEASUREMENT                 | 15        |
| <b>6. ANTENNA APPLICATION</b>                     | <b>28</b> |
| <b>7. 6DB BANDWIDTH MEASUREMENT</b>               | <b>29</b> |
| 7.1 TEST SETUP                                    | 29        |
| 7.2 LIMITS OF 6DB BANDWIDTH MEASUREMENT           | 29        |
| 7.3 TEST PROCEDURE                                | 29        |
| 7.4 TEST RESULT                                   | 29        |
| 8. MAXIMUM CONDUCTED OUTPUT POWER                 | 37        |
| <b>9. POWER SPECTRAL DENSITY MEASUREMENT</b>      | <b>39</b> |
| 9.1 TEST SETUP                                    | 39        |
| 9.2 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT  | 39        |
| 9.3 TEST PROCEDURE                                | 39        |
| 9.4 TEST RESULT                                   | 40        |
| <b>10. OUT OF BAND MEASUREMENT</b>                | <b>47</b> |
| 10.1 TEST SETUP FOR BAND EDGE                     | 47        |
| 10.2 LIMITS OF OUT OF BAND EMISSIONS MEASUREMENT  | 47        |
| 10.3 TEST PROCEDURE                               | 47        |
| 10.4 TEST RESULT                                  | 47        |
| <b>11. EUT TEST PHOTO</b>                         | <b>60</b> |
| <b>12. PHOTOGRAPHS OF EUT</b>                     | <b>62</b> |





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

# 1. GENERAL INFORMATION

|                              |   |
|------------------------------|---|
| <b>Product:</b>              | Mobile phone  |
| <b>Model No.:</b>            | X620B   |
| <b>Additional Model:</b>     | N/A   |
| <b>Applicant:</b>            | INFINIX MOBILITY LIMITED  |
| <b>Address:</b>              | RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST KLN HONG KONG  |
| <b>Manufacturer:</b>         | SHENZHEN TECNO TECHNOLOGY CO.,LTD.  |
| <b>Address:</b>              | 1/F-4/F,7/F, BUILDING 3, TAIPINGYANG INDUSTRIAL ZONE, NO.2088, SHENYAN ROAD, YANTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, P.R.C |
| <b>Data of receipt</b>       | July 16, 2018   |
| <b>Date of Test:</b>         | July 16, 2018 to July 25, 2018  |
| <b>Applicable Standards:</b> | FCC Rules Part15 Subpart C.   |

The above equipment has been tested by World Standardization Certification & Testing Group Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Tested By:** Pushixi  
( Pu Shixi)

**Date:** July 27, 2018

**Check By:** Qin Shuiquan  
( Qin Shuiquan)

**Date:** July 27, 2018

**Approved By:** Wang Fengbing  
(Wang Fengbing)

**Date:** July 27, 2018





### 1.1.GENERAL DESCRIPTION OF EUT

|                          |   |
|--------------------------|---|
| Equipment Type:          | Mobile phone  |
| Test Model:              | X620B   |
| Additional Model:        | N/A   |
| Trade Mark               | Infinix   |
| Applicant:               | INFINIX MOBILITY LIMITED  |
| Address:                 | RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST KLN HONG KONG  |
| Manufacturer:            | SHENZHEN TECNO TECHNOLOGY CO.,LTD.  |
| Address:                 | 1/F-4/F,7/F, BUILDING 3, TAIPINGYANG INDUSTRIAL ZONE, NO.2088, SHENYAN ROAD, YANTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, P.R.C |
| Hardware version:        | V2.1  |
| Software version:        | X620B-Q6361A-O-180702V06  |
| Extreme Temp. Tolerance: | -10°C to +65°C  |
| Battery information:     | Li-Polymer Battery : BL-35BX<br>Voltage: 3.85V<br>Capacity: 3550mAh/3650mAh(min/typ)<br>Limited Charge Voltage: 4.4V                    |
| Adapter Information:     | Adapter: CQ-18VX<br>Input: AC 100-240V 50/60Hz 0.5A<br>Output: DC 5.0V---3.0A/ 9.0V---2.0A/ 12.0V---1.5A                                |
| Operating Frequency      | 2412-2462MHz  |
| Channels                 | 11  |
| Channel Spacing          | 5MHz  |
| Modulation Type          | CCK for IEEE 802.11b<br>OFDM for IEEE 802.11g/n HT-20/n HT-40   |
| Antenna Type:            | Integral Antenna  |
| Antenna gain:            | 0.5dBi  |
| Deviation                | None  |
| Condition of Test Sample | Normal  |



## 1.2. FACILITIES AND ACCREDITATIONS

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group Co., Ltd.**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

**Registration Number: 366353**

### 1.2.1. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

- USA** NVLAP (The certificate registration number is NVLAP LAB CODE:600142-0)
- Japan** VCCI (The certificate registration number is C-4790, R-3684, G-837)
- Canada** INDUSTRY CANADA (The certificated registration number is 7700A-1)
- China** CNAS (The certificated registration number is L3732)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.com>





## 2. TEST DESCRIPTION

### 2.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

| No. | Item                          | Uncertainty             |
|-----|-------------------------------|-------------------------|
| 1   | Conducted Emission Test       | $\pm 3.2\text{dB}$      |
| 2   | RF power, conducted           | $\pm 0.16\text{dB}$     |
| 3   | Spurious emissions, conducted | $\pm 0.21\text{dB}$     |
| 4   | All emissions, radiated(<1G)  | $\pm 4.7\text{dB}$      |
| 5   | All emissions, radiated(>1G)  | $\pm 4.7\text{dB}$      |
| 6   | Temperature                   | $\pm 0.5^\circ\text{C}$ |
| 7   | Humidity                      | $\pm 2\%$               |





## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-------------|
| Mode 1       | 802.11b     |
| Mode 2       | 802.11g     |
| Mode 3       | 802.11n20   |
| Mode 4       | 802.11n40   |

| For Conducted Emission |             |
|------------------------|-------------|
| Final Test Mode        | Description |
| Mode 1                 | 802.11b     |

| For Radiated Emission |             |
|-----------------------|-------------|
| Final Test Mode       | Description |
| Mode 1                | 802.11b     |
| Mode 2                | 802.11g     |
| Mode 3                | 802.11n20   |
| Mode 4                | 802.11n40   |

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3) The data rate was set in 1Mbps, 6 Mbps, 6.5 Mbps and 13.5M for radiated emission due to the highest RF output power.
- (4) Record the worst case of each test item in this report.
- (5) When we test it, the duty cycle  $\geq 98\%$





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

|                          |             |          |          |
|--------------------------|-------------|----------|----------|
| Test software Version    | N/A         |          |          |
| Test program             | ***#2008#** |          |          |
| Frequency(802.11b/g/n20) | 2412 MHz    | 2437 MHz | 2462 MHz |
| Frequency(802.11n40)     | 2422 MHz    | 2437 MHz | 2452 MHz |

### 2.4 CONFIGURATION OF SYSTEM UNDER TEST



(EUT: Mobile phone)

| I/O Port of EUT |      |                          |             |
|-----------------|------|--------------------------|-------------|
| I/O Port Type   | Q'TY | Cable                    | Tested with |
| USB port        | 1    | 1m USB cable, unshielded | 1           |
| Power           | 1    | 1m                       | 1           |


### 2.5 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|------|-----------|-----------|----------------|------------|------|
| 1    | Adapter   | /         | CQ-18VX        | /          | /    |
| 2    | /         | /         | N/A            | /          | /    |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”, “NO” is means “unshielded” “without core”.
- (4) The adapter supply by the applicant.







### 3. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C |   |          |          |
|---------------------------------|---|----------|----------|
| Standard Section                | Test Item   | Judgment | Remark   |
| 15.207                          | Conducted Emission Test   | PASS     | Complies |
| 15.247(a)(2) Limit              | Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System<br>Limit: 6dB bandwidth>500kHz | PASS     | Complies |
| 15.247(b)                       | Maximum peak outputpower<br>Limit: max. 30dBm   | PASS     | Complies |
| 15.109,15.205 & 15.209          | Transmitter Radiated Emission<br>Limit: Table 15.209  | PASS     | Complies |
| 15.247(e)                       | Power Spectral Density<br>Limit: max. 8dBm  | PASS     | Complies |
| 15.247(d)                       | Band edge<br>Limit: 30dB less than Reference level<br>Restricted band limit: Table 15.209             | PASS     | Complies |

NOTE:

(1) "N/A" denotes test is not applicable in this test report.





## 4. MEASUREMENT INSTRUMENTS

| NAME OF EQUIPMENT                    | MANUFACTURER           | MODEL        | SERIAL NUMBER | Calibration Date | Calibration Due. |
|--------------------------------------|------------------------|--------------|---------------|------------------|------------------|
| EMI Test Receiver                    | R&S                    | ESCI         | 100005        | 08/19/2017       | 08/18/2018       |
| LISN                                 | AFJ                    | LS16         | 16010222119   | 08/19/2017       | 08/18/2018       |
| LISN(EUT)                            | Mestec                 | AN3016       | 04/10040      | 08/19/2017       | 08/18/2018       |
| Universal Radio Communication Tester | R&S                    | CMU 200      | 1100.0008.02  | 08/19/2017       | 08/18/2018       |
| Coaxial cable                        | Megalon                | LMR400       | N/A           | 08/12/2017       | 08/11/2018       |
| GPIO cable                           | Megalon                | GPIO         | N/A           | 08/12/2017       | 08/11/2018       |
| Spectrum Analyzer                    | R&S                    | FSU          | 100114        | 08/19/2017       | 08/18/2018       |
| Pre Amplifier                        | H.P.                   | HP8447E      | 2945A02715    | 10/13/2017       | 10/12/2018       |
| Pre-Amplifier                        | CDSI                   | PAP-1G18-38  | --            | 10/13/2017       | 10/12/2018       |
| Bi-log Antenna                       | SUNOL Sciences         | JB3          | A021907       | 09/13/2017       | 09/12/2018       |
| 9*6*6 Anechoic                       | --                     | --           | --            | 08/21/2017       | 08/20/2018       |
| Horn Antenna                         | COMPLIANCE ENGINEERING | CE18000      | --            | 09/13/2017       | 09/12/2018       |
| Horn Antenna                         | SCHWARZBECK            | BBHA9120D    | 9120D-631     | 08/23/2017       | 08/22/2018       |
| Cable                                | TIME MICROWAVE         | LMR-400      | N-TYPE04      | 04/25/2018       | 04/24/2019       |
| System-Controller                    | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Turn Table                           | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| Antenna Tower                        | CCS                    | N/A          | N/A           | N.C.R            | N.C.R            |
| RF cable                             | Murata                 | MXHQ87WA3000 | -             | 08/21/2017       | 08/20/2018       |
| Loop Antenna                         | EMCO                   | 6502         | 00042960      | 08/22/2017       | 08/21/2018       |
| Horn Antenna                         | SCHWARZBECK            | BBHA 9170    | 1123          | 08/19/2017       | 08/18/2018       |
| Power meter                          | Anritsu                | ML2487A      | 6K00003613    | 08/23/2017       | 08/22/2018       |
| Power sensor                         | Anritsu                | MX248XD      | --            | 08/19/2017       | 08/18/2018       |





## 5. EMC EMISSION TEST

### 5.1 CONDUCTED EMISSION MEASUREMENT

#### 5.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |






**5.1.2 TEST PROCEDURE**

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

**5.1.3 DEVIATION FROM TEST STANDARD**

No deviation

**5.1.4 TEST SETUP**



- Note:**
- Support units were connected to second LISN.
  - Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

**5.1.5 EUT OPERATING CONDITIONS**

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

**5.1.6 TEST RESULTS**

|             |         |                   |     |
|-------------|---------|-------------------|-----|
| Temperature | 26 °C   | Relative Humidity | 54% |
| Pressure    | 1010hPa | Phase             | L   |
| Test Mode   | Mode 1  |                   |     |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1   |     | 0.1580       | 35.86                    | 10.44                   | 46.30                    | 65.56         | -19.26     | QP       |
| 2   |     | 0.1580       | 27.15                    | 10.44                   | 37.59                    | 55.56         | -17.97     | AVG      |
| 3   |     | 0.2180       | 21.38                    | 10.43                   | 31.81                    | 52.89         | -21.08     | AVG      |
| 4   |     | 0.2740       | 29.21                    | 10.43                   | 39.64                    | 60.99         | -21.35     | QP       |
| 5   |     | 0.6580       | 25.17                    | 10.38                   | 35.55                    | 46.00         | -10.45     | AVG      |
| 6   |     | 0.6660       | 29.73                    | 10.38                   | 40.11                    | 56.00         | -15.89     | QP       |
| 7   |     | 1.6300       | 24.61                    | 10.31                   | 34.92                    | 56.00         | -21.08     | QP       |
| 8   |     | 1.6300       | 20.73                    | 10.31                   | 31.04                    | 46.00         | -14.96     | AVG      |
| 9   |     | 2.1099       | 21.33                    | 10.29                   | 31.62                    | 46.00         | -14.38     | AVG      |
| 10  |     | 2.3060       | 23.36                    | 10.28                   | 33.64                    | 56.00         | -22.36     | QP       |
| 11  |     | 21.8460      | 35.45                    | 10.11                   | 45.56                    | 60.00         | -14.44     | QP       |
| 12  | *   | 21.8460      | 30.28                    | 10.11                   | 40.39                    | 50.00         | -9.61      | AVG      |


Remark: All the modes have been investigated, and only worst mode is presented in this report.





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

|             |         |                   |     |
|-------------|---------|-------------------|-----|
| Temperature | 26 °C   | Relative Humidity | 54% |
| Pressure    | 1010hPa | Phase             | N   |
| Test Mode   | Mode 1  |                   |     |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1   |     | 0.1539       | 22.89                    | 10.44                   | 33.33                    | 55.78         | -22.45     | AVG      |
| 2   |     | 0.1620       | 31.29                    | 10.44                   | 41.73                    | 65.36         | -23.63     | QP       |
| 3   |     | 0.6620       | 31.49                    | 10.38                   | 41.87                    | 56.00         | -14.13     | QP       |
| 4   |     | 0.6660       | 22.81                    | 10.38                   | 33.19                    | 46.00         | -12.81     | AVG      |
| 5   |     | 1.3180       | 23.27                    | 10.32                   | 33.59                    | 56.00         | -22.41     | QP       |
| 6   |     | 1.6460       | 15.15                    | 10.31                   | 25.46                    | 46.00         | -20.54     | AVG      |
| 7   |     | 2.1180       | 14.93                    | 10.29                   | 25.22                    | 46.00         | -20.78     | AVG      |
| 8   |     | 2.3260       | 22.83                    | 10.28                   | 33.11                    | 56.00         | -22.89     | QP       |
| 9   |     | 11.7020      | 10.95                    | 10.18                   | 21.13                    | 50.00         | -28.87     | AVG      |
| 10  |     | 11.7500      | 20.81                    | 10.18                   | 30.99                    | 60.00         | -29.01     | QP       |
| 11  |     | 22.3940      | 36.99                    | 10.11                   | 47.10                    | 60.00         | -12.90     | QP       |
| 12  | *   | 22.3940      | 27.64                    | 10.11                   | 37.75                    | 50.00         | -12.25     | AVG      |

Remark: All the modes have been investigated, and only worst mode is presented in this report.





## 5.2 RADIATED EMISSION MEASUREMENT

### 5.2.1 Radiated Emission Limits (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490       | 2400/F(KHz)                       | 300                           |
| 0.490~1.705       | 24000/F(KHz)                      | 30                            |
| 1.705~30.0        | 30                                | 30                            |
| 30~88             | 100                               | 3                             |
| 88~216            | 150                               | 3                             |
| 216~960           | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                    | Setting   |
|---------------------------------------|---|
| Attenuation                           | Auto  |
| Start Frequency                       | 1000 MHz  |
| Stop Frequency                        | 10th carrier harmonic                           |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 1Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

**5.2.2 TEST PROCEDURE**

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

***Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported***

**5.2.3 DEVIATION FROM TEST STANDARD**

No deviation









For Question, Please Contact with WSCT www.wsct-cert.com

5.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz





(C) Radiated Emission Test-Up Frequency Above 1GHz



5.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.





### 5.2.5.1 RESULTS (Below 30 MHz)

|             |          |                   |        |
|-------------|----------|-------------------|--------|
| Temperature | 20 °C    | Relative Humidity | 48%    |
| Pressure    | 1010 hPa | Test Mode         | Mode 1 |

| Freq.<br>(MHz) | Reading<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | State<br>P/F |
|----------------|---------------------|-------------------|----------------|--------------|
| --             | --                  | --                | --             | P            |
| --             | --                  | --                | --             | P            |

**NOTE:**

No result in this part for margin above 20dB.

Distance extrapolation factor = 40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

**5.2.5.2 TEST RESULTS (Between 30M – 1000 MHz)**

|             |          |                   |            |
|-------------|----------|-------------------|------------|
| Temperature | 20 °C    | Relative Humidity | 48%        |
| Pressure    | 1010 hPa | Polarization :    | Horizontal |
| Test Mode   | Mode 1   |                   |            |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|
| 1   | *   | 31.9546      | 25.67                    | 4.05                    | 29.72                      | 40.00           | -10.28     | QP       |
| 2   |     | 89.5899      | 35.64                    | -5.96                   | 29.68                      | 43.50           | -13.82     | QP       |
| 3   |     | 137.4202     | 33.99                    | -4.12                   | 29.87                      | 43.50           | -13.63     | QP       |
| 4   |     | 195.8220     | 38.35                    | -7.09                   | 31.26                      | 43.50           | -12.24     | QP       |
| 5   |     | 265.6757     | 34.52                    | -3.93                   | 30.59                      | 46.00           | -15.41     | QP       |
| 6   |     | 394.8545     | 30.51                    | -1.55                   | 28.96                      | 46.00           | -17.04     | QP       |

Remark: All the modes have been investigated, and only worst mode is presented in this report.





For Question, Please Contact with WSCT  
www.wsct-cert.com

|             |          |                   |          |
|-------------|----------|-------------------|----------|
| Temperature | 20 °C    | Relative Humidity | 48%      |
| Pressure    | 1010 hPa | Polarization :    | Vertical |
| Test Mode   | Mode 1   |                   |          |



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measurement dBuV/m | Limit dBuV/m | Over dB | Detector |
|-----|-----|-----------|--------------------|-------------------|--------------------|--------------|---------|----------|
| 1   | *   | 43.2017   | 36.18              | -1.33             | 34.85              | 40.00        | -5.15   | QP       |
| 2   | !   | 52.0251   | 40.11              | -5.26             | 34.85              | 40.00        | -5.15   | QP       |
| 3   |     | 60.0691   | 36.09              | -6.22             | 29.87              | 40.00        | -10.13  | QP       |
| 4   | !   | 145.8611  | 42.27              | -4.68             | 37.59              | 43.50        | -5.91   | QP       |
| 5   |     | 178.1327  | 35.62              | -6.93             | 28.69              | 43.50        | -14.81  | QP       |
| 6   |     | 601.4265  | 25.39              | 1.45              | 26.84              | 46.00        | -19.16  | QP       |

Remark: All the modes have been investigated, and only worst mode is presented in this report.





### 5.2.5.3 TEST RESULTS (1GHz to 25GHz)

|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 1 TX |
| Frequency   | 2412MHz  |                   |           |

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|-----------|----------------------|-------|------------------|----|----------|--------|
|             |           | PK                   | AV    | PK               | AV | PK       | AV     |
| 4824        | V         | 58.65                | 39.31 | 74               | 54 | -15.35   | -14.69 |
| 7236        | V         | 58.58                | 40.68 | 74               | 54 | -15.42   | -13.32 |
| 4824        | H         | 59.05                | 39.23 | 74               | 54 | -14.95   | -14.77 |
| 7236        | H         | 58.28                | 39.28 | 74               | 54 | -15.72   | -14.72 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 1 TX |
| Frequency   | 2437MHz  |                   |           |

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|-----------|----------------------|-------|------------------|----|----------|--------|
|             |           | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874        | V         | 60.25                | 40.59 | 74               | 54 | -13.75   | -13.41 |
| 7311        | V         | 58.92                | 40.74 | 74               | 54 | -15.08   | -13.26 |
| 4874        | H         | 59.85                | 39.63 | 74               | 54 | -14.15   | -14.37 |
| 7311        | H         | 59.38                | 40.38 | 74               | 54 | -14.62   | -13.62 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 1 TX |
| Frequency   | 2462MHz  |                   |           |

| Freq.<br>(MHz) | Ant.Pol. | Emission Level(dBuV) |       | Limit<br>3m(dBuV/m) |    | Over(dB) |        |
|----------------|----------|----------------------|-------|---------------------|----|----------|--------|
|                |          | PK                   | AV    | PK                  | AV | PK       | AV     |
| 4924           | V        | 60.97                | 39.77 | 74                  | 54 | -13.03   | -14.23 |
| 7386           | V        | 59.33                | 39.24 | 74                  | 54 | -14.67   | -14.76 |
| 4924           | H        | 58.60                | 39.87 | 74                  | 54 | -15.40   | -14.13 |
| 7386           | H        | 58.39                | 39.39 | 74                  | 54 | -15.61   | -14.61 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

|             |          |                   |          |
|-------------|----------|-------------------|----------|
| Temperature | 20 °C    | Relative Humidity | 48%      |
| Pressure    | 1010 hPa | Test Mode         | Mode2 TX |
| Frequency   | 2412MHz  |                   |          |

| Freq.<br>(MHz) | Ant. Pol. | Emission<br>Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|----------------|-----------|-------------------------|-------|------------------|----|----------|--------|
|                |           | PK                      | AV    | PK               | AV | PK       | AV     |
| 4824           | V         | 60.15                   | 41.48 | 74               | 54 | -13.85   | -12.52 |
| 7236           | V         | 59.68                   | 40.00 | 74               | 54 | -14.32   | -14.00 |
| 4824           | H         | 59.08                   | 39.10 | 74               | 54 | -14.92   | -14.90 |
| 7236           | H         | 58.50                   | 39.50 | 74               | 54 | -15.50   | -14.50 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 2 TX |
| Frequency   | 2437MHz  |                   |           |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|----------|----------------------|-------|------------------|----|----------|--------|
|             |          | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874        | V        | 58.20                | 40.28 | 74               | 54 | -15.80   | -13.72 |
| 7311        | V        | 59.05                | 39.15 | 74               | 54 | -14.95   | -14.85 |
| 4874        | H        | 59.76                | 39.62 | 74               | 54 | -14.24   | -14.38 |
| 7311        | H        | 59.37                | 40.37 | 74               | 54 | -14.63   | -13.63 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
All the x/y/z orientation has been investigated, and only worst case is presented in this report.

|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 2 TX |
| Frequency   | 2462MHz  |                   |           |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|----------|----------------------|-------|------------------|----|----------|--------|
|             |          | PK                   | AV    | PK               | AV | PK       | AV     |
| 4924        | V        | 60.73                | 40.50 | 74               | 54 | -13.27   | -13.50 |
| 7386        | V        | 58.74                | 39.35 | 74               | 54 | -15.26   | -14.65 |
| 4924        | H        | 58.36                | 40.34 | 74               | 54 | -15.64   | -13.66 |
| 7386        | H        | 58.02                | 39.02 | 74               | 54 | -15.98   | -14.98 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
All the x/y/z orientation has been investigated, and only worst case is presented in this report.







|             |          |                   |          |
|-------------|----------|-------------------|----------|
| Temperature | 20 °C    | Relative Humidity | 48%      |
| Pressure    | 1010 hPa | Test Mode         | Mode3 TX |
| Frequency   | 2412MHz  |                   |          |

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|-----------|----------------------|-------|------------------|----|----------|--------|
|             |           | PK                   | AV    | PK               | AV | PK       | AV     |
| 4824        | V         | 60.90                | 41.22 | 74               | 54 | -13.10   | -12.78 |
| 7236        | V         | 59.66                | 39.34 | 74               | 54 | -14.34   | -14.66 |
| 4824        | H         | 58.72                | 39.66 | 74               | 54 | -15.28   | -14.34 |
| 7236        | H         | 58.40                | 39.40 | 74               | 54 | -15.60   | -14.60 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 3 TX |
| Frequency   | 2437MHz  |                   |           |

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|-----------|----------------------|-------|------------------|----|----------|--------|
|             |           | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874        | V         | 59.97                | 40.47 | 74               | 54 | -14.03   | -13.53 |
| 7311        | V         | 58.99                | 39.25 | 74               | 54 | -15.01   | -14.75 |
| 4874        | H         | 58.01                | 39.41 | 74               | 54 | -15.99   | -14.59 |
| 7311        | H         | 58.43                | 39.43 | 74               | 54 | -15.57   | -14.57 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.




 For Question, Please Contact with WSCT  
 www.wsct-cert.com

|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 3 TX |
| Frequency   | 2462MHz  |                   |           |

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|-----------|----------------------|-------|------------------|----|----------|--------|
|             |           | PK                   | AV    | PK               | AV | PK       | AV     |
| 4924        | V         | 60.33                | 40.19 | 74               | 54 | -13.67   | -13.81 |
| 7386        | V         | 58.90                | 40.93 | 74               | 54 | -15.10   | -13.07 |
| 4924        | H         | 59.06                | 40.62 | 74               | 54 | -14.94   | -13.38 |
| 7386        | H         | 59.08                | 40.08 | 74               | 54 | -14.92   | -13.92 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.  
 Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
 All the x/y/z orientation has been investigated, and only worst case is presented in this report.

|             |          |                   |          |
|-------------|----------|-------------------|----------|
| Temperature | 20 °C    | Relative Humidity | 48%      |
| Pressure    | 1010 hPa | Test Mode         | Mode4 TX |
| Frequency   | 2422MHz  |                   |          |

| Freq. (MHz) | Ant. Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|-----------|----------------------|-------|------------------|----|----------|--------|
|             |           | PK                   | AV    | PK               | AV | PK       | AV     |
| 4844        | V         | 58.49                | 41.27 | 74               | 54 | -15.51   | -12.73 |
| 7266        | V         | 59.49                | 39.69 | 74               | 54 | -14.51   | -14.31 |
| 4844        | H         | 58.65                | 40.92 | 74               | 54 | -15.35   | -13.08 |
| 7266        | H         | 59.05                | 40.05 | 74               | 54 | -14.95   | -13.95 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.  
 Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
 All the x/y/z orientation has been investigated, and only worst case is presented in this report.





|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 4 TX |
| Frequency   | 2437MHz  |                   |           |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|----------|----------------------|-------|------------------|----|----------|--------|
|             |          | PK                   | AV    | PK               | AV | PK       | AV     |
| 4874        | V        | 59.09                | 40.13 | 74               | 54 | -14.91   | -13.87 |
| 7311        | V        | 58.47                | 39.60 | 74               | 54 | -15.53   | -14.40 |
| 4874        | H        | 58.51                | 39.94 | 74               | 54 | -15.49   | -14.06 |
| 7311        | H        | 59.60                | 40.60 | 74               | 54 | -14.40   | -13.40 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.

|             |          |                   |           |
|-------------|----------|-------------------|-----------|
| Temperature | 20 °C    | Relative Humidity | 48%       |
| Pressure    | 1010 hPa | Test Mode         | Mode 4 TX |
| Frequency   | 2452MHz  |                   |           |

| Freq. (MHz) | Ant.Pol. | Emission Level(dBuV) |       | Limit 3m(dBuV/m) |    | Over(dB) |        |
|-------------|----------|----------------------|-------|------------------|----|----------|--------|
|             |          | PK                   | AV    | PK               | AV | PK       | AV     |
| 4904        | V        | 58.55                | 40.73 | 74               | 54 | -15.45   | -13.27 |
| 7356        | V        | 58.22                | 39.10 | 74               | 54 | -15.78   | -14.90 |
| 4904        | H        | 58.09                | 40.55 | 74               | 54 | -15.91   | -13.45 |
| 7356        | H        | 58.37                | 39.37 | 74               | 54 | -15.63   | -14.63 |

**Remark:**

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

All the x/y/z orientation has been investigated, and only worst case is presented in this report.





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

## 6. ANTENNA APPLICATION


### 6.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247

FCC part 15C section 15.247 requirements: Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 6.2 Result


The EUT's antenna Integral Antenna, The antenna's gain is 0.5dBi and meets the requirement.





## 7. 6DB BANDWIDTH MEASUREMENT

### 7.1 TEST SETUP



### 7.2 LIMITS OF 6DB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is >500 kHz

### 7.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 7.4 TEST RESULT

6dB Occupied Bandwidth

| Mode        |                         | 802.11b                   | Humidity             |                     | 56% RH     |
|-------------|-------------------------|---------------------------|----------------------|---------------------|------------|
| Temperature |                         | 24 deg. C,                |                      |                     |            |
| Channel     | Channel Frequency (MHz) | Data Transfer Rate (Mbps) | 6 dB Bandwidth (kHz) | Minimum Limit (MHz) | Pass/ Fail |
| 1           | 2412                    | 1                         | 8589.7               | 0.5                 | Pass       |
| 6           | 2437                    | 1                         | 9615.4               | 0.5                 | Pass       |
| 11          | 2462                    | 1                         | 9679.5               | 0.5                 | Pass       |

| Mode        |                         | 802.11g                   | Humidity             |                     | 56% RH     |
|-------------|-------------------------|---------------------------|----------------------|---------------------|------------|
| Temperature |                         | 24 deg. C,                |                      |                     |            |
| Channel     | Channel Frequency (MHz) | Data Transfer Rate (Mbps) | 6 dB Bandwidth (kHz) | Minimum Limit (MHz) | Pass/ Fail |
| 1           | 2412                    | 6                         | 11282.1              | 0.5                 | Pass       |
| 6           | 2437                    | 6                         | 16089.7              | 0.5                 | Pass       |
| 11          | 2462                    | 6                         | 12756.4              | 0.5                 | Pass       |





|             |                         |                           |                      |                     |            |        |  |
|-------------|-------------------------|---------------------------|----------------------|---------------------|------------|--------|--|
| Mode        |                         | 802.11n20                 |                      | Humidity            |            | 56% RH |  |
| Temperature |                         | 24 deg. C,                |                      |                     |            |        |  |
| Channel     | Channel Frequency (MHz) | Data Transfer Rate (Mbps) | 6 dB Bandwidth (kHz) | Minimum Limit (MHz) | Pass/ Fail |        |  |
| 1           | 2412                    | 6.5                       | 11410.3              | 0.5                 | Pass       |        |  |
| 6           | 2437                    | 6.5                       | 17307.7              | 0.5                 | Pass       |        |  |
| 11          | 2462                    | 6.5                       | 12500.0              | 0.5                 | Pass       |        |  |

TESTING  
NVLAP LAB CODE 6001425

For Question,  
Please Contact with WSCT  
www.wsct-cert.com


|             |                         |                           |                      |                     |            |        |  |
|-------------|-------------------------|---------------------------|----------------------|---------------------|------------|--------|--|
| Mode        |                         | 802.11n40                 |                      | Humidity            |            | 56% RH |  |
| Temperature |                         | 24 deg. C,                |                      |                     |            |        |  |
| Channel     | Channel Frequency (MHz) | Data Transfer Rate (Mbps) | 6 dB Bandwidth (kHz) | Minimum Limit (MHz) | Pass/ Fail |        |  |
| 3           | 2422                    | 13.5                      | 16794.9              | 0.5                 | Pass       |        |  |
| 6           | 2437                    | 13.5                      | 14615.4              | 0.5                 | Pass       |        |  |
| 9           | 2452                    | 13.5                      | 17179.5              | 0.5                 | Pass       |        |  |






For Question, Please Contact with WSCT www.wsct-cert.com

802.11b at 1Mbps of CH1



802.11b at 1Mbps of CH6






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### 802.11b at 1Mbps of CH11



### 802.11g at 6Mbps of CH1









For Question, Please Contact with WSCT www.wsct-cert.com

### 802.11g at 6Mbps of CH6




### 802.11g at 6Mbps of CH11






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### 802.11n at HT20 of CH1




### 802.11n at HT20 of CH6






For Question, Please Contact with WSCT www.wsct-cert.com

802.11n at HT20 of CH11



Date: 24.JUL.2018 12:08:05

802.11n at HT40 of CH3




Date: 24.JUL.2018 12:10:05






For Question, Please Contact with WSCT www.wsct-cert.com

802.11n at HT40 of CH6



802.11n at HT40 of CH9





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### 8. MAXIMUM CONDUCTED OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C 15.247(b)


Test Method: KDB 789033 D02 v01r04 Section E.3.a (Method PM)

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure:

1. Connected the EUT's antenna port to measure device by 10dB attenuator.
2. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of Tx on burst.

For Conducted RF test setup



(EUT: Mobile phone)





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Test Data:

| Mode              | Channel/<br>Frequency<br>(MHz) | Maximum conducted<br>output<br>power (dBm) | Limit(dBm) | Pass / Fail |
|-------------------|--------------------------------|--|------------|-------------|
|                   |                                | Meas Power                                 |            |             |
| 802.11b           | 1(2412)                        | 14.28                                      | 30         | Pass        |
|                   | 6(2437)                        | <b>14.36</b>                               | 30         | Pass        |
|                   | 11(2462)                       | 14.24                                      | 30         | Pass        |
| 802.11g           | 1(2412)                        | 13.66                                      | 30         | Pass        |
|                   | 6(2437)                        | 13.68                                      | 30         | Pass        |
|                   | 11(2462)                       | 13.48                                      | 30         | Pass        |
| 802.11n(HT20)     | 1(2412)                        | 13.69                                      | 30         | Pass        |
|                   | 6(2437)                        | 13.08                                      | 30         | Pass        |
|                   | 11(2462)                       | 13.41                                      | 30         | Pass        |
| 802.11n<br>(HT40) | 3(2422)                        | 12.19                                      | 30         | Pass        |
|                   | 6(2437)                        | 12.28                                      | 30         | Pass        |
|                   | 9(2452)                        | 12.30                                      | 30         | Pass        |





## 9. POWER SPECTRAL DENSITY MEASUREMENT

### 9.1 TEST SETUP



### 9.2 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum Power Spectral Density Measurement is 8dBm.

### 9.3 TEST PROCEDURE

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 3 kHz.
3. Set the VBW = 10 kHz.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be  $\leq 8$  dBm.




**9.4 TEST RESULT**

|             |                         |                               |                     |            |  |
|-------------|-------------------------|-------------------------------|---------------------|------------|--|
| Mode        | 802.11b                 |                               | Humidity            | 56% RH     |  |
| Temperature | 24 deg. C,              |                               |                     |            |  |
| Channel     | Channel Frequency (MHz) | Final RF Power Level in (dBm) | Maximum Limit (dBm) | Pass/ Fail |  |
| 1Mbps       |                         |                               |                     |            |  |
| 1           | 2412                    | -12.27                        | 8                   | Pass       |  |
| 6           | 2437                    | -14.59                        | 8                   | Pass       |  |
| 11          | 2462                    | -12.43                        | 8                   | Pass       |  |

For Question, Please Contact with WSCT  
www.wsct-cert.com

|             |                         |                               |                     |            |  |
|-------------|-------------------------|-------------------------------|---------------------|------------|--|
| Mode        | 802.11g                 |                               | Humidity            | 56% RH     |  |
| Temperature | 24 deg. C,              |                               |                     |            |  |
| Channel     | Channel Frequency (MHz) | Final RF Power Level in (dBm) | Maximum Limit (dBm) | Pass/ Fail |  |
| 6Mbps       |                         |                               |                     |            |  |
| 1           | 2412                    | -10.75                        | 8                   | Pass       |  |
| 6           | 2437                    | -15.13                        | 8                   | Pass       |  |
| 11          | 2462                    | -13.17                        | 8                   | Pass       |  |

|             |                         |                               |                     |            |  |
|-------------|-------------------------|-------------------------------|---------------------|------------|--|
| Mode        | 802.11n HT20            |                               | Humidity            | 56% RH     |  |
| Temperature | 24 deg. C,              |                               |                     |            |  |
| Channel     | Channel Frequency (MHz) | Final RF Power Level in (dBm) | Maximum Limit (dBm) | Pass/ Fail |  |
| 6.5Mbps     |                         |                               |                     |            |  |
| 1           | 2412                    | -12.80                        | 8                   | Pass       |  |
| 6           | 2437                    | -16.13                        | 8                   | Pass       |  |
| 11          | 2462                    | -12.64                        | 8                   | Pass       |  |

|             |                         |                               |                     |            |  |
|-------------|-------------------------|-------------------------------|---------------------|------------|--|
| Mode        | 802.11n HT40            |                               | Humidity            | 56% RH     |  |
| Temperature | 24 deg. C,              |                               |                     |            |  |
| Channel     | Channel Frequency (MHz) | Final RF Power Level in (dBm) | Maximum Limit (dBm) | Pass/ Fail |  |
| 13.5Mbps    |                         |                               |                     |            |  |
| 3           | 2422                    | -14.16                        | 8                   | Pass       |  |
| 6           | 2437                    | -14.91                        | 8                   | Pass       |  |
| 9           | 2452                    | -13.12                        | 8                   | Pass       |  |

Remark: All of the modes have been investigated, and only worst mode is presented in this report.








For Question, Please Contact with WSCT www.wsct-cert.com

802.11b at 1Mbps of CH1




802.11b at 1Mbps at CH6






For Question, Please Contact with WSCT www.wsct-cert.com

802.11b at 1Mbps of CH11




802.11g at 6Mbps of CH1






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

802.11g at 6Mbps of CH6




802.11g at 6Mbps of CH11






For Question, Please Contact with WSCT www.wsct-cert.com

802.11n HT20 at 6.5Mbps of CH1



802.11n HT20 at 6.5Mbps of CH6



世标检测认证股份 World Standardization Certification & Testing Group Co.,Ltd.


ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China TEL:86-755-26996143/26996144/26996145/26996192 FAX:86-755-86376605 E-mail:Fengbing.Wang@wsct-cert.com Http:www.wsct-cert.com

Member of the WSCT, INC.




For Question, please Contact with WSCT www.wsct-cert.com

802.11n HT20 at 6.5Mbps of CH11




802.11n HT40 at 13.5Mbps of CH3






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

802.11n HT40 at 13.5Mbps of CH6



802.11n HT40 at 13.5Mbps of CH9




Date: 24.JUL.2018 14:55:22





## 10. OUT OF BAND MEASUREMENT

### 10.1 TEST SETUP FOR BAND EDGE



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

### 10.2 LIMITS OF OUT OF BAND EMISSIONS MEASUREMENT

1. Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

### 10.3 TEST PROCEDURE

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. ( Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz,VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=100 kHz. A conducted measurement used

### 10.4 TEST RESULT

Please see next pages

Note: This is a handheld device. The radiated emissions should be tested under 3-axes position (Lying, Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.




**Radiated measurement:**
**802.11b**

| Indicated              |                                       | result<br>(PK/AV) | Antenna<br>Polar<br>(H/V) | Correction Factor        |                       |                          | FCC Part 15.247                 |                         |                |
|------------------------|---------------------------------------|-------------------|---------------------------|--------------------------|-----------------------|--------------------------|---------------------------------|-------------------------|----------------|
| Frequency<br>(MHz)     | Receiver<br>Reading<br>(dB $\mu$ V/m) |                   |                           | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Pre-Amp.<br>Gain<br>(dB) | Cord.<br>Amp.<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
| Low Channel (2412MHz)  |                                       |                   |                           |                          |                       |                          |                                 |                         |                |
| 2390                   | 31.00                                 | AV                | V                         | 30.3                     | 4.1                   | 33.1                     | 32.30                           | 54                      | 21.70          |
| 2390                   | 30.28                                 | AV                | H                         | 30.3                     | 4.1                   | 33.1                     | 31.58                           | 54                      | 22.42          |
| 2390                   | 40.34                                 | PK                | V                         | 30.3                     | 4.1                   | 33.1                     | 41.64                           | 74                      | 32.36          |
| 2390                   | 42.16                                 | PK                | H                         | 30.3                     | 4.1                   | 33.1                     | 43.46                           | 74                      | 30.54          |
| High Channel (2462MHz) |                                       |                   |                           |                          |                       |                          |                                 |                         |                |
| 2483.5                 | 31.12                                 | AV                | V                         | 31                       | 4.4                   | 32.7                     | 33.82                           | 54                      | 20.18          |
| 2483.5                 | 31.62                                 | AV                | H                         | 31                       | 4.4                   | 32.7                     | 34.32                           | 54                      | 19.68          |
| 2483.5                 | 42.02                                 | PK                | V                         | 31                       | 4.4                   | 32.7                     | 44.72                           | 74                      | 29.28          |
| 2483.5                 | 41.39                                 | PK                | H                         | 31                       | 4.4                   | 32.7                     | 44.09                           | 74                      | 29.91          |

**802.11g**

| Indicated              |                                       | result<br>(PK/AV) | Antenna<br>Polar<br>(H/V) | Correction Factor        |                       |                          | FCC Part 15.247                 |                         |                |
|------------------------|---------------------------------------|-------------------|---------------------------|--------------------------|-----------------------|--------------------------|---------------------------------|-------------------------|----------------|
| Frequency<br>(MHz)     | Receiver<br>Reading<br>(dB $\mu$ V/m) |                   |                           | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Pre-Amp.<br>Gain<br>(dB) | Cord.<br>Amp.<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | Margin<br>(dB) |
| Low Channel (2412MHz)  |                                       |                   |                           |                          |                       |                          |                                 |                         |                |
| 2390                   | 30.01                                 | AV                | V                         | 30.3                     | 4.1                   | 33.1                     | 31.31                           | 54                      | 22.69          |
| 2390                   | 30.03                                 | AV                | H                         | 30.3                     | 4.1                   | 33.1                     | 31.33                           | 54                      | 22.67          |
| 2390                   | 40.58                                 | PK                | V                         | 30.3                     | 4.1                   | 33.1                     | 41.88                           | 74                      | 32.12          |
| 2390                   | 41.51                                 | PK                | H                         | 30.3                     | 4.1                   | 33.1                     | 42.81                           | 74                      | 31.19          |
| High Channel (2462MHz) |                                       |                   |                           |                          |                       |                          |                                 |                         |                |
| 2483.5                 | 31.90                                 | AV                | V                         | 31                       | 4.4                   | 32.7                     | 34.60                           | 54                      | 19.40          |
| 2483.5                 | 30.83                                 | AV                | H                         | 31                       | 4.4                   | 32.7                     | 33.53                           | 54                      | 20.47          |
| 2483.5                 | 40.51                                 | PK                | V                         | 31                       | 4.4                   | 32.7                     | 43.21                           | 74                      | 30.79          |
| 2483.5                 | 40.50                                 | PK                | H                         | 31                       | 4.4                   | 32.7                     | 43.20                           | 74                      | 30.80          |

Note: The BAND EDGE RESTRICTED BANDS emission is too low at least 20dB to the Fundamental.







For Question,  
Please Contact with WSCT  
t.com

**802.11n HT20**

| Indicated              |                           | result (PK/AV) | Antenna Polar (H/V) | Correction Factor  |                 |                    | FCC Part 15.247     |                |             |
|------------------------|---------------------------|----------------|---------------------|--------------------|-----------------|--------------------|---------------------|----------------|-------------|
| Frequency (MHz)        | Receiver Reading (dBμV/m) |                |                     | Ant. Factor (dB/m) | Cable Loss (dB) | Pre-Amp. Gain (dB) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Low Channel (2412MHz)  |                           |                |                     |                    |                 |                    |                     |                |             |
| 2390                   | 34.05                     | AV             | V                   | 30.3               | 4.1             | 33.1               | 35.35               | 54             | 18.65       |
| 2390                   | 34.48                     | AV             | H                   | 30.3               | 4.1             | 33.1               | 35.78               | 54             | 18.22       |
| 2390                   | 50.31                     | PK             | V                   | 30.3               | 4.1             | 33.1               | 51.61               | 74             | 22.39       |
| 2390                   | 51.69                     | PK             | H                   | 30.3               | 4.1             | 33.1               | 52.99               | 74             | 21.01       |
| High Channel (2462MHz) |                           |                |                     |                    |                 |                    |                     |                |             |
| 2483.5                 | 31.73                     | AV             | V                   | 31                 | 4.4             | 32.7               | 34.43               | 54             | 19.57       |
| 2483.5                 | 29.96                     | AV             | H                   | 31                 | 4.4             | 32.7               | 32.66               | 54             | 21.34       |
| 2483.5                 | 41.63                     | PK             | V                   | 31                 | 4.4             | 32.7               | 44.33               | 74             | 29.67       |
| 2483.5                 | 39.27                     | PK             | H                   | 31                 | 4.4             | 32.7               | 41.97               | 74             | 32.03       |

**802.11n HT40**

| Indicated              |                           | result (PK/AV) | Antenna Polar (H/V) | Correction Factor  |                 |                    | FCC Part 15.247     |                |             |
|------------------------|---------------------------|----------------|---------------------|--------------------|-----------------|--------------------|---------------------|----------------|-------------|
| Frequency (MHz)        | Receiver Reading (dBμV/m) |                |                     | Ant. Factor (dB/m) | Cable Loss (dB) | Pre-Amp. Gain (dB) | Cord. Amp. (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| Low Channel (2422MHz)  |                           |                |                     |                    |                 |                    |                     |                |             |
| 2390                   | 37.30                     | AV             | V                   | 30.3               | 4.1             | 33.1               | 38.60               | 54             | 15.40       |
| 2390                   | 36.82                     | AV             | H                   | 30.3               | 4.1             | 33.1               | 38.12               | 54             | 15.88       |
| 2390                   | 55.18                     | PK             | V                   | 30.3               | 4.1             | 33.1               | 56.48               | 74             | 17.52       |
| 2390                   | 54.30                     | PK             | H                   | 30.3               | 4.1             | 33.1               | 55.60               | 74             | 18.40       |
| High Channel (2452MHz) |                           |                |                     |                    |                 |                    |                     |                |             |
| 2483.5                 | 31.91                     | AV             | V                   | 31                 | 4.4             | 32.7               | 34.61               | 54             | 19.39       |
| 2483.5                 | 32.12                     | AV             | H                   | 31                 | 4.4             | 32.7               | 34.82               | 54             | 19.18       |
| 2483.5                 | 46.71                     | PK             | V                   | 31                 | 4.4             | 32.7               | 49.41               | 74             | 24.59       |
| 2483.5                 | 46.91                     | PK             | H                   | 31                 | 4.4             | 32.7               | 49.61               | 74             | 24.39       |

Note: The BAND EDGE RESTRICTED BANDS emission is too low at least 20dB to the Fundamental.






For Question, Please Contact with WSCT www.wsct-cert.com


Band Edges Measurement:

802.11b:

Low channel



High channel







For Question, Please Contact with WSCT www.wsct-cert.com

802.11g:

Low channel



High channel







For Question, Please Contact with WSCT www.wsct-cert.com

802.11n HT20:

Low channel



High channel







For Question, Please Contact with WSCT www.wsct-cert.com

802.11n HT40:

Low channel



High channel







For Question, Please Contact with WSCT www.wsct-cert.com

Conducted measurement: 802.11b:

Low channel




Middle channel






For Question, Please Contact with WSCT www.wsct-cert.com

High channel



802.11g:


Low channel






For Question, Please Contact with WSCT www.wsct-cert.com

Middle channel



High channel









For Question,  
Please Contact with WSCT  
www.wsct-cert.com

802.11n HT20:

### Low channel




### Middle channel






For Question, Please Contact with WSCT www.wsct-cert.com

High channel




802.11n HT40:

Low channel






For Question,  
Please Contact with WSCT  
www.wsct-cert.com



High channel






For Question,  
Please Contact with WSCT  
www.wsct-cert.com

# 11. EUT TEST PHOTO

## CONDUCTED EMISSION TEST




## RADIATED EMISSION TEST (Frequency from 30MHz to 1GHz)





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

### RADIATED EMISSION TEST (Frequency above 1GHz)





For Question,  
Please Contact with WSCT  
[www.wsct-cert.com](http://www.wsct-cert.com)

## 12. PHOTOGRAPHS OF EUT

Refer to test report FCC18070037A-15B

---END OF REPORT---

