



FCC Test Report

APPLICANT : INFINIX MOBILITY LIMITED
EQUIPMENT : Mobile Phone
BRAND NAME : Infinix
MODEL NAME : X623
FCC ID : 2AIZN-X623
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jul. 09, 2018 and testing was completed on Aug. 02, 2018. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

Sporton International (Shenzhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China**



TABLE OF CONTENTS

REVISION HISTORY3

SUMMARY OF TEST RESULT4

1. GENERAL DESCRIPTION.....5

 1.1. Applicant5

 1.2. Manufacturer5

 1.3. Product Feature of Equipment Under Test5

 1.4. Product Specification of Equipment Under Test6

 1.5. Modification of EUT.....7

 1.6. Test Location.....7

 1.7. Applicable Standards7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST8

 2.1. Test Mode8

 2.2. Connection Diagram of Test System9

 2.3. Support Unit used in test configuration and system9

 2.4. EUT Operation Test Setup10

3. TEST RESULT11

 3.1. Test of AC Conducted Emission Measurement11

 3.2. Test of Radiated Emission Measurement15

4. LIST OF MEASURING EQUIPMENT20

5. UNCERTAINTY OF EVALUATION.....21

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 7.33 dB at 0.460 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 7.76 dB at 266.680 MHz



1. General Description

1.1. Applicant

INFINIX MOBILITY LIMITED

RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST
KLN HONG KONG

1.2. Manufacturer

SHENZHEN TECNO TECHNOLOGY CO.,LTD.

1/-4/TH FLOOR,7TH FLOOR, 3RD BUILDING, PACIFIC INDUSTRIAL PARK, NO.2088, SHENYAN
ROAD, YANTIAN DISTRICT, SHENZHEN , GUANGDONG ,CHINA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Infinix
Model Name	X623
FCC ID	2AIZN-X623
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+(16 QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth BR / EDR / LE
IMEI Code	Conduction: 358942090025843/358942090025850 Radiation: 358942090025769/358942090025777
HW Version	2.0
SW Version	X623-QL1819ABCDEF-O-18-626V11
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7: 2622.5 MHz ~ 2687.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS: 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz
Antenna Type	WWAN : Loop Antenna Bluetooth/WLAN/GNSS : IFA Antenna FM: External headset Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK (Uplink) HSDPA/ DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+:16QAM (uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM

Note: GNSS=GPS+BDS



1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	CO01-SZ	251365

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	03CH03-SZ	577730

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + Camera(Rear) + SIM 1
	Mode 2 : GSM 1900 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + Camera(Front) + SIM 2
	Mode 3 : WCDMA Band V Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM 1
	Mode 4 : LTE Band 4 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Data Link with Notebook) + Earphone + GNSS RX + SIM 2
	Mode 5 : LTE Band 7 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + FM RX + SIM 1
Radiated Emissions	Mode 1 : GSM 850 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + Camera(Rear) + SIM 1
	Mode 2 : GSM 1900 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + Camera(Front) + SIM 2
	Mode 3 : WCDMA Band V Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + MPEG4 + SIM 1
	Mode 4 : LTE Band 4 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Data Link with Notebook) + Earphone + GNSS RX + SIM 2
	Mode 5 : LTE Band 7 Idle + Bluetooth Idle + WLAN(2.4G) Idle + SD card + USB Cable (Charging from Adapter) + Earphone + FM RX + SIM 1
Remark:	
<ol style="list-style-type: none"> The worst case of AC is mode 3; only the test data of this mode is reported. The worst case of RE is mode 4; only the test data of this mode is reported. Data Link with Notebook means data application transferred mode between EUT and Notebook. 	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GNSS Station	ADIVIE	MP9000	N/A	N/A	Unshielded, 1.8m
3.	GNSS Station	RACELOGIC	RLLS03-2P	Fcc DoC	N/A	Unshielded, 1.8m
4.	iPod	Apple	MC69029/A	FCC DoC	N/A	N/A
5.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A
6.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
7.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8m
8.	iPod	Apple	MC525 ZP/A	DoC	Shielded, 1.0m	N/A
9.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
10.	SD Card	N/A	MicroSD HC	FCC DoC	N/A	N/A
12.	SD Card	Kingston	3300-10000-078	Fcc DoC	N/A	N/A
13.	FM Base Station	R&S	SMB100A	Fcc DoC	N/A	Shielded, 1.5m



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on FM receiver function to make the EUT receive continuous signals from FM station.
5. Execute "Video player" to play MPEG4 files.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup






3.1.5 Test Result of AC Conducted Emission





Test Engineer :	Zhang Xu	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-SZ
 Condition: FCC 15B_QP LISN_20170907_N NEUTRAL
 Project : 870907
 Mode : Mode 3
 IMEI : 358942090025843/358942090025850

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.21	26.30	-27.10	53.40	16.20	0.03	10.07	Average
2	0.21	41.20	-22.20	63.40	31.10	0.03	10.07	QP
3	0.26	29.61	-21.90	51.51	19.50	0.03	10.08	Average
4	0.26	41.31	-20.20	61.51	31.20	0.03	10.08	QP
5	0.36	30.60	-18.05	48.65	20.50	0.02	10.08	Average
6	0.36	41.00	-17.65	58.65	30.90	0.02	10.08	QP
7	0.46	31.40	-15.27	46.67	21.30	0.02	10.08	Average
8	0.46	42.10	-14.57	56.67	32.00	0.02	10.08	QP
9	0.72	30.30	-15.70	46.00	20.20	0.02	10.08	Average
10	0.72	40.90	-15.10	56.00	30.80	0.02	10.08	QP
11 *	0.83	34.72	-11.28	46.00	24.60	0.03	10.09	Average
12	0.83	43.52	-12.48	56.00	33.40	0.03	10.09	QP



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Reid Huang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#7 is system simulator signal which can be ignored.		




Site : 03CH03-SZ
 Condition : FCC CLASS-B 3m LF47611_CBL6111D_6 HORIZONTAL
 Project : 870907
 Mode : Mode 4

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	80.44	31.10	-8.90	40.00	49.27	13.30	0.93	32.40	---	---	Peak
2	167.74	35.04	-8.46	43.50	49.68	15.90	1.34	31.88	---	---	Peak
3	266.68	38.24	-7.76	46.00	48.95	19.64	1.71	32.06	126	---	51 Peak
4	361.74	37.50	-8.50	46.00	46.56	20.83	2.01	31.90	---	---	Peak
5	480.08	30.67	-15.33	46.00	36.35	23.42	2.34	31.44	---	---	Peak
6	960.23	32.13	-21.87	54.00	32.66	27.21	3.41	31.15	---	---	Peak
7	2132.50	50.09			76.46	27.43	4.75	58.55	---	---	Peak
8	2948.00	42.11	-31.89	74.00	65.94	28.48	6.34	58.65	---	---	Peak
9	4862.00	44.54	-29.46	74.00	63.13	31.15	8.60	58.34	---	---	Peak
10	6938.00	46.67	-27.33	74.00	60.96	34.86	10.06	59.21	---	---	Peak
11	8812.00	49.75	-24.25	74.00	60.76	37.88	10.87	59.76	---	---	Peak
12	10472.00	50.06	-23.94	74.00	59.20	39.97	11.67	60.78	---	---	Peak
13	12892.00	50.52	-23.48	74.00	56.77	40.62	12.61	59.48	137	260	Peak



Test Engineer :	Reid Huang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH03-SZ
 Condition : FCC CLASS-B 3m LF47611_CBL6111D_6 VERTICAL
 Project : 870907
 Mode : Mode 4

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.97	24.29	-15.71	40.00	31.70	24.62	0.57	32.60	---	---	Peak
2	175.50	33.22	-10.28	43.50	48.06	15.53	1.35	31.72	100	258	Peak
3	242.43	29.30	-16.70	46.00	41.78	17.90	1.63	32.01	---	---	Peak
4	299.66	29.68	-16.32	46.00	40.46	19.40	1.82	32.00	---	---	Peak
5	363.68	29.33	-16.67	46.00	38.33	20.88	2.02	31.90	---	---	Peak
6	799.21	33.57	-12.43	46.00	35.97	26.10	3.10	31.60	---	---	Peak
7	2132.50	49.88			76.25	27.43	4.75	58.55	---	---	Peak
8	2944.00	42.12	-31.88	74.00	65.99	28.43	6.34	58.64	---	---	Peak
9	4816.00	46.04	-27.96	74.00	64.69	31.10	8.59	58.34	---	---	Peak
10	6244.00	47.59	-26.41	74.00	63.53	33.12	9.62	58.68	---	---	Peak
11	8882.00	48.92	-25.08	74.00	59.84	37.96	10.90	59.78	---	---	Peak
12	10982.00	49.88	-24.12	74.00	57.15	40.57	11.86	59.70	---	---	Peak
13	11528.00	50.26	-23.74	74.00	56.70	41.14	12.06	59.64	125	246	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 19, 2018	Aug. 02, 2018	Apr. 18, 2019	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 19, 2018	Aug. 02, 2018	Apr. 18, 2019	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Apr. 19, 2018	Aug. 02, 2018	Apr. 18, 2019	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Mar. 29 2018	Aug. 02, 2018	Mar. 28, 2019	Radiation (03CH03-SZ)
LF Amplifier	Burgeon	BPA-530	102210	0.01Hz~3000MHz	Oct. 19, 2017	Aug. 02, 2018	Oct. 18, 2018	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101 800-30-10P-R	1943528	1GHz~18GHz	Oct.19, 2017	Aug. 02, 2018	Oct. 18, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Aug. 02, 2018	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Aug. 02, 2018	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Aug. 02, 2018	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 26, 2017	Jul. 20, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Dec. 26, 2017	Jul. 20, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Nov. 01, 2017	Jul. 20, 2018	Oct. 31, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 18, 2018	Jul. 20, 2018	Jul. 17, 2019	Conduction (CO01-SZ)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6 dB
-------------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
-------------------------------------------------------------------------	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
-------------------------------------------------------------------------	--------