User Manual

Mobile Phone Infinix X657B

FCC ID: 2AIZN-X657B


INFINIX MOBILITY LIMITED

Explosion diagram specification



1	FL(CTP+LCM)	2	fornt housing Assembly
3	PCBA Main	4	Front Camera
5	Back Camera	6	Back Camera
7	Back Camera	8	R CAM Con foams
9	LT sensor Seal rubber	10	Fornt CAM rubber
11	REC con fb	12	MAIN Cop foil
13	Recover	14	FPC REC
15	LT sensor diffuse film	16	UP frame asm
17	Bat cover asm	18	3in1 card holder
19	Rear CAM Lens	20	Fingerchip spacer
21	FP support plate	22	LCM FPC con rubber
23	FP BTBsiliconeLoop	24	Bat con rubber
25	FPC Switch key	26	FP Con foams
27	M1.4xL2.5 SCREW	28	PCBA SUB
29	SPK	30	FPC SPK
31	Battery	32	Moto
33	M1.4xL3.0 SCREW	34	SUB PCB BTB Rubber
35	USB Seal rubber	36	Audio Jack Seal rubber
37	LCM FPC seal mylar	38	coaxial cable
39	SPK frame asm	40	R vice CAM rubber

Know your phone



- Front camera
 Volume + key
 Volume key
 Power key

SIM/SD card installation


- 1. Power off mobile.
- 2. Refer to the following picture for SIM / SD card installation.



Charging the phone

You can charge your device using a charger or by connecting it to the computer using a USB cable (comes with the phone).

- 1. Please remind the front and back of the plug.
- Use only INFINIX charger and cables. Other chargers or cables may damage the device. This will invalidate your phone warranty.



Emergency call

If any emergency arises, dial 112/911 (or other emergency call number) for emergency help.

Due to the nature of cellular networking, the success of emergency call

FCC Warning:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.

The SAR limit of USA (FCC) is 1.6 W/kg averaged over one gram of tissue. Device types X657B (FCC ID: 2AIZN-X657B) has also been tested against this SAR limit. The highest reported SAR values for head, body-worn accessory, and product specific (Hotspot) are 1.00 W/kg, 0.75 W/kg, and 0.81 W/kg respectively. The Max simultaneous SAR is 1.21 W/kg. This device was tested for typical body-worn operations with the back of the handset kept 10mm from the body. To maintain compliance with FCC RF exposure requirements, use accessories that maintain a 10mm separation distance between the user's body and the back of the handset. The use of belt clips, holsters and similar accessories should not contain metallic components in its assembly. The use of accessories that do not satisfy these requirements may not comply with FCC RF exposure requirements, and should be avoided.

50

For 5150-5250 and 5725-5850 frequency band,

Operations in the 5150-5250 and 5725-5850 band are restricted to indoor usage only.

5G

Any emission is maintained within the band of operation under all conditions of normal operation. The max. frequency stability is less than 20ppm.