




Test Data


Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-2.504	30	Pass
NVNT	BLE	2442	Ant1	-1.999	30	Pass
NVNT	BLE	2480	Ant1	-2.551	30	Pass














-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	limit	Verdic
NVNT	BLE	2402	Ant1	0.682	0.5	Pass
NVNT	BLE	2442	Ant1	0.682	0.5	Pass
NVNT	BLE	2480	Ant1	0.68	0.5	Pass













Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	
NVNT	BLE	2402	Ant1	1.048330558	
NVNT	BLE	2442	Ant1	1.051500945	
NVNT	BLE	2480	Ant1	1.053006728	

Project No.: JYTSZR2205049













Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-8.794	8	Pass
NVNT	BLE	2442	Ant1	-8.298	8	Pass
NVNT	BLE	2480	Ant1	-8.876	8	Pass















Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-50.1	-20	Pass
NVNT	BLE	2480	Ant1	-50.72	-20	Pass













Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-43.53	-20	Pass
NVNT	BLE	2442	Ant1	-44.75	-20	Pass
NVNT	BLE	2480	Ant1	-44.14	-20	Pass







