

FCC RF Test Report

(BLE)

Report No.: JYTSZ-R12-2301778
Applicant: INFINIX MOBILITY LIMITED
Address of Applicant: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE
19-25 SHAN MEI STREET FOTAN NT HONGKONG

Equipment Under Test (EUT)

Product Name: Mobile Phone
Model No.: X6851
Trade Mark: Infinix
FCC ID: 2AIZN-X6851
Applicable Standards: FCC CFR Title 47 Part 15C (§15.247)
Date of Sample Receipt: 15 Dec., 2023
Date of Test: 16 Dec., 2023 to Feb 29., 2024
Date of Report Issued: 01 Mar., 2024
Test Result: PASS

Project by: _____

Date: _____

01 Mar., 2024

Reviewed by: _____

Date: _____

01 Mar., 2024

Approved by: _____

Date: _____

01 Mar., 2024

Manager

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	01 Mar., 2024	Original

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents	3
3 General Information	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Test Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions from the Method	5
3.7 Laboratory Facility	5
3.8 Laboratory Location	6
3.9 Test Instruments List	6
4 Measurement Setup and Procedure	9
4.1 Test Channel	9
4.2 Test Setup	9
4.3 Test Procedure	11
5 Test Results	12
5.1 Summary	12
5.1.1 Clause and Data Summary	12
5.1.2 Test Limit	13
5.2 Antenna requirement	14
5.3 AC Power Line Conducted Emission	15
5.4 Emissions in Restricted Frequency Bands	17
5.5 Emissions in Non-restricted Frequency Bands	49

3 General Information

3.1 Client Information

Applicant:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer:	INFINIX MOBILITY LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Factory:	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

3.2 General Description of E.U.T.

Product Name:	Mobile Phone	
Model No.:	X6851	
Operation Frequency:	LE 1M PHY	2402 MHz - 2480 MHz
	LE 2M PHY	2404MHz - 2478MHz
	LE Coded PHY, S=8	2402 MHz - 2480 MHz
	LE Coded PHY, S=2	2402 MHz - 2480 MHz
Channel Numbers:	40	
Channel Separation:	2MHz	
Modulation Technology:	GFSK	
Data Speed:	1 Mbps (LE 1M PHY), 2 Mbps (LE 2M PHY), 125 kbps (LE Coded PHY, S=8), 500 kbps (LE Coded PHY, S=2)	
Antenna Type:	Internal Antenna	
Antenna Gain:	ANT 8: -3.88 dBi (declare by applicant)	
	ANT 13: -1.91 dBi (declare by applicant)	
Antenna transmit mode:	SISO (1TX, 1RX) (with ANT 8 and ANT 13, and they stand alone to transmit)	
Power Supply:	Rechargeable Li-ion Polymer Battery DC3.91V, 4900mAh	
AC Adapter:	Model: U450XSB Input: AC100-240V, 50/60Hz, 1.8A Output: DC 5.0V, 3.0A 15.0W or DC 5.0-10.0V, 4.5A or DC 11.0V, 4.1A 45.0W MAX	
Test Sample Condition:	The test samples were provided in good working order with no visible defects.	

3.3 Test Mode and Test Environment

Test Mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Remark:	
1. For AC power line conducted emission and radiated spurious emission (below 1GHz), pre-scan all data speed, found 1 Mbps (LE 1M PHY) was worse case mode. The report only reflects the test data of worst mode. 2. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes. Just the worst case position (H mode) shown in report.	
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.91Vdc, Extreme: Low 3.45Vdc, High 4.50Vdc
Test Engineer:	Logan Li (Conducted measurement) Kiran Zeng (Radiated measurement)

3.4 Description of Test Auxiliary Equipment

The EUT has been tested as an independent unit.

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	3.57 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	3.14 dB
Radiated Emission (30MHz ~ 200MHz) (3m SAC)	4.6 dB
Radiated Emission (200MHz ~ 1000MHz) (3m SAC)	5.8 dB
Radiated Emission (1GHz ~ 6GHz) (3m FAR)	4.95 dB
Radiated Emission (6GHz ~ 18GHz) (3m FAR)	5.23 dB
Radiated Emission (18GHz ~ 40GHz) (3m FAR)	5.32 dB

Note: All the measurement uncertainty value were shown with a coverage $k=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

3.6 Additions to, Deviations, or Exclusions from the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.
 Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.
 Tel: +86-755-23118282, Fax: +86-755-23116366
 Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	02-09-2023	02-08-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	02-09-2023	02-08-2024
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-10-2023	01-09-2024
				12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	01-11-2023	01-10-2024
				12-27-2023	12-26-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-10-2023	01-09-2024
				12-27-2023	12-26-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	09-25-2023	09-24-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-18-2023	01-17-2024
				01-17-2024	01-16-2025
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Radiated Emission(3m FAR):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m FAR	YUNYI	9m*6m*6m	WXJ097	06-15-2023	06-14-2028
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ097-2	07-13-2023	07-12-2024
Biconical Antenna	Schwarzbeck	VUBA9117	WXJ002-1	07-02-2021	07-01-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ097-3	07-14-2023	07-13-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-3	01-09-2023	01-08-2024
				12-28-2023	12-27-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	01-09-2023	01-08-2024
				12-28-2023	12-27-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-6	01-09-2023	01-08-2024
				12-28-2023	12-27-2024
Pre-amplifier (30MHz ~ 1GHz)	YUNYI	PAM-310N	WXJ097-5	05-14-2023	05-13-2024
Pre-amplifier (1GHz ~ 18GHz)	YUNYI	PAM-118N	WXJ097-6	05-14-2023	05-13-2024
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	01-11-2023	01-10-2024
				12-27-2023	12-26-2024
EMI Test Receiver	Rohde & Schwarz	ESCI3	WXJ003	01-10-2023	01-09-2024
				12-27-2023	12-26-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-10-2023	01-09-2024
				12-27-2023	12-26-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ081-1	06-13-2023	06-12-2024
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-13M	WXG097-1	08-01-2023	07-31-2024
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG097-2	08-01-2023	07-31-2024
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG097-3	08-01-2023	07-31-2024
High Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Low Band Reject Filter Group	Tonscend	JS0806-F	WXJ097-4	N/A	
Test Software	Tonscend	TS+	Version: 5.0.0		
Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	07-05-2023	07-04-2024
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	01-10-2023	01-09-2024
				12-27-2023	12-26-2024
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	01-11-2023	01-10-2024
				12-27-2023	12-26-2024
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	01-18-2023	01-17-2024
				01-17-2024	01-16-2025
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	WXJ004-3	11-01-2023	10-31-2024
Temperature Humidity Chamber	ZHONG ZHI	CZ-A-80D	WXJ032-3	01-09-2023	01-08-2025
Power Detector Box	MWRFTEST	MW100-PSB	WXJ007-4	09-25-2023	09-24-2024
DC Power Supply	Keysight	E3642A	WXJ025-2	N/A	
RF Control Unit	MWRFTEST	MW100-RFCB	WXG006	N/A	
Test Software	MWRFTEST	MTS 8310	Version: 2.0.0.0		

4 Measurement Setup and Procedure

4.1 Test Channel


According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	20	2442	39	2480
1	2404	20	2442	38	2478

Note: For LE 2M PHY, channels 1, 12, 39 have been removed. Therefore, at LE 2M PHY, channels 1, 20, and 38 were selected to correspond to the lowest, middle, and highest channels respectively for testing.

4.2 Test Setup


1) Conducted emission measurement:




Note: The detailed descriptions please refer to Figure 8 of ANSI C63.4:2014.

2) Radiated emission measurement:

Below 1GHz (3m SAC)





4.3 Test Procedure

Test method	Test step
Conducted emission	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Radiated emission	<p>For below 1GHz:</p> <ol style="list-style-type: none"> 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. <p>For above 1GHz:</p> <ol style="list-style-type: none"> 1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	<ol style="list-style-type: none"> 1. The BLE antenna port of EUT was connected to the test port of the test system through an RF cable. 2. The EUT is keeping in continuous transmission mode and tested in all modulation modes. 3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203 15.247 (b)(4)	See Section 5.2	Pass
AC Power Line Conducted Emission	15.207	See Section 5.3	Pass
Conducted Output Power	15.247 (b)(3)	Appendix A – BLE 1M PHY ANT8 Appendix A – BLE 1M PHY ANT13 Appendix B – BLE 2M PHY ANT8 Appendix B – BLE 2M PHY ANT13 Appendix C – BLE Coded PHY, S=2 ANT8 Appendix C – BLE Coded PHY, S=2 ANT13 Appendix D – BLE Coded PHY, S=8 ANT8 Appendix D – BLE Coded PHY, S=8 ANT13	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)		Pass
Power Spectral Density	15.247 (e)		Pass
Band-edge Emission Conduction Spurious Emission	15.247 (d)		Pass
Emissions in Restricted Frequency Bands	15.205 15.247 (d)	See Section 5.4	Pass
Emissions in Non-restricted Frequency Bands	15.209 15.247(d)	See Section 5.5	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

5.1.2 Test Limit


Test items	Limit																														
AC Power Line Conducted Emission	<table border="1"> <thead> <tr> <th rowspan="2">Frequency (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-Peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 – 0.5</td> <td>66 to 56 <small>Note 1</small></td> <td>56 to 46 <small>Note 1</small></td> </tr> <tr> <td>0.5 – 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 – 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>Note 1: The limit level in dBμV decreases linearly with the logarithm of frequency. Note 2: The more stringent limit applies at transition frequencies.</p>	Frequency (MHz)	Limit (dB μ V)		Quasi-Peak	Average	0.15 – 0.5	66 to 56 <small>Note 1</small>	56 to 46 <small>Note 1</small>	0.5 – 5	56	46	5 – 30	60	50																
Frequency (MHz)	Limit (dB μ V)																														
	Quasi-Peak	Average																													
0.15 – 0.5	66 to 56 <small>Note 1</small>	56 to 46 <small>Note 1</small>																													
0.5 – 5	56	46																													
5 – 30	60	50																													
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.																														
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.																														
99% Occupied Bandwidth	N/A																														
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.																														
Band-edge Emission Conduction Spurious Emission	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).																														
Emissions in Restricted Frequency Bands Emissions in Non-restricted Frequency Bands	<table border="1"> <thead> <tr> <th rowspan="2">Frequency (MHz)</th> <th colspan="2">Limit (dBμV/m)</th> <th rowspan="2">Detector</th> </tr> <tr> <th>@ 3m</th> <th>@ 10m</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>40.0</td> <td>30.0</td> <td>Quasi-peak</td> </tr> <tr> <td>88 – 216</td> <td>43.5</td> <td>33.5</td> <td>Quasi-peak</td> </tr> <tr> <td>216 – 960</td> <td>46.0</td> <td>36.0</td> <td>Quasi-peak</td> </tr> <tr> <td>960 – 1000</td> <td>54.0</td> <td>44.0</td> <td>Quasi-peak</td> </tr> </tbody> </table> <p>Note: The more stringent limit applies at transition frequencies.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency</th> <th colspan="2">Limit (dBμV/m) @ 3m</th> </tr> <tr> <th>Average</th> <th>Peake</th> </tr> </thead> <tbody> <tr> <td>Above 1 GHz</td> <td>54.0</td> <td>74.0</td> </tr> </tbody> </table> <p>Note: The measurement bandwidth shall be 1 MHz or greater.</p>	Frequency (MHz)	Limit (dB μ V/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	Frequency	Limit (dB μ V/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0
Frequency (MHz)	Limit (dB μ V/m)		Detector																												
	@ 3m	@ 10m																													
30 – 88	40.0	30.0	Quasi-peak																												
88 – 216	43.5	33.5	Quasi-peak																												
216 – 960	46.0	36.0	Quasi-peak																												
960 – 1000	54.0	44.0	Quasi-peak																												
Frequency	Limit (dB μ V/m) @ 3m																														
	Average	Peake																													
Above 1 GHz	54.0	74.0																													

5.2 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)(4)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<p>15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
E.U.T Antenna:	
<p>The BLE antenna is an Internal antenna which cannot replace by end-user, the best case gain of the antenna: ANT8 is -3.88 dBi and ANT13 is -1.91 dBi. See product internal photos for details.</p>	

5.3 AC Power Line Conducted Emission

Product name:	Mobile Phone	Product model:	X6851
Test by:	Asher	Test mode:	BLE Tx (LE 1M PHY)
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




Trace: 11

	Read	LISN	Aux2	Cable	Limit	Over		
Freq	Level	Factor	Factor	Loss	Line	Limit	Remark	
MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.190	18.73	0.20	9.88	0.03	28.84	54.02	-25.18 Average
2	0.190	26.27	0.20	9.88	0.03	36.38	64.02	-27.64 QP
3	0.541	28.90	0.20	9.88	0.03	39.01	56.00	-16.99 QP
4	0.595	19.68	0.20	9.88	0.02	29.78	46.00	-16.22 Average
5	1.191	24.81	0.20	9.88	0.09	34.98	56.00	-21.02 QP
6	1.331	14.04	0.20	9.88	0.12	24.24	46.00	-21.76 Average
7	3.074	25.06	0.20	9.89	0.07	35.22	56.00	-20.78 QP
8	3.472	12.01	0.20	9.89	0.08	22.18	46.00	-23.82 Average
9	8.683	22.12	0.20	9.91	0.11	32.34	60.00	-27.66 QP
10	18.328	26.25	0.27	9.95	0.15	36.62	60.00	-23.38 QP
11	18.426	13.45	0.27	9.95	0.15	23.82	50.00	-26.18 Average
12	21.715	13.67	0.30	9.98	0.16	24.11	50.00	-25.89 Average

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Mobile Phone	Product model:	X6851
Test by:	Asher	Test mode:	BLE Tx (LE 1M PHY)
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



	Freq	Read Level	LISN Factor	Aux2 Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.198	27.16	0.20	9.88	0.04	37.28	63.71	-26.43	QP
2	0.222	15.98	0.20	9.88	0.03	26.09	52.74	-26.65	Average
3	0.449	21.06	0.20	9.88	0.03	31.17	46.89	-15.72	Average
4	0.585	33.41	0.20	9.88	0.02	43.51	56.00	-12.49	QP
5	0.595	25.20	0.20	9.88	0.02	35.30	46.00	-10.70	Average
6	1.374	29.17	0.25	9.88	0.12	39.42	56.00	-16.58	QP
7	1.800	19.67	0.28	9.88	0.19	30.02	46.00	-15.98	Average
8	2.527	29.95	0.30	9.88	0.13	40.26	56.00	-15.74	QP
9	9.107	29.67	0.37	9.91	0.11	40.06	60.00	-19.94	QP
10	17.383	31.43	0.40	9.95	0.15	41.93	60.00	-18.07	QP
11	17.475	18.89	0.40	9.95	0.15	29.39	50.00	-20.61	Average
12	22.063	17.48	0.38	9.98	0.16	28.00	50.00	-22.00	Average


Remark:

1. Level = Read level + LISN Factor + Cable Loss.

5.4 Emissions in Restricted Frequency Bands

ANT13

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2322.78	25.22	34.14	59.36	74.00	14.64	254	PK	PASS	Vertical	
2	2322.78	12.19	34.14	46.33	54.00	7.67	155	AV	PASS	Vertical	
3	2362.83	12.67	34.19	46.86	54.00	7.14	136	AV	PASS	Vertical	
4	2362.83	25.36	34.19	59.55	74.00	14.45	219	PK	PASS	Vertical	
5	2390.00	23.99	34.13	58.12	74.00	15.88	291	PK	PASS	Vertical	
6	2390.00	12.90	34.13	47.03	54.00	6.97	358	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2329.27	25.83	34.21	60.04	74.00	13.96	301	PK	PASS	Horizontal
2	2329.27	12.35	34.21	46.56	54.00	7.44	293	AV	PASS	Horizontal
3	2363.58	12.72	34.19	46.91	54.00	7.09	30	AV	PASS	Horizontal
4	2363.58	25.07	34.19	59.26	74.00	14.74	256	PK	PASS	Horizontal
5	2390.00	24.65	34.13	58.78	74.00	15.22	38	PK	PASS	Horizontal
6	2390.00	12.65	34.13	46.78	54.00	7.22	211	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2483.50	24.51	34.51	59.02	74.00	14.98	19	PK	PASS	Vertical	
2	2483.50	13.22	34.51	47.73	54.00	6.27	2	AV	PASS	Vertical	
3	2492.19	26.03	34.52	60.55	74.00	13.45	286	PK	PASS	Vertical	
4	2492.19	13.13	34.52	47.65	54.00	6.35	267	AV	PASS	Vertical	
5	2499.38	25.99	34.53	60.52	74.00	13.48	202	PK	PASS	Vertical	
6	2499.38	13.24	34.53	47.77	54.00	6.23	69	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.38	34.51	58.89	74.00	15.11	116	PK	PASS	Horizontal
2	2483.50	13.03	34.51	47.54	54.00	6.46	44	AV	PASS	Horizontal
3	2490.76	25.91	34.52	60.43	74.00	13.57	269	PK	PASS	Horizontal
4	2490.76	13.28	34.52	47.80	54.00	6.20	208	AV	PASS	Horizontal
5	2498.70	25.70	34.53	60.23	74.00	13.77	94	PK	PASS	Horizontal
6	2498.70	13.40	34.53	47.93	54.00	6.07	148	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2319.70	25.79	34.11	59.90	74.00	14.10	175	PK	PASS	Vertical	
2	2319.70	12.37	34.11	46.48	54.00	7.52	38	AV	PASS	Vertical	
3	2354.45	12.47	34.21	46.68	54.00	7.32	68	AV	PASS	Vertical	
4	2354.45	25.74	34.21	59.95	74.00	14.05	268	PK	PASS	Vertical	
5	2390.00	24.55	34.13	58.68	74.00	15.32	136	PK	PASS	Vertical	
6	2390.00	12.60	34.13	46.73	54.00	7.27	201	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2327.28	25.73	34.19	59.92	74.00	14.08	217	PK	PASS	Horizontal
2	2327.28	12.38	34.19	46.57	54.00	7.43	340	AV	PASS	Horizontal
3	2356.94	12.76	34.20	46.96	54.00	7.04	126	AV	PASS	Horizontal
4	2356.94	25.68	34.20	59.88	74.00	14.12	88	PK	PASS	Horizontal
5	2390.00	23.97	34.13	58.10	74.00	15.90	138	PK	PASS	Horizontal
6	2390.00	12.82	34.13	46.95	54.00	7.05	206	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2483.50	24.06	34.51	58.57	74.00	15.43	134	PK	PASS	Vertical	
2	2483.50	13.04	34.51	47.55	54.00	6.45	190	AV	PASS	Vertical	
3	2491.07	26.01	34.52	60.53	74.00	13.47	220	PK	PASS	Vertical	
4	2491.07	13.22	34.52	47.74	54.00	6.26	326	AV	PASS	Vertical	
5	2497.50	25.85	34.53	60.38	74.00	13.62	206	PK	PASS	Vertical	
6	2497.50	13.37	34.53	47.90	54.00	6.10	341	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.94	34.51	59.45	74.00	14.55	47	PK	PASS	Horizontal
2	2483.50	13.02	34.51	47.53	54.00	6.47	196	AV	PASS	Horizontal
3	2490.02	25.92	34.52	60.44	74.00	13.56	62	PK	PASS	Horizontal
4	2490.02	13.22	34.52	47.74	54.00	6.26	184	AV	PASS	Horizontal
5	2498.73	26.37	34.53	60.90	74.00	13.10	358	PK	PASS	Horizontal
6	2498.73	13.39	34.53	47.92	54.00	6.08	24	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2329.36	26.54	34.22	60.76	74.00	13.24	305	PK	PASS	Vertical	
2	2329.36	12.35	34.22	46.57	54.00	7.43	286	AV	PASS	Vertical	
3	2355.40	25.80	34.20	60.00	74.00	14.00	202	PK	PASS	Vertical	
4	2355.40	12.56	34.20	46.76	54.00	7.24	236	AV	PASS	Vertical	
5	2390.00	24.68	34.13	58.81	74.00	15.19	274	PK	PASS	Vertical	
6	2390.00	12.76	34.13	46.89	54.00	7.11	358	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2319.12	25.60	34.11	59.71	74.00	14.29	63	PK	PASS	Horizontal
2	2319.12	12.32	34.11	46.43	54.00	7.57	358	AV	PASS	Horizontal
3	2359.82	12.53	34.20	46.73	54.00	7.27	17	AV	PASS	Horizontal
4	2359.82	25.71	34.20	59.91	74.00	14.09	355	PK	PASS	Horizontal
5	2390.00	24.31	34.13	58.44	74.00	15.56	215	PK	PASS	Horizontal
6	2390.00	12.81	34.13	46.94	54.00	7.06	275	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2483.50	24.27	34.51	58.78	74.00	15.22	240	PK	PASS	Vertical	
2	2483.50	13.00	34.51	47.51	54.00	6.49	176	AV	PASS	Vertical	
3	2492.54	26.37	34.52	60.89	74.00	13.11	240	PK	PASS	Vertical	
4	2492.54	13.30	34.52	47.82	54.00	6.18	290	AV	PASS	Vertical	
5	2498.50	25.97	34.53	60.50	74.00	13.50	290	PK	PASS	Vertical	
6	2498.50	13.18	34.53	47.71	54.00	6.29	31	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	25.33	34.51	59.84	74.00	14.16	166	PK	PASS	Horizontal
2	2483.50	13.18	34.51	47.69	54.00	6.31	249	AV	PASS	Horizontal
3	2490.17	25.74	34.52	60.26	74.00	13.74	294	PK	PASS	Horizontal
4	2490.17	13.10	34.52	47.62	54.00	6.38	322	AV	PASS	Horizontal
5	2498.39	26.78	34.53	61.31	74.00	12.69	322	PK	PASS	Horizontal
6	2498.39	13.19	34.53	47.72	54.00	6.28	3	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2320.72	25.41	34.12	59.53	74.00	14.47	189	PK	PASS	Vertical
2	2320.72	12.35	34.12	46.47	54.00	7.53	174	AV	PASS	Vertical
3	2351.36	12.55	34.21	46.76	54.00	7.24	136	AV	PASS	Vertical
4	2351.36	25.26	34.21	59.47	74.00	14.53	358	PK	PASS	Vertical
5	2390.00	24.46	34.13	58.59	74.00	15.41	136	PK	PASS	Vertical
6	2390.00	12.73	34.13	46.86	54.00	7.14	87	AV	PASS	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2325.23	25.59	34.17	59.76	74.00	14.24	159	PK	PASS	Horizontal
2	2325.23	12.37	34.17	46.54	54.00	7.46	359	AV	PASS	Horizontal
3	2361.32	12.55	34.19	46.74	54.00	7.26	30	AV	PASS	Horizontal
4	2361.32	25.82	34.19	60.01	74.00	13.99	4	PK	PASS	Horizontal
5	2390.00	24.58	34.13	58.71	74.00	15.29	8	PK	PASS	Horizontal
6	2390.00	12.66	34.13	46.79	54.00	7.21	260	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2483.50	24.40	34.51	58.91	74.00	15.09	117	PK	PASS	Vertical	
2	2483.50	12.95	34.51	47.46	54.00	6.54	144	AV	PASS	Vertical	
3	2491.71	26.10	34.52	60.62	74.00	13.38	53	PK	PASS	Vertical	
4	2491.71	13.14	34.52	47.66	54.00	6.34	206	AV	PASS	Vertical	
5	2498.81	25.87	34.53	60.40	74.00	13.60	313	PK	PASS	Vertical	
6	2498.81	13.15	34.53	47.68	54.00	6.32	360	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	25.32	34.51	59.83	74.00	14.17	48	PK	PASS	Horizontal
2	2483.50	13.24	34.51	47.75	54.00	6.25	60	AV	PASS	Horizontal
3	2489.55	27.05	34.52	61.57	74.00	12.43	14	PK	PASS	Horizontal
4	2489.55	13.12	34.52	47.64	54.00	6.36	3	AV	PASS	Horizontal
5	2497.07	26.30	34.52	60.82	74.00	13.18	147	PK	PASS	Horizontal
6	2497.07	13.26	34.52	47.78	54.00	6.22	204	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

ANT8

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2324.10	25.37	34.16	59.53	74.00	14.47	334	PK	PASS	Vertical
2	2324.10	12.40	34.16	46.56	54.00	7.44	360	AV	PASS	Vertical
3	2357.38	12.45	34.20	46.65	54.00	7.35	80	AV	PASS	Vertical
4	2357.38	25.81	34.20	60.01	74.00	13.99	330	PK	PASS	Vertical
5	2390.00	24.67	34.13	58.80	74.00	15.20	175	PK	PASS	Vertical
6	2390.00	12.81	34.13	46.94	54.00	7.06	284	AV	PASS	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2332.18	25.64	34.22	59.86	74.00	14.14	352	PK	PASS	Horizontal
2	2332.18	12.45	34.22	46.67	54.00	7.33	78	AV	PASS	Horizontal
3	2364.33	25.44	34.19	59.63	74.00	14.37	321	PK	PASS	Horizontal
4	2364.33	12.74	34.19	46.93	54.00	7.07	177	AV	PASS	Horizontal
5	2390.00	23.53	34.13	57.66	74.00	16.34	104	PK	PASS	Horizontal
6	2390.00	12.81	34.13	46.94	54.00	7.06	253	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.07	34.51	58.58	74.00	15.42	266	PK	PASS	Vertical
2	2483.50	13.23	34.51	47.74	54.00	6.26	44	AV	PASS	Vertical
3	2490.80	13.13	34.52	47.65	54.00	6.35	288	AV	PASS	Vertical
4	2490.80	25.98	34.52	60.50	74.00	13.50	228	PK	PASS	Vertical
5	2498.88	25.87	34.53	60.40	74.00	13.60	167	PK	PASS	Vertical
6	2498.88	13.17	34.53	47.70	54.00	6.30	70	AV	PASS	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 1M PHY)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.84	34.51	59.35	74.00	14.65	203	PK	PASS	Horizontal
2	2483.50	13.04	34.51	47.55	54.00	6.45	8	AV	PASS	Horizontal
3	2491.09	25.50	34.52	60.02	74.00	13.98	5	PK	PASS	Horizontal
4	2491.09	13.12	34.52	47.64	54.00	6.36	68	AV	PASS	Horizontal
5	2499.10	26.05	34.53	60.58	74.00	13.42	165	PK	PASS	Horizontal
6	2499.10	13.37	34.53	47.90	54.00	6.10	192	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2326.42	25.20	34.19	59.39	74.00	14.61	269	PK	PASS	Vertical	
2	2326.42	12.54	34.19	46.73	54.00	7.27	40	AV	PASS	Vertical	
3	2356.08	12.41	34.20	46.61	54.00	7.39	284	AV	PASS	Vertical	
4	2356.08	25.28	34.20	59.48	74.00	14.52	209	PK	PASS	Vertical	
5	2390.00	23.79	34.13	57.92	74.00	16.08	223	PK	PASS	Vertical	
6	2390.00	12.78	34.13	46.91	54.00	7.09	152	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2326.51	25.21	34.19	59.40	74.00	14.60	80	PK	PASS	Horizontal
2	2326.51	12.41	34.19	46.60	54.00	7.40	8	AV	PASS	Horizontal
3	2362.42	25.56	34.19	59.75	74.00	14.25	43	PK	PASS	Horizontal
4	2362.42	12.88	34.19	47.07	54.00	6.93	304	AV	PASS	Horizontal
5	2390.00	24.02	34.13	58.15	74.00	15.85	345	PK	PASS	Horizontal
6	2390.00	12.67	34.13	46.80	54.00	7.20	247	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2483.50	24.31	34.51	58.82	74.00	15.18	291	PK	PASS	Vertical	
2	2483.50	12.96	34.51	47.47	54.00	6.53	200	AV	PASS	Vertical	
3	2491.12	13.13	34.52	47.65	54.00	6.35	356	AV	PASS	Vertical	
4	2491.12	25.51	34.52	60.03	74.00	13.97	231	PK	PASS	Vertical	
5	2498.73	26.22	34.53	60.75	74.00	13.25	333	PK	PASS	Vertical	
6	2498.73	13.27	34.53	47.80	54.00	6.20	85	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE 2M PHY)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.22	34.51	58.73	74.00	15.27	76	PK	PASS	Horizontal
2	2483.50	13.00	34.51	47.51	54.00	6.49	133	AV	PASS	Horizontal
3	2490.71	13.14	34.52	47.66	54.00	6.34	292	AV	PASS	Horizontal
4	2490.71	25.96	34.52	60.48	74.00	13.52	242	PK	PASS	Horizontal
5	2498.08	26.48	34.53	61.01	74.00	12.99	2	PK	PASS	Horizontal
6	2498.08	13.35	34.53	47.88	54.00	6.12	269	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List											
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity	
1	2327.67	24.83	34.19	59.02	74.00	14.98	143	PK	PASS	Vertical	
2	2327.67	12.54	34.19	46.73	54.00	7.27	242	AV	PASS	Vertical	
3	2363.11	12.44	34.19	46.63	54.00	7.37	355	AV	PASS	Vertical	
4	2363.11	26.33	34.19	60.52	74.00	13.48	93	PK	PASS	Vertical	
5	2390.00	24.25	34.13	58.38	74.00	15.62	261	PK	PASS	Vertical	
6	2390.00	12.74	34.13	46.87	54.00	7.13	222	AV	PASS	Vertical	

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2329.55	25.24	34.22	59.46	74.00	14.54	356	PK	PASS	Horizontal
2	2329.55	12.42	34.22	46.64	54.00	7.36	30	AV	PASS	Horizontal
3	2361.51	12.66	34.19	46.85	54.00	7.15	46	AV	PASS	Horizontal
4	2361.51	24.99	34.19	59.18	74.00	14.82	110	PK	PASS	Horizontal
5	2390.00	24.60	34.13	58.73	74.00	15.27	342	PK	PASS	Horizontal
6	2390.00	12.79	34.13	46.92	54.00	7.08	277	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.66	34.51	59.17	74.00	14.83	70	PK	PASS	Vertical
2	2483.50	13.05	34.51	47.56	54.00	6.44	230	AV	PASS	Vertical
3	2492.26	25.73	34.52	60.25	74.00	13.75	207	PK	PASS	Vertical
4	2492.26	13.19	34.52	47.71	54.00	6.29	272	AV	PASS	Vertical
5	2499.23	26.04	34.53	60.57	74.00	13.43	134	PK	PASS	Vertical
6	2499.23	13.20	34.53	47.73	54.00	6.27	172	AV	PASS	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=2)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	25.15	34.51	59.66	74.00	14.34	8	PK	PASS	Horizontal
2	2483.50	13.17	34.51	47.68	54.00	6.32	169	AV	PASS	Horizontal
3	2492.78	26.10	34.52	60.62	74.00	13.38	294	PK	PASS	Horizontal
4	2492.78	13.16	34.52	47.68	54.00	6.32	57	AV	PASS	Horizontal
5	2498.28	25.96	34.53	60.49	74.00	13.51	136	PK	PASS	Horizontal
6	2498.28	13.20	34.53	47.73	54.00	6.27	290	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2332.28	25.53	34.22	59.75	74.00	14.25	0	PK	PASS	Vertical
2	2332.28	12.50	34.22	46.72	54.00	7.28	113	AV	PASS	Vertical
3	2359.35	12.68	34.20	46.88	54.00	7.12	276	AV	PASS	Vertical
4	2359.35	25.98	34.20	60.18	74.00	13.82	291	PK	PASS	Vertical
5	2390.00	24.54	34.13	58.67	74.00	15.33	29	PK	PASS	Vertical
6	2390.00	12.66	34.13	46.79	54.00	7.21	333	AV	PASS	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2326.92	25.09	34.19	59.28	74.00	14.72	360	PK	PASS	Horizontal
2	2326.92	12.31	34.19	46.50	54.00	7.50	199	AV	PASS	Horizontal
3	2366.40	12.67	34.18	46.85	54.00	7.15	145	AV	PASS	Horizontal
4	2366.40	25.78	34.18	59.96	74.00	14.04	340	PK	PASS	Horizontal
5	2390.00	24.09	34.13	58.22	74.00	15.78	187	PK	PASS	Horizontal
6	2390.00	12.78	34.13	46.91	54.00	7.09	50	AV	PASS	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	26.02	34.51	60.53	74.00	13.47	55	PK	PASS	Vertical
2	2483.50	13.00	34.51	47.51	54.00	6.49	243	AV	PASS	Vertical
3	2492.12	25.63	34.52	60.15	74.00	13.85	311	PK	PASS	Vertical
4	2492.12	13.13	34.52	47.65	54.00	6.35	164	AV	PASS	Vertical
5	2497.58	25.76	34.53	60.29	74.00	13.71	14	PK	PASS	Vertical
6	2497.58	13.16	34.53	47.69	54.00	6.31	63	AV	PASS	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Kiran	Test mode:	BLE Tx (LE Coded PHY, S=8)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 3.91V		



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV]	Factor [dB/m]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Angle [°]	Detector	Verdict	Polarity
1	2483.50	24.92	34.51	59.43	74.00	14.57	105	PK	PASS	Horizontal
2	2483.50	13.06	34.51	47.57	54.00	6.43	162	AV	PASS	Horizontal
3	2491.05	13.15	34.52	47.67	54.00	6.33	23	AV	PASS	Horizontal
4	2491.05	25.94	34.52	60.46	74.00	13.54	41	PK	PASS	Horizontal
5	2496.92	26.06	34.52	60.58	74.00	13.42	30	PK	PASS	Horizontal
6	2496.92	13.28	34.52	47.80	54.00	6.20	252	AV	PASS	Horizontal


Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor).

5.5 Emissions in Non-restricted Frequency Bands

Below 1GHz:

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Robin	Test mode:	BLE Tx (LE 1M PHY)
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	DC 3.91V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	48.6249	28.31	-12.67	15.64	40.00	24.36	PK	Vertical
2	66.7648	31.93	-15.58	16.35	40.00	23.65	PK	Vertical
3	94.2172	28.38	-15.61	12.77	43.50	30.73	PK	Vertical
4	121.087	28.08	-16.90	11.18	43.50	32.32	PK	Vertical
5	249.958	31.46	-13.49	17.97	46.00	28.03	PK	Vertical
6	711.313	30.88	-4.81	26.07	46.00	19.93	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	Mobile Phone	Product Model:	X6851
Test By:	Robin	Test mode:	BLE Tx (LE 1M PHY)
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	DC 3.91V		



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBµV/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Trace	Polarity
1	51.2926	29.57	-12.66	16.91	40.00	23.09	PK	Horizontal
2	62.8361	30.05	-14.55	15.50	40.00	24.50	PK	Horizontal
3	93.6352	29.99	-15.69	14.30	43.50	29.20	PK	Horizontal
4	120.214	29.34	-16.76	12.58	43.50	30.92	PK	Horizontal
5	437.371	30.57	-9.71	20.86	46.00	25.14	PK	Horizontal
6	728.095	31.06	-4.53	26.53	46.00	19.47	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

ANT8:

BLE Tx (LE 1M PHY)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	57.28	-7.66	49.62	74.00	24.38	Vertical
4804.00	57.86	-7.66	50.20	74.00	23.80	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	49.45	-7.66	41.79	54.00	12.21	Vertical
4804.00	50.54	-7.66	42.88	54.00	11.12	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.69	-7.77	49.92	74.00	24.08	Vertical
4884.00	57.39	-7.77	49.62	74.00	24.38	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	49.00	-7.77	41.23	54.00	12.77	Vertical
4884.00	50.97	-7.77	43.20	54.00	10.80	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	57.22	-7.82	49.40	74.00	24.60	Vertical
4960.00	56.92	-7.82	49.10	74.00	24.90	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	49.21	-7.82	41.39	54.00	12.61	Vertical
4960.00	50.74	-7.82	42.92	54.00	11.08	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BLE Tx (LE 2M PHY)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	56.87	-7.66	49.21	74.00	24.79	Vertical
4804.00	57.04	-7.66	49.38	74.00	24.62	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	49.66	-7.66	42.00	54.00	12.00	Vertical
4804.00	50.95	-7.66	43.29	54.00	10.71	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.22	-7.77	49.45	74.00	24.55	Vertical
4884.00	56.62	-7.77	48.85	74.00	25.15	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	49.67	-7.77	41.90	54.00	12.10	Vertical
4884.00	51.23	-7.77	43.46	54.00	10.54	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	57.12	-7.82	49.30	74.00	24.70	Vertical
4960.00	57.04	-7.82	49.22	74.00	24.78	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	49.18	-7.82	41.36	54.00	12.64	Vertical
4960.00	51.05	-7.82	43.23	54.00	10.77	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BEL Tx (LE Coded PHY, S=2)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	56.98	-7.66	49.32	74.00	24.68	Vertical
4804.00	56.56	-7.66	48.90	74.00	25.10	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	49.18	-7.66	41.52	54.00	12.48	Vertical
4804.00	50.50	-7.66	42.84	54.00	11.16	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.31	-7.77	49.54	74.00	24.46	Vertical
4884.00	56.34	-7.77	48.57	74.00	25.43	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	49.51	-7.77	41.74	54.00	12.26	Vertical
4884.00	50.56	-7.77	42.79	54.00	11.21	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	57.55	-7.82	49.73	74.00	24.27	Vertical
4960.00	56.84	-7.82	49.02	74.00	24.98	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	49.08	-7.82	41.26	54.00	12.74	Vertical
4960.00	50.84	-7.82	43.02	54.00	10.98	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BEL Tx (LE Coded PHY, S=8)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	56.59	-7.66	48.93	74.00	25.07	Vertical
4804.00	56.70	-7.66	49.04	74.00	24.96	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	49.22	-7.66	41.56	54.00	12.44	Vertical
4804.00	50.14	-7.66	42.48	54.00	11.52	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	56.35	-7.77	48.58	74.00	25.42	Vertical
4884.00	56.37	-7.77	48.60	74.00	25.40	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	49.17	-7.77	41.40	54.00	12.60	Vertical
4884.00	50.34	-7.77	42.57	54.00	11.43	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	55.87	-7.82	48.05	74.00	25.95	Vertical
4960.00	56.78	-7.82	48.96	74.00	25.04	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	48.81	-7.82	40.99	54.00	13.01	Vertical
4960.00	50.46	-7.82	42.64	54.00	11.36	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

ANT 13:

BLE Tx (LE 1M PHY)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	58.15	-7.66	50.49	74.00	23.51	Vertical
4804.00	58.29	-7.66	50.63	74.00	23.37	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	49.90	-7.66	42.24	54.00	11.76	Vertical
4804.00	51.12	-7.66	43.46	54.00	10.54	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.99	-7.77	50.22	74.00	23.78	Vertical
4884.00	58.49	-7.77	50.72	74.00	23.28	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	50.47	-7.77	42.70	54.00	11.30	Vertical
4884.00	51.84	-7.77	44.07	54.00	9.93	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	58.08	-7.82	50.26	74.00	23.74	Vertical
4960.00	58.24	-7.82	50.42	74.00	23.58	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	50.40	-7.82	42.58	54.00	11.42	Vertical
4960.00	51.92	-7.82	44.10	54.00	9.90	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BLE Tx (LE 2M PHY)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	57.75	-7.66	50.09	74.00	23.91	Vertical
4804.00	59.12	-7.66	51.46	74.00	22.54	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	50.25	-7.66	42.59	54.00	11.41	Vertical
4804.00	50.90	-7.66	43.24	54.00	10.76	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.86	-7.77	50.09	74.00	23.91	Vertical
4884.00	59.42	-7.77	51.65	74.00	22.35	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	49.96	-7.77	42.19	54.00	11.81	Vertical
4884.00	51.09	-7.77	43.32	54.00	10.68	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	58.43	-7.82	50.61	74.00	23.39	Vertical
4960.00	58.44	-7.82	50.62	74.00	23.38	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	50.08	-7.82	42.26	54.00	11.74	Vertical
4960.00	51.55	-7.82	43.73	54.00	10.27	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BEL Tx (LE Coded PHY, S=2)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	57.35	-7.66	49.69	74.00	24.31	Vertical
4804.00	59.57	-7.66	51.91	74.00	22.09	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	50.66	-7.66	43.00	54.00	11.00	Vertical
4804.00	52.39	-7.66	44.73	54.00	9.27	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.60	-7.77	49.83	74.00	24.17	Vertical
4884.00	59.48	-7.77	51.71	74.00	22.29	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	50.56	-7.77	42.79	54.00	11.21	Vertical
4884.00	52.83	-7.77	45.06	54.00	8.94	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	58.08	-7.82	50.26	74.00	23.74	Vertical
4960.00	58.36	-7.82	50.54	74.00	23.46	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	51.02	-7.82	43.20	54.00	10.80	Vertical
4960.00	52.80	-7.82	44.98	54.00	9.02	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BEL Tx (LE Coded PHY, S=8)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	57.40	-7.66	49.74	74.00	24.26	Vertical
4804.00	59.41	-7.66	51.75	74.00	22.25	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	50.69	-7.66	43.03	54.00	10.97	Vertical
4804.00	52.87	-7.66	45.21	54.00	8.79	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	57.78	-7.77	50.01	74.00	23.99	Vertical
4884.00	59.14	-7.77	51.37	74.00	22.63	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	50.60	-7.77	42.83	54.00	11.17	Vertical
4884.00	52.94	-7.77	45.17	54.00	8.83	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	58.15	-7.82	50.33	74.00	23.67	Vertical
4960.00	58.68	-7.82	50.86	74.00	23.14	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	50.53	-7.82	42.71	54.00	11.29	Vertical
4960.00	52.59	-7.82	44.77	54.00	9.23	Horizontal
Remark:						
1. Level = Reading + Factor.						
2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

-----End of report-----