# RF EXPOSURE REPORT



Report No.: 18070336-FCC-H						
Supersede Report No.: N/A						
Applicant		OBILITY LIMITED				
Product Name	Smart Brac	elet				
Model No.	XB02					
Serial No.	N/A					
Test Standard	FCC 2.109	3:2017				
Test Date	March 31 to	o May 04, 2018				
Issue Date	May 07, 20	18				
Test Result	Pass	Pass Fail				
Equipment compl	ied with the	specification				
Equipment did no	t comply witl	n the specification				
Aaron Liong		David Huang				
Aaron Liang		David Huang				
Test Engineer		Checked By				
This test report may be reproduced in full only						
Test result presented in this test report is applicable to the tested sample only						

Issued by:

#### SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108 Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report18070336-FCC-HPage2 of 8

### Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Country/Region	Scope	
USA	EMC, RF/Wireless, SAR, Telecom	
Canada	EMC, RF/Wireless, SAR, Telecom	
Taiwan EMC, RF, Telecom, SAR, Safety		
Hong Kong	RF/Wireless, SAR, Telecom	
Australia	EMC, RF, Telecom, SAR, Safety	
Korea	EMI, EMS, RF, SAR, Telecom, Safety	
Japan	EMI, RF/Wireless, SAR, Telecom	
Singapore	EMC, RF, SAR, Telecom	
Europe	EMC, RF, SAR, Telecom, Safety	

#### Accreditations for Conformity Assessment



Test Report	18070336-FCC-H
Page	3 of 8

This page has been left blank intentionally.



Test Report18070336-FCC-HPage4 of 8

### CONTENTS

1.	REPORT REVISION HISTORY
2.	CUSTOMER INFORMATION
3.	TEST SITE INFORMATION
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.7
5.1	RF EXPOSURE7
5.2	TEST RESULT



Test Report	18070336-FCC-H
Page	5 of 8

### 1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070336-FCC-H	NONE	Original	May 07, 2018

### 2. Customer information

Applicant Name	INFINIX MOBILITY LIMITED			
Applicant Add	ROOMS 05-15, 13A/F., SOUTH TOWER, WORLD FINANCE CENTRE,			
	IARBOUR CITY, 17 CANTON ROAD, TSIM SHA TSUI, KOWLOON, HONG			
	KONG			
Manufacturer	INFINIX MOBILITY LIMITED.			
Manufacturer Add	ROOMS 05-15, 13A/F., SOUTH TOWER, WORLD FINANCE CENTRE,			
	HARBOUR CITY, 17 CANTON ROAD, TSIM SHA TSUI, KOWLOON, HONG			
	KONG			

### 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China
	518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0



Test Report	18070336-FCC-H
Page	6 of 8

## 4. Equipment under Test (EUT) Information

Description of EUT:	Smart Bracelet
Main Model:	XB02
Serial Model:	N/A
Date EUT received:	March 30, 2018
Test Date(s):	March 31 to May 04, 2018
Antenna Gain:	BLE: 1dBi
Antenna Type:	PIFA Antenna
Type of Modulation:	BLE: GFSK
RF Operating Frequency (ies):	BLE: 2402-2480 MHz
Number of Channels:	BLE: 40CH
Port:	Please refer to user' s manual
Input Power:	Battery Spec: 3.7V, 0.388Wh,105mAh
Brand Name:	Infinix
Trade Name :	XB02
FCC ID:	2AIZN-XB02



Test Report18070336-FCC-HPage7 of 8

# 5. <u>FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable</u> devices.

#### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)].

- $[\sqrt{f_{(GHz)}}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR,<sup>16</sup> where
- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $\leq$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

#### result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

- F= Channel frequency in GHz
- D= Minimum test separation distance in mm



Test Report	18070336-FCC-H
Page	8 of 8

### 5.2 Test Result

#### BLE Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-6.53	-6±1	-5	0.316	0.10	3
	Mid	2440	-6.32	-6±1	-5	0.316	0.10	3
	High	2480	-5.29	-6±1	-5	0.316	0.10	3

#### Result: Compliance

No SAR measurement is required.