



FCC TEST REPORT

FCC ID: 2AIZY20S-01

| | | |
|---|---|----------------------|
| Product Name | : | Wireless Soundbar |
| Model Name | : | Live1,Live1 PLUS |
| Brand Name | : | iDeaPLAY |
| Report No. | : | PTC20082901502E-FC02 |
| Prepared for | | |
| IDEA ELECTRONICS INC | | |
| 13620 Benson Ave. Suite B, Chino, CA. 91710 United States | | |
| Prepared by | | |
| Precise Testing & Certification Co., Ltd. | | |
| Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China | | |



TEST RESULT CERTIFICATION

Applicant's name : IDEA ELECTRONICS INC
Address : 13620 Benson Ave. Suite B, Chino, CA. 91710 United States
Manufacture's name : Dongguan Aiue Electronic Technology Co., Ltd
Address : Room 103, No. 42, Yanhe East Street, Ailingkan Village,
Dalingshan Town, Dongguan City, Guangdong Province, China
Product name : Wireless Soundbar
Model name : Live1, Live1 PLUS
Test procedure : KDB 447498 D01 General RF Exposure Guidance v06
Test Date : Sep.4, 2020 to Sep. 24, 2020
Date of Issue : Sep. 24, 2020
Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Leo Yang".

Leo Yang / Engineer

Technical Manager:

A handwritten signature in black ink that appears to read "Chris Du".

Chris Du / Manager



Contents

| | Page |
|---------------------------------------|-------------|
| 2 TEST SUMMARY..... | 4 |
| 3 GENERAL INFORMATION..... | 5 |
| 3.1 GENERAL DESCRIPTION OF E.U.T..... | 5 |
| 4 RF EXPOSURE..... | 6 |
| 4.1 REQUIREMENTS..... | 6 |
| 4.2 THE PROCEDURES / LIMIT..... | 6 |
| 4.3 MPE CALCULATION METHOD..... | 7 |
| 4.4 TEST RESULT..... | 7 |



2 Test Summary

| Test Items | Test Requirement | Result |
|---|------------------|--------|
| Maximum Permissible Exposure (Exposure of Humans to RF Fields) | 1.1307(b)(1) | PASS |
| Remark: | | |
| N/A: Not Applicable | | |



3 General Information

3.1 General Description of E.U.T.

| | | |
|---------------------|---|---|
| Product Name | : | Wireless Soundbar |
| Model Name | : | Live1 |
| Additional model | : | Live1 PLUS Note:Different appearance colors, the others are the same |
| Bluetooth Version | : | BT 5.0 BDR+EDR |
| Operating frequency | : | 2402-2480MHz |
| Numbers of Channel | : | 79 channels |
| Antenna Type | : | PCB Antenna |
| Antenna Gain | : | 0 dBi |
| Type of Modulation | : | GFSK, $\pi/4$ -DQPSK, 8DPSK For DSS |
| Power supply | : | Adapter model:N/A Input:120V 60HZ Output:24V/1.6A |
| Hardware Version | : | V2.1 |
| Software Version | : | V4.0 |



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : FCC Part 2.1091

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

| Frequency Range | Electric Field | Magnetic Field | Power Density (S) | Averaging Time |
|-----------------|----------------|----------------|-------------------|----------------|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range | Electric Field | Magnetic Field | Power Density (S) | Averaging Time |
|-----------------|----------------|----------------|-------------------|----------------|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

| Item | Antenna Gain (numeric) | Max. Peak Output Power (dBm) | Peak Output Power (mW) | Power Density (mW/cm ²) | Limit of Power Density (mW/cm ²) | Result |
|------|------------------------|------------------------------|------------------------|-------------------------------------|--|--------|
| BT | 1.00 | -0.466 | 0.90 | 0.0002 | 1 | Pass |

*******THE END REPORT*******