

TEST REPORT
No.: 16-1-0191201T05a

According to:
FCC Regulations
Part 1.1310 , Part 2.1091

for

Intel Corporation

INTEL FALCON 8+ UAS

Contains 5 GHz Transmitter Module FCC-ID: 2AJ2A-VLMTX58G

Contains 2.4 GHz Transmitter Module FCC-ID: 2AJ2A-RCM24G







Laboratory Accreditation and Listings			
 <p>Deutsche Akkreditierungsstelle D-PL-12047-01-01</p>	 <p>FEDERAL COMMUNICATIONS COMMISSION U.S.A. MRA US-EU 0003</p>	 <p>Industry Canada Reg. No.: 3462D-1 Reg. No.: 3462D-2 Reg. No.: 3462D-3</p>	 <p>Voluntary Controls for Electromagnetic Emissions Reg. No.: R-2666 C-2914, T-1967, G-301</p>
 <p>WiFi ALLIANCE</p>	 <p>ctia AuthorizedTM Test Lab Lab Code: 20011130-00</p>		
accredited according to DIN EN ISO/IEC 17025			
<p>CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964 E-mail: info@cetecom.com • Internet: www.cetecom.com</p>			

Table of contents

1. SUMMARY OF TEST RESULTS.....	3
1.1 Summary of tests results	3
1.2 Summary of product description.....	4
1.3 Refer Rules	4
1.4 EUT Technologies	4
1.5 Antenna Information.....	6
1.6 Description of EUT.....	10
1.7 Auxiliary Equipment (AE).....	10
1.8 EUT Set-ups	11
1.9 Configuration of cables used for testing	11
2 ADMINISTRATIVE DATA	12
2.1 Identification of the testing laboratory.....	12
2.2 Test location	12
2.3 Organizational items	12
2.4 Applicant's details	12
2.5 Manufacturer's details	12
3 MEASUREMENTS	13
3.1. Test location	13
3.2 Evaluation Rules.....	13
3.3 Limits.....	13
3.4 MPE Calculation method.....	14
3.5 Conducted Output Power.....	14
3.6 Evaluation Method.....	15
3.7 Conclusion.....	17
4 MEASUREMENT UNCERTAINTIES.....	18
5 ABBREVIATIONS USED IN THIS REPORT	19
6 ACCREDITATION DETAILS OF CETECOM'S LABORATORIES AND TEST SITES	20
7 TEST REPORT VERSION.....	21

1. Summary of test results

The test results apply exclusively to the test samples as presented in this Report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests.

Following tests have been performed to show compliance with applicable FCC Part 2.1091 and FCC Part 1.1310 of the FCC CFR 47 Rules.

The presented Equipment Under Test (in this report, hereinafter referred as EUT) : **INTEL FALCON 8+ UAS** integrates

- Total 1 of VLMTX58G (FCC-ID:2AJ2A-VLMTX58G) & supports operating frequency range from 5150 – 5850 MHz with specified protocol implementation. **Measurements only valid and pass result with power setting: +10 dBm**
- Total 2 of RCM24G (FCC-ID: 2AJ2A-RCM24G) Proprietary 2.4 GHz RF Transceiver & supports operating frequency range from 2402.5 – 2471.5 MHz.

1.1 Summary of tests results

RF-Exposure Evaluation (separation distance user to RF-radiating element greater 20cm)						
Test cases	Port	References & Limits		EUT set-up	EUT op. mode	Result
		FCC Standard	Test Limit			
Radio frequency radiation exposure Requirements	Cabinet + Inter-Connecting Cables (conducted)	§2.1091 §2.1093	RF-Field Strength Limits: FCC: "general population/ uncontrolled" environment	1	1	Pass



.....
Dipl.-Ing. Rachid Acharkaoui
Responsible for test section

.....
M.Sc. Ajit Phadtare
Responsible for test report

1.2 Summary of product description

FCC ID:	Contains FCC-ID: 2AJ2A-VLMTX58G Contains FCC-ID: 2AJ2A-RCM24G	
Product name	INTEL FALCON 8+ UAS	
Exposure category	<input checked="" type="checkbox"/> General population/uncontrolled environment <input type="checkbox"/> Occupational exposure/controlled environment	
Output power	<input checked="" type="checkbox"/> Conducted <input type="checkbox"/> ERP <input type="checkbox"/> EIRP <input type="checkbox"/> Peak <input checked="" type="checkbox"/> Source-based time-averaging	
Antenna gain	2.4 GHz: 2.5dBi 5 GHz: 5.47dBi	
Technology	<input checked="" type="checkbox"/> MIMO (5 GHz)	<input checked="" type="checkbox"/> 2T2R <input type="checkbox"/> 3T3R <input type="checkbox"/> 4T4R
	<input checked="" type="checkbox"/> non-MIMO (2.4 GHz)	<input checked="" type="checkbox"/> 1T1R <input type="checkbox"/> 1T2R <input type="checkbox"/> 2T1R
Evaluation type	<input checked="" type="checkbox"/> Standalone <input checked="" type="checkbox"/> Simultaneous transmission	
Evaluation distance	<input checked="" type="checkbox"/> 20 cm	
	<input type="checkbox"/> XXX cm	declares by manufacturer
EUT type	<input checked="" type="checkbox"/> Production Unit <input type="checkbox"/> Engineering Unit	
Device type	<input checked="" type="checkbox"/> Mobile device <input type="checkbox"/> Fixed device	
Refer rules	<input checked="" type="checkbox"/> CFR 47 FCC Part 2.1091 <input checked="" type="checkbox"/> CFR 47 FCC Part 1.1310 <input checked="" type="checkbox"/> KDB 447497 D01v06 October 23, 2015 <input checked="" type="checkbox"/> KDB 865664 D01v01r02 October 23, 2015	

1.3 Refer Rules

ANSI C95.1-1999	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
KDB 447498 D01 v06 October 23, 2015	Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.
KDB 865664 D01v01r02 October 23, 2015	RF Exposure Compliance Reporting and Documentation Considerations.
CFR 47 FCC Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.
CFR 47 FCC Part 1.1310	Radiofrequency radiation exposure limits.

1.4 EUT Technologies

Wireless Technologies	Frequency bands	Operation mode		Duty cycle
<input type="checkbox"/> GSM	<input type="checkbox"/> 850 <input type="checkbox"/> 1900 <input type="checkbox"/> Support DTM (Dual Transfer Mode)	Voice (GMSK)	1 slot	<input type="checkbox"/> 12.5%
<input type="checkbox"/> GPRS	<input type="checkbox"/> 850 <input type="checkbox"/> 1900	GPRS (GMSK) Multi – Slot Class	<input type="checkbox"/> 8 1 slot (1 Up, 4 Down)	<input type="checkbox"/> 12.5%
			<input type="checkbox"/> 10 2 slots (2 Up, 4 Down)	<input type="checkbox"/> 12.5% <input type="checkbox"/> 25%
			<input type="checkbox"/> 12 4 slots (4 Up, 4 Down)	<input type="checkbox"/> 12.5% <input type="checkbox"/> 25% <input type="checkbox"/> 37.5% <input type="checkbox"/> 50%
<input type="checkbox"/> EDGE	<input type="checkbox"/> 850	EDGE (8-PSK)	<input type="checkbox"/> 8 1 slot (1 Up, 4 Down)	<input type="checkbox"/> 12.5%

	<input type="checkbox"/> 1900	Multi – Slot Class	<input type="checkbox"/> 10	2 slots (2 Up, 4 Down)	<input type="checkbox"/> 12.5% <input type="checkbox"/> 25%
			<input type="checkbox"/> 12	4 slots (4 Up, 4 Down)	<input type="checkbox"/> 12.5% <input type="checkbox"/> 25% <input type="checkbox"/> 37.5% <input type="checkbox"/> 50%
<input type="checkbox"/> WCDMA (UMTS)	<input type="checkbox"/> Band II <input type="checkbox"/> Band IV <input type="checkbox"/> Band V	<input type="checkbox"/> UMTS Rel.99 (Voice & Data) <input type="checkbox"/> HSDPA(Rel.5) <input type="checkbox"/> HSUPA(Rel.6) <input type="checkbox"/> DC-HSDPA(Rel.8) <input type="checkbox"/> HSPA+(Rel.7)			<input type="checkbox"/> 100%
<input type="checkbox"/> CDMA (CDMA2000)	<input type="checkbox"/> BC0 <input type="checkbox"/> BC1 <input type="checkbox"/> BC10	<input type="checkbox"/> 1xRTT (Voice & Data) <input type="checkbox"/> 1xEVDO Rel.0 <input type="checkbox"/> 1xEVDO Rel.A <input type="checkbox"/> 1xAdvanced			<input type="checkbox"/> 100%
<input type="checkbox"/> Support SV-DO (1xRTT-1xEVDO)					
<input type="checkbox"/> LTE-FDD	<input type="checkbox"/> Band 2 <input type="checkbox"/> Band 4 <input type="checkbox"/> Band 5 <input type="checkbox"/> Band 7 <input type="checkbox"/> Band 12 <input type="checkbox"/> Band 13 <input type="checkbox"/> Band 17 <input type="checkbox"/> Band 25 <input type="checkbox"/> Band 26 <input type="checkbox"/> Band 27 <input type="checkbox"/> Band 30	<input type="checkbox"/> QPSK <input type="checkbox"/> 16QAM <input type="checkbox"/> Rel.11 Carrier Aggregation	<input type="checkbox"/> 2 Uplinks 2 Downlinks <input type="checkbox"/> 2 Uplinks 3 Downlinks <input type="checkbox"/> 3 Uplinks 2 Downlinks <input type="checkbox"/> 3 Uplinks 3 Downlinks		100%
<input type="checkbox"/> Supports SV-LTE (1xRTT-LTE)					
<input type="checkbox"/> LTE-TDD	<input type="checkbox"/> Band 38 <input type="checkbox"/> Band 39 <input type="checkbox"/> Band 40 <input type="checkbox"/> Band 41 <input type="checkbox"/> Band 42	<input type="checkbox"/> QPSK <input type="checkbox"/> 16QAM <input type="checkbox"/> Rel.11 Carrier Aggregation	<input type="checkbox"/> 2 Uplinks 2 Downlinks <input type="checkbox"/> 2 Uplinks 3 Downlinks <input type="checkbox"/> 3 Uplinks 2 Downlinks <input type="checkbox"/> 3 Uplinks 3 Downlinks		63.3% This device supports uplink –downlink configuration 0-6. The configuration with highest duty cycle was used (configuration. 0 at 63.3%)
<input type="checkbox"/> Supports SV-LTE (1xRTT-LTE)					
<input type="checkbox"/> Wi-Fi	<input type="checkbox"/> 2.4GHz	<input type="checkbox"/> IEEE 802.11b	<input type="checkbox"/> 2412 – 2462 MHz <input type="checkbox"/> 2412 – 2472 MHz	<input type="checkbox"/> 100%	
		<input type="checkbox"/> IEEE 802.11g	<input type="checkbox"/> 2412 – 2462 MHz <input type="checkbox"/> 2412 – 2472 MHz	<input type="checkbox"/> 100%	
		<input type="checkbox"/> IEEE 802.11n HT20	<input type="checkbox"/> 2412 – 2462 MHz <input type="checkbox"/> 2412 – 2472 MHz	<input type="checkbox"/> 100%	
		<input type="checkbox"/> IEEE 802.11n HT40	<input type="checkbox"/> 2422 – 2452 MHz	<input type="checkbox"/> 100%	
	<input type="checkbox"/> 5GHz	<input type="checkbox"/> IEEE 802.11a	<input type="checkbox"/> 5180 – 5240 MHz <input type="checkbox"/> 5260 – 5320 MHz <input type="checkbox"/> 5500 – 5700 MHz <input type="checkbox"/> 5745 – 5825 MHz	<input type="checkbox"/> 100%	
		<input type="checkbox"/> IEEE 802.11n HT20	<input type="checkbox"/> 5180 – 5240 MHz <input type="checkbox"/> 5260 – 5320 MHz <input type="checkbox"/> 5500 – 5700 MHz <input type="checkbox"/> 5745 – 5825 MHz	<input type="checkbox"/> 100%	
		<input type="checkbox"/> IEEE 802.11n HT40	<input type="checkbox"/> 5190 – 5230 MHz <input type="checkbox"/> 5270 – 5310 MHz <input type="checkbox"/> 5510 – 5670 MHz <input type="checkbox"/> 5755 – 5795 MHz	<input type="checkbox"/> 100%	

		<input type="checkbox"/> IEEE 802.11ac VHT20	<input type="checkbox"/> 5180 – 5240 MHz <input type="checkbox"/> 5260 – 5320 MHz <input type="checkbox"/> 5500 – 5700 MHz <input type="checkbox"/> 5745 – 5825 MHz	<input type="checkbox"/> 100%
		<input type="checkbox"/> IEEE 802.11ac VHT40	<input type="checkbox"/> 5190 – 5230 MHz <input type="checkbox"/> 5270 – 5310 MHz <input type="checkbox"/> 5510 – 5670 MHz <input type="checkbox"/> 5755 – 5795 MHz	<input type="checkbox"/> 100%
		<input type="checkbox"/> IEEE 802.11ac VHT80	<input type="checkbox"/> 5210 – 5210 MHz <input type="checkbox"/> 5290 – 5290 MHz <input type="checkbox"/> 5530 – 5530 MHz <input type="checkbox"/> 5775 – 5775 MHz	<input type="checkbox"/> 100%
<input type="checkbox"/> Supports Band gap channels				
<input checked="" type="checkbox"/> Others	<input checked="" type="checkbox"/> 2.4GHz	<input checked="" type="checkbox"/> 1 MHz Bandwidth	<input checked="" type="checkbox"/> 2402.5 – 2471.5 MHz	<input checked="" type="checkbox"/> 100%
	<input checked="" type="checkbox"/> 5GHz	<input checked="" type="checkbox"/> 40 MHz Bandwidth	<input checked="" type="checkbox"/> 5190 – 5230 MHz <input checked="" type="checkbox"/> 5270 – 5310 MHz <input checked="" type="checkbox"/> 5510 – 5670 MHz <input checked="" type="checkbox"/> 5755 – 5795 MHz	<input checked="" type="checkbox"/> 100%
<input type="checkbox"/> Bluetooth	<input type="checkbox"/> 2.4GHz	<input type="checkbox"/> Version 2.1+EDR		<input type="checkbox"/> 77.5%
		<input type="checkbox"/> Version 3.0+HS		<input type="checkbox"/> 77.5%
		<input type="checkbox"/> Version 4.0		<input type="checkbox"/> 100%
		<input type="checkbox"/> Version 4.1+EDR		<input type="checkbox"/> 77.5%
		<input type="checkbox"/> Version 4.2+EDR		<input type="checkbox"/> 77.5%

1.5 Antenna Information

Wireless Technologies	Frequency bands	Antenna type	Maximum antenna gain	
<input type="checkbox"/> GSM	<input type="checkbox"/> 850	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
<input type="checkbox"/> GSM	<input type="checkbox"/> 1900	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
<input type="checkbox"/> WCDMA (UMTS)	<input type="checkbox"/> Band II	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 1	
	<input type="checkbox"/> Band IV	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 1	
	<input type="checkbox"/> Band V	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 1	
<input type="checkbox"/> CDMA	<input type="checkbox"/> CDMA800	<input type="checkbox"/> PIFA	<input type="checkbox"/> Antenna 0	

(CDMA2000)		<input type="checkbox"/> PCB		
		<input type="checkbox"/>		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/>		
<input type="checkbox"/> CDMA1900		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/>		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/>		
<input type="checkbox"/> LTE-FDD	<input type="checkbox"/> Band 2	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 4	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 5	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 7	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 12	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 13	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 17	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 25	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/>		
	<input type="checkbox"/> Band 26	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	

		<input type="checkbox"/>			
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
	<input type="checkbox"/> Band 27	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
<input type="checkbox"/> LTE-TDD	<input type="checkbox"/> Band 38	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
	<input type="checkbox"/> Band 39	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
	<input type="checkbox"/> Band 40	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
	<input type="checkbox"/> Band 41	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
	<input type="checkbox"/> Band 42	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
	<input type="checkbox"/> Wi-Fi	<input type="checkbox"/> 2.4GHz	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0	
			<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1	
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 2		
<input type="checkbox"/> 5GHz		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 0		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 1		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB	<input type="checkbox"/> Antenna 2		
<input checked="" type="checkbox"/> Others	<input checked="" type="checkbox"/> 5GHz	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input checked="" type="checkbox"/> WAL SIN	<input checked="" type="checkbox"/> Antenna 0	5.47 dBi	

		PCB ANTENNA RFPCA201018IM5B301		
		<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input checked="" type="checkbox"/> WAL SIN PCB ANTENNA RFPCA201018IM5B301	<input checked="" type="checkbox"/> Antenna 1	5.47 dBi
	<input checked="" type="checkbox"/> 2.4GHz	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input checked="" type="checkbox"/> Prestta WLAN Embedded Antenna P/N: 1000418	<input checked="" type="checkbox"/> Antenna 2	2.5 dBi
	<input checked="" type="checkbox"/> 2.4GHz	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input checked="" type="checkbox"/> Prestta WLAN Embedded Antenna P/N: 1000418	<input checked="" type="checkbox"/> Antenna 3	2.5 dBi
<input type="checkbox"/> Bluetooth	<input type="checkbox"/> 2.4GHz	<input type="checkbox"/> PIFA <input type="checkbox"/> PCB <input type="checkbox"/>	<input type="checkbox"/> Antenna 0	

1.6 Description of EUT

Short description*)	EUT	Type	S/N serial number	HW hardware status	SW software status
EUT A	INTEL FALCON8 + UAS	Professional Drone	601	0.90	0.793
EUT B	INTEL FALCON8 + UAS	Professional Drone	602	0.90	0.793

*) EUT short description is used to simplify the identification of the EUT in this test report.

1.7 Auxiliary Equipment (AE)

AE short description *)	Auxiliary Equipment	Type	S/N serial number	HW hardware status	SW software status
AE 1	Payload Camera with interchangeable lens	SONY Alpha 7R Camera	3985095	WW328261 STT-C 50i 7.2V	--
		SONY CORP. Lens Carl Zeiss ALC-SH129 FE 2,8/35 0,35m/1,15ft	1881978	MODEL: SEL35F28Z	
AE 2	Payload Camera with interchangeable lens	SONY Alpha 7R Camera	3983233	WW328261 STT-C 50i 7.2V	--
		SONY CORP. Lens Carl Zeiss ALC-SH129 FE 2,8/35 0,35m/1,15ft	1880393	MODEL: SEL35F28Z	
AE 3	WLAN 2.4 GHz Access Point	FRITZ!Box 3490 Article Nr.: 2000 2680	F504.538.00. 063.337	CWMP-Account: 00040E- 5C4979583599	--

*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

1.8 EUT Set-ups

EUT set-up no. *)	Combination of EUT and AE	Description
set. 1	<p>EUT A + AE 1 (+ AE 3)</p> <p>[AE 1 was connected to AE 3 :WLAN 2.4 GHz access point]</p> <p>[AE 3 was only used to set test mode & kept outside test chamber]</p>	<p>9kHz – 30 MHz 30 MHz – 1GHz 18 GHz – 40 GHz</p> <p>Radiated Measurements Set-up : EUT Laying Position</p>
	<p>EUT B + AE 2 (+ AE 3)</p> <p>[AE 2 was connected to AE 3 :WLAN 2.4 GHz access point]</p> <p>[AE 3 was only used to set test mode & kept outside test chamber]</p>	<p>1 GHz – 7 GHz 7 GHz – 18 GHz</p> <p>Radiated Measurements Set-up : EUT Laying Position</p>
set. 2	<p>EUT A + AE 1 (+ AE 3)</p> <p>[AE 1 was connected to AE 3 :WLAN 2.4 GHz access point]</p> <p>[AE 3 was only used to set test mode & kept outside test chamber]</p>	<p>9kHz – 30 MHz 30 MHz – 1GHz 18 GHz – 40 GHz</p> <p>Radiated Measurements Set-up : EUT Standing Position</p>
	<p>EUT B + AE 2 (+ AE 3)</p> <p>[AE 2 was connected to AE 3 :WLAN 2.4 GHz access point]</p> <p>[AE 3 was only used to set test mode & kept outside test chamber]</p>	<p>1 GHz – 7 GHz 7 GHz – 18 GHz</p> <p>Radiated Measurements Set-up : EUT Standing Position</p>

*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

1.9 Configuration of cables used for testing

Cable number	Item	Type	S/N serial number	HW hardware status	Cable length
Cable 1	--	--	--	--	--

2 Administrative Data

2.1 Identification of the testing laboratory

Company name:	CETECOM GmbH
Address:	Im Teelbruch 116 45219 Essen - Kettwig Germany
Responsible for testing laboratory:	Dipl.-Ing. Rachid Acharkaoui
Deputy:	Dipl.-Ing. Niels Jeß

2.2 Test location

2.2.1 Test laboratory "CTC"

Company name:	see chapter 2.1 Identification of the testing laboratory
---------------	----------------------------------------------------------

2.3 Organizational items

Responsible for test report:	M.Sc. Ajit Phadtare
Project leader:	M.Sc. Ajit Phadtare
Receipt of EUT:	2017-01-12
Date(s) of test:	2017-02-01 to 2017-02-28
Date of report:	2017-04-27

Version of template: 13.02	

Remark 1: based on applicants tune-up info

2.4 Applicant's details

Applicant's name:	Intel Corporation
Address:	2200 Mission College Boulevard Santa Clara, CA 95054 USA
Contact person:	+1 408-765-8080

2.5 Manufacturer's details

Manufacturer's name:	Intel Deutschland GmbH
Address:	Konrad-Zuse-Bogen 4, 82152 Krailling, GERMANY

3 Measurements

3.1. Test location

test location	<input checked="" type="checkbox"/> CETECOM Essen	<input type="checkbox"/>	<input type="checkbox"/>
For Evaluation instruments are not needed. Results are determined by calculation based on applicants delivered Tune-Up procedure.			

3.2 Evaluation Rules

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limits

Table 1: LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

(A) Limits for Occupational/Controlled Exposure				
Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm ²]	Averaging time [minutes]
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	--	6
1500-100,000	--	--	--	6
(B) Limits for General Population/Uncontrolled Exposure				
Frequency range [MHz]	Electric field strength [V/m]	Magnetic field strength [A/m]	Power density [mW/cm ²]	Averaging time [minutes]
0.3-3.0	614	1.63	*(100)	30
3.0-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f=frequency in MHz

*Plane-wave equivalent power density

NOTE1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure. These limits apply to amateur station licensees and members of their immediate household as discussed in the text.

NOTE2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure. As discussed in the text, these limits apply to neighbours living near amateur radio stations.

3.4 MPE Calculation method

Predication of MPE limit at a given distance
 Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{EIRP}{4\pi R^2} = \frac{P * G}{4\pi R^2}$$

$$G_{NUMERIC} = \frac{S * 4\pi R^2}{P}$$

Where: S=power density
 P=power input to antenna
 G=power gain of the antenna in the direction of interest relative to an isotropic radiator
 R=distance to the centre of radiation of the antenna

3.5 Conducted Output Power

5 GHz Transmitter Module

VLMTX58G Module								
U-NII-1 HT40								
Frequency (MHz)	Antenna 0				Antenna 1			
	5190	/	/	5230	5190	/	/	5230
Average Conducted Power (dBm)	11.55	/	/	10.14	11.63	/	/	10.50
U-NII-2A HT40								
Frequency (MHz)	Antenna 0				Antenna 1			
	5270	/	/	5310	5270	/	/	5310
Average Conducted Power (dBm)	9.09	/	/	8.80	9.50	/	/	9.30
U-NII-2C HT40								
Frequency (MHz)	Antenna 0				Antenna 1			
	5510	5550	5590	5670	5510	5550	5590	5670
Average Conducted Power (dBm)	9.70	9.25	8.15	8.77	9.64	9.25	8.58	9.70
U-NII-3 HT40								
Frequency (MHz)	Antenna 0				Antenna 1			
	5755	/	/	5795	5755	/	/	5795
Average Conducted Power (dBm)	9.54	/	/	10.23	9.79	/	/	9.89

2.4 GHz Transmitter Module

RCM24G Module			
Modulation: MSK / Data Rate: 50 Kbps			
Frequency (MHz)	2402.5	2436.5	2471.5
Average Conducted Power (dBm)	10.19	19.93	9.32
Modulation: MSK / Data Rate: 100 Kbps			
Frequency (MHz)	2402.5	2436.5	2471.5
Average Conducted Power (dBm)	10.20	19.89	9.39
Modulation: MSK / Data Rate: 250 Kbps			
Frequency (MHz)	2402.5	2436.5	2471.5
Average Conducted Power (dBm)	10.19	19.78	9.40
Modulation: MSK / Data Rate: 500 Kbps			
Frequency (MHz)	2402.5	2436.5	2471.5
Average Conducted Power (dBm)	10.26	19.92	9.42

3.6 Evaluation Method

3.6.1 Standalone

Valid for GSM/GPRS/EDGE mode:

- The power was tested on 3 frequencies (lowest/middle/highest) within each operable bands and the results compared to applicant's declared power values (tune-up info).
- Average burst power (slot power) and burst average values were measured;
- Measured burst average power at all TX slots possible for this device and calculated as worst-case
- A duty-cycle correction factor of $10 \cdot \log_{10}$ (max. number of possible active slots / 8 slots) were applied

Please find in the following tables the calculations based on applicants tune-up information for the power values. Also the maximum admissible allowed antenna gain is calculated which is not exceeding the MPE limit for fixed and mobile operations.

Valid for W-CDMA/LTE Mode:

- The power was checked on 3 frequencies (lowest/middle/highest) within each operable FDD-band and the results compared to applicant's declared power values (tune-up info).
- No duty-cycle correction factor is applicable

Please find in the following tables the calculations based on applicants tune-up information for the power values. Also the maximum admissible allowed antenna gain is calculated which is not exceeding the MPE limit for fixed and mobile operations.

Valid for WLAN/BT Mode:

- The average power was checked on 3 frequencies (lowest/middle/highest) within each operable WiFi band and the results compared to applicant's declared power values (tune-up info). A RMS detector was used.
- No duty-cycle correction factor is applicable

Please find in the following tables the calculations based on applicants tune-up information for the power values.

INTEL FALCON 8+ UAS: 5 GHz Transmitter Module

The presented Equipment Under Test INTEL FALCON 8+ UAS integrates

- Total 1 of VLMTX58G (FCC-ID:2AJ2A-VLMTX58G) MIMO Module & supports operating frequency range from 5150 – 5850 MHz with specified protocol implementation.
- During the tests Antenna 0 & Antenna 1 were connected to the MIMO ports of VLMTX58G module.

INTEL FALCON 8+ UAS: 5 GHz Transmitter Module (VLMTX58G) + Antenna 0							
Wireless Technologies	Output power*		Antenna Gain (dBi)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	Verdict
	dBm	mW					
U-NII-1 HT40	13.25	21.1349	5.47	100%	0.0148	1.0000	Pass
U-NII-2A HT40	11.09	12.8529	5.47	100%	0.0090	1.0000	Pass
U-NII-2C HT40	11.70	14.7911	5.47	100%	0.0104	1.0000	Pass
U-NII-3 HT40	12.23	16.7109	5.47	100%	0.0117	1.0000	Pass

INTEL FALCON 8+ UAS: 5 GHz Transmitter Module (VLMTX58G) + Antenna 1							
Wireless Technologies	Output power*		Antenna Gain (dBi)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	Verdict
	dBm	mW					
U-NII-1 HT40	13.33	21.5278	5.47	100%	0.0151	1.0000	Pass
U-NII-2A HT40	11.50	14.1254	5.47	100%	0.0099	1.0000	Pass
U-NII-2C HT40	11.70	14.7911	5.47	100%	0.0104	1.0000	Pass
U-NII-3 HT40	11.89	15.4525	5.47	100%	0.0108	1.0000	Pass

INTEL FALCON 8+ UAS: 2.4 GHz Transmitter Modules

The presented Equipment Under Test: INTEL FALCON 8+ UAS integrates

- Total 2 of RCM24G (FCC-ID: 2AJ2A-RCM24G) Proprietary 2.4 GHz RF Transceiver & supports operating frequency range from 2402.5 – 2471.5 MHz.
- RCM24G (FCC-ID: 2AJ2A-RCM24G) Module has only one RF Output Port & does not support MIMO operations.
- During tests Antenna 2 was connected to RCM24G Module1 & Antenna 3 was connected to RCM24G Module 2.

INTEL FALCON 8+ UAS: 2.4 GHz Transmitter Modules RCM24G Module 1+ Antenna 2 & RCM24G Module 2+ Antenna 3							
Wireless Technologies	Output power*		Antenna Gain (dBi)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	Verdict
	dBm	mW					
Modulation: MSK / Data Rate: 50 Kbps	20.93	123.8797	2.5	100%	0.0438	1.0000	Pass
Modulation: MSK / Data Rate: 100 Kbps	20.89	122.7439	2.5	100%	0.0434	1.0000	Pass
Modulation: MSK / Data Rate: 250 Kbps	20.78	119.6741	2.5	100%	0.0423	1.0000	Pass
Modulation: MSK / Data Rate: 500 Kbps	20.92	123.5947	2.5	100%	0.0437	1.0000	Pass

Remark:

1. Output power (Average) including turn-up tolerance;
2. Output power was adjust to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer;

3.6.2 Simultaneous Transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 \sum of MPE ratios ≤ 1.0

3.1.6.2.1 Summary simultaneous transmission information

Wireless Technologies	Work Frequency Band	Transmit Antenna				Synchronization transmit
		Antenna 0	Antenna 1	Antenna 2	Antenna 3	
BPSK, OFDM, MSK	5 GHz 2.4 GHz	☒	☒	☒	☒	☒

3.6.2.2 Summary simultaneous transmission results

Simultaneous transmission results at Antenna 0, Antenna 1, Antenna 2 and Antenna 3							
Wireless Technologies	MPE _{Antenna 0} (mW/cm ²)	MPE _{Antenna 1} (mW/cm ²)	MPE _{Antenna 2} (mW/cm ²)	MPE _{Antenna 3} (mW/cm ²)	\sum MPE ratios	Limit	Verdict
BPSK, OFDM, MSK	0.0148	0.0151	0.0438	0.0438	0.1175	1.0	PASS

Remark: Depending on output power only the worst case is reported;

3.7 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

4 Measurement uncertainties

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved.

For uncertainty determination, each component used in the concrete measurement set-up was taken in account and it's contribution to the overall uncertainty according it's statistical distribution calculated.

Following table shows expectable uncertainties for each measurement type performed.

RF-Measurement	Reference	Frequency range	Calculated uncertainty based on a confidence level of 95%						Remarks
Conducted emissions (U _{CISPR})	CISPR 16-2-1	9 kHz - 150 kHz	4.0 dB						-
		150 kHz - 30 MHz	3.6 dB						
Radiated emissions Enclosure	CISPR 16-2-3	30 MHz - 1 GHz	4.2 dB						E-Field
		1 GHz - 18 GHz	5.1 dB						
Disturbance power	CISPR 16-2-2	30 MHz - 300 MHz	-						-
Power Output radiated	-	30 MHz - 4 GHz	3.17 dB						Substitution method
Power Output conducted	-	Set-up No.	Cel-C1	Cel-C2	BT1	W1	W2		
		9 kHz - 12.75 GHz	N/A	0.60	--	--	--		-
		12.75 - 26.5GHz	N/A	0.82	--	--	--		
Conducted emissions on RF-port	-	9 kHz - 2.8 GHz	0.70	N/A	--	--	--		N/A - not applicable
		2.8 GHz - 12.75GHz	1.48	N/A	--	--	--		
		12.75 GHz - 18GHz	1.81	N/A	--	--	--		
		18 GHz - 26.5GHz	1.83	N/A	--	--	--		
Occupied bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)						Frequency error
			1.0 dB						Power
Emission bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)						Frequency error
			See above: 0.70 dB						Power
Frequency stability	-	9 kHz - 20 GHz	0.0636 ppm						-
Radiated emissions Enclosure	-	150 kHz - 30 MHz	5.0 dB						Magnetic field E-field Substitution
		30 MHz - 1 GHz	4.2 dB						
		1 GHz - 20 GHz	3.17 dB						

Table: measurement uncertainties, valid for conducted/radiated measurements

5 Abbreviations used in this report

The abbreviations	
ANSI	American National Standards Institute
AV, AVG, CAV	Average detector
EIRP	Equivalent isotropically radiated power, determined within a separate measurement
EUT	Equipment Under Test
FCC	Federal Communications Commission, USA
n.a.	not applicable
Op-Mode	Operating mode of the equipment
PK	Peak
RBW	resolution bandwidth
RF	Radio frequency
RSS	Radio Standards Specification, Documents from Industry Canada
Rx	Receiver
TCH	Traffic channel
Tx	Transmitter
QP	Quasi peak detector
VBW	Video bandwidth
ERP	Effective radiated power

6 Accreditation details of CETECOM’s laboratories and test sites

Ref.-No.	Accreditation Certificate	Valid for laboratory area or test site	Accreditation Body
-	D-PL-12047-01-01	All laboratories and test sites of CETECOM GmbH, Essen	DAkkS, Deutsche Akkreditierungsstelle GmbH
337 487 558 348 348	MRA US-EU 0003	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measur.	FCC, Federal Communications Commission Laboratory Division, USA
337 487 550 558	3462D-1 3462D-2 3462D-2 3462D-3	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR)	IC, Industry Canada Certification and Engineering Bureau
487 550 348 348	R-2666 G-301 C-2914 T-1967	Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measur.	VCCI, Voluntary Control Council for Interference by Information Technology Equipment, Japan
OATS = Open Area Test Site, SAR = Semi Anechoic Room, FAR = Fully Anechoic Room			

7 Test report version

Version	Applied changes	Date of release
--	Initial release	2017-04-27
--	--	--