

# Test Report

*Electromagnetic Compatibility (EMC)*



Equipment Under Test: USB powered controller for drones

Marketing name: Intel® Drone Link DVT FabA

Type: IWBS1

Manufacturer: Intel  
Behringstraße 10  
82152 Planegg  
GERMANY

Customer: Intel Corporation  
2200 Mission College Blvd  
Santa Clara, CA 95054  
USA

## Tests have been performed according to the following standards

FCC CFR 47 Part 15 (October 2017)	Subpart B	Class B
ICES-003 Issue 6	Class B	

Date: 30 October 2017

Issued by:

Pekka Kälviäinen  
Testing Engineer

Date: 30 October 2017

Checked by:

Rauno Repo  
Testing Engineer

## Table of Contents

PRODUCT DESCRIPTION	3
Equipment Under Test (EUT)	3
Type Of The EUT	3
Cable Lengths and Types	3
Peripherals	4
Disclaimer	5
TEST CONDITIONS	6
EUT Test Conditions During EMC-Testing	6
Photographs of the EUT	7
SUMMARY OF TESTING	10
EMISSION TEST RESULTS	11
Conducted Emissions In The Frequency Range 150 kHz - 30 MHz.	11
Radiated Emissions In The Frequency Range 30 MHz - 1000 MHz.	13
Radiated Emissions In The Frequency Range 1-2 GHz	15
LIST OF TEST EQUIPMENT	17
Conducted Emissions	17
Radiated Emissions	17

## PRODUCT DESCRIPTION

### Equipment Under Test (EUT)

EUT:	USB powered controller for drones
Type:	IWBS1
Serial no:	W1DVT1KY7380023
SW:	Main FW: F407_test_171009 Radio card FWs: v3.8 testing editions Bluetooth FW: 9.1.10.0
FCC ID:	CC2500: 2AJ2A-RCM24G Bluetooth: SQGBT900
IC:	CC2500: 1000B-RCM24G Bluetooth: 3147A-BT900

Max. internal frequency 168 MHz.

### Type Of The EUT

The EUT will be tested as a tabletop unit.

### Ratings and declarations

#### Remote controller radios:

Operating Frequency Range (OFR):	2402.5 – 2471.5 MHz
Channels:	70
Channel separation:	1 MHz
Effective conducted power:	19.93 dBm
Transmission technique:	ADFSS
Modulation:	MSK
Antenna gain:	2.0 dBi

#### Bluetooth:

Operating Frequency Range (OFR):	2402 – 2480 MHz
Channels:	80
Channel separation:	1 MHz
Effective conducted power:	8 dBm
Transmission technique:	FHSS
Modulation:	GFSK
Antenna gain:	0.5 dBi

### Power Supply

Operating voltage range: 5.0 VDC (UBS connection), USB cable 1.0 m lenght

### Mechanical Size of the EUT

Height: 2 cm                      Width: 11 cm                      Length: 11 cm

### Cable Lengths and Types

Cable:	Length:	Type:
USB cable	1.0 m	Shielded

**Peripherals**

Computer: type HP EliteBook 8540w, s/n CND1177MFQ,  
supplied by the customer.

## Disclaimer

*This document is issued by the Company under its General Conditions of service accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.*

*Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.*


*Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. This document cannot be reproduced except in full, without prior approval of the Company.*

## **TEST CONDITIONS**

### **EUT Test Conditions During EMC-Testing**

The USB port of the EUT was connected to the computer. The transmitters of the EUT were in stand-by mode all the tests.

## Photographs of the EUT



Picture 1 EUT.



Picture 2 EUT back.






**Picture 3.** The EUT and test set-up for conducted emission test.



**Picture 4.** The EUT and the test set-up for radiated emission test 30MHz-1GHz.





**Picture 5.** The EUT and the test set-up for radiated emission test 1-2GHz.

## SUMMARY OF TESTING

Test Specification	Description of Test	Result
§15.107	Conducted Emissions	PASS
§15.109	Radiated Emissions	PASS

## Test Facility

<input type="checkbox"/> Testing Location / address: FCC registration number: <b>90598</b>	SGS Fimko Ltd Särkiniementie 3 FI-00210, HELSINKI FINLAND
<input checked="" type="checkbox"/> Testing Location / address: FCC registration number: <b>178986</b> Industry Canada registration number: <b>8708A-2</b>	SGS Fimko Ltd Karakaarenkuja 4 FI-02610, ESPOO FINLAND

### Conducted Emissions In The Frequency Range 150 kHz - 30 MHz.

**Standard:** ANSI C63.4 (2014)  
**Tested by:** MIH  
**Date:** 23 October 2017  
**Temperature:** 23 °C  
**Humidity:** 19 %  
**Barometric pressure:** 1019 hPa  
**Measurement uncertainty:**  $\pm 2.9$  dB Level of confidence 95 % ( $k = 2$ )

#### Test Plan


Conducted disturbance voltage was measured with an artificial main network from 150 kHz to 30 MHz with 80 Hz steps and a resolution bandwidth of 9 kHz. Measurements were carried out with peak and average detectors from the phase(s) and neutral lines of the power supply cable.

The EUT was working as described in the section "EUT Test Conditions".

The input voltage of the computer was 115V 60Hz during the test.

#### Test results

Conducted Emission Mains FCC Part 15 Class B with ENV216



**Figure 1.** The measured curves with peak- and average-detectors, measured from AC mains.

**Final measurements from the worst frequencies**
**Table 1.** Quasi-peak Results.

Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.150000	47.8	1000.0	9.000	On	L1	9.9	18.2	66.0
0.680000	33.0	1000.0	9.000	On	N	10.3	23.0	56.0
4.137750	29.7	1000.0	9.000	On	N	10.4	26.3	56.0
12.762000	27.5	1000.0	9.000	On	L1	10.4	32.5	60.0
13.935000	32.1	1000.0	9.000	On	N	10.6	27.9	60.0

**Table 2.** Average Results.

Frequency (MHz)	Average (dB $\mu$ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.188250	35.5	1000.0	9.000	On	N	10.1	18.6	54.1
3.811750	23.0	1000.0	9.000	On	N	10.4	23.0	46.0
3.884000	22.7	1000.0	9.000	On	N	10.4	23.3	46.0

Correction factor (dB) in the final result tables contains the sum of the transducers.  
Final values are the measured values corrected with the correction factor.

## Radiated Emissions In The Frequency Range 30 MHz - 1000 MHz.

<b>Standard:</b>	ANSI C63.4	(2014)
<b>Tested by:</b>	MIH	
<b>Date:</b>	23 October 2017	
<b>Temperature:</b>	23 °C	
<b>Humidity:</b>	19 %	
<b>Barometric pressure</b>	1019 hPa	
<b>Measurement uncertainty:</b>	$\pm 4.9$ dB (30 to 200 MHz) Level of confidence 95 % (k = 2). $\pm 4.1$ dB (0.2 to 1 GHz)	

Radiated electric field strength was measured from 30 MHz to 1 GHz in a semi-anechoic chamber. Measurements were done with a resolution bandwidth of 120 kHz. The preview measurements were done with a peak detector and the final measurements with a quasi peak detector.

The measuring distance between EUT and the receiving antenna was 3 meters.

The AC-supply to the turntable was fed through the filter.

The EUT was placed on a table and 0.8 m above the reflecting ground plane.

### Radiated measurement settings

#### Preliminary testing:


Turntable movement:	20 ° step
Turntable position:	10 ° to 350°
Antenna movement:	1.5 m step
Antenna height:	1.0 m to 4.0 m
Antenna polarization:	Vertical and horizontal

#### Final testing:

Turntable movement:	Continuous
Turntable position:	$\pm 15$ °
Antenna movement:	Continuous
Antenna height:	$\pm 0.75$ m
Antenna polarization:	Vertical and horizontal

## Test results

Radiated Emission FCC Part 15 Class B 30-1000MHz 3m



**Figure 2.** The measured curves with the peak-detector and both measuring antenna polarization.

**Table 3.** Final quasi-peak measurements from the worst frequencies.

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
33.295000	28.6	1000.0	120.000	100.0	V	3.0	17.1	11.4	40.0
63.695000	25.9	1000.0	120.000	400.0	H	3.0	17.2	14.1	40.0
99.895000	28.1	1000.0	120.000	120.0	V	3.0	13.8	15.4	43.5
157.075000	28.0	1000.0	120.000	100.0	V	3.0	18.4	15.5	43.5
241.495000	23.1	1000.0	120.000	100.0	H	3.0	17.0	22.9	46.0
389.975000	32.3	1000.0	120.000	100.0	H	3.0	21.3	13.7	46.0

Correction factor (dB) in the final result tables contains the sum of the transducers (cables + antenna factor). Final values are the measured values corrected with the correction factor.

## Radiated Emissions In The Frequency Range 1-2 GHz

<b>Standard:</b>	ANSI C63.4	(2014)
<b>Tested by:</b>	MIH	
<b>Date:</b>	23 October 2017	
<b>Temperature:</b>	23 °C	
<b>Humidity:</b>	19 %	
<b>Barometric pressure:</b>	1019 hPa	
<b>Measurement uncertainty:</b>	$\pm 4.3$ dB (1-2 GHz)	Level of confidence 95 % (k = 2).

### Test plan

Radiated electric field strength was measured in a semi-anechoic chamber. The preview measurements were done with a peak detector and the final measurements with peak- and average detectors. The EUT was placed on a table 0.8 meters above the ground plane. The AC-supply to the turntable was fed through the filter.

The measuring distance between EUT and the receiving antenna was 3 meters.

The highest internal source frequency of the EUT is 168 MHz.

The EUT was working as described in the section "EUT Test Conditions During Testing".

### Radiated measurement settings

#### Preliminary testing (1 to 2 GHz):

Turntable movement:	15 ° step
Turntable position:	0 ° to 345°
Antenna movement:	1 m step
Antenna height:	1.0 m to 4.00 m
Antenna polarization:	Vertical and horizontal


#### Final testing (1 to 2 GHz):

Turntable movement:	Continuous
Turntable position:	$\pm 15$ °
Antenna movement:	Continuous
Antenna height:	$\pm 0.5$ m
Antenna polarization:	Vertical and horizontal



## Test results

Radiated Emission FCC Part 15 Class B 1-18GHz 3m



**Figure 3.** The measured curves with the peak-detector and both measuring antenna polarization.

**Table 4.** Final quasi-peak measurements from the worst frequencies.

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1104.975000	43.5	1000.0	1000.000	285.0	V	217.0	-0.8	30.4	73.9
1170.575000	44.1	1000.0	1000.000	106.0	V	240.0	-0.5	29.8	73.9
1948.875000	42.1	1000.0	1000.000	289.0	V	194.0	3.2	31.8	73.9

**Table 5.** Final quasi-peak measurements from the worst frequencies.

Frequency (MHz)	Average (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1500.025000	28.6	1000.0	1000.000	100.0	V	107.0	-0.1	25.3	53.9

Correction factor (dB) in the final result tables contains the sum of the transducers (cables + antenna factor). Final values are the measured values corrected with the correction factor.

## List of test equipment

### Conducted Emissions

Equipment	Manufacturer	Type	Inv number	Prev Calib	Next Calib
TEST SOFTWARE	ROHDE & SCHWARZ	EMC-32	-	-	-
LISN	ROHDE & SCHWARZ	ENV216	inv:9611	2017-02-23	2018-02-23
EMI TEST RECEIVER	ROHDE & SCHWARZ	ESU 26	inv:8453	2017-07-10	2018-07-10

### Radiated Emissions

Equipment	Manufacturer	Type	Inv or serial	Prev Calib	Next Calib
ANTENNA	EMCO	3117	inv:7293	2016-03-16	2018-03-06
ANTENNA	SCHWARZBECK	VULB 9168	inv:8911	2016-25-10	2018-25-10
PREAMPLIFIER	CIAO	CA118-3123	inv. 10278	2016-11-28	2017-11-28
TURNTABLE	MATURO	DS430 UPGRADED	inv:10182	-	-
MAST & TURNTABLE CONTROLLER	MATURO	NCD	inv:10183	-	-
ANTENNA MAST	MATURO	TAM 4.0E	inv:10181	-	-
TEST SOFTWARE	ROHDE & SCHWARZ	EMC-32	-	-	-
ATTENUATOR	PASTERNAK	PE 7004-4	inv:10126	2016-12-30	2017-12-30