



TEST REPORT

Applicant Name : Telepower Communication Co., Ltd.
Address : 5 Bld, Zone A, Hantian Technology Town No.17 ShenHai RD, Nanhai District Foshan, China
Report Number : SZNS220422-15855E-RF-00B
FCC ID: 2AJ2B-K5

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Self-Service Kiosk
Model No.: K5
Multiple Model(s) No.: K7, K10, K15, K16, K17, K20, K30, TPS700, TPS720 (Please refer to DOS for Model difference)
Trade Mark: N/A
Date Received: 2022/04/22
Report Date: 2022/05/25

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Ting Lü
EMC Engineer

Approved By:

Robert Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*" .

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "**". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC §15.247 (I) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	14
FCC §15.203 - ANTENNA REQUIREMENT	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	16
TRANSD FACTOR & MARGIN CALCULATION.....	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
FACTOR & MARGIN CALCULATION	21
TEST DATA	21
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST DATA	44
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	46
APPLICABLE STANDARD	46

TEST PROCEDURE	46
TEST DATA	46
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	Wi-Fi: 802.11b: 18.86dBm, 802.11g: 23.14dBm, 802.11n-HT20: 23.02dBm, 802.11n-HT40: 20.62dBm
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification*	5 dBi (provided by the applicant)
Voltage Range	AC 120V/60Hz
Sample serial number	SZNS220422-15855E-RF-S1 for CE&RE SZNS220422-15855E-RF-S2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4GHz Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.
802.11n-HT40 mode was tested with Channel 3, 6 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software


“ADB Command”* software was used to test and power level as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	Default	Default	Default
802.11g	6Mbps	Default	Default	Default
802.11n-HT20	MCS0	Default	Default	Default
802.11n-HT40	MCS0	Default	Default	Default

The software and power level was provided by the applicant.


Duty cycle

802.11b mode




Date: 16.MAY.2022 17:36:50

802.11g mode




Date: 16.MAY.2022 17:23:14

802.11n-HT20 Mode



Date: 16.MAY.2022 17:12:36

802.11n-HT40 Mode



Date: 16.MAY.2022 17:07:08

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)	1/T (kHz)
802.11b	100	100	100	0.01
802.11g	2.087	2.152	96.98	0.48
802.11n-HT20	1.942	2.023	96.00	0.51
802.11n-HT40	0.957	1.026	93.27	1.04

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
HUAWEI	Router	WS5100	A4933FEF1D01
Unknown	U disk*2	Unknown	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded detachable RJ45 cable	8.0	EUT	Router
Un-shielded detachable AC cable	3.0	LISN	EUT

Block Diagram of Test Setup

For Conducted Emission



For Radiated Emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2021/12/13	2022/12/12
SPECTRUM ANALYZER	Rohde & Schwarz	FSU26	200982	2021/07/06	2022/07/05
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	
Unknown	RF Cable	Unknown	Unknown	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	5.0	3.16	23.5	223.87	20	0.141	1

Note: BT and wifi cannot transmit at same time.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one external antenna with unique antenna connector and the antenna gain is 5.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions


Temperature:	23 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Jason Liu on 2022-05-20.

EUT operation mode: Transmitting

Wi-Fi: (Worst case is 802.11g mode, middle Channel)


AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : SZNS220422-15855E-RF
 Mode : 2.4G WIFI
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.164	9.80	20.36	30.16	55.24	-25.08	Average
2	0.164	9.80	33.16	42.96	65.24	-22.28	QP
3	0.282	9.80	21.92	31.72	50.75	-19.03	Average
4	0.282	9.80	29.54	39.34	60.75	-21.41	QP
5	0.453	9.80	24.39	34.19	46.81	-12.62	Average
6	0.453	9.80	34.37	44.17	56.81	-12.64	QP
7	0.561	9.81	31.99	41.80	46.00	-4.20	Average
8	0.561	9.81	34.12	43.93	56.00	-12.07	QP
9	2.023	9.82	25.86	35.68	46.00	-10.32	Average
10	2.023	9.82	28.97	38.79	56.00	-17.21	QP
11	13.569	9.94	20.60	30.54	50.00	-19.46	Average
12	13.569	9.94	15.96	25.90	60.00	-34.10	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room
 Condition: Neutral
 Job No. : SZNS220422-15855E-RF
 Mode : 2.4G WIFI
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB
1	0.160	9.80	23.74	33.54	55.48	-21.94 Average
2	0.160	9.80	33.40	43.20	65.48	-22.28 QP
3	0.293	9.80	20.66	30.46	50.43	-19.97 Average
4	0.293	9.80	29.07	38.87	60.43	-21.56 QP
5	0.455	9.80	27.99	37.79	46.78	-8.99 Average
6	0.455	9.80	34.52	44.32	56.78	-12.46 QP
7	0.608	9.81	31.54	41.35	46.00	-4.65 Average
8	0.608	9.81	31.63	41.44	56.00	-14.56 QP
9	4.936	9.89	24.46	34.35	46.00	-11.65 Average
10	4.936	9.89	26.76	36.65	56.00	-19.35 QP
11	5.025	9.89	23.66	33.55	50.00	-16.45 Average
12	5.025	9.89	27.37	37.26	60.00	-22.74 QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	28 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa


The testing was performed by Level Li on 2022-05-20.

EUT operation mode: Transmitting

30MHz-1GHz: (Worst case is 802.11g mode, low Channel)

Note: when the test result of peak was below the limit of QP more than 6dB, just the peak value was recorded.


Horizontal



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : SZNS220422-15855E-RF
 Test Mode: 2.4G WIFI

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	162.753	-14.29	46.38	32.09	43.50	-11.41	Peak
2	240.093	-10.90	49.91	39.01	46.00	-6.99	Peak
3	320.077	-8.45	40.84	32.39	46.00	-13.61	Peak
4	480.107	-5.00	42.73	37.73	46.00	-8.27	Peak
5	512.060	-4.27	36.87	32.60	46.00	-13.40	Peak
6	880.249	1.23	36.62	37.85	46.00	-8.15	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220422-15855E-RF
 Test Mode: 2.4G WIFI

	Freq	Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	239.987	-10.91	54.20	43.29	46.00	-2.71	QP
2	320.077	-8.45	39.04	30.59	46.00	-15.41	Peak
3	480.107	-5.00	49.15	44.15	46.00	-1.85	QP
4	720.146	-1.35	39.81	38.46	46.00	-7.54	Peak
5	880.249	1.23	40.20	41.43	46.00	-4.57	QP
6	960.477	2.36	38.11	40.47	54.00	-13.53	Peak

1-25 GHz: (worst case)

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	68.13	PK	283	2	H	-7.24	60.89	74	-13.11
2310	53.51	AV	283	2	H	-7.24	46.27	54	-7.73
2310	68.02	PK	118	1.4	V	-7.24	60.78	74	-13.22
2310	53.44	AV	118	1.4	V	-7.24	46.20	54	-7.80
2390	69.21	PK	19	1.8	H	-7.22	61.99	74	-12.01
2390	54.25	AV	19	1.8	H	-7.22	47.03	54	-6.97
2390	69.10	PK	184	1.2	V	-7.22	61.88	74	-12.12
2390	54.14	AV	184	1.2	V	-7.22	46.92	54	-7.08
4824	54.37	PK	250	2	H	-3.53	50.84	74	-23.16
4824	54.68	PK	209	1.4	V	-3.53	51.15	74	-22.85
802.11B, Middle Channel									
4874	54.41	PK	26	1.6	H	-3.41	51	74	-23.00
4874	54.69	PK	151	1.6	V	-3.41	51.28	74	-22.72
11B, High Channel									
2483.5	69.91	PK	67	1.5	H	-7.2	62.71	74	-11.29
2483.5	54.97	AV	67	1.5	H	-7.2	47.77	54	-6.23
2483.5	69.80	PK	80	2	V	-7.2	62.6	74	-11.4
2483.5	54.88	AV	80	2	V	-7.2	47.68	54	-6.32
2500	69.03	PK	341	1.6	H	-7.18	61.85	74	-12.15
2500	54.74	AV	341	1.6	H	-7.18	47.56	54	-6.44
2500	68.93	PK	69	2.5	V	-7.18	61.75	74	-12.25
2500	54.67	AV	69	2.5	V	-7.18	47.49	54	-6.51
4924	53.99	PK	264	1.3	H	-3.16	50.83	74	-23.17
4924	54.18	PK	240	1.6	V	-3.16	51.02	74	-22.98

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11G, Low Channel									
2310	69.77	PK	254	1.5	H	-7.24	62.53	74	-11.47
2310	54.10	AV	254	1.5	H	-7.24	46.86	54	-7.14
2310	69.54	PK	309	1.4	V	-7.24	62.30	74	-11.70
2310	53.86	AV	309	1.4	V	-7.24	46.62	54	-7.38
2390	74.34	PK	126	1.3	H	-7.22	67.12	74	-6.88
2390	59.72	AV	126	1.3	H	-7.22	52.50	54	-1.50
2390	72.83	PK	253	1.4	V	-7.22	65.61	74	-8.39
2390	58.06	AV	253	1.4	V	-7.22	50.84	54	-3.16
4824	54.70	PK	229	1.1	H	-3.53	51.17	74	-22.83
4824	55.23	PK	325	1.1	V	-3.53	51.70	74	-22.30
802.11G, Middle Channel									
4874	54.82	PK	43	1.7	H	-3.41	51.41	74	-22.59
4874	55.3	PK	150	1.7	V	-3.41	51.89	74	-22.11
802.11G, High Channel									
2483.5	79.78	PK	75	2.3	H	-7.2	72.58	74	-1.42
2483.5	60.02	AV	75	2.3	H	-7.2	52.82	54	-1.18
2483.5	79.20	PK	184	2.2	V	-7.2	72	74	-2
2483.5	59.71	AV	184	2.2	V	-7.2	52.51	54	-1.49
2500	70.63	PK	233	2.5	H	-7.18	63.45	74	-10.55
2500	55.47	AV	233	2.5	H	-7.18	48.29	54	-5.71
2500	70.46	PK	10	1.2	V	-7.18	63.28	74	-10.72
2500	55.32	AV	10	1.2	V	-7.18	48.14	54	-5.86
4924	54.31	PK	156	2	H	-3.16	51.15	74	-22.85
4924	54.83	PK	189	2.4	V	-3.16	51.67	74	-22.33

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11N20, Low Channel									
2310	69.84	PK	342	1.3	H	-7.24	62.60	74	-11.40
2310	54.25	AV	342	1.3	H	-7.24	47.01	54	-6.99
2310	69.60	PK	171	2.4	V	-7.24	62.36	74	-11.64
2310	54.02	AV	171	2.4	V	-7.24	46.78	54	-7.22
2390	75.97	PK	112	1.2	H	-7.22	68.75	74	-5.25
2390	60.04	AV	112	1.2	H	-7.22	52.82	54	-1.18
2390	73.78	PK	235	2.2	V	-7.22	66.56	74	-7.44
2390	58.22	AV	235	2.2	V	-7.22	51.00	54	-3.00
4824	54.68	PK	93	2.1	H	-3.53	51.15	74	-22.85
4824	55.00	PK	333	1.9	V	-3.53	51.47	74	-22.53
802.11N20, Middle Channel									
4874	54.69	PK	114	2.4	H	-3.41	51.28	74	-22.72
4874	55.13	PK	90	1.6	V	-3.41	51.72	74	-22.28
802.11N20, High Channel									
2483.5	80.02	PK	350	1.2	H	-7.2	72.82	74	-1.18
2483.5	60.20	AV	350	1.2	H	-7.2	53	54	-1
2483.5	79.58	PK	306	1.8	V	-7.2	72.38	74	-1.62
2483.5	59.97	AV	306	1.8	V	-7.2	52.77	54	-1.23
2500	70.89	PK	352	1.9	H	-7.18	63.71	74	-10.29
2500	55.57	AV	352	1.9	H	-7.18	48.39	54	-5.61
2500	69.63	PK	143	1.8	V	-7.18	62.45	74	-11.55
2500	55.44	AV	143	1.8	V	-7.18	48.26	54	-5.74
4924	53.99	PK	229	2.3	H	-3.16	50.83	74	-23.17
4924	54.56	PK	347	2.2	V	-3.16	51.4	74	-22.6

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
802.11N40, Low Channel									
2310	70.12	PK	45	1.5	H	-7.24	62.88	74	-11.12
2310	54.59	AV	45	1.5	H	-7.24	47.35	54	-6.65
2310	69.94	PK	299	1.8	V	-7.24	62.70	74	-11.30
2310	54.45	AV	299	1.8	V	-7.24	47.21	54	-6.79
2390	79.74	PK	252	1.3	H	-7.22	72.52	74	-1.48
2390	60.21	AV	252	1.3	H	-7.22	52.99	54	-1.01
2390	78.57	PK	83	1.5	V	-7.22	71.35	74	-2.65
2390	59.96	AV	83	1.5	V	-7.22	52.74	54	-1.26
4844	54.50	PK	93	1.3	H	-3.54	50.96	74	-23.04
4844	54.98	PK	72	1.4	V	-3.54	51.44	74	-22.56
802.11N40, Middle Channel									
4874	54.62	PK	193	1.3	H	-3.41	51.21	74	-22.79
4874	55.08	PK	124	1.4	V	-3.41	51.67	74	-22.33
802.11N40, High Channel									
2483.5	80.11	PK	251	2.2	H	-7.2	72.91	74	-1.09
2483.5	60.20	AV	251	2.2	H	-7.2	53	54	-1
2483.5	79.86	PK	342	2.3	V	-7.2	72.66	74	-1.34
2483.5	59.94	AV	342	2.3	V	-7.2	52.74	54	-1.26
2500	70.85	PK	104	1.7	H	-7.18	63.67	74	-10.33
2500	58.16	AV	104	1.7	H	-7.18	50.98	54	-3.02
2500	70.60	PK	176	2.4	V	-7.18	63.42	74	-10.58
2500	57.63	AV	176	2.4	V	-7.18	50.45	54	-3.55
4904	54.14	PK	14	1.1	H	-3.26	50.88	74	-23.12
4904	54.77	PK	303	2	V	-3.26	51.51	74	-22.49

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit


The other spurious emission which is 20dB below to the limit or in noise floor level was not recorded.

When the test result of peak was less than the limit of average, just peak values were recorded.


1-18 GHz:

Pre-scan Plots:

802.11 g Middle Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 g Middle Channel
Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	27.9~28.5 °C
Relative Humidity:	48~74 %
ATM Pressure:	100.9~101.0 kPa

The testing was performed by Key Pei from 2022-05-14 to 2022-05-25.

EUT operation mode: Transmitting


Please refer to the following table and plots.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode				
Low	2412	10.115	14.935	≥500
Middle	2437	10.084	14.880	≥500
High	2462	10.115	14.978	≥500
802.11g mode				
Low	2412	16.449	16.715	≥500
Middle	2437	16.346	17.496	≥500
High	2462	16.521	16.541	≥500
802.11n-HT20 mode				
Low	2412	17.639	17.887	≥500
Middle	2437	17.410	17.757	≥500
High	2462	17.564	17.713	≥500
802.11n-HT40 mode				
Low	2422	35.479	36.122	≥500
Middle	2437	35.499	36.237	≥500
High	2452	35.558	36.237	≥500


6 dB Emission Bandwidth

802.11b Low Channel




Date: 24.MAY.2022 00:27:44

802.11b Middle Channel




Date: 24.MAY.2022 00:34:19

802.11b High Channel




Date: 24.MAY.2022 00:31:17

802.11g Low Channel




Date: 23.MAY.2022 23:36:56

802.11g Middle Channel




Date: 24.MAY.2022 00:40:37

802.11g High Channel




Date: 24.MAY.2022 00:44:04

802.11n-HT20 Low Channel




Date: 23.MAY.2022 23:48:11

802.11n-HT20 Middle Channel




Date: 23.MAY.2022 23:53:10

802.11n-HT20 High Channel




Date: 23.MAY.2022 23:55:52

802.11n-HT40 Low Channel




Date: 25.MAY.2022 20:59:02

802.11n-HT40 Middle Channel



Date: 24.MAY.2022 00:15:37


802.11n-HT40 High Channel



Date: 25.MAY.2022 21:12:54


99% Emission Bandwidth

802.11b Low Channel




Date: 14.MAY.2022 16:32:02

802.11b Middle Channel




Date: 24.MAY.2022 00:36:52

802.11b High Channel




Date: 16.MAY.2022 15:00:25

802.11g Low Channel




Date: 14.MAY.2022 16:24:05

802.11g Middle Channel




Date: 16.MAY.2022 14:49:30

802.11g High Channel




Date: 16.MAY.2022 15:02:04

802.11n-HT20 Low Channel




Date: 14.MAY.2022 16:40:41

802.11n-HT20 Middle Channel




Date: 16.MAY.2022 15:07:32

802.11n-HT20 High Channel




Date: 16.MAY.2022 15:05:34

802.11n-HT40 Low Channel




Date: 14.MAY.2022 16:49:23

802.11n-HT40 Middle Channel



Date: 14.MAY.2022 16:51:51

802.11n-HT40 High Channel



Date: 16.MAY.2022 14:45:18


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

- c. Place the EUT on a bench and set it in transmitting mode.
- d. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
- e. Add a correction factor to the display.



Note: the Open Switch and Control Unit have a built-in power sensor.

Test Data

Environmental Conditions

Temperature:	27.9 °C
Relative Humidity:	74 %
ATM Pressure:	101.0 kPa

The testing was performed by Key Pei on 2022-05-16.

EUT operation mode: Transmitting

Test Result: Compliant.

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b mode			
Low	2412	18.22	30
Middle	2437	18.45	30
High	2462	18.86	30
802.11g mode			
Low	2412	23.01	30
Middle	2437	23.14	30
High	2462	22.74	30
802.11n HT20 mode			
Low	2412	22.59	30
Middle	2437	23.02	30
High	2462	22.77	30
802.11n HT40 mode			
Low	2422	20.61	30
Middle	2437	20.62	30
High	2452	20.02	30


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- f. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- g. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- h. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- i. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- j. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	27.9 °C
Relative Humidity:	74 %
ATM Pressure:	101.0 kPa


The testing was performed by Key Pei on 2022-05-25.

EUT operation mode: Transmitting

Test Result: Compliant.


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 25.MAY.2022 21:47:27

802.11b: Band Edge, Right Side




Date: 25.MAY.2022 21:49:49

802.11g: Band Edge, Left Side




Date: 25.MAY.2022 21:43:23

802.11g: Band Edge, Right Side




Date: 25.MAY.2022 21:40:24

802.11n-HT20: Band Edge, Left Side




Date: 25.MAY.2022 21:30:59

802.11n-HT20: Band Edge, Right Side




Date: 25.MAY.2022 21:35:48

802.11n-HT40: Band Edge, Left Side



Date: 25.MAY.2022 21:27:17

802.11n-HT40: Band Edge, Right Side



Date: 25.MAY.2022 21:21:15


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- k. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- l. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
- m. Set the VBW $\geq 3 \times \text{RBW}$.
- n. Set the span to 1.5 times the DTS bandwidth.
- o. Detector = peak.
- p. Sweep time = auto couple.
- q. Trace mode = max hold.
- r. Allow trace to fully stabilize.
- s. Use the peak marker function to determine the maximum amplitude level within the RBW.
- t. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	27.9 °C
Relative Humidity:	74 %
ATM Pressure:	101.0 kPa


The testing was performed by Key Pei on 2022-05-16.

EUT operation mode: Transmitting

Test Result: Compliant.


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-16.48	≤ 8
Middle	2437	-17.09	≤ 8
High	2462	-16.64	≤ 8
802.11g mode			
Low	2412	-21.03	≤ 8
Middle	2437	-21.36	≤ 8
High	2462	-21.69	≤ 8
802.11n-HT20 mode			
Low	2412	-22.74	≤ 8
Middle	2437	-22.54	≤ 8
High	2462	-23.04	≤ 8
802.11n-HT40 mode			
Low	2422	-25.68	≤ 8
Middle	2437	-25.46	≤ 8
High	2452	-25.65	≤ 8

Power Spectral Density, 802.11b Low Channel




Date: 16.MAY.2022 15:31:28

Power Spectral Density, 802.11b Middle Channel




Date: 16.MAY.2022 15:33:16

Power Spectral Density, 802.11b High Channel




Date: 16.MAY.2022 15:35:32

Power Spectral Density, 802.11g Low Channel




Date: 16.MAY.2022 15:28:14

Power Spectral Density, 802.11g Middle Channel




Date: 16.MAY.2022 15:25:39

Power Spectral Density, 802.11g High Channel




Date: 16.MAY.2022 15:22:36

Power Spectral Density, 802.11n-HT20 Low Channel




Date: 16.MAY.2022 15:16:40

Power Spectral Density, 802.11n-HT20 Middle Channel




Date: 16.MAY.2022 15:13:00

Power Spectral Density, 802.11n-HT20 High Channel




Date: 16.MAY.2022 15:40:56

Power Spectral Density, 802.11n-HT40 Low Channel




Date: 16.MAY.2022 15:49:54

Power Spectral Density, 802.11n-HT40 Middle Channel



Date: 16.MAY.2022 15:46:35

Power Spectral Density, 802.11n-HT40 High Channel



Date: 16.MAY.2022 15:44:20

***** END OF REPORT *****