
WHAT YOU GET

The following items are included in the box:



PRODUCT:	LED LAMP	
MODEL:	EBE-BAW419-B	
POWER:	AC 120V	
LUMINOUS FLUX:	1050 Iumens	
COLOR TEMP:	2700k	
LIFE SPAN:	25000 hour	
BEAM ANGLE:	220 °	
DIMMABLE:	Bright	
DIMENSION:	D70*H133mm	
	5	
?	≥	





Dimmable

Remote Access



Set Schedule

Select Color

Energy Saving

INSTALLATION

STEP 1

Screw in LED lamp to lampholder.

STEP 2

Power on and off 3 times

STEP 3

Confirm that lamp is rapidly flashing

STEP 4

Proceed to connect the network via Wi-Fi




MAKE SURE WI-FI NETWORK IS AVAILABLE







SUPPORT





FCC Statement:

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and

(2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.