



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: ZHEJIANG EBOY TECHNOLOGY CO., LTD

Address: No. 568, Huabao street, Qianyuan Town, Deqing County, Huzhou City,
Zhejiang Province

FCC ID: 2AJ3WEBEBBW502

Product Name: LED LAMP

Standard(s): 47 CFR Part 15, Subpart C (15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230844594-00A

Date Of Issue: 2023/8/21

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	9
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	16
3.2.5 Corrected Amplitude & Margin Calculation.....	16
3.3 MINIMUM 6 dB EMISSION BANDWIDTH	17
3.3.1 Applicable Standard.....	17
3.3.2 EUT Setup.....	17
3.3.3 Test Procedure	17
3.4 99% OCCUPIED BANDWIDTH.....	18
3.4.1 EUT Setup.....	18
3.4.2 Test Procedure	18
3.5 MAXIMUM CONDUCTED OUTPUT POWER.....	19
3.5.1 Applicable Standard.....	19
3.5.2 EUT Setup.....	19
3.5.3 Test Procedure	19
3.6 MAXIMUM POWER SPECTRAL DENSITY	20
3.6.1 Applicable Standard.....	20
3.6.2 EUT Setup.....	20
3.6.3 Test Procedure	20
3.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	21

3.7.1 Applicable Standard.....	21
3.7.2 EUT Setup.....	21
3.7.3 Test Procedure	21
3.8 DUTY CYCLE	22
3.8.1 EUT Setup.....	22
3.8.2 Test Procedure	22
3.9 ANTENNA REQUIREMENT.....	22
3.9.1 Applicable Standard.....	22
3.9.2 Judgment.....	22
4. Test DATA AND RESULTS	23
4.1 AC LINE CONDUCTED EMISSIONS.....	23
4.2 RADIATION SPURIOUS EMISSIONS	32
4.3 MINIMUM 6 dB EMISSION BANDWIDTH	67
4.4 99% OCCUPIED BANDWIDTH.....	72
4.5 MAXIMUM CONDUCTED OUTPUT POWER.....	77
4.6 MAXIMUM POWER SPECTRAL DENSITY	78
4.7 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	83
4.8 DUTY CYCLE:.....	88
5. RF EXPOSURE EVALUATION	90
5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)	90
5.1.1 Applicable Standard.....	90
5.1.2 Procedure	90
5.1.3 Calculated Result	90
6. EUT PHOTOGRAPHS	91
7. TEST SETUP PHOTOGRAPHS	92

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230844594-00A	Original Report	2023/8/21

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	LED LAMP
EUT Model:	EBE-BBW539
Multiple Model:	EBE-BBW502, BW426, BW326, BW926, BW226, BW906, BW406, BW306, BW206, EBE-BBW539-F, EBE-BBW418, EBE-BBW418-F, EBE-BBW543
Operation Frequency:	2412-2462MHz (802.11b/g/n ht20), 2422-2452MHz (802.11n ht40)
Maximum Average Output Power (Conducted):	15.66dBm
Modulation Type:	802.11b: DSSS-DBPSK, DQPSK, CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM
Rated Input Voltage:	AC 120 V
Serial Number:	298Q-1 (Model: EBE-BBW539, for RF Conducted Test) 298Q-2 (Model: EBE-BBW539, for Emissions Test) 298Q-3 (Model: EBE-BBW539-F, for Emissions Test) 298Q-4 (Model: EBE-BBW418, for Emissions Test) 298Q-5 (Model: EBE-BBW418-F, for Emissions Test)
EUT Received Date:	2023/8/3
EUT Received Status:	Good

Note:

The models list above are electrically identical with each other, the model EBE-BBW539 was fully tested. The difference between them please refer to the declaration letter for more details, which was provided by manufacturer.

Operation Frequency Detail:

For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2412
Middle	2437
Highest	2462

For 802.11n ht40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Per section 15.31(m), the below frequencies were performed the test as below:

Test Channel	Frequency (MHz)
Lowest	2422
Middle	2437
Highest	2452

Antenna Information Detail ▲ :

Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
PCB	50	2.4~2.5GHz	1.94 dBi

The Method of §15.203 Compliance:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
/	/	/	/

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For 802.11b/g/n:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.
Equipment Modifications:	No
EUT Exercise Software:	Beken WIFI Test Tool.exe

The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲:

Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	20	20	20
802.11g	6Mbps	50	50	50
802.11n ht20	MCS0	50	50	50
802.11n ht40	MCS0	45	45	45

The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
BULL	Lamp base	E27E14	CR23457121
BULL	Socket	GN-B3440	Unknown

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Power Cable	NO	NO	1	Socket	Lamp base
Power Cable	NO	NO	2	AC Mains	Lamp base

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB,200M~1GHz: 5.61 dB,1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB,18G~26.5G:5.47 dB,26.5G~40G:5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1310 & §2.1091	RF Exposure Evaluation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Emission Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup




3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4 99% Occupied Bandwidth

3.4.1 EUT Setup



3.4.2 Test Procedure

According to ANSI C63.10-2013 Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).


3.5 Maximum Conducted Output Power

3.5.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.


3.6 Maximum Power Spectral Density

3.6.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2 EUT Setup



3.6.3 Test Procedure

Duty cycle $\geq 98\%$

According to ANSI C63.10-2013 Section 11.10.3

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

According to ANSI C63.10-2013 Section 11.10.5

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$

According to ANSI C63.10-2013 Section 11.10.7


3.7 100 kHz Bandwidth of Frequency Band Edge

3.7.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.7.2 EUT Setup



3.7.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.8 Duty Cycle

3.8.1 EUT Setup



3.8.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.9 Antenna Requirement

3.9.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.9.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	298Q-2; 298Q-3; 298Q-4; 298Q-5	Test Date:	2023/8/9
Test Site:	CE	Test Mode:	Transmitting (Test at maximum output power mode 802.11b mode low channel)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.1	Relative Humidity: (%)	57	ATM Pressure: (kPa)	100.6
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/03/31	2024/03/30
R&S	EMI Test Receiver	ESR3	102726	2023/03/31	2024/03/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/08/06	2024/08/05
Audix	Test Software	E3	190306 (V9)	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

1)Test Results for Model: EBE-BBW418

Project No.: CR230844594-RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(EBE-BBW418)


Date: 2023-08-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.212	4.93	9.61	14.54	53.14	38.60	Average
2	0.212	24.05	9.61	33.66	63.14	29.48	QP
3	0.284	6.14	9.61	15.75	50.70	34.95	Average
4	0.284	23.72	9.61	33.33	60.70	27.37	QP
5	0.424	6.58	9.61	16.19	47.36	31.17	Average
6	0.424	22.70	9.61	32.31	57.36	25.05	QP
7	0.671	5.85	9.62	15.47	46.00	30.53	Average
8	0.671	20.47	9.62	30.09	56.00	25.91	QP
9	1.238	15.06	9.62	24.68	46.00	21.32	Average
10	1.238	22.35	9.62	31.97	56.00	24.03	QP
11	1.564	8.60	9.63	18.23	46.00	27.77	Average
12	1.564	22.01	9.63	31.64	56.00	24.36	QP

Project No.: CR230844594-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(EBE-BBW418)

Date: 2023-08-09




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.160	5.89	9.61	15.50	55.47	39.97	Average
2	0.160	23.39	9.61	33.00	65.47	32.47	QP
3	0.286	6.80	9.61	16.41	50.65	34.24	Average
4	0.286	23.66	9.61	33.27	60.65	27.38	QP
5	0.397	7.88	9.61	17.49	47.92	30.43	Average
6	0.397	22.81	9.61	32.42	57.92	25.50	QP
7	1.168	15.03	9.62	24.65	46.00	21.35	Average
8	1.168	21.93	9.62	31.55	56.00	24.45	QP
9	1.563	8.01	9.63	17.64	46.00	28.36	Average
10	1.563	20.73	9.63	30.36	56.00	25.64	QP
11	25.151	8.27	9.76	18.03	50.00	31.97	Average
12	25.151	14.35	9.76	24.11	60.00	35.89	QP

2) Test Results for Model: EBE-BBW418-F

Project No.: CR230844594-RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(EBE-BBW418-F)


Date: 2023-08-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.158	8.27	9.61	17.88	55.57	37.69	Average
2	0.158	26.08	9.61	35.69	65.57	29.88	QP
3	0.245	6.30	9.61	15.91	51.93	36.02	Average
4	0.245	24.30	9.61	33.91	61.93	28.02	QP
5	0.345	7.33	9.61	16.94	49.08	32.14	Average
6	0.345	23.62	9.61	33.23	59.08	25.85	QP
7	0.570	6.13	9.62	15.75	46.00	30.25	Average
8	0.570	22.28	9.62	31.90	56.00	24.10	QP
9	1.140	14.96	9.62	24.58	46.00	21.42	Average
10	1.140	22.12	9.62	31.74	56.00	24.26	QP
11	1.581	6.37	9.63	16.00	46.00	30.00	Average
12	1.581	19.22	9.63	28.85	56.00	27.15	QP

Project No.: CR230844594-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(EBE-BBW418-F)

Date: 2023-08-09




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.160	6.46	9.61	16.07	55.48	39.41	Average
2	0.160	23.72	9.61	33.33	65.48	32.15	QP
3	0.183	7.05	9.61	16.66	54.36	37.70	Average
4	0.183	23.84	9.61	33.45	64.36	30.91	QP
5	0.291	7.33	9.61	16.94	50.51	33.57	Average
6	0.291	23.98	9.61	33.59	60.51	26.92	QP
7	0.404	9.73	9.61	19.34	47.76	28.42	Average
8	0.404	31.07	9.61	40.68	57.76	17.08	QP
9	0.648	6.45	9.62	16.07	46.00	29.93	Average
10	0.648	21.15	9.62	30.77	56.00	25.23	QP
11	1.195	12.46	9.62	22.08	46.00	23.92	Average
12	1.195	19.69	9.62	29.31	56.00	26.69	QP

3) Test Results for Model: EBE-BBW539

Project No.: CR230844594-RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(EBE-BBW539)


Date: 2023-08-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.166	17.25	9.61	26.86	55.15	28.29	Average
2	0.166	37.32	9.61	46.93	65.15	18.22	QP
3	0.216	17.10	9.61	26.71	52.95	26.24	Average
4	0.216	36.50	9.61	46.11	62.95	16.84	QP
5	0.253	16.93	9.61	26.54	51.67	25.13	Average
6	0.253	37.09	9.61	46.70	61.67	14.97	QP
7	0.518	13.98	9.61	23.59	46.00	22.41	Average
8	0.518	34.64	9.61	44.25	56.00	11.75	QP
9	0.719	11.60	9.62	21.22	46.00	24.78	Average
10	0.719	31.78	9.62	41.40	56.00	14.60	QP
11	1.720	12.42	9.63	22.05	46.00	23.95	Average
12	1.720	23.46	9.63	33.09	56.00	22.91	QP

Project No.: CR230844594-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(EBE-BBW539)

Date: 2023-08-09




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.162	15.40	9.61	25.01	55.35	30.34	Average
2	0.162	35.16	9.61	44.77	65.35	20.58	QP
3	0.226	16.53	9.61	26.14	52.61	26.47	Average
4	0.226	36.43	9.61	46.04	62.61	16.57	QP
5	0.293	13.93	9.61	23.54	50.44	26.90	Average
6	0.293	35.30	9.61	44.91	60.44	15.53	QP
7	0.439	14.63	9.61	24.24	47.09	22.85	Average
8	0.439	35.66	9.61	45.27	57.09	11.82	QP
9	0.617	12.38	9.62	22.00	46.00	24.00	Average
10	0.617	32.94	9.62	42.56	56.00	13.44	QP
11	1.760	10.31	9.63	19.94	46.00	26.06	Average
12	1.760	22.28	9.63	31.91	56.00	24.09	QP

4) Test Results for Model: EBE-BBW539-F:

Project No.: CR230844594-RF
 Tester: David Huang
 Port: Line
 Note: Transmitting(EBE-BBW539-F)


Date: 2023-08-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.186	4.51	9.61	14.12	54.21	40.09	Average
2	0.186	23.95	9.61	33.56	64.21	30.65	QP
3	0.254	7.63	9.61	17.24	51.63	34.39	Average
4	0.254	24.17	9.61	33.78	61.63	27.85	QP
5	0.358	6.76	9.61	16.37	48.78	32.41	Average
6	0.358	23.94	9.61	33.55	58.78	25.23	QP
7	0.419	6.61	9.61	16.22	47.48	31.26	Average
8	0.419	23.08	9.61	32.69	57.48	24.79	QP
9	1.187	14.07	9.62	23.69	46.00	22.31	Average
10	1.187	22.09	9.62	31.71	56.00	24.29	QP
11	25.093	8.88	9.81	18.69	50.00	31.31	Average
12	25.093	14.82	9.81	24.63	60.00	35.37	QP

Project No.: CR230844594-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(EBE-BBW539-F)

Date: 2023-08-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.240	6.52	9.61	16.13	52.11	35.98	Average
2	0.240	23.96	9.61	33.57	62.11	28.54	QP
3	0.404	6.29	9.61	15.90	47.77	31.87	Average
4	0.404	22.95	9.61	32.56	57.77	25.21	QP
5	1.190	15.13	9.62	24.75	46.00	21.25	Average
6	1.190	23.07	9.62	32.69	56.00	23.31	QP
7	1.561	7.59	9.63	17.22	46.00	28.78	Average
8	1.561	21.57	9.63	31.20	56.00	24.80	QP
9	1.768	8.46	9.63	18.09	46.00	27.91	Average
10	1.768	20.70	9.63	30.33	56.00	25.67	QP
11	25.152	9.30	9.76	19.06	50.00	30.94	Average
12	25.152	15.38	9.76	25.14	60.00	34.86	QP

4.2 Radiation Spurious Emissions

Serial Number:	298Q-2; 298Q-3; 298Q-4; 298Q-5	Test Date:	2023/8/12~2023/8/16
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Carl Xue, Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.8~27.2	Relative Humidity: (%)	49~67	ATM Pressure: (kPa)	99.7~100.2
----------------------	-----------	---------------------------	-------	------------------------	------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2022/9/16	2023/9/15
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below tables.

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

1) 30MHz-1GHz


Test Results for Model: EBE-BBW539 (Test at 802.11b mode low channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	28.10	-4.00	24.10	40.00	15.90	Peak
2	71.080	33.21	-16.59	16.62	40.00	23.38	Peak
3	142.324	32.25	-11.92	20.33	43.50	23.17	Peak
4	305.680	33.63	-10.57	23.06	46.00	22.94	Peak
5	361.714	40.27	-9.78	30.49	46.00	15.51	Peak
6	719.200	29.01	-3.30	25.71	46.00	20.29	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	27.68	-4.00	23.68	40.00	16.32	Peak
2	37.416	32.52	-9.31	23.21	40.00	16.79	Peak
3	70.832	42.75	-16.55	26.20	40.00	13.80	Peak
4	144.842	31.28	-11.94	19.34	43.50	24.16	Peak
5	426.521	32.76	-7.65	25.11	46.00	20.89	Peak
6	721.726	29.41	-3.22	26.19	46.00	19.81	Peak

Test Results for Model: EBE-BBW539 (Test at 802.11b mode Middle channel)


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



Date: 2023-08-16

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	27.20	-3.60	23.60	40.00	16.40	Peak
2	71.080	33.28	-16.59	16.69	40.00	23.31	Peak
3	137.420	31.87	-11.75	20.12	43.50	23.38	Peak
4	361.714	36.15	-9.78	26.37	46.00	19.63	Peak
5	406.088	33.89	-8.58	25.31	46.00	20.69	Peak
6	706.700	29.88	-3.49	26.39	46.00	19.61	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	37.416	33.42	-9.31	24.11	40.00	15.89	Peak
2	69.114	42.04	-16.59	25.45	40.00	14.55	Peak
3	81.212	35.23	-17.38	17.85	40.00	22.15	Peak
4	144.842	31.51	-11.94	19.57	43.50	23.93	Peak
5	321.061	35.04	-10.52	24.52	46.00	21.48	Peak
6	515.437	30.07	-5.83	24.24	46.00	21.76	Peak


Test Results for Model: EBE-BBW539 (Test at 802.11b mode High channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	28.53	-3.60	24.93	40.00	15.07	Peak
2	70.832	32.71	-16.55	16.16	40.00	23.84	Peak
3	138.874	35.39	-11.80	23.59	43.50	19.91	Peak
4	361.714	39.68	-9.78	29.90	46.00	16.10	Peak
5	470.523	30.49	-6.33	24.16	46.00	21.84	Peak
6	706.700	28.67	-3.49	25.18	46.00	20.82	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	26.84	-3.60	23.24	40.00	16.76	Peak
2	37.285	34.09	-9.22	24.87	40.00	15.13	Peak
3	43.659	35.42	-13.46	21.96	40.00	18.04	Peak
4	69.600	42.69	-16.52	26.17	40.00	13.83	Peak
5	81.212	36.40	-17.38	19.02	40.00	20.98	Peak
6	360.448	32.99	-9.84	23.15	46.00	22.85	Peak


Test Results for Model: EBE-BBW539-F (Test at 802.11b mode Low channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.853	27.82	-4.26	23.56	40.00	16.44	Peak
2	143.830	32.55	-11.96	20.59	43.50	22.91	Peak
3	314.377	35.02	-10.60	24.42	46.00	21.58	Peak
4	361.714	35.49	-9.78	25.71	46.00	20.29	Peak
5	480.528	30.23	-6.25	23.98	46.00	22.02	Peak
6	932.272	28.75	-0.55	28.20	46.00	17.80	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	30.28	-3.60	26.68	40.00	13.32	Peak
2	39.437	39.90	-10.87	29.03	40.00	10.97	Peak
3	62.871	37.97	-17.13	20.84	40.00	19.16	Peak
4	141.826	30.89	-11.92	18.97	43.50	24.53	Peak
5	480.528	31.82	-6.25	25.57	46.00	20.43	Peak
6	952.094	28.09	-0.12	27.97	46.00	18.03	Peak


Test Results for Model: EBE-BBW539-F (Test at 802.11b mode Middle channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.620	29.05	-4.83	24.22	40.00	15.78	Peak
2	146.374	32.46	-11.98	20.48	43.50	23.02	Peak
3	301.422	31.25	-10.61	20.64	46.00	25.36	Peak
4	364.260	33.01	-9.68	23.33	46.00	22.67	Peak
5	422.058	33.88	-7.83	26.05	46.00	19.95	Peak
6	866.088	28.20	-1.19	27.01	46.00	18.99	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.955	31.61	-5.08	26.53	40.00	13.47	Peak
2	39.715	39.08	-11.09	27.99	40.00	12.01	Peak
3	62.871	37.06	-17.13	19.93	40.00	20.07	Peak
4	142.324	32.85	-11.92	20.93	43.50	22.57	Peak
5	361.714	35.56	-9.78	25.78	46.00	20.22	Peak
6	457.507	30.78	-6.73	24.05	46.00	21.95	Peak


Test Results for Model: EBE-BBW539-F (Test at 802.11b mode High channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	31.180	29.33	-4.50	24.83	40.00	15.17	Peak
2	142.324	32.15	-11.92	20.23	43.50	23.27	Peak
3	203.523	28.79	-12.32	16.47	43.50	27.03	Peak
4	307.831	32.57	-10.59	21.98	46.00	24.02	Peak
5	364.260	31.90	-9.68	22.22	46.00	23.78	Peak
6	922.516	28.10	-0.66	27.44	46.00	18.56	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.105	30.22	-3.68	26.54	40.00	13.46	Peak
2	38.212	37.63	-9.91	27.72	40.00	12.28	Peak
3	130.379	29.39	-11.31	18.08	43.50	25.42	Peak
4	361.714	35.29	-9.78	25.51	46.00	20.49	Peak
5	426.521	35.02	-7.65	27.37	46.00	18.63	Peak
6	942.131	27.81	-0.34	27.47	46.00	18.53	Peak


Test Results for Model: EBE-BBW418 (Test at 802.11b mode Low channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	27.86	-4.00	23.86	40.00	16.14	Peak
2	142.324	33.85	-11.92	21.93	43.50	21.57	Peak
3	290.017	31.93	-11.04	20.89	46.00	25.11	Peak
4	361.714	38.00	-9.78	28.22	46.00	17.78	Peak
5	494.199	31.71	-6.17	25.54	46.00	20.46	Peak
6	848.056	28.97	-1.53	27.44	46.00	18.56	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	30.12	-4.00	26.12	40.00	13.88	Peak
2	37.416	38.41	-9.31	29.10	40.00	10.90	Peak
3	40.276	39.66	-11.48	28.18	40.00	11.82	Peak
4	132.685	29.30	-11.48	17.82	43.50	25.68	Peak
5	480.528	33.02	-6.25	26.77	46.00	19.23	Peak
6	900.147	28.52	-0.96	27.56	46.00	18.44	Peak


Test Results for Model: EBE-BBW418 (Test at 802.11b mode Middle channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.424	28.64	-3.93	24.71	40.00	15.29	Peak
2	144.335	32.80	-11.96	20.84	43.50	22.66	Peak
3	287.990	32.54	-11.16	21.38	46.00	24.62	Peak
4	314.377	32.03	-10.60	21.43	46.00	24.57	Peak
5	361.714	35.24	-9.78	25.46	46.00	20.54	Peak
6	909.667	27.81	-0.68	27.13	46.00	18.87	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	29.83	-3.60	26.23	40.00	13.77	Peak
2	39.437	38.96	-10.87	28.09	40.00	11.91	Peak
3	57.594	37.80	-17.35	20.45	40.00	19.55	Peak
4	144.842	29.70	-11.94	17.76	43.50	25.74	Peak
5	420.580	33.53	-7.90	25.63	46.00	20.37	Peak
6	711.674	30.94	-3.44	27.50	46.00	18.50	Peak


Test Results for Model: EBE-BBW418 (Test at 802.11b mode High channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	28.17	-3.85	24.32	40.00	15.68	Peak
2	145.861	34.38	-11.97	22.41	43.50	21.09	Peak
3	360.448	35.92	-9.84	26.08	46.00	19.92	Peak
4	480.528	30.65	-6.25	24.40	46.00	21.60	Peak
5	668.142	29.64	-4.12	25.52	46.00	20.48	Peak
6	938.833	27.44	-0.40	27.04	46.00	18.96	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	29.27	-3.85	25.42	40.00	14.58	Peak
2	39.437	39.19	-10.87	28.32	40.00	11.68	Peak
3	57.392	37.68	-17.33	20.35	40.00	19.65	Peak
4	361.714	34.22	-9.78	24.44	46.00	21.56	Peak
5	480.528	31.71	-6.25	25.46	46.00	20.54	Peak
6	925.756	27.92	-0.62	27.30	46.00	18.70	Peak


Test Results for Model: EBE-BBW418-F (Test at 802.11b mode Low channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	28.05	-3.85	24.20	40.00	15.80	Peak
2	73.103	28.95	-16.75	12.20	40.00	27.80	Peak
3	147.404	32.94	-11.99	20.95	43.50	22.55	Peak
4	319.937	32.29	-10.55	21.74	46.00	24.26	Peak
5	362.985	35.12	-9.73	25.39	46.00	20.61	Peak
6	929.008	27.65	-0.58	27.07	46.00	18.93	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	30.12	-4.00	26.12	40.00	13.88	Peak
2	37.416	38.41	-9.31	29.10	40.00	10.90	Peak
3	40.276	39.66	-11.48	28.18	40.00	11.82	Peak
4	132.685	29.30	-11.48	17.82	43.50	25.68	Peak
5	480.528	33.02	-6.25	26.77	46.00	19.23	Peak
6	900.147	28.52	-0.96	27.56	46.00	18.44	Peak


Test Results for Model: EBE-BBW418-F (Test at 802.11b mode Middle channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.424	28.64	-3.93	24.71	40.00	15.29	Peak
2	144.335	32.80	-11.96	20.84	43.50	22.66	Peak
3	287.990	32.54	-11.16	21.38	46.00	24.62	Peak
4	314.377	32.03	-10.60	21.43	46.00	24.57	Peak
5	361.714	35.24	-9.78	25.46	46.00	20.54	Peak
6	909.667	27.81	-0.68	27.13	46.00	18.87	Peak


Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	29.83	-3.60	26.23	40.00	13.77	Peak
2	39.437	38.96	-10.87	28.09	40.00	11.91	Peak
3	57.594	37.80	-17.35	20.45	40.00	19.55	Peak
4	144.842	29.70	-11.94	17.76	43.50	25.74	Peak
5	420.580	33.53	-7.90	25.63	46.00	20.37	Peak
6	711.674	30.94	-3.44	27.50	46.00	18.50	Peak


Test Results for Model: EBE-BBW418-F (Test at 802.11b mode High channel)

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: horizontal
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	28.17	-3.85	24.32	40.00	15.68	Peak
2	145.861	34.38	-11.97	22.41	43.50	21.09	Peak
3	360.448	35.92	-9.84	26.08	46.00	19.92	Peak
4	480.528	30.65	-6.25	24.40	46.00	21.60	Peak
5	668.142	29.64	-4.12	25.52	46.00	20.48	Peak
6	938.833	27.44	-0.40	27.04	46.00	18.96	Peak

Project No.: CR230844594-RF
 Tester: Carl Xue
 Polarization: vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	29.27	-3.85	25.42	40.00	14.58	Peak
2	39.437	39.19	-10.87	28.32	40.00	11.68	Peak
3	57.392	37.68	-17.33	20.35	40.00	19.65	Peak
4	361.714	34.22	-9.78	24.44	46.00	21.56	Peak
5	480.528	31.71	-6.25	25.46	46.00	20.54	Peak
6	925.756	27.92	-0.62	27.30	46.00	18.70	Peak

2) 1-25GHz: (Test Results for Model: EBE-BBW539)
802.11b Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2412 MHz							
2412.000	63.80	PK	H	31.53	95.33	N/A	N/A
2412.000	58.32	AV	H	31.53	89.85	N/A	N/A
2412.000	61.50	PK	V	31.53	93.03	N/A	N/A
2412.000	56.17	AV	V	31.53	87.70	N/A	N/A
2390.000	27.08	PK	H	31.46	58.54	74.00	15.46
2390.000	14.43	AV	H	31.46	45.89	54.00	8.11
4824.000	46.29	PK	H	10.94	57.23	74.00	16.77
4824.000	41.63	AV	H	10.94	52.57	54.00	1.43
7236.000	33.74	PK	H	14.44	48.18	74.00	25.82
7236.000	21.37	AV	H	14.44	35.81	54.00	18.19
Middle Channel: 2437 MHz							
2437.000	65.36	PK	H	31.60	96.96	N/A	N/A
2437.000	60.51	AV	H	31.60	92.11	N/A	N/A
2437.000	63.39	PK	V	31.60	94.99	N/A	N/A
2437.000	58.24	AV	V	31.60	89.84	N/A	N/A
4874.000	43.07	PK	H	11.05	54.12	74.00	19.88
4874.000	38.44	AV	H	11.05	49.49	54.00	4.51
7311.000	34.02	PK	H	14.80	48.82	74.00	25.18
7311.000	22.01	AV	H	14.80	36.81	54.00	17.19
High Channel: 2462MHz							
2462.000	64.64	PK	H	31.63	96.27	N/A	N/A
2462.000	59.81	AV	H	31.63	91.44	N/A	N/A
2462.000	62.11	PK	V	31.63	93.74	N/A	N/A
2462.000	57.05	AV	V	31.63	88.68	N/A	N/A
2483.500	28.16	PK	H	31.64	59.80	74.00	14.20
2483.500	14.21	AV	H	31.64	45.85	54.00	8.15
4924.000	41.90	PK	H	11.18	53.08	74.00	20.92
4924.000	36.58	AV	H	11.18	47.76	54.00	6.24
7386.000	33.46	PK	H	14.89	48.35	74.00	25.65
7386.000	21.23	AV	H	14.89	36.12	54.00	17.88

802.11g Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2412 MHz							
2412.000	67.28	PK	H	31.53	98.81	N/A	N/A
2412.000	57.53	AV	H	31.53	89.06	N/A	N/A
2412.000	65.86	PK	V	31.53	97.39	N/A	N/A
2412.000	55.25	AV	V	31.53	86.78	N/A	N/A
2390.000	28.57	PK	H	31.46	60.03	74.00	13.97
2390.000	15.01	AV	H	31.46	46.47	54.00	7.53
4824.000	46.69	PK	H	10.94	57.63	74.00	16.37
4824.000	34.35	AV	H	10.94	45.29	54.00	8.71
7236.000	33.56	PK	H	14.44	48.00	74.00	26.00
7236.000	21.28	AV	H	14.44	35.72	54.00	18.28
Middle Channel: 2437 MHz							
2437.000	65.52	PK	H	31.60	97.12	N/A	N/A
2437.000	56.17	AV	H	31.60	87.77	N/A	N/A
2437.000	63.46	PK	V	31.60	95.06	N/A	N/A
2437.000	54.38	AV	V	31.60	85.98	N/A	N/A
4874.000	41.53	PK	H	11.05	52.58	74.00	21.42
4874.000	29.27	AV	H	11.05	40.32	54.00	13.68
7311.000	34.12	PK	H	14.80	48.92	74.00	25.08
7311.000	22.06	AV	H	14.80	36.86	54.00	17.14
High Channel: 2462MHz							
2462.000	64.32	PK	H	31.63	95.95	N/A	N/A
2462.000	55.56	AV	H	31.63	87.19	N/A	N/A
2462.000	62.13	PK	V	31.63	93.76	N/A	N/A
2462.000	52.47	AV	V	31.63	84.10	N/A	N/A
2483.500	27.56	PK	H	31.64	59.20	74.00	14.80
2483.500	14.40	AV	H	31.64	46.04	54.00	7.96
4924.000	45.63	PK	H	11.18	56.81	74.00	17.19
4924.000	33.32	AV	H	11.18	44.50	54.00	9.50
7386.000	33.28	PK	H	14.89	48.17	74.00	25.83
7386.000	21.14	AV	H	14.89	36.03	54.00	17.97

802.11n ht20 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2412 MHz							
2412.000	69.48	PK	H	31.53	101.01	N/A	N/A
2412.000	60.14	AV	H	31.53	91.67	N/A	N/A
2412.000	68.01	PK	V	31.53	99.54	N/A	N/A
2412.000	59.36	AV	V	31.53	90.89	N/A	N/A
2390.000	28.48	PK	H	31.46	59.94	74.00	14.06
2390.000	14.82	AV	H	31.46	46.28	54.00	7.72
4824.000	46.93	PK	H	10.94	57.87	74.00	16.13
4824.000	34.47	AV	H	10.94	45.41	54.00	8.59
7236.000	33.44	PK	H	14.44	47.88	74.00	26.12
7236.000	21.22	AV	H	14.44	35.66	54.00	18.34
Middle Channel: 2437 MHz							
2437.000	69.13	PK	H	31.60	100.73	N/A	N/A
2437.000	59.47	AV	H	31.60	91.07	N/A	N/A
2437.000	67.33	PK	V	31.60	98.93	N/A	N/A
2437.000	57.46	AV	V	31.60	89.06	N/A	N/A
4874.000	43.65	PK	H	11.05	54.70	74.00	19.30
4874.000	31.33	AV	H	11.05	42.38	54.00	11.62
7311.000	34.02	PK	H	14.80	48.82	74.00	25.18
7311.000	22.01	AV	H	14.80	36.81	54.00	17.19
High Channel: 2462MHz							
2462.000	68.91	PK	H	31.63	100.54	N/A	N/A
2462.000	59.61	AV	H	31.63	91.24	N/A	N/A
2462.000	67.02	PK	V	31.63	98.65	N/A	N/A
2462.000	57.24	AV	V	31.63	88.87	N/A	N/A
2483.500	28.00	PK	H	31.64	59.64	74.00	14.36
2483.500	14.72	AV	H	31.64	46.36	54.00	7.64
4924.000	41.82	PK	H	11.18	53.00	74.00	21.00
4924.000	29.41	AV	H	11.18	40.59	54.00	13.41
7386.000	33.48	PK	H	14.89	48.37	74.00	25.63
7386.000	21.24	AV	H	14.89	36.13	54.00	17.87

802.11n ht40 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector					
Low Channel: 2422 MHz							
2422.000	64.34	PK	H	31.56	95.90	N/A	N/A
2422.000	54.37	AV	H	31.56	85.93	N/A	N/A
2422.000	63.78	PK	V	31.56	95.34	N/A	N/A
2422.000	53.46	AV	V	31.56	85.02	N/A	N/A
2390.000	29.74	PK	H	31.46	61.20	74.00	12.80
2390.000	15.56	AV	H	31.46	47.02	54.00	6.98
4844.000	39.67	PK	H	10.96	50.63	74.00	23.37
4844.000	27.34	AV	H	10.96	38.30	54.00	15.70
7266.000	33.56	PK	H	14.63	48.19	74.00	25.81
7266.000	21.28	AV	H	14.63	35.91	54.00	18.09
Middle Channel: 2437 MHz							
2437.000	63.46	PK	H	31.60	95.06	N/A	N/A
2437.000	53.23	AV	H	31.60	84.83	N/A	N/A
2437.000	61.68	PK	V	31.60	93.28	N/A	N/A
2437.000	51.34	AV	V	31.60	82.94	N/A	N/A
4874.000	37.65	PK	H	11.05	48.70	74.00	25.30
4874.000	25.33	AV	H	11.05	36.38	54.00	17.62
7311.000	33.14	PK	H	14.80	47.94	74.00	26.06
7311.000	21.07	AV	H	14.80	35.87	54.00	18.13
High Channel: 2452MHz							
2452.000	63.11	PK	H	31.63	94.74	N/A	N/A
2452.000	53.69	AV	H	31.63	85.32	N/A	N/A
2452.000	62.54	PK	V	31.63	94.17	N/A	N/A
2452.000	52.17	AV	V	31.63	83.80	N/A	N/A
2483.500	29.69	PK	H	31.64	61.33	74.00	12.67
2483.500	15.69	AV	H	31.64	47.33	54.00	6.67
4904.000	35.46	PK	H	11.14	46.60	74.00	27.40
4904.000	23.23	AV	H	11.14	34.37	54.00	19.63
7356.000	33.78	PK	H	14.80	48.58	74.00	25.42
7356.000	21.39	AV	H	14.80	36.19	54.00	17.81

Worst Case Test plots (802.11b mode low channel was the worst)


1)1-6GHZ Horizontal:



1-6GHZ Vertical:

Project No.: CR230844594-RF
 Tester: Mack Huang
 Polarization: Vertical
 Note:

Date: 2023-08-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4824.000	39.41	10.94	50.35	54.00	3.65	Average
2	4824.000	44.82	10.94	55.76	74.00	18.24	Peak

2)6-18GHZ Horizontal:

Project No.: CR230844594-RF
 Tester: Mack Huang
 Polarization: horizontal
 Note:

Date: 2023-08-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7236.000	21.38	14.44	35.82	54.00	18.18	Average
2	7236.000	33.75	14.44	48.19	74.00	25.81	Peak
3	17594.320	17.62	29.50	47.12	54.00	6.88	Average
4	17594.320	29.74	29.50	59.24	74.00	14.76	Peak

6-18GHZ Vertical:

Project No.: CR230844594-RF
 Tester: Mack Huang
 Polarization: Vertical
 Note:

Date: 2023-08-12




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7236.000	19.08	14.44	33.52	54.00	20.48	Average
2	7236.000	31.15	14.44	45.59	74.00	28.41	Peak
3	17555.910	18.08	29.19	47.27	54.00	6.73	Average
4	17555.910	30.35	29.19	59.54	74.00	14.46	Peak

3)18-25GHz Horizontal:

Project No.: CR230844594-RF
 Tester: Mack Huang
 Polarization: Horizontal
 Note:


Date: 2023-08-12



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	21745.750	38.33	5.04	43.37	54.00	10.63	Average
2	21745.750	50.69	5.04	55.73	74.00	18.27	Peak

18-25GHz Vertical:

Project No.: CR230844594-RF
 Tester: Mack Huang
 Polarization: Vertical
 Note:



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	24277.460	38.22	5.06	43.28	54.00	10.72	Average
2	24277.460	50.50	5.06	55.56	74.00	18.44	Peak

4.3 Minimum 6 dB Emission Bandwidth

Serial Number:	298Q-1	Test Date:	2023/8/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	---------------------------	----	------------------------	-------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A




* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	12.756	0.5
	2437	12.244	0.5
	2462	12.244	0.5
802.11g	2412	15.321	0.5
	2437	15.449	0.5
	2462	15.321	0.5
802.11n ht20	2412	15.256	0.5
	2437	15.256	0.5
	2462	15.321	0.5
802.11n ht40	2422	35.385	0.5
	2437	35.385	0.5
	2452	35.385	0.5




6dB Emission Bandwidth

<p>802.11g Lowest Channel</p>	<p></p> <p>Date: 18_AUG_2023 11:45:40</p>
<p>802.11g Middle Channel</p>	<p></p> <p>Date: 18_AUG_2023 11:48:18</p>
<p>802.11g Highest Channel</p>	<p></p> <p>Date: 18_AUG_2023 11:50:31</p>


6dB Emission Bandwidth

802.11n ht20
Lowest Channel




Date: 18_AUG_2023 11:31:30

802.11n ht20
Middle Channel



Date: 18_AUG_2023 11:31:38


802.11n ht20
Highest Channel




Date: 18_AUG_2023 11:35:42

6dB Emission Bandwidth


802.11n ht40
Lowest Channel



802.11n ht40
Middle Channel



802.11n ht40
Highest Channel



Date: 18_AUG_2023 12:03:26

4.4 99% Occupied Bandwidth

Serial Number:	298Q-1	Test Date:	2023/8/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	N/A

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Channel	Test Channel	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)
802.11b	Lowest	2412	15.256
	Middle	2437	15.192
	Highest	2462	15.256
802.11g	Lowest	2412	17.436
	Middle	2437	17.244
	Highest	2462	17.308
802.11n ht20	Lowest	2412	18.397
	Middle	2437	18.333
	Highest	2462	18.269
802.11n ht40	Lowest	2422	35.897
	Middle	2437	35.897
	Highest	2452	35.897


99% Occupied Bandwidth

802.11b
Lowest Channel




Date: 18_AUG_2023 12:11:25

802.11b
Middle Channel



Date: 18_AUG_2023 12:11:47


802.11b
Highest Channel



Date: 18_AUG_2023 12:12:05


99% Occupied Bandwidth

802.11g
Lowest Channel




Date: 18_AUG_2023 12:13:26

802.11g
Middle Channel



Date: 18_AUG_2023 12:13:00


802.11g
Highest Channel




Date: 18_AUG_2023 12:12:37

99% Occupied Bandwidth


802.11n ht20
Lowest Channel



802.11n ht20
Middle Channel




802.11n ht20
Highest Channel




99% Occupied Bandwidth

802.11n ht40
Lowest Channel




Date: 18_AUG_2023 12:15:18

802.11n ht40
Middle Channel



Date: 18_AUG_2023 12:15:44

802.11n ht40
Highest Channel



Date: 18_AUG_2023 12:16:09

4.5 Maximum Conducted Output Power

Serial Number:	298Q-1	Test Date:	2023/8/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.5	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Average Power Sensor	U2001H	MY50000380	2023/3/31	2024/3/30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	2412	15.66	30
	2437	15.44	30
	2462	15.05	30
802.11g	2412	15.04	30
	2437	14.79	30
	2462	14.44	30
802.11n ht20	2412	14.9	30
	2437	14.52	30
	2462	14.09	30
802.11n ht40	2422	12.87	30
	2437	12.63	30
	2452	12.05	30

4.6 Maximum Power Spectral Density

Serial Number:	298Q-1	Test Date:	2023/8/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Channel	Test Frequency (MHz)	Reading (dBm/10kHz)	Power Spectral Density (dBm/10kHz)	Limit (dBm/3kHz)
802.11b	2412	-13.24	-13.24	8.00
	2437	-13.45	-13.45	8.00
	2462	-13.71	-13.71	8.00
802.11g	2412	-13.52	-13.52	8.00
	2437	-13.98	-13.98	8.00
	2462	-13.79	-13.79	8.00
802.11n ht20	2412	-13.81	-13.81	8.00
	2437	-14.10	-14.10	8.00
	2462	-14.48	-14.48	8.00
802.11n ht40	2422	-16.46	-16.46	8.00
	2437	-17.64	-17.64	8.00
	2452	-18.02	-18.02	8.00

Note:


Duty cycle $\geq 98\%$, method ANSI C63.10-2013 Section 11.10.3 was used.

Maximum power spectral density


802.11b
Lowest Channel



802.11b
Middle Channel




802.11b
Highest Channel



Date: 18_AUG_2023 11:54:05


Maximum power spectral density

802.11g
Lowest Channel




Date: 18_AUG_2023 11:47:03

802.11g
Middle Channel



Date: 18_AUG_2023 11:49:37


802.11g
Highest Channel




Date: 18_AUG_2023 11:51:31

Maximum power spectral density


802.11n ht20
Lowest Channel



802.11n ht20
Middle Channel




802.11n ht20
Highest Channel




Maximum power spectral density

802.11n ht40
Lowest Channel




Date: 18_AUG_2023 11:40:06

802.11n ht40
Middle Channel



Date: 18_AUG_2023 11:44:05

802.11n ht40
Highest Channel



Date: 18_AUG_2023 12:06:47

4.7 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	298Q-1	Test Date:	2023/8/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edge



Date: 18_AUG_2023 11:27:46


802.11b
Highest Band edge



Date: 18_AUG_2023 11:29:05


100 kHz Bandwidth of Frequency Band Edge

802.11g
Lowest Band edge



Date: 18_AUG_2023 11:26:20


802.11g
Highest Band edge



Date: 18_AUG_2023 11:25:10


100 kHz Bandwidth of Frequency Band Edge

802.11n ht20
Lowest Band edge



Date: 18_AUG_2023 11:23:06


802.11n ht20
Highest Band edge




Date: 18_AUG_2023 11:24:08

100 kHz Bandwidth of Frequency Band Edge

802.11n ht40
Lowest Band edge



802.11n ht40
Highest Band edge



4.8 Duty Cycle:

Serial Number:	298Q-1	Test Date:	2023/8/18
Test Site:	RF	Test Mode:	Transmitting
Tester:	LingLing Li	Test Result:	N/A

Environmental Conditions:					
Temperature: (°C)	25.9	Relative Humidity: (%)	60	ATM Pressure: (kPa)	100.2


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2023-03-31	2024-03-30
zhuoxiang	Coaxial Cable	SMA-178	211003	Each time	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	Duty Factor (dB)	VBW Setting (Hz)
802.11b	100	100	100.00	10	/	10
802.11g	100	100	100.00	10	/	10
802.11n ht20	100	100	100.00	10	/	10
802.11n ht40	100	100	100.00	10	/	10




802.11g



802.11n ht20



802.11n ht40



5. RF EXPOSURE EVALUATION

5.1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

5.1.1 Applicable Standard

FCC §15.247 (i) & §1.1310 & §2.1091

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

5.1.2 Procedure

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

5.1.3 Calculated Result

Operation Bands	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
2.4GHz WLAN	2412-2462	1.94	1.563	16	39.81	20	0.0124	1

Result: The device meets FCC MPE at 20 cm distance.

6. EUT PHOTOGRAPHS

Please refer to the attachment CR230844594-EXP EUT EXTERNAL PHOTOGRAPHS and
CR230844594-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230844594-00A-TSP TEST SETUP PHOTOGRAPHS.

==== END OF REPORT ====