

FCC

RF

TEST REPORT


ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
LED lamp

ISSUED TO
ZHEJIANG EBOY TECHNOLOGY CO., LTD

No.568 Huabao street, Qianyuan Town, Deqing, Huzhou, China



Tested by: Ye Hongji

Ye Hongji

Date Aug. 13, 2020

Approved by: Liao Jianming

Liao Jianming
(Technical Director)

Date Aug. 13, 2020

Report No.: BL-EC2030044-601

EUT Name: LED lamp

Model Name: EBE-QPW112 (refer section 2.4)

Brand Name: EBOY

Test Standard: 47 CFR Part 15 Subpart C

FCC ID: 2AJ3WEBEQPW112

Test Conclusion: Pass

Test Date: Mar. 27, 2020 ~ Mar. 29, 2020

Date of Issue: Aug. 13, 2020

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Aug. 13, 2020</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

- 1 ADMINISTRATIVE DATA (GENERAL INFORMATION)..... 5
 - 1.1 Identification of the Testing Laboratory 5
 - 1.2 Identification of the Responsible Testing Location..... 5
 - 1.3 Laboratory Condition..... 5
 - 1.4 Announce 5
- 2 PRODUCT INFORMATION 6
 - 2.1 Applicant Information 6
 - 2.2 Manufacturer Information 6
 - 2.3 Factory Information 6
 - 2.4 General Description for Equipment under Test (EUT) 6
 - 2.5 Technical Information..... 7
 - 2.6 Additional Instructions 8
- 3 SUMMARY OF TEST RESULTS..... 10
 - 3.1 Test Standards 10
 - 3.2 Verdict..... 10
- 4 GENERAL TEST CONFIGURATIONS 11
 - 4.1 Test Environments..... 11
 - 4.2 Test Equipment List 11
 - 4.3 Measurement Uncertainty 12
 - 4.4 Description of Test Setup 13
 - 4.4.1 For Antenna Port Test..... 13
 - 4.4.2 For AC Power Supply Port Test..... 13
 - 4.4.3 For Radiated Test (Below 30 MHz)..... 14
 - 4.4.4 For Radiated Test (30 MHz-1 GHz) 14
 - 4.4.5 For Radiated Test (Above 1 GHz) 15
 - 4.5 Measurement Results Explanation Example..... 15

4.5.1	For conducted test items:	15
4.5.2	For radiated band edges and spurious emission test:	15
5	TEST ITEMS	16
5.1	Antenna Requirements	16
5.1.1	Relevant Standards	16
5.1.2	Antenna Anti-Replacement Construction	16
5.1.3	Antenna Gain.....	16
5.2	Output Power.....	17
5.2.1	Test Limit.....	17
5.2.2	Test Setup	17
5.2.3	Test Procedure	17
5.2.4	Test Result	18
5.3	6dB Bandwidth	19
5.3.1	Limit	19
5.3.2	Test Setup	19
5.3.3	Test Procedure	19
5.3.4	Test Result	19
5.4	Conducted Spurious Emission	20
5.4.1	Limit	20
5.4.2	Test Setup	20
5.4.3	Test Procedure	20
5.4.4	Test Result	21
5.5	Band Edge (Authorized-band band-edge).....	22
5.5.1	Limit	22
5.5.2	Test Setup	22
5.5.3	Test Procedure	22
5.5.4	Test Result	23
5.6	Conducted Emission	24
5.6.1	Limit	24
5.6.2	Test Setup	24
5.6.3	Test Procedure	24
5.6.4	Test Result	24

5.7	Radiated Spurious Emission	25
5.7.1	Limit	25
5.7.2	Test Setup	25
5.7.3	Test Procedure	25
5.7.4	Test Result	28
5.8	Band Edge (Restricted-band band-edge).....	29
5.8.1	Limit	29
5.8.2	Test Setup	29
5.8.3	Test Procedure	29
5.8.4	Test Result	29
5.9	Power Spectral density (PSD)	30
5.9.1	Limit	30
5.9.2	Test Setup	30
5.9.3	Test Procedure	30
5.9.4	Test Result	30
ANNEX A	TEST RESULT	31
A.1	Output Power.....	31
A.2	Bandwidth.....	33
A.3	Conducted Spurious Emissions.....	38
A.4	Band Edge (Authorized-band band-edge).....	45
A.5	Conducted Emissions	48
A.6	Radiated Emission.....	50
A.7	Band Edge (Restricted-band band-edge).....	61
A.8	Power Spectral Density (PSD).....	64
ANNEX B	TEST SETUP PHOTOS.....	67
ANNEX C	EUT EXTERNAL PHOTOS	67
ANNEX D	EUT INTERNAL PHOTOS	67

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.</p> <p>The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20°C to 25°C
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v6.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	ZHEJIANG EBOY TECHNOLOGY CO., LTD
Address	No.568 Huabao street, Qianyuan Town, Deqing, Huzhou, China

2.2 Manufacturer Information

Manufacturer	ZHEJIANG EBOY TECHNOLOGY CO., LTD
Address	No.568 Huabao street, Qianyuan Town, Deqing, Huzhou, China

2.3 Factory Information

Factory	ZHEJIANG EBOY TECHNOLOGY CO., LTD
Address	No.568 Huabao street, Qianyuan Town, Deqing, Huzhou, China

2.4 General Description for Equipment under Test (EUT)

EUT Type	LED lamp
Model Name Under Test	EBE-QPW112
Series Model Name	EBE-QPW112-F
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, only the number of lamp beads is different.
Hardware Version	1.0.0
Software Version	3.4.2
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	2.4G WIFI 802.11b, 802.11g, 802.11n(HT20)
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1)*5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11.
Modulation Type	DSSS, OFDM
Product Type	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Antenna Type	PCB Antenna
Antenna Gain	2.5 dBi
About the Product	Only the WIFI 802.11b, 802.11g and 802.11n (HT20) was tested in this report.

Modulation technology	Modulation Type	Transfer Rate (Mbps)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n-20MHz)	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
6dB Bandwidth	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20	1/6/6.5/13.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 and 2.6 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.6 Additional Instructions

EUT Software Settings:

Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

EUT Software Settings:

Power level setup in software			
Test Software Version	Wifi Test Toolv1.4.1		
Support Units (Software installation media)	Description	Manufacturer	Model
		Notebook	Lenovo
Mode	Channel	Soft Set	
802.11 b	1	0	
	6	0	
	11	0	
802.11 g	1	0	
	6	0	
	11	0	
802.11 n20	1	0	
	6	0	
	11	0	

Run software:

The screenshot shows the 'Wifi Test Tool V1.4.1' application window. At the top, there is a 'Port Name' dropdown menu set to 'Not Port Connected', with 'Set Port', 'Connect Port', and 'Disconnect Port' buttons. Below this are two tabs: 'Main' (selected) and 'Efuse'. The 'Main' tab contains several configuration panels: 'Control' with fields for MAC Address, Wlan Mode, and Testing Item (set to 'WiFi - Tx'), and 'Start/Stop' buttons; 'Setting' with dropdowns for Channel (1), Bandwidth (20 MHz), Data Rate (OFDM_54M), and Mode (HT-MM); 'TX Setting' with dropdowns for Single Tone, Tx Opt, Temperature Cali, TXPwr, and Xtal C, and a 'SAVE IN FLASH' button; and 'TX Packet Setup' with fields for Pattern, Interval, Count, and Length. At the bottom left is the 'RX Packet Counter' panel with 'Test Mode' (Continuous), 'Interval' (2), and a 'Single Reset' button. The 'View Window' on the bottom right is currently empty.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
3	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203; 15.247(b)	N/A	Pass ^{Note 1}
2	Output Power	15.247(b)	ANNEX A.1	Pass
3	6dB Bandwidth	15.247(a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.209; 15.247(d)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209; 15.247(d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247(d)	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	ANNEX A.8	Pass
10	Receiver Spurious Emissions	N/A	N/A	N/A ^{Note 2}

Note 1: Please refer to section 5.1.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	AC 120 V/60Hz

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Software /Firmware Version	Cal. Date	Cal. Due
Conducted Test System						
Test Software 1	R&S	CMUgo	N/A	V2.0.1	N/A	N/A
Test Software 2	R&S	CMWRun	N/A	V1.8.9	N/A	N/A
Test Software 3	BALUN	BL410R	N/A	V2.1.1.38 7	N/A	N/A
Universal Radio Communication Tester	R&S	CMU 200	119280	V5.13	2020.02.19	2021.02.18
Wideband Radio Communication Tester	R&S	CMW 500	127794	V3.5.137	2019.06.13	2020.06.12
Wideband Radio Communication Tester	R&S	CMW 500	120598	V3.5.137	2020.02.19	2021.02.18
Spectrum Analyzer	R&S	FSV-30	103118	2.30.SP1	2019.06.13	2020.06.12
Spectrum Analyzer	Agilent	E4440A	MY45304434	A.11.21	2019.10.30	2020.10.29
Spectrum Analyzer	Agilent	E4440A	MY46181663	A.11.21	2019.10.30	2020.10.29
Temperature Chamber	AHK	SP20	1412	N/A	2019.06.24	2020.06.23
DC Power Supply	ITECH	IT6863A	6000140106 87210020	N/A	2019.06.18	2020.06.17
Power Sensor	Agilent	E9304A H18	MY41497164	N/A	2019.10.30	2020.10.29
Power Splitter	KMW	DCPD- LDC	1305003215	N/A	N/A	N/A
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	N/A	N/A	N/A
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	N/A	N/A	N/A
Radiated Test System						
Test Software	BALUN	BL410_E	N/A	V16.921	N/A	N/A

Description	Manufacturer	Model	Serial No.	Software /Firmware Version	Cal. Date	Cal. Due
Test Antenna-Bi-Log(30 MHz-3 GHz)	Schwarzbeck	VULB 9163	9163-624	N/A	2018.08.22	2020.08.21
Test Antenna-Horn(1-18 GHz)	Schwarzbeck	BBHA 9120D	9120D-1600	N/A	2018.07.11	2020.07.10
Test Antenna-Horn(18-40 GHz)	A-INFO	LB-180400KF	J211060273	N/A	2019.01.05	2021.01.04
Anechoic Chamber	YIHENG	9m*6m*6m	#3	N/A	2018.07.18	2021.07.17
Shielded Enclosure	ChangNing	CN-130701	130703	N/A	N/A	N/A
EMI Receiver	KEYSIGHT	N9038A	MY53220118	A.14.16	2019.10.29	2020.10.28
Spectrum Analyzer	R&S	FSV-30	103118	2.30.SP1	2019.06.13	2020.06.12
Wideband Radio Communication Tester	R&S	CMW 500	127794	V3.2.73	2019.06.13	2020.06.12

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP = Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b);

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b);

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle to the measurement result.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 6dB Bandwidth

5.3.1 Limit

FCC §15.247(a);

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207;

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(c);

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW ≥ 3 x RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz

> 1000 MHz	1 MHz
------------	-------

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(c);

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(d);

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	Duty Cycle	Duty Factor (dB)	T (ms)	1/T(kHz)
802.11b	1	0	N/A	N/A
802.11g	1	0	N/A	N/A
802.11n-20 MHz	1	0	N/A	N/A

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	16.56	45.29	30	1000	Pass
6	16.74	47.21			Pass
11	16.12	40.93			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	18.72	74.47	30	1000	Pass
6	18.69	73.96			Pass
11	18.24	66.68			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
1	17.52	56.49	30	1000	Pass
6	17.47	55.85			Pass
11	16.73	47.10			Pass

Average Power Test Data
802.11b Mode:

Channel	Measured Output Average Power	Duty Factor	Total Output Average Power		Limit		Verdict
	dBm		dB	dBm	mW	dBm	
1	12.87	0	12.87	19.36	30	1000	Pass
6	12.99	0	12.99	19.91			Pass
11	12.34	0	12.34	17.14			Pass

802.11g Mode:

Channel	Measured Output Average Power	Duty Factor	Total Output Average Power		Limit		Verdict
	dBm		dB	dBm	mW	dBm	
1	12.87	0	12.87	19.36	30	1000	Pass
6	12.81	0	12.81	19.10			Pass
11	12.30	0	12.30	16.98			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power	Duty Factor	Total Output Average Power		Limit		Verdict
	dBm		dB	dBm	mW	dBm	
1	11.71	0	11.71	14.83	30	1000	Pass
6	11.62	0	11.62	14.52			Pass
11	10.87	0	10.87	12.22			Pass

A.2 Bandwidth

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	9.16	14.5712	≥ 500
Middle	9.16	14.5684	≥ 500
High	9.16	14.5235	≥ 500

802.11g Mode:


Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	10.16	16.0434	≥ 500
Middle	11.41	16.0597	≥ 500
High	11.41	16.0819	≥ 500

802.11n-20MHz Mode:


Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	10.21	16.8124	≥ 500
Middle	11.41	16.8305	≥ 500
High	11.41	16.9013	≥ 500

Test plots (6dB Bandwidth)


802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL



802.11 n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




Test plots (99% Bandwidth)


802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL



802.11 n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-49.91	3.99	-16.01	Pass
6	-49.93	3.54	-16.46	Pass
11	-49.25	3.55	-16.45	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-49.23	2.66	-17.34	Pass
6	-49.75	2.27	-17.73	Pass
11	-49.81	2.54	-17.46	Pass

802.11n-20MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-49.90	3.10	-16.90	Pass
6	-49.43	2.68	-17.32	Pass
11	-48.57	0.60	-19.40	Pass

Test Plots


802.11b CHANNEL 1 CARRIER LEVEL




802.11b CHANNEL 1, SPURIOUS 30 MHz ~ 3 GHz




802.11b CHANNEL 1, SPURIOUS 2 GHz ~ 25 GHz




802.11b CHANNEL 6 CARRIER LEVEL




802.11b CHANNEL 6, SPURIOUS
30 MHz ~ 3 GHz




802.11b CHANNEL 6, SPURIOUS
2 GHz ~ 25 GHz




802.11b CHANNEL 11 CARRIER LEVEL




802.11b CHANNEL 11, SPURIOUS
30 MHz ~ 3 GHz




802.11b CHANNEL 11, SPURIOUS
2 GHz ~ 25 GHz




802.11g CHANNEL 1 CARRIER LEVEL




802.11g CHANNEL 1, SPURIOUS 30 MHz ~ 3 GHz





802.11g CHANNEL 1, SPURIOUS 2 GHz ~ 25 GHz






802.11g CHANNEL 6 CARRIER LEVEL



802.11g CHANNEL 6, SPURIOUS
 30 MHz ~ 3 GHz

 802.11g CHANNEL 6, SPURIOUS
 2 GHz ~ 25 GHz



802.11g CHANNEL 11 CARRIER LEVEL


 802.11g CHANNEL 11, SPURIOUS
 30 MHz ~ 3 GHz

 802.11g CHANNEL 11, SPURIOUS
 2 GHz ~ 25 GHz



802.11n-20 CHANNEL 1 CARRIER LEVEL



802.11n-20 CHANNEL 1, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 CHANNEL 1, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 CHANNEL 6 CARRIER LEVEL




802.11n-20 CHANNEL 6, SPURIOUS
30 MHz ~ 3 GHz




802.11n-20 CHANNEL 6, SPURIOUS
2 GHz ~ 25 GHz




802.11n-20 CHANNEL 11 CARRIER LEVEL



802.11n-20 CHANNEL 11, SPURIOUS
30 MHz ~ 3 GHz



802.11n-20 CHANNEL 11, SPURIOUS
2 GHz ~ 25 GHz



A.4 Band Edge (Authorized-band band-edge)

Test Data

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-35.75	3.99	-16.01	Pass
11	-52.40	3.55	-16.45	Pass

802.11g Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-40.61	2.66	-17.34	Pass
11	-48.73	2.54	-17.46	Pass

802.11n-20 MHz Mode:


Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
1	-41.74	3.10	-16.90	Pass
11	-49.47	0.60	-19.40	Pass

Test Plots


802.11b CHANNEL 1, Carrier level




802.11b CHANNEL 1, Reference level




802.11b CHANNEL 11, Carrier level




802.11b CHANNEL 11, Reference level




802.11g CHANNEL 1, Carrier level




802.11g LOW CHANNEL 1, Reference level




802.11g CHANNEL 11, Carrier level




802.11g LOW CHANNEL 11, Reference level




802.11n-20 MHz CHANNEL 1, Carrier level




802.11n-20 MHz CHANNEL 1, Reference level



802.11n-20 MHz CHANNEL 11, Carrier level




802.11n-20 MHz CHANNEL 11, Reference level



A.5 Conducted Emissions


Note ¹: The EUT is working in the Normal link mode.

Test Data and Plots



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	54.76	11.16	66.00	-11.24	Peak	L	Pass
1**	0.150	42.67	11.16	56.00	-13.33	AV	L	Pass
2	0.192	54.42	11.20	63.95	-9.53	Peak	L	Pass
2**	0.192	42.87	11.20	53.95	-11.08	AV	L	Pass
3	0.272	49.34	11.34	61.06	-11.72	Peak	L	Pass
3**	0.272	35.48	11.34	51.06	-15.58	AV	L	Pass
4	0.428	41.45	11.40	57.29	-15.84	Peak	L	Pass
4**	0.428	29.44	11.40	47.29	-17.85	AV	L	Pass
5	0.818	38.85	11.04	56.00	-17.15	Peak	L	Pass
5**	0.818	23.73	11.04	46.00	-22.27	AV	L	Pass
6	0.930	43.24	11.21	56.00	-12.76	Peak	L	Pass
6**	0.930	37.19	11.21	46.00	-8.81	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	45.68	11.16	66.00	-20.32	Peak	N	Pass
1**	0.150	29.10	11.16	56.00	-26.90	AV	N	Pass
2	0.190	57.85	11.19	64.04	-6.19	Peak	N	Pass
2**	0.190	39.61	11.19	54.04	-14.43	AV	N	Pass
3	0.226	55.71	11.30	62.60	-6.89	Peak	N	Pass
3**	0.226	30.47	11.30	52.60	-22.13	AV	N	Pass
4	0.382	46.96	11.46	58.24	-11.28	Peak	N	Pass
4**	0.382	33.54	11.46	48.24	-14.70	AV	N	Pass
5	0.954	44.69	11.21	56.00	-11.31	Peak	N	Pass
5**	0.954	35.67	11.21	46.00	-10.33	AV	N	Pass
6	0.988	44.28	11.21	56.00	-11.72	Peak	N	Pass
6**	0.988	34.81	11.21	46.00	-11.19	AV	N	Pass

A.6 Radiated Emission

Note¹: The symbol of "--" in the table which means not application.


Note²: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note⁴: The EUT is working in the Normal link mode below 1 GHz.


Test Data and Plots

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	57.160	37.33	-25.06	40.0	-2.67	Peak	42.00	100	Vertical	Pass
2	151.460	43.21	-28.74	43.5	-0.29	Peak	75.00	100	Vertical	N/A
2*	151.460	36.39	-28.74	43.5	-7.11	QP	75.00	100	Vertical	Pass
3	240.005	39.52	-24.75	46.0	-6.48	Peak	323.00	100	Vertical	Pass
4	312.426	44.43	-23.42	46.0	-1.57	Peak	12.00	132	Vertical	N/A
4*	312.426	37.96	-23.42	46.0	-8.04	QP	12.00	132	Vertical	Pass
5	344.892	43.53	-21.84	46.0	-2.47	Peak	194.00	127	Vertical	N/A
5*	344.892	38.36	-21.84	46.0	-7.64	QP	194.00	127	Vertical	Pass
6	461.650	40.17	-20.07	46.0	-5.83	Peak	328.00	100	Vertical	Pass

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.735	22.73	-24.54	40.0	-17.27	Peak	45.00	100	Horizontal	Pass
2	150.523	35.14	-29.01	43.5	-8.36	Peak	258.00	100	Horizontal	Pass
3	238.065	35.24	-24.73	46.0	-10.76	Peak	285.00	100	Horizontal	Pass
4	348.645	40.03	-21.88	46.0	-5.97	Peak	283.00	100	Horizontal	Pass
5	441.522	37.83	-20.49	46.0	-8.17	Peak	84.00	100	Horizontal	Pass
6	555.013	30.72	-18.00	46.0	-15.28	Peak	300.00	100	Horizontal	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18G-25G is noise only, do not show on the report.

1 GHz to 18 GHz, ANT V 802.11b Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1199.000	50.36	-16.67	74.0	-23.64	Peak	99.00	100	Vertical	Pass
1**	1199.000	29.65	-16.67	54.0	-24.35	AV	99.00	100	Vertical	Pass
2	1567.000	50.88	-16.20	74.0	-23.12	Peak	356.00	100	Vertical	Pass
2**	1567.000	32.09	-16.20	54.0	-21.91	AV	356.00	100	Vertical	Pass
3	2413.000	92.95	-11.74	74.0	18.95	Peak	199.00	100	Vertical	N/A
3**	2413.000	89.61	-11.74	54.0	35.61	AV	199.00	100	Vertical	N/A
4	3992.000	47.02	-5.02	74.0	-26.98	Peak	269.00	100	Vertical	Pass
4**	3992.000	35.62	-5.02	54.0	-18.38	AV	269.00	100	Vertical	Pass
5	4824.000	48.95	-2.62	74.0	-25.05	Peak	269.00	100	Vertical	Pass
5**	4824.000	37.22	-2.62	54.0	-16.78	AV	269.00	100	Vertical	Pass
6	14567.999	56.07	11.77	74.0	-17.93	Peak	165.00	100	Vertical	Pass
6**	14567.999	47.09	11.77	54.0	-6.91	AV	165.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1198.500	44.11	-16.85	74.0	-29.89	Peak	99.00	100	Horizontal	Pass
1**	1198.500	28.40	-16.85	54.0	-25.60	AV	99.00	100	Horizontal	Pass
2	1439.500	44.93	-16.26	74.0	-29.07	Peak	166.00	100	Horizontal	Pass
2**	1439.500	29.98	-16.26	54.0	-24.02	AV	166.00	100	Horizontal	Pass
3	2415.000	99.77	-11.56	74.0	25.77	Peak	343.00	100	Horizontal	N/A
3**	2415.000	97.20	-11.56	54.0	43.20	AV	343.00	100	Horizontal	N/A
4	3500.000	45.53	-6.45	74.0	-28.47	Peak	45.00	100	Horizontal	Pass
4**	3500.000	34.76	-6.45	54.0	-19.24	AV	45.00	100	Horizontal	Pass
5	3996.000	47.40	-5.09	74.0	-26.60	Peak	190.00	100	Horizontal	Pass
5**	3996.000	35.41	-5.09	54.0	-18.59	AV	190.00	100	Horizontal	Pass
6	11391.750	51.53	6.83	74.0	-22.47	Peak	147.00	100	Horizontal	Pass
6**	11391.750	42.83	6.83	54.0	-11.17	AV	147.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1197.000	45.98	-17.06	74.0	-28.02	Peak	99.00	100	Vertical	Pass
1**	1197.000	26.19	-17.06	54.0	-27.81	AV	99.00	100	Vertical	Pass
2	1572.500	50.38	-16.57	74.0	-23.62	Peak	70.00	100	Vertical	Pass
2**	1572.500	31.87	-16.57	54.0	-22.13	AV	70.00	100	Vertical	Pass
3	2438.000	93.12	-12.47	74.0	19.12	Peak	196.00	100	Vertical	N/A
3**	2438.000	89.85	-12.47	54.0	35.85	AV	196.00	100	Vertical	N/A
4	3990.000	47.04	-4.85	74.0	-26.96	Peak	96.00	100	Vertical	Pass
4**	3990.000	35.46	-4.85	54.0	-18.54	AV	96.00	100	Vertical	Pass
5	4874.000	49.68	-2.47	74.0	-24.32	Peak	252.00	100	Vertical	Pass
5**	4874.000	37.40	-2.47	54.0	-16.60	AV	252.00	100	Vertical	Pass
6	9871.000	50.93	6.21	74.0	-23.07	Peak	230.00	100	Vertical	Pass
6**	9871.000	40.22	6.21	54.0	-13.78	AV	230.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1198.000	45.61	-17.01	74.0	-28.39	Peak	35.00	100	Horizontal	Pass
1**	1198.000	24.61	-17.01	54.0	-29.39	AV	35.00	100	Horizontal	Pass
2	1567.000	45.84	-16.20	74.0	-28.16	Peak	295.00	100	Horizontal	Pass
2**	1567.000	27.59	-16.20	54.0	-26.41	AV	295.00	100	Horizontal	Pass
3	2438.000	98.69	-12.47	74.0	24.69	Peak	360.00	100	Horizontal	N/A
3**	2438.000	95.47	-12.47	54.0	41.47	AV	360.00	100	Horizontal	N/A
4	3999.000	48.57	-4.93	74.0	-25.43	Peak	184.00	100	Horizontal	Pass
4**	3999.000	34.89	-4.93	54.0	-19.11	AV	184.00	100	Horizontal	Pass
5	6557.000	53.63	1.82	74.0	-20.37	Peak	96.00	100	Horizontal	Pass
5**	6557.000	41.40	1.82	54.0	-12.60	AV	96.00	100	Horizontal	Pass
6	13941.000	56.18	10.62	74.0	-17.82	Peak	334.00	100	Horizontal	Pass
6**	13941.000	44.46	10.62	54.0	-9.54	AV	334.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1197.000	48.08	-17.06	74.0	-25.92	Peak	77.00	100	Vertical	Pass
1**	1197.000	29.71	-17.06	54.0	-24.29	AV	77.00	100	Vertical	Pass
2	1566.500	50.46	-16.22	74.0	-23.54	Peak	7.00	100	Vertical	Pass
2**	1566.500	26.64	-16.22	54.0	-27.36	AV	7.00	100	Vertical	Pass
3	2461.000	93.92	-11.46	74.0	19.92	Peak	202.00	100	Vertical	N/A
3**	2461.000	91.70	-11.46	54.0	37.70	AV	202.00	100	Vertical	N/A
4	3990.000	47.01	-4.85	74.0	-26.99	Peak	98.00	100	Vertical	Pass
4**	3990.000	34.81	-4.85	54.0	-19.19	AV	98.00	100	Vertical	Pass
5	4924.000	49.96	-2.47	74.0	-24.04	Peak	147.00	100	Vertical	Pass
5**	4924.000	38.24	-2.47	54.0	-15.76	AV	147.00	100	Vertical	Pass
6	10685.000	51.39	6.66	74.0	-22.61	Peak	247.00	100	Vertical	Pass
6**	10685.000	42.17	6.66	54.0	-11.83	AV	247.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1196.500	45.29	-16.98	74.0	-28.71	Peak	82.00	100	Horizontal	Pass
1**	1196.500	25.89	-16.98	54.0	-28.11	AV	82.00	100	Horizontal	Pass
2	1750.500	46.19	-16.03	74.0	-27.81	Peak	268.00	100	Horizontal	Pass
2**	1750.500	26.23	-16.03	54.0	-27.77	AV	268.00	100	Horizontal	Pass
3	2461.000	99.19	-11.46	74.0	25.19	Peak	354.00	100	Horizontal	N/A
3**	2461.000	96.73	-11.46	54.0	42.73	AV	354.00	100	Horizontal	N/A
4	3997.000	48.44	-5.11	74.0	-25.56	Peak	187.00	100	Horizontal	Pass
4**	3997.000	35.60	-5.11	54.0	-18.40	AV	187.00	100	Horizontal	Pass
5	10118.500	50.79	6.33	74.0	-23.21	Peak	56.00	100	Horizontal	Pass
5**	10118.500	40.94	6.33	54.0	-13.06	AV	56.00	100	Horizontal	Pass
6	14570.750	55.61	11.86	74.0	-18.39	Peak	95.00	100	Horizontal	Pass
6**	14570.750	46.34	11.86	54.0	-7.66	AV	95.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1200.000	45.73	-16.33	74.0	-28.27	Peak	79.00	100	Vertical	Pass
1**	1200.000	26.22	-16.33	54.0	-27.78	AV	79.00	100	Vertical	Pass
2	1703.000	51.64	-16.39	74.0	-22.36	Peak	360.00	100	Vertical	Pass
2**	1703.000	28.99	-16.39	54.0	-25.01	AV	360.00	100	Vertical	Pass
3	2414.000	97.37	-11.53	74.0	23.37	Peak	191.00	100	Vertical	N/A
3**	2414.000	90.92	-11.53	54.0	36.92	AV	191.00	100	Vertical	N/A
4	3999.000	47.03	-4.93	74.0	-26.97	Peak	73.00	100	Vertical	Pass
4**	3999.000	34.94	-4.93	54.0	-19.06	AV	73.00	100	Vertical	Pass
5	4831.000	50.58	-2.65	74.0	-23.42	Peak	143.00	100	Vertical	Pass
5**	4831.000	38.19	-2.65	54.0	-15.81	AV	143.00	100	Vertical	Pass
6	8578.500	48.35	2.59	74.0	-25.65	Peak	0.00	100	Vertical	Pass
6**	8578.500	37.30	2.59	54.0	-16.70	AV	0.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1194.500	46.23	-16.82	74.0	-27.77	Peak	37.00	100	Horizontal	Pass
1**	1194.500	23.95	-16.82	54.0	-30.05	AV	37.00	100	Horizontal	Pass
2	1439.500	43.87	-16.26	74.0	-30.13	Peak	163.00	100	Horizontal	Pass
2**	1439.500	35.29	-16.26	54.0	-18.71	AV	163.00	100	Horizontal	Pass
3	2411.000	104.68	-11.83	74.0	30.68	Peak	0.00	100	Horizontal	N/A
3**	2411.000	96.18	-11.83	54.0	42.18	AV	0.00	100	Horizontal	N/A
4	3999.000	48.89	-4.93	74.0	-25.11	Peak	181.00	100	Horizontal	Pass
4**	3999.000	34.55	-4.93	54.0	-19.45	AV	181.00	100	Horizontal	Pass
5	6895.000	53.51	2.59	74.0	-20.49	Peak	357.00	100	Horizontal	Pass
5**	6895.000	41.90	2.59	54.0	-12.10	AV	357.00	100	Horizontal	Pass
6	14620.250	55.25	12.08	74.0	-18.75	Peak	227.00	100	Horizontal	Pass
6**	14620.250	46.53	12.08	54.0	-7.47	AV	227.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1199.500	44.59	-16.43	74.0	-29.41	Peak	89.00	100	Vertical	Pass
1**	1199.500	25.81	-16.43	54.0	-28.19	AV	89.00	100	Vertical	Pass
2	1641.500	49.85	-16.13	74.0	-24.15	Peak	-1.00	100	Vertical	Pass
2**	1641.500	31.90	-16.13	54.0	-22.10	AV	-1.00	100	Vertical	Pass
3	2436.000	98.20	-12.67	74.0	24.20	Peak	194.00	100	Vertical	N/A
3**	2436.000	91.41	-12.67	54.0	37.41	AV	194.00	100	Vertical	N/A
4	3984.000	47.13	-5.07	74.0	-26.87	Peak	96.00	100	Vertical	Pass
4**	3984.000	35.38	-5.07	54.0	-18.62	AV	96.00	100	Vertical	Pass
5	4875.000	51.14	-2.34	74.0	-22.86	Peak	271.00	100	Vertical	Pass
5**	4875.000	42.08	-2.34	54.0	-11.92	AV	271.00	100	Vertical	Pass
6	14579.000	55.98	12.16	74.0	-18.02	Peak	0.00	100	Vertical	Pass
6**	14579.000	46.76	12.16	54.0	-7.24	AV	0.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1198.500	48.43	-16.85	74.0	-25.57	Peak	90.00	100	Horizontal	Pass
1**	1198.500	25.84	-16.85	54.0	-28.16	AV	90.00	100	Horizontal	Pass
2	1758.500	45.47	-16.35	74.0	-28.53	Peak	284.00	100	Horizontal	Pass
2**	1758.500	25.78	-16.35	54.0	-28.22	AV	284.00	100	Horizontal	Pass
3	2436.000	103.89	-12.67	74.0	29.89	Peak	350.00	100	Horizontal	N/A
3**	2436.000	96.25	-12.67	54.0	42.25	AV	350.00	100	Horizontal	N/A
4	4000.000	48.74	-4.90	74.0	-25.26	Peak	191.00	100	Horizontal	Pass
4**	4000.000	36.43	-4.90	54.0	-17.57	AV	191.00	100	Horizontal	Pass
5	4876.000	49.99	-2.38	74.0	-24.01	Peak	285.00	100	Horizontal	Pass
5**	4876.000	39.65	-2.38	54.0	-14.35	AV	285.00	100	Horizontal	Pass
6	14177.500	55.58	10.77	74.0	-18.42	Peak	313.00	100	Horizontal	Pass
6**	14177.500	45.54	10.77	54.0	-8.46	AV	313.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1174.500	43.15	-16.90	74.0	-30.85	Peak	64.00	100	Vertical	Pass
1**	1174.500	26.76	-16.90	54.0	-27.24	AV	64.00	100	Vertical	Pass
2	1577.500	49.68	-16.44	74.0	-24.32	Peak	73.00	100	Vertical	Pass
2**	1577.500	29.73	-16.44	54.0	-24.27	AV	73.00	100	Vertical	Pass
3	2462.500	97.85	-11.45	74.0	23.85	Peak	205.00	100	Vertical	N/A
3**	2462.500	89.63	-11.45	54.0	35.63	AV	205.00	100	Vertical	N/A
4	3992.000	47.17	-5.02	74.0	-26.83	Peak	264.00	100	Vertical	Pass
4**	3992.000	34.83	-5.02	54.0	-19.17	AV	264.00	100	Vertical	Pass
5	4924.000	49.50	-2.47	74.0	-24.50	Peak	149.00	100	Vertical	Pass
5**	4924.000	40.89	-2.47	54.0	-13.11	AV	149.00	100	Vertical	Pass
6	14587.250	55.53	12.38	74.0	-18.47	Peak	0.00	100	Vertical	Pass
6**	14587.250	46.99	12.38	54.0	-7.01	AV	0.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1196.000	44.50	-16.97	74.0	-29.50	Peak	36.00	100	Horizontal	Pass
1**	1196.000	30.16	-16.97	54.0	-23.84	AV	36.00	100	Horizontal	Pass
2	1736.500	46.75	-15.83	74.0	-27.25	Peak	291.00	100	Horizontal	Pass
2**	1736.500	28.24	-15.83	54.0	-25.76	AV	291.00	100	Horizontal	Pass
3	2461.000	102.46	-11.46	74.0	28.46	Peak	27.00	100	Horizontal	N/A
3**	2461.000	96.06	-11.46	54.0	42.06	AV	27.00	100	Horizontal	N/A
4	3200.000	46.57	-6.82	74.0	-27.43	Peak	44.00	100	Horizontal	Pass
4**	3200.000	31.92	-6.82	54.0	-22.08	AV	44.00	100	Horizontal	Pass
5	4000.000	49.61	-4.90	74.0	-24.39	Peak	185.00	100	Horizontal	Pass
5**	4000.000	37.55	-4.90	54.0	-16.45	AV	185.00	100	Horizontal	Pass
6	14581.750	56.21	12.24	74.0	-17.79	Peak	140.00	100	Horizontal	Pass
6**	14581.750	47.01	12.24	54.0	-6.99	AV	140.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1189.500	45.52	-17.02	74.0	-28.48	Peak	73.00	100	Vertical	Pass
1**	1189.500	34.60	-17.02	54.0	-19.40	AV	73.00	100	Vertical	Pass
2	1629.000	49.31	-16.47	74.0	-24.69	Peak	14.00	100	Vertical	Pass
2**	1629.000	27.99	-16.47	54.0	-26.01	AV	14.00	100	Vertical	Pass
3	2415.000	97.29	-11.56	74.0	23.29	Peak	200.00	100	Vertical	N/A
3**	2415.000	90.50	-11.56	54.0	36.50	AV	200.00	100	Vertical	N/A
4	3987.000	47.04	-5.14	74.0	-26.96	Peak	266.00	100	Vertical	Pass
4**	3987.000	34.12	-5.14	54.0	-19.88	AV	266.00	100	Vertical	Pass
5	4823.000	50.70	-2.57	74.0	-23.30	Peak	145.00	100	Vertical	Pass
5**	4823.000	40.20	-2.57	54.0	-13.80	AV	145.00	100	Vertical	Pass
6	13825.500	54.61	9.89	74.0	-19.39	Peak	353.00	100	Vertical	Pass
6**	13825.500	44.60	9.89	54.0	-9.40	AV	353.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1199.000	44.31	-16.67	74.0	-29.69	Peak	186.00	100	Horizontal	Pass
1**	1199.000	25.31	-16.67	54.0	-28.69	AV	186.00	100	Horizontal	Pass
2	1726.500	45.78	-16.00	74.0	-28.22	Peak	282.00	100	Horizontal	Pass
2**	1726.500	25.68	-16.00	54.0	-28.32	AV	282.00	100	Horizontal	Pass
3	2413.000	104.40	-11.74	74.0	30.40	Peak	0.00	100	Horizontal	N/A
3**	2413.000	97.47	-11.74	54.0	43.47	AV	0.00	100	Horizontal	N/A
4	3998.000	47.40	-5.07	74.0	-26.60	Peak	223.00	100	Horizontal	Pass
4**	3998.000	35.66	-5.07	54.0	-18.34	AV	223.00	100	Horizontal	Pass
5	6586.000	53.44	1.67	74.0	-20.56	Peak	206.00	100	Horizontal	Pass
5**	6586.000	41.30	1.67	54.0	-12.70	AV	206.00	100	Horizontal	Pass
6	9978.250	50.75	6.28	74.0	-23.25	Peak	284.00	100	Horizontal	Pass
6**	9978.250	40.09	6.28	54.0	-13.91	AV	284.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1193.500	49.12	-16.98	74.0	-24.88	Peak	93.00	100	Vertical	Pass
1**	1193.500	27.44	-16.98	54.0	-26.56	AV	93.00	100	Vertical	Pass
2	1567.000	50.36	-16.20	74.0	-23.64	Peak	360.00	100	Vertical	Pass
2**	1567.000	32.73	-16.20	54.0	-21.27	AV	360.00	100	Vertical	Pass
3	2438.000	99.13	-12.47	74.0	25.13	Peak	194.00	100	Vertical	N/A
3**	2438.000	91.31	-12.47	54.0	37.31	AV	194.00	100	Vertical	N/A
4	3992.000	47.16	-5.02	74.0	-26.84	Peak	94.00	100	Vertical	Pass
4**	3992.000	35.23	-5.02	54.0	-18.77	AV	94.00	100	Vertical	Pass
5	4873.000	51.99	-2.55	74.0	-22.01	Peak	148.00	100	Vertical	Pass
5**	4873.000	43.08	-2.55	54.0	-10.92	AV	148.00	100	Vertical	Pass
6	14815.500	56.05	13.46	74.0	-17.95	Peak	284.00	100	Vertical	Pass
6**	14815.500	46.12	13.46	54.0	-7.88	AV	284.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1200.500	46.95	-16.39	74.0	-27.05	Peak	44.00	100	Horizontal	Pass
1**	1200.500	26.63	-16.39	54.0	-27.37	AV	44.00	100	Horizontal	Pass
2	1764.000	45.02	-15.42	74.0	-28.98	Peak	263.00	100	Horizontal	Pass
2**	1764.000	26.73	-15.42	54.0	-27.27	AV	263.00	100	Horizontal	Pass
3	2438.500	103.27	-12.51	74.0	29.27	Peak	356.00	100	Horizontal	N/A
3**	2438.500	96.59	-12.51	54.0	42.59	AV	356.00	100	Horizontal	N/A
4	3994.000	48.18	-5.06	74.0	-25.82	Peak	191.00	100	Horizontal	Pass
4**	3994.000	35.95	-5.06	54.0	-18.05	AV	191.00	100	Horizontal	Pass
5	4874.000	49.18	-2.47	74.0	-24.82	Peak	128.00	100	Horizontal	Pass
5**	4874.000	40.46	-2.47	54.0	-13.54	AV	128.00	100	Horizontal	Pass
6	14592.750	56.76	12.45	74.0	-17.24	Peak	343.00	100	Horizontal	Pass
6**	14592.750	47.42	12.45	54.0	-6.58	AV	343.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1195.500	47.56	-16.84	74.0	-26.44	Peak	89.00	100	Vertical	Pass
1**	1195.500	39.68	-16.84	54.0	-14.32	AV	89.00	100	Vertical	Pass
2	1561.500	51.26	-16.27	74.0	-22.74	Peak	54.00	100	Vertical	Pass
2**	1561.500	27.24	-16.27	54.0	-26.76	AV	54.00	100	Vertical	Pass
3	2460.000	97.97	-11.53	74.0	23.97	Peak	201.00	100	Vertical	N/A
3**	2460.000	91.25	-11.53	54.0	37.25	AV	201.00	100	Vertical	N/A
4	3991.000	47.76	-4.89	74.0	-26.24	Peak	97.00	100	Vertical	Pass
4**	3991.000	35.12	-4.89	54.0	-18.88	AV	97.00	100	Vertical	Pass
5	4929.000	50.34	-2.19	74.0	-23.66	Peak	244.00	100	Vertical	Pass
5**	4929.000	41.06	-2.19	54.0	-12.94	AV	244.00	100	Vertical	Pass
6	14587.250	55.83	12.38	74.0	-18.17	Peak	174.00	100	Vertical	Pass
6**	14587.250	46.78	12.38	54.0	-7.22	AV	174.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1197.500	45.22	-17.14	74.0	-28.78	Peak	39.00	100	Horizontal	Pass
1**	1197.500	25.19	-17.14	54.0	-28.81	AV	39.00	100	Horizontal	Pass
2	1764.000	46.42	-15.42	74.0	-27.58	Peak	0.00	100	Horizontal	Pass
2**	1764.000	28.77	-15.42	54.0	-25.23	AV	0.00	100	Horizontal	Pass
3	2463.000	102.81	-11.46	74.0	28.81	Peak	25.00	100	Horizontal	N/A
3**	2463.000	95.71	-11.46	54.0	41.71	AV	25.00	100	Horizontal	N/A
4	3999.000	48.18	-4.93	74.0	-25.82	Peak	180.00	100	Horizontal	Pass
4**	3999.000	36.28	-4.93	54.0	-17.72	AV	180.00	100	Horizontal	Pass
5	6763.000	53.11	2.55	74.0	-20.89	Peak	361.00	100	Horizontal	Pass
5**	6763.000	41.49	2.55	54.0	-12.51	AV	361.00	100	Horizontal	Pass
6	10115.750	50.10	6.33	74.0	-23.90	Peak	95.00	100	Horizontal	Pass
6**	10115.750	41.50	6.33	54.0	-12.50	AV	95.00	100	Horizontal	Pass

A.7 Band Edge (Restricted-band band-edge)

Test Data


Note¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
802.11b	1	2390	49.653	74	24.347	PEAK	Pass
		2390	N/A	54	N/A	AVERAGE	Pass
	11	2483.5	48.977	74	25.023	PEAK	Pass
		2483.5	N/A	54	N/A	AVERAGE	Pass
802.11g	1	2390	66.978	74	7.022	PEAK	Pass
		2390	51.374	54	2.626	AVERAGE	Pass
	11	2483.5	64.453	74	9.547	PEAK	Pass
		2483.5	42.190	54	11.810	AVERAGE	Pass
802.11n20	1	2390	65.660	74	8.340	PEAK	Pass
		2390	51.379	54	2.621	AVERAGE	Pass
	11	2483.5	61.758	74	12.242	PEAK	Pass
		2483.5	47.355	54	6.645	AVERAGE	Pass

802.11b CHANNEL 1, PEAK




802.11b CHANNEL 11, PEAK



802.11g CHANNEL 1, PEAK





802.11g CHANNEL 1, AV



802.11g CHANNEL 11, PEAK

802.11g CHANNEL 11, AV



802.11n-20 MHz CHANNEL 1, PEAK

802.11n-20 MHz CHANNEL 1, AV



802.11n-20 MHz CHANNEL 11, PEAK

802.11n-20 MHz CHANNEL 11, AV



A.8 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Measurement Value (dBm/3kHz)	Limit (dBm/3kHz)
1	-9.91	8
6	-11.36	8
11	-11.84	8

802.11g Mode:


Channel	Measurement Value (dBm/3kHz)	Limit (dBm/3kHz)
1	-10.98	8
6	-9.72	8
11	-11.54	8

802.11n-20 MHz Mode:


Channel	Measurement Value (dBm/3kHz)	Limit (dBm/3kHz)
1	-12.00	8
6	-11.82	8
11	-12.81	8

Test plots


802.11b CHANNEL 1




802.11b CHANNEL 6




802.11b CHANNEL 11




802.11g CHANNEL 1




802.11g CHANNEL 6




802.11g CHANNEL 11




802.11n-20 MHz CHANNEL 1



802.11 n-20 MHz CHANNEL 6



802.11n-20 MHz CHANNEL 11



ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-EC2030044-AR.pdf".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-EC2030044-AW.pdf".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-EC2030044-AI.pdf".

--END OF REPORT--