


FCC Test Report

FCC ID : 2AJ4H-T815
Equipment : TPMS Sensor
Model No. : TIY-081005
Brand Name : TYC-TIY
Applicant : I YUAN PRECISION INDUSTRIAL CO., LTD.
Address : NO.24, Dinghu Rd., Guishan Dist., Taoyuan
City 33378, Taiwa(R.O.C.)
Standard : 47 CFR FCC Part 15.231
Received Date : Mar. 21, 2019
Tested Date : Mar. 22 ~ Mar. 25, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	6
1.3	Test Setup Chart	6
1.4	The Equipment List	7
1.5	Test Standards	7
1.6	Deviation from Test Standard and Measurement Procedure.....	7
1.7	Measurement Uncertainty	7
2	TEST CONFIGURATION	8
2.1	Testing Condition	8
2.2	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS.....	9
3.1	Radiated Emission	9
3.2	Transmission and Deactivation Time	26
3.3	20dB and Occupied Bandwidth	33
4	TEST LABORATORY INFORMATION	36

Release Record

Report No.	Version	Description	Issued Date
FR931905	Rev. 01	Initial issue	Apr. 12, 2019

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	Note ¹	N/A
15.231(b)	Field Strength of Fundamental emissions	Meet the requirement of limit	Pass
15.231(b) 15.209	Unwanted Emissions	Meet the requirement of limit	Pass
15.231(a)	Transmission and Deactivation Time	Meet the requirement of limit	Pass
15.231(c)	20dB bandwidth	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass
N/A means Not Applicable. Note ¹ : The EUT consumes DC power from battery, so the test is not required.			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared values of gain for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of the gain.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Modulation	Ch. Freq. (MHz)	Channel Number	Channel Bandwidth (kHz)
315	ASK	315	1	---
315	FSK	315	1	---

Note: The device supports below 3 modes:
 1) Rotating mode
 2) Stationary mode
 3) Alert mode

1.1.2 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector
1	Monopole	---	---

1.1.3 EUT Operational Condition

Power Supply Type	3Vdc from battery
--------------------------	-------------------


1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	Battery	Brand: maxell Model: CR2050HR Power Rating: 3Vdc

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	315MHz controller	---	TIY tool	---	provided by applicant

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 18, 2018	Jul. 17, 2019
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019
Preamplifier	EMC	EMC02325	980225	Jul. 20, 2018	Jul. 19, 2019
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 08, 2018	Oct. 07, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 08, 2018	Oct. 07, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 08, 2018	Oct. 07, 2019
LF cable 1M	EMC	EMCCFD400-NM-NM-100 0	160502	Oct. 08, 2018	Oct. 07, 2019
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 08, 2018	Oct. 07, 2019

Note: Calibration Interval of instruments listed above is one year.

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.231

ANSI C63.10-2013

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$))

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission \leq 1GHz	± 3.41 dB
Radiated emission $>$ 1GHz	± 4.59 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	24°C / 65%	Aska Huang
RF Conducted	TH01-WS	24°C / 65%	Aska Huang

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Test Configuration
Field Strength of Fundamental emissions	ASK, FSK	315	a
Unwanted Emissions	ASK, FSK	315	a
Deactivation Time	ASK, FSK	315	a / b / c
20dB bandwidth	ASK, FSK	315	a

Note:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.
2. Three test configurations are listing as follows:
 Configuration a: Rotating mode.
 Configuration b: Stationary mode.
 Configuration c: Alert mode.
3. The output power of above 3 configurations is same thus only one mode (Configuration a) is selected to perform emission and 20 dB bandwidth test item.

3 Transmitter Test Results

3.1 Radiated Emission

This section includes field strength of fundamental, field strength of harmonics and emissions radiated outside of the operating frequency bands.

3.1.1 Limit of field strength of fundamental and field strength of harmonics

Fundamental Frequency (MHz)	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
40.66~40.70	1000	100
70 -130	500	50
130 -174	500 to 1500 ^{Note}	50 to 150 ^{Note}
174 -260	1500	150
260 -470	1500 to 5000 ^{Note}	150 to 500 ^{Note}
above 470	5000	500

Note: Linear interpolations.

3.1.2 Limit of Unwanted Emissions

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

Radiated emission limits			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Quasi-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.3 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

1. Radiated emission below 1GHz
120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission
 2. Radiated emission Peak value for harmonics
RBW=1MHz, VBW=3MHz and Peak detector
 3. Radiated emission Peak value for fundamental
RBW=1MHz, VBW=3MHz and Peak detector
- Radiated emission Average value for field strength of fundamental and harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:

4. ASK mode

$$20\log (\text{Duty cycle}) = 20\log \frac{31*1\text{ms}}{100 \text{ ms}} = -10.17\text{dB}$$


Please see page 18 for plotted duty

FSK mode

$$20\log (\text{Duty cycle}) = 20\log \frac{14.6*1 \text{ ms}}{100 \text{ ms}} = -16.71\text{dB}$$


Please see page 25 for plotted duty

3.1.4 Test Setup




ASK mode

3.1.5 Transmitter Field strength of fundamental emissions and harmonics

Modulation	ASK	Test Freq. (MHz)	315						
Polarization	Horizontal								
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	315.00	63.95	67.66	-3.71	71.30	-7.35	Average	100	0
2	315.00	74.12	87.66	-13.54	81.47	-7.35	Peak	100	0
3	630.00	29.25	47.66	-18.41	29.52	-0.27	Average	100	123
4	630.00	39.42	67.66	-28.24	39.69	-0.27	Peak	100	123
5	945.00	31.66	47.66	-16.00	27.26	4.40	Average	142	6
6	945.00	41.83	67.66	-25.83	37.43	4.40	Peak	142	6
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

Modulation	ASK	Test Freq. (MHz)	315
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	315.00	56.50	67.66	-11.16	63.85	-7.35	Average	217	311
2	315.00	66.67	87.66	-20.99	74.02	-7.35	Peak	217	311
3	630.00	33.63	47.66	-14.03	33.90	-0.27	Average	100	11
4	630.00	43.80	67.66	-23.86	44.07	-0.27	Peak	100	11
5	945.00	34.69	47.66	-12.97	30.29	4.40	Average	100	287
6	945.00	44.86	67.66	-22.80	40.46	4.40	Peak	100	287

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.1.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	ASK	Test Freq. (MHz)	315						
Polarization	Horizontal								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 200 MHz, and 46 dBuV/m from 200 to 1000 MHz. Six blue vertical lines represent emission peaks labeled 1 through 6, with their respective frequencies and levels indicated in the table below.</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	38.73	23.73	40.00	-16.27	31.99	-8.26	Peak	---	---
2	157.07	22.03	43.50	-21.47	30.28	-8.25	Peak	---	---
3	448.07	26.02	46.00	-19.98	29.98	-3.96	Peak	---	---
4	488.81	26.96	46.00	-19.04	30.06	-3.10	Peak	---	---
5	754.59	31.74	46.00	-14.26	29.89	1.85	Peak	---	---
6	867.11	33.10	46.00	-12.90	29.91	3.19	Peak	---	---
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.</p>									

Modulation	ASK	Test Freq. (MHz)	315
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	38.73	28.67	40.00	-11.33	36.93	-8.26	Peak	---	---
2	119.24	26.55	43.50	-16.95	37.25	-10.70	Peak	---	---
3	150.28	22.48	43.50	-21.02	30.84	-8.36	Peak	---	---
4	439.34	28.17	46.00	-17.83	32.32	-4.15	Peak	---	---
5	585.81	30.08	46.00	-15.92	31.09	-1.01	Peak	---	---
6	773.99	33.15	46.00	-12.85	31.21	1.94	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.1.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	ASK	Test Freq. (MHz)	315						
Polarization	Horizontal								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 4000). Two horizontal red lines represent limits: 'NCC 315MHZ(AUTO)' at approximately 74 dBuV/m and 'NCC 315MHZ(AUTO)AV' at approximately 54 dBuV/m. Eight vertical blue lines represent emission points, labeled 1 through 8, with their corresponding SA readings and factors indicated in the table below.</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1575.00	43.24	54.00	-10.76	50.19	-6.95	Average	265	169
2	1575.00	53.41	74.00	-20.59	60.36	-6.95	Peak	265	169
3	1890.00	50.94	54.00	-3.06	57.10	-6.16	Average	258	4
4	1890.00	61.11	74.00	-12.89	67.27	-6.16	Peak	258	4
5	2205.00	51.79	54.00	-2.21	54.71	-2.92	Average	326	0
6	2205.00	61.96	74.00	-12.04	64.88	-2.92	Peak	326	0
7	3150.00	42.08	54.00	-11.92	42.85	-0.77	Average	100	330
8	3150.00	52.25	74.00	-21.75	53.02	-0.77	Peak	100	330

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	ASK	Test Freq. (MHz)	315
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1575.00	41.57	54.00	-12.43	48.52	-6.95	Average	141	101
2	1575.00	51.74	74.00	-22.26	58.69	-6.95	Peak	141	101
3	1890.00	42.26	54.00	-11.74	48.42	-6.16	Average	174	169
4	1890.00	52.43	74.00	-21.57	58.59	-6.16	Peak	174	169
5	2205.00	40.86	54.00	-13.14	43.78	-2.92	Average	100	337
6	2205.00	51.03	74.00	-22.97	53.95	-2.92	Peak	100	337
7	3150.00	39.48	54.00	-14.52	40.25	-0.77	Average	287	19
8	3150.00	49.65	74.00	-24.35	50.42	-0.77	Peak	287	19

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).




$$20\log(\text{Duty cycle}) = 20\log \frac{31 * 1 \text{ ms}}{100 \text{ ms}} = -10.17\text{dB}$$

FSK mode

3.1.8 Transmitter Field strength of fundamental emissions and harmonics

Modulation	FSK	Test Freq. (MHz)	315																																																																												
Polarization	Horizontal																																																																														
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High</th> <th>Turn Table</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>315.00</td> <td>57.72</td> <td>67.66</td> <td>-9.94</td> <td>65.07</td> <td>-7.35</td> <td>Average</td> <td>100</td> <td>1</td> </tr> <tr> <td>2</td> <td>315.00</td> <td>74.43</td> <td>87.66</td> <td>-13.23</td> <td>81.78</td> <td>-7.35</td> <td>Peak</td> <td>100</td> <td>1</td> </tr> <tr> <td>3</td> <td>630.00</td> <td>22.70</td> <td>47.66</td> <td>-24.96</td> <td>22.97</td> <td>-0.27</td> <td>Average</td> <td>100</td> <td>133</td> </tr> <tr> <td>4</td> <td>630.00</td> <td>39.41</td> <td>67.66</td> <td>-28.25</td> <td>39.68</td> <td>-0.27</td> <td>Peak</td> <td>100</td> <td>133</td> </tr> <tr> <td>5</td> <td>945.00</td> <td>25.94</td> <td>47.66</td> <td>-21.72</td> <td>21.54</td> <td>4.40</td> <td>Average</td> <td>146</td> <td>6</td> </tr> <tr> <td>6</td> <td>945.00</td> <td>42.65</td> <td>67.66</td> <td>-25.01</td> <td>38.25</td> <td>4.40</td> <td>Peak</td> <td>146</td> <td>6</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	315.00	57.72	67.66	-9.94	65.07	-7.35	Average	100	1	2	315.00	74.43	87.66	-13.23	81.78	-7.35	Peak	100	1	3	630.00	22.70	47.66	-24.96	22.97	-0.27	Average	100	133	4	630.00	39.41	67.66	-28.25	39.68	-0.27	Peak	100	133	5	945.00	25.94	47.66	-21.72	21.54	4.40	Average	146	6	6	945.00	42.65	67.66	-25.01	38.25	4.40	Peak	146	6
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																							
1	315.00	57.72	67.66	-9.94	65.07	-7.35	Average	100	1																																																																						
2	315.00	74.43	87.66	-13.23	81.78	-7.35	Peak	100	1																																																																						
3	630.00	22.70	47.66	-24.96	22.97	-0.27	Average	100	133																																																																						
4	630.00	39.41	67.66	-28.25	39.68	-0.27	Peak	100	133																																																																						
5	945.00	25.94	47.66	-21.72	21.54	4.40	Average	146	6																																																																						
6	945.00	42.65	67.66	-25.01	38.25	4.40	Peak	146	6																																																																						
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																															

Modulation	FSK	Test Freq. (MHz)	315
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	315.00	49.65	67.66	-18.01	57.00	-7.35	Average	225	321
2	315.00	66.36	87.66	-21.30	73.71	-7.35	Peak	225	321
3	630.00	27.66	47.66	-20.00	27.93	-0.27	Average	100	15
4	630.00	44.37	67.66	-23.29	44.64	-0.27	Peak	100	15
5	945.00	28.51	47.66	-19.15	24.11	4.40	Average	100	287
6	945.00	45.22	67.66	-22.44	40.82	4.40	Peak	100	287

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.1.9 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	FSK	Test Freq. (MHz)	315						
Polarization	Horizontal								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red stepped line represents the FCC CLASS-B limit, which is approximately 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 200 MHz, and 46 dBuV/m from 200 to 1000 MHz. Six blue vertical lines represent measured peaks at frequencies 1, 2, 3, 4, 5, and 6. The peak levels are approximately 24, 23, 27, 29, 31, and 35 dBuV/m respectively.</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	38.73	24.30	40.00	-15.70	32.56	-8.26	Peak	---	---
2	143.49	23.47	43.50	-20.03	31.98	-8.51	Peak	---	---
3	418.97	27.44	46.00	-18.56	32.00	-4.56	Peak	---	---
4	514.03	29.71	46.00	-16.29	32.14	-2.43	Peak	---	---
5	676.99	31.92	46.00	-14.08	31.45	0.47	Peak	---	---
6	847.71	35.15	46.00	-10.85	32.12	3.03	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	FSK	Test Freq. (MHz)	315
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	39.70	26.93	40.00	-13.07	35.08	-8.15	Peak	---	---
2	120.21	25.50	43.50	-18.00	36.10	-10.60	Peak	---	---
3	380.17	30.71	46.00	-15.29	36.26	-5.55	Peak	---	---
4	549.92	31.12	46.00	-14.88	32.85	-1.73	Peak	---	---
5	780.78	34.15	46.00	-11.85	32.10	2.05	Peak	---	---
6	845.77	34.27	46.00	-11.73	31.21	3.06	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.1.10 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	FSK	Test Freq. (MHz)	315						
Polarization	Horizontal								
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1575.00	36.79	54.00	-17.21	43.74	-6.95	Average	262	167
2	1575.00	53.50	74.00	-20.50	60.45	-6.95	Peak	262	167
3	1890.00	44.56	54.00	-9.44	50.72	-6.16	Average	255	3
4	1890.00	61.27	74.00	-12.73	67.43	-6.16	Peak	255	3
5	2205.00	45.12	54.00	-8.88	48.04	-2.92	Average	322	0
6	2205.00	61.83	74.00	-12.17	64.75	-2.92	Peak	322	0
7	3150.00	35.83	54.00	-18.17	36.60	-0.77	Average	100	325
8	3150.00	52.54	74.00	-21.46	53.31	-0.77	Peak	100	325

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	FSK	Test Freq. (MHz)	315
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1575.00	34.87	54.00	-19.13	41.82	-6.95	Average	138	105
2	1575.00	51.58	74.00	-22.42	58.53	-6.95	Peak	138	105
3	1890.00	35.56	54.00	-18.44	41.72	-6.16	Average	172	172
4	1890.00	52.27	74.00	-21.73	58.43	-6.16	Peak	172	172
5	2205.00	34.14	54.00	-19.86	37.06	-2.92	Average	100	335
6	2205.00	50.85	74.00	-23.15	53.77	-2.92	Peak	100	335
7	3150.00	33.05	54.00	-20.95	33.82	-0.77	Average	285	22
8	3150.00	49.76	74.00	-24.24	50.53	-0.77	Peak	285	22

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



$$20\log(\text{Duty cycle}) = 20\log \frac{14.6 \times 1 \text{ ms}}{100 \text{ ms}} = -16.71 \text{ dB}$$

3.2 Transmission and Deactivation Time


3.2.1 Limit of Transmission and Deactivation Time

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

3.2.2 Test Procedures

1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Set Sweep = fitting time as shown on plots of next pages, Allow the trace to stabilize.
4. Set the EUT to operates at operation modes then record the transmission and deactivation time.

3.2.3 Test Setup




3.2.4 Test Result of Rotating mode

ASK mode

Rotating mode			
Frequency(MHz)	Transmission time (S)	Limit (s)	Pass/Fail
315.00	0.96174	1.0	PASS
Frequency(MHz)	Deactivation Time (S)	Limit (s)	Pass/Fail
315.00	29.3551	28.85	PASS


Note: The limit is longer than 10 seconds and is not shorter than transmission time multiplied by 30 (0.96174 s * 30 = 28.85 s)



FSK mode

Rotating mode			
Frequency(MHz)	Transmission time (S)	Limit (s)	Pass/Fail
315.00	0.81884	1.0	PASS
Frequency(MHz)	Deactivation Time (S)	Limit (s)	Pass/Fail
315.00	29.3696	24.57	PASS

Note: The limit is longer than 10 seconds and is not shorter than transmission time multiplied by 30 (0.81884 s * 30 = 24.57 s)




3.2.5 Test Result of Stationary mode

ASK mode

Stationary mode			
Frequency(MHz)	Transmission time (S)	Limit (s)	Pass/Fail
315.00	0.307971	1.0	PASS
Frequency(MHz)	Deactivation Time (S)	Limit (s)	Pass/Fail
315.00	59.957	10.0	PASS


Note: The limit is longer than 10 seconds and is not shorter than transmission time multiplied by 30 (0.307971 s * 30 = 9.24 s)



FSK mode

Stationary mode			
Frequency(MHz)	Transmission time (S)	Limit (s)	Pass/Fail
315.00	0.014493	1.0	PASS
Frequency(MHz)	Deactivation Time (S)	Limit (s)	Pass/Fail
315.00	60.058	10.0	PASS


Note: The limit is longer than 10 seconds and is not shorter than transmission time multiplied by 30 (0.014493 s * 30 = 0.43 s)



3.2.6 Test Result of Alert mode


ASK mode

Transmission Time Alert mode			
Frequency(MHz)	Transmission time (S)	Limit (s)	Pass/Fail
315.00	0.954	5.0	PASS



FSK mode

Transmission Time Alert mode			
Frequency(MHz)	Transmission time (S)	Limit (s)	Pass/Fail
315.00	0.832	5.0	PASS



3.3 20dB and Occupied Bandwidth

3.3.1 Limit of 20 dB Bandwidth

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz.

3.3.2 Test Procedures


For 20dB bandwidth

1. Set resolution bandwidth (RBW) = 10 kHz, Video bandwidth = 30 kHz
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20dB relative to the maximum level measured in the fundamental emission.

For Occupied bandwidth

1. Set resolution bandwidth (RBW) = 3 kHz, Video bandwidth = 10 kHz
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Use the occupied measurement function of spectrum analyzer to measure 99% occupied bandwidth


3.3.3 Test Setup



3.3.4 20dB and Occupied Bandwidth

ASK mode

20dB and Occupied Bandwidth				
Frequency(MHz)	20dB Bandwidth (MHz)	20dB BW Limit (MHz)	99% BW (MHz)	Pass/Fail
315.00	0.061	0.7875	0.082	PASS




FSK mode

20dB and Occupied Bandwidth


Frequency(MHz)	20dB Bandwidth (MHz)	20dB BW Limit (MHz)	99% BW (MHz)	Pass/Fail
315.00	0.139	0.7875	0.113	PASS

Worst Plots

20dB BW



99% BW



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==