

# TEST REPORT

**Product Name** : quadcopter  
**Model Number** : See Page 4  
**FCC ID** : 2AJ55HOLYSTONE6W

**Prepared for** : Xiamen Huoshiquan Import & Export CO., LTD  
**Address** : Unit. 33, Room 806, NO. 2 Huming Road, Siming District,  
Xiamen, China

**Prepared by** : EMTEK (SHENZHEN) CO., LTD.  
**Address** : Building 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

Tel: (0755) 26954280  
Fax: (0755) 26954282

**Report Number** : ENS2202220091W00201R  
**Date(s) of Tests** : February 22, 2022 to April 16, 2022  
**Date of issue** : April 18, 2022

## TABLE OF CONTENTS

<b>1 TEST RESULT CERTIFICATION .....</b>	<b>3</b>
<b>2 EUT TECHNICAL DESCRIPTION .....</b>	<b>4</b>
<b>3 SUMMARY OF TEST RESULT .....</b>	<b>5</b>
<b>4 TEST METHODOLOGY .....</b>	<b>6</b>
4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
4.2 MEASUREMENT EQUIPMENT USED .....	6
4.3 DESCRIPTION OF TEST MODES .....	7
<b>5 FACILITIES AND ACCREDITATIONS .....</b>	<b>8</b>
5.1 FACILITIES .....	8
5.2 LABORATORY ACCREDITATIONS AND LISTINGS .....	8
<b>6 TEST SYSTEM UNCERTAINTY .....</b>	<b>9</b>
<b>7 SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
7.1 RADIO FREQUENCY TEST SETUP 1 .....	10
7.2 RADIO FREQUENCY TEST SETUP 2 .....	10
7.3 CONDUCTED EMISSION TEST SETUP .....	11
7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM .....	12
7.5 SUPPORT EQUIPMENT .....	12
<b>8 TEST REQUIREMENTS .....</b>	<b>13</b>
8.1 DTS (6DB) BANDWIDTH .....	13
8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	20
8.3 MAXIMUM POWER SPECTRAL DENSITY .....	28
8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS .....	35
8.5 RADIATED SPURIOUS EMISSION .....	56
8.6 CONDUCTED EMISSIONS TEST .....	69
8.7 ANTENNA APPLICATION .....	72

# 1 TEST RESULT CERTIFICATION

Applicant : Xiamen Huoshiquan Import & Export CO., LTD  
 Address : Unit. 33, Room 806, NO. 2 Huming Road, Siming District, Xiamen, China  
 Manufacturer : Xiamen Huoshiquan Import & Export CO., LTD  
 Address : Unit. 33, Room 806, NO. 2 Huming Road, Siming District, Xiamen, China  
 EUT : quadcopter  
 Model Name : See Page 4  
 Trademark : Holy Stone

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test : February 22, 2022 to April 16, 2022

Prepared by :   
 Una Yu /Editor

Reviewer :   
 Joe Xia/Editor

Approve & Authorized Signer :   
 Lisa Wang/Manager



## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
<b>Product</b>	quadcopter
<b>Model Number</b>	HS260, HS260W, HS260D, HS260S, HS320, HT30, HS610, HS176, HS290, HS380, HS390, HS400, HS460, HS480, HS490, HS500, HS520, HS530, HS540, HS560, HS570, HS580, HS590, HS610, HS620, HS630, HS640, HS660, HS670, HS680, HS690, HS730, HS740, HS750, HS760, HS770, HS780, HS790, HS800, HS810, HS820, HS830, HS840, HS850, HS860, HS870, HS880, HS890, HS900, HS910, HT300, HT40, HT15, HT35, HT45, HT05, HT10, D11, D33, D60, D70, D80, D35, D55, D20L, HS130, HS280, HT50, HT60, HT65, HT70, HT75, HT80, D65, D75, D85
<b>IEEE 802.11 WLAN Mode Supported</b>	<input checked="" type="checkbox"/> 802.11b <input checked="" type="checkbox"/> 802.11g <input checked="" type="checkbox"/> 802.11n(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11n(40MHz channel bandwidth)
<b>Data Rate</b>	<input checked="" type="checkbox"/> 802.11 b:1,2,5.5,11Mbps; <input checked="" type="checkbox"/> 802.11 g:6,9,12,18,24,36,48,54Mbps; <input checked="" type="checkbox"/> 802.11n(HT20):MCS0-MCS15; <input checked="" type="checkbox"/> 802.11n(HT40):MCS0-MCS15;
<b>Modulation</b>	<input checked="" type="checkbox"/> DSSS with DBPSK/DQPSK/CCK for 802.11b; <input checked="" type="checkbox"/> OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
<b>Operating Frequency Range</b>	<input checked="" type="checkbox"/> 2412-2462MHz for 802.11b/g/n(HT20); <input checked="" type="checkbox"/> 2422-2452MHz for 802.11n(HT40);
<b>Number of Channels</b>	<input checked="" type="checkbox"/> 11 channels for 802.11b/g n(HT20); <input checked="" type="checkbox"/> 7 channels for 802.11n(HT40);
<b>Transmit Power Max</b>	10.46dBm
<b>Antenna Type</b>	Internal Antenna
<b>Antenna Gain</b>	3 dBi
<b>Power Supply</b>	DC 3.7V from internal battery DC 5V from Charger

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC PartClause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted EmissionTest	PASS	
15.247(b)	Antenna Application	PASS	
	NOTE1:N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.		

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AJ55HOLYSTONE6W filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Conducted Emission Test Equipment

EQUIPMENT	Manufacturer	MODELNo.	SERIALNo.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde & Schwarz	ESCI	101384	2021/5/15	1Year
AMN	Rohde & Schwarz	ENV216	5	2021/5/15	1Year
AMN	Kyoritsu	KNW-407	8-1492-9	2021/5/15	1Year
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	2021/5/15	1Year
Current probe	Rohde & Schwarz	EZ-17	100213	2021/5/15	1Year
Capacitive Voltage Probe	TESEQ	CVP 2200 A	47173	2021/5/15	1Year

#### 4.2.2 Radiated Emission Test Equipment

EQUIPMENT	Manufacturer	MODELNo.	SERIALNo.	Last Cal.	Cal. Interval
Pre-Amplifier	HP	8447F	2944A07999	2021/5/15	1Year
EMI Test Receiver	Rohde & Schwarz	ESCI	101414	2021/5/15	1Year
Bilog Antenna	Schwarzbeck	VULB9163	712	2021/9/22	2 Year
Horn antenna	Schwarzbeck	BBHA9120D	9120D-1178	2020/7/4	2 Year
Pre-Amplifie	Lunar EM	LNA1G18-48	J1011131010001	2021/5/15	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2021/5/15	1Year
Loop Antenna	Schwarzbeck	FMZB1519	1519-012	2021/6/12	2 Year

#### 4.2.3 Radio Frequency Test Equipment

EQUIPMENT	Manufacturer	MODELNo.	SERIALNo.	Last Cal.	Cal. Interval
Signal Analyzer	Agilent	N9010A	MY53470879	2021/5/16	1Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	100967	2021/5/15	1Year
RF Power Meter. Dual Channel	BOONTON	4232A	10539	2021/5/15	1 Year
50ohm Diode Power Sensor	BOONTON	51011EMC	36164	2021/5/15	1 Year

### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Frequency and Channel list for 802.11n(HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452
4	2427	7	2442		
5	2432	8	2447		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Test Frequency and channel for 802.11n(HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291.

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01 (identical to ISO/IEC 17025:2017)

**Accredited by FCC**

Designation Number: CN1204

Test Firm Registration Number: 882943

**Accredited by A2LA**

The Certificate Number is 4321.01.

**Accredited by Industry Canada**

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Building 69, Majialong Industry Zone,  
Nanshan District, Shenzhen, Guangdong, China




## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%



## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 7.5 SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	LENOVO	M713A	SA12582190

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. Unless otherwise denoted as EUT in [Remark] column, device(s) used in tested system is a support equipment

## 8 TEST REQUIREMENTS

### 8.1 DTS (6DB) BANDWIDTH

#### 8.1.1 Applicable Standard

According to FCC Part15.247 (a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

#### 8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Measure and record the results in the test report.

#### 8.1.5 Test Results

Temperature : 26°C                      ATM Pressure:: 1011 mbar  
 Humidity : 55 %                      Test By: Lily

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.08	2406.96	2417.04	0.5	PASS
		2437	10.04	2431.96	2442.00	0.5	PASS
		2462	10.08	2456.96	2467.04	0.5	PASS
11G	Ant1	2412	16.32	2403.84	2420.16	0.5	PASS
		2437	16.36	2428.84	2445.20	0.5	PASS
		2462	16.36	2453.84	2470.20	0.5	PASS
11N20SISO	Ant1	2412	17.60	2403.20	2420.80	0.5	PASS
		2437	17.60	2428.20	2445.80	0.5	PASS
		2462	17.60	2453.20	2470.80	0.5	PASS
11N40SISO	Ant1	2422	17.60	2413.20	2430.80	0.5	PASS
		2437	17.60	2428.20	2445.80	0.5	PASS
		2452	17.60	2443.20	2460.80	0.5	PASS


## 11B\_Ant1\_2412



## 11B\_Ant1\_2437




## 11B\_Ant1\_2462




Date: 2 APR 2022 14:10:45

## 11G\_Ant1\_2412




Date: 2 APR 2022 14:17:06

## 11G\_Ant1\_2437



Date: 2 APR 2022 14:33:33


## 11G\_Ant1\_2462



Date: 2 APR 2022 14:36:59




## 11N20SISO\_Ant1\_2412




Date: 2 APR 2022 14:42:37

## 11N20SISO\_Ant1\_2437




Date: 2 APR 2022 14:46:25

## 11N20SISO\_Ant1\_2462




Date: 2 APR 2022 14:50:00

## 11N40SISO\_Ant1\_2422




Date: 2 APR 2022 14:54:25

## 11N40SISO\_Ant1\_2437



Date: 2 APR 2022 14:58:04

## 11N40SISO\_Ant1\_2452



Date: 2 APR 2022 15:01:27

## 8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 8.2.1 Applicable Standard

According to FCC Part15.247 (b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

### 8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.2.4 Test Procedure

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain- 6)

### 8.2.5 Test Results

Temperature :	26°C	ATM Pressure:	1011 mbar
Humidity :	55 %	Test By:	Lily


Note:


802.11b Duty cycle factor= $10\log(1/\text{duty cycle})=0\text{db}$


802.11g Duty cycle factor= $10\log(1/\text{duty cycle})=0\text{db}$

802.11n(HT20) Duty cycle factor= $10\log(1/\text{duty cycle})=0\text{db}$

TestMode	Antenna	Frequen cy[MHz]	Set Power	Peak Power[dBm]	Conducted Limit[dBm]	EIRP [dBm]	EIRP Limit[dBm]	Verdict
11B	Ant1	2412	---	10.46	$\leq 30.00$	10.46	$\leq 36.00$	PASS
		2437	---	9.43	$\leq 30.00$	9.43	$\leq 36.00$	PASS
		2462	---	9.62	$\leq 30.00$	9.62	$\leq 36.00$	PASS
11G	Ant1	2412	---	10.15	$\leq 30.00$	10.15	$\leq 36.00$	PASS
		2437	---	9.94	$\leq 30.00$	9.94	$\leq 36.00$	PASS
		2462	---	9.00	$\leq 30.00$	9.00	$\leq 36.00$	PASS
11N20SIS O	Ant1	2412	---	9.66	$\leq 30.00$	9.66	$\leq 36.00$	PASS
		2437	---	10.22	$\leq 30.00$	10.22	$\leq 36.00$	PASS
		2462	---	9.66	$\leq 30.00$	9.66	$\leq 36.00$	PASS
11N40SIS O	Ant1	2422	---	5.85	$\leq 30.00$	5.85	$\leq 36.00$	PASS
		2437	---	6.10	$\leq 30.00$	6.10	$\leq 36.00$	PASS
		2452	---	5.39	$\leq 30.00$	5.39	$\leq 36.00$	PASS












## 11N20SISO\_Ant1\_2412



## 11N20SISO\_Ant1\_2437




## 11N20SISO\_Ant1\_2462



Date: 2 APR 2022 14:50:34

## 11N40SISO\_Ant1\_2422



Date: 2 APR 2022 14:54:59



### 8.3 MAXIMUM POWER SPECTRAL DENSITY

#### 8.3.1 Applicable Standard

According to FCC Part15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to:10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.


Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain- 6)

#### 8.3.5 Test Results

Temperature : 26°C      ATM Pressure:: 1011 mbar  
 Humidity : 55 %      Test By: Lily

TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-21.11	≤8.00	PASS
		2437	-22.76	≤8.00	PASS
		2462	-21.72	≤8.00	PASS
11G	Ant1	2412	-24.5	≤8.00	PASS
		2437	-24.29	≤8.00	PASS
		2462	-25.24	≤8.00	PASS
11N20SISO	Ant1	2412	-25.04	≤8.00	PASS
		2437	-24.79	≤8.00	PASS
		2462	-25.36	≤8.00	PASS
11N40SISO	Ant1	2422	-29.13	≤8.00	PASS
		2437	-28.8	≤8.00	PASS
		2452	-29.13	≤8.00	PASS

## 11B\_Ant1\_2412



Date: 2 APR 2022 13:56:25

## 11B\_Ant1\_2437




Date: 2 APR 2022 14:08:48

## 11B\_Ant1\_2462




Date: 2 APR 2022 14:12:01

## 11G\_Ant1\_2412




Date: 2 APR 2022 14:18:44

## 11G\_Ant1\_2437




Date: 2 APR 2022 14:34:59

## 11G\_Ant1\_2462




Date: 2 APR 2022 14:38:26

## 11N20SISO\_Ant1\_2412



Date: 2 APR 2022 14:44:07


## 11N20SISO\_Ant1\_2437



Date: 2 APR 2022 14:47:55




## 11N20SISO\_Ant1\_2462




Date: 2 APR 2022 14:51:30

## 11N40SISO\_Ant1\_2422




Date: 2 APR 2022 14:55:56

## 11N40SISO\_Ant1\_2437



Date: 2 APR 2022 14:59:35

## 11N40SISO\_Ant1\_2452



Date: 2 APR 2022 15:02:58

## 8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

### 8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to  $\geq 1.5$  times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW  $\geq 3 \times$  RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

#### ■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

### 8.4.5 Test Results

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
11B	Ant1	2412	2409.53	0.98
		2437	2437.52	0.27
		2462	2460.49	0.19
11G	Ant1	2412	2407.01	-2.16
		2437	2431.99	-1.94
		2462	2460.76	-2.21
11N20SISO	Ant1	2412	2414.52	-2.55
		2437	2432.00	-2.08
		2462	2460.74	-2.10
11N40SISO	Ant1	2422	2423.26	-5.74
		2437	2432.03	-5.68
		2452	2447.00	-5.24




## 11B\_Ant1\_2412




Date: 2 APR 2022 13:56:33

## 11B\_Ant1\_2437




Date: 2 APR 2022 14:08:56

## 11B\_Ant1\_2462




Date: 2 APR 2022 14:12:09

## 11G\_Ant1\_2412




Date: 2 APR 2022 14:18:52

## 11G\_Ant1\_2437




Date: 2 APR 2022 14:35:07

## 11G\_Ant1\_2462




Date: 2 APR 2022 14:38:34

## 11N20SISO\_Ant1\_2412




## 11N20SISO\_Ant1\_2437






## 11N20SISO\_Ant1\_2462




Date: 2 APR 2022 14:51:37

## 11N40SISO\_Ant1\_2422




Date: 2 APR 2022 14:56:04

## 11N40SISO\_Ant1\_2437




## 11N40SISO\_Ant1\_2452




TestMode	Antenna	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	30~1000	0.98	-50.38	≤-29.02	PASS
			1000~26500	0.98	-47.78	≤-29.02	PASS
		2437	30~1000	0.27	-53.24	≤-29.73	PASS
			1000~26500	0.27	-49.57	≤-29.73	PASS
		2462	30~1000	0.19	-52.92	≤-29.81	PASS
			1000~26500	0.19	-49.13	≤-29.81	PASS
11G	Ant1	2412	30~1000	-2.16	-39.71	≤-32.16	PASS
			1000~26500	-2.16	-49.8	≤-32.16	PASS
		2437	30~1000	-1.94	-52.66	≤-31.94	PASS
			1000~26500	-1.94	-49.42	≤-31.94	PASS
		2462	30~1000	-2.21	-53.03	≤-32.21	PASS
			1000~26500	-2.21	-49.59	≤-32.21	PASS
11N20SISO	Ant1	2412	30~1000	-2.55	-52.62	≤-32.55	PASS
			1000~26500	-2.55	-49.2	≤-32.55	PASS
		2437	30~1000	-2.08	-52.45	≤-32.08	PASS
			1000~26500	-2.08	-48.48	≤-32.08	PASS
		2462	30~1000	-2.10	-52.3	≤-32.1	PASS
			1000~26500	-2.10	-48.94	≤-32.1	PASS
11N40SISO	Ant1	2422	30~1000	-5.74	-52.72	≤-35.74	PASS
			1000~26500	-5.74	-49.42	≤-35.74	PASS
		2437	30~1000	-5.68	-53.08	≤-35.68	PASS
			1000~26500	-5.68	-48.29	≤-35.68	PASS
		2452	30~1000	-5.24	-52.86	≤-35.24	PASS
			1000~26500	-5.24	-49.57	≤-35.24	PASS

## 11B\_Ant1\_2412\_30~1000




Date: 2 APR 2022 13:57:01

## 11B\_Ant1\_2412\_1000~26500




Date: 2 APR 2022 13:57:38

## 11B\_Ant1\_2437\_30~1000




Date: 2 APR 2022 14:09:08

## 11B\_Ant1\_2437\_1000~26500




Date: 2 APR 2022 14:09:45

## 11B\_Ant1\_2462\_30~1000




Date: 2 APR 2022 14:12:37

## 11B\_Ant1\_2462\_1000~26500




Date: 2 APR 2022 14:13:14

## 11G\_Ant1\_2412\_30~1000




Date: 2 APR 2022 14:19:20

## 11G\_Ant1\_2412\_1000~26500




Date: 2 APR 2022 14:19:57

## 11G\_Ant1\_2437\_30~1000



Date: 2 APR 2022 14:35:19


## 11G\_Ant1\_2437\_1000~26500



Date: 2 APR 2022 14:35:57




## 11G\_Ant1\_2462\_30~1000




Date: 2 APR 2022 14:39:01

## 11G\_Ant1\_2462\_1000~26500




Date: 2 APR 2022 14:39:39

## 11N20SISO\_Ant1\_2412\_30~1000




Date: 2 APR 2022 14:44:42

## 11N20SISO\_Ant1\_2412\_1000~26500




Date: 2 APR 2022 14:45:20

## 11N20SISO\_Ant1\_2437\_30~1000




Date: 2 APR 2022 14:48:15

## 11N20SISO\_Ant1\_2437\_1000~26500




Date: 2 APR 2022 14:48:52

## 11N20SISO\_Ant1\_2462\_30~1000




Date: 2 APR 2022 14:52:05

## 11N20SISO\_Ant1\_2462\_1000~26500




Date: 2 APR 2022 14:52:42

## 11N40SISO\_Ant1\_2422\_30~1000




Date: 2 APR 2022 14:56:31

## 11N40SISO\_Ant1\_2422\_1000~26500




Date: 2 APR 2022 14:57:09

## 11N40SISO\_Ant1\_2437\_30~1000




Date: 2 APR 2022 14:59:55

## 11N40SISO\_Ant1\_2437\_1000~26500




Date: 2 APR 2022 15:00:32

## 11N40SISO\_Ant1\_2452\_30~1000



Date: 2 APR 2022 15:03:33

## 11N40SISO\_Ant1\_2452\_1000~26500



Date: 2 APR 2022 15:04:10

## 8.5 RADIATED SPURIOUS EMISSION

### 8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 Meas Guidance v05r02

### 8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency (MHz)	Field Strength ( $\mu\text{V}/\text{m}$ )	Field Strength ( $\text{dB}\mu\text{V}/\text{m}$ )	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu\text{V}/\text{m}$ )	300
0.490-1.705	2400/F(KHz)	20 log ( $\mu\text{V}/\text{m}$ )	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak



Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit. Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

Temperature:	25.7° C
Relative Humidity:	55%
ATM Pressure:	1011 mbar


■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40 \log(\text{Specific distance} / \text{test distance})$  (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor



- Spurious Emission Above 1GHz(1GHz to 25GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

Test mode: 802.11b Frequency: Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
7846.852	V	53.01	38.26	74	54	-20.99	-15.74
11923.29	V	55.98	39.48	74	54	-18.02	-14.52
17935.08	V	62.66	46.38	74	54	-11.34	-7.62
7846.852	H	53.50	37.60	74	54	-20.50	-16.40
11901.77	H	56.49	39.48	74	54	-17.51	-14.52
18000.00	H	63.36	45.28	74	54	-10.64	-8.72

Test mode: 802.11b Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
8239.070	V	53.92	37.46	74	54	-20.08	-16.54
11975.09	V	56.49	40.28	74	54	-17.51	-13.72
17967.51	V	63.08	47.35	74	54	-10.92	-6.65
12014.10	H	56.71	40.13	74	54	-17.29	-13.87
14554.92	H	55.49	39.58	74	54	-18.51	-14.42
17967.51	H	62.88	46.57	74	54	-11.12	-7.43

Test mode: 802.11b Frequency: Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
11400.90	V	55.34	39.14	74	54	-18.66	-14.86
14554.92	V	57.15	41.22	74	54	-16.85	-12.78
17980.50	V	62.67	46.27	74	54	-11.33	-7.73
11405.02	H	54.82	38.22	74	54	-19.18	-15.78
14544.41	H	56.73	40.18	74	54	-17.27	-13.82
17922.12	H	62.73	46.33	74	54	-11.27	-7.67

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4)The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:

Test mode: 802.11b Frequency: Channel 1: 2412MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2386.740	H	52.65	74	36.38	54
2370.320	V	51.55	74	35.86	54


Test mode: 802.11b Frequency: Channel 11: 2462MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.702	H	53.03	74	37.49	54
2484.110	V	47.37	74	31.28	54

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Correct Factor +Cable Loss.
  - (3) Correct Factor= Ant\_F + Cab\_L - Preamp
  - (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


**Spurious Emission in Restricted Band 2310-2390MHz**

Test Model	<input checked="" type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> Channel 1: 2412MHz	<input type="checkbox"/> Channel 3: 2422MHz		Polarity: H
	VBW=3MHz			




**Spurious Emission in Restricted Band 2310-2390MHz**

Test Model	<input checked="" type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> Channel 1: 2412MHz	<input type="checkbox"/> Channel 3: 2422MHz		Polarity: V
	VBW=3MHz			




**Spurious Emission in Restricted Band 2483.5-2500MHz**

Test Model	<input checked="" type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> Channel 11: 2462MHz	<input type="checkbox"/> Channel 9: 2452MHz	Polarity: H	
VBW=3MHz				




**Spurious Emission in Restricted Band 2483.5-2500MHz**

Test Model	<input checked="" type="checkbox"/> 802.11b	<input type="checkbox"/> 802.11g	<input type="checkbox"/> 802.11n(HT20)	<input type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> Channel 11: 2462MHz	<input type="checkbox"/> Channel 9: 2452MHz	Polarity: V	
VBW=3MHz				




- Spurious Emission below 1GHz (30MHz to 1GHz)
- All modes 2.4G 802.11b/g/n have been tested, and the worst result of 802.11b recorded was report as below:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 28.1 C  
 Limit: (RE)FCC PART 15 CLASS B Power: DC 6V Humidity: 43 %  
 Mode:WIFI 2412  
 Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		32.5768	40.26	-14.37	25.89	40.00	-14.11	QP		
2		50.4090	40.96	-11.96	29.00	40.00	-11.00	QP		
3		359.9741	42.97	-7.44	35.53	46.00	-10.47	QP		
4	!	480.1065	45.84	-5.48	40.36	46.00	-5.64	QP		
5	*	600.1100	44.57	-2.84	41.73	46.00	-4.27	QP		
6	!	832.5870	39.16	2.54	41.70	46.00	-4.30	QP		




Site 3m Chamber #1      Polarization: **Horizontal**      Temperature: 28.1 C  
 Limit: (RE)FCC PART 15 CLASS B      Power: DC 6V      Humidity: 43 %  
 Mode:WIFI 2412  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		312.0426	43.87	-9.11	34.76	46.00	-11.24	QP		
2	!	420.0276	48.13	-6.08	42.05	46.00	-3.95	QP		
3	!	480.1065	48.18	-5.48	42.70	46.00	-3.30	QP		
4	!	600.1098	44.35	-2.84	41.51	46.00	-4.49	QP		
5	!	840.2860	40.03	2.86	42.89	46.00	-3.11	QP		
6	*	936.3668	43.76	0.37	44.13	46.00	-1.87	QP		





No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		50.4090	41.46	-11.96	29.50	40.00	-10.50	QP		
2		216.0240	40.31	-13.27	27.04	46.00	-18.96	QP		
3		359.9740	40.97	-7.44	33.53	46.00	-12.47	QP		
4		480.1064	44.34	-5.48	38.86	46.00	-7.14	QP		
5		600.1097	42.57	-2.84	39.73	46.00	-6.27	QP		
6	*	888.3882	38.37	1.53	39.90	46.00	-6.10	QP		



Site 3m Chamber #1      Polarization: **Horizontal**      Temperature: 28.1 C


Limit: (RE)FCC PART 15 CLASS B  
Mode:WIFI 2437

Power: DC 6V

Humidity: 43 %


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		216.0240	37.97	-13.27	24.70	46.00	-21.30	QP		
2		312.0425	42.87	-9.11	33.76	46.00	-12.24	QP		
3		360.1317	46.78	-7.44	39.34	46.00	-6.66	QP		
4	!	480.1064	46.68	-5.48	41.20	46.00	-4.80	QP		
5	!	648.2373	42.19	-1.86	40.33	46.00	-5.67	QP		
6	*	936.3668	42.76	0.37	43.13	46.00	-2.87	QP		



Site 3m Chamber #1      Polarization: *Vertical*      Temperature: 28.1 C  
 Limit: (RE)FCC PART 15 CLASS B      Power: DC 6V      Humidity: 43 %  
 Mode:WIFI 2462  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		32.5767	40.76	-14.37	26.39	40.00	-13.61			QP
2		50.4090	41.46	-11.96	29.50	40.00	-10.50			QP
3		216.0240	39.31	-13.27	26.04	46.00	-19.96			QP
4		480.1064	45.34	-5.48	39.86	46.00	-6.14			QP
5	*	600.1095	44.07	-2.84	41.23	46.00	-4.77			QP
6		888.3881	38.37	1.53	39.90	46.00	-6.10			QP



Site 3m Chamber #1

Polarization: *Horizontal*

Temperature: 28.1 C

Limit: (RE)FCC PART 15 CLASS B

Power: DC 6V

Humidity: 43 %

Mode:WIFI 2462

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		216.0240	37.97	-13.27	24.70	46.00	-21.30	QP		
2		360.1317	44.28	-7.44	36.84	46.00	-9.16	QP		
3	!	420.0276	47.13	-6.08	41.05	46.00	-4.95	QP		
4	!	480.1064	46.18	-5.48	40.70	46.00	-5.30	QP		
5		696.2460	39.82	-1.00	38.82	46.00	-7.18	QP		
6	*	936.3668	42.76	0.37	43.13	46.00	-2.87	QP		

## 8.6 CONDUCTED EMISSIONS TEST

### 8.6.1 Applicable Standard

According to FCC Part 15.207(a)

### 8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.6.3 Test Configuration

Test according to clause 7.3conducted emission test setup


### 8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.  
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
 Repeat above procedures until all frequency measured were complete.

### 8.6.5 Test Results


Pass

The 120V &240V voltagehave been tested, and the worst result recorded was report as below:



Site Conduction #2 Phase: **N** Temperature: 25.1  
 Limit: (CE)FCC PART 15 class B\_QP Power: AC 120V/60Hz Humidity: 45 %  
 Mode: Charging Mode  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1540	36.13	10.48	46.61	65.78	-19.17	QP	
2		0.1540	15.74	10.48	26.22	55.78	-29.56	AVG	
3		0.1780	32.46	10.45	42.91	64.58	-21.67	QP	
4		0.1780	14.86	10.45	25.31	54.58	-29.27	AVG	
5		0.2700	28.23	10.41	38.64	61.12	-22.48	QP	
6		0.2700	14.15	10.41	24.56	51.12	-26.56	AVG	
7		0.7460	29.73	10.36	40.09	56.00	-15.91	QP	
8		0.7460	21.10	10.36	31.46	46.00	-14.54	AVG	
9		15.4620	34.18	10.70	44.88	60.00	-15.12	QP	
10		15.4620	22.32	10.70	33.02	50.00	-16.98	AVG	
11	*	22.8660	35.76	10.82	46.58	60.00	-13.42	QP	
12		22.8660	18.34	10.82	29.16	50.00	-20.84	AVG	



Site Conduction #2

Phase: **L1**

Temperature: 25.1

Limit: (CE)FCC PART 15 class B\_QP

Power: AC 120V/60Hz

Humidity: 45 %

Mode: Charging Mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	35.75	10.48	46.23	66.00	-19.77	QP	
2		0.1500	17.76	10.48	28.24	56.00	-27.76	AVG	
3		0.1700	32.37	10.46	42.83	64.96	-22.13	QP	
4		0.1700	17.60	10.46	28.06	54.96	-26.90	AVG	
5		0.7380	28.46	10.36	38.82	56.00	-17.18	QP	
6	*	0.7380	21.52	10.36	31.88	46.00	-14.12	AVG	
7		9.3820	27.37	10.76	38.13	60.00	-21.87	QP	
8		9.3820	20.01	10.76	30.77	50.00	-19.23	AVG	
9		16.0660	34.52	10.72	45.24	60.00	-14.76	QP	
10		16.0660	24.82	10.72	35.54	50.00	-14.46	AVG	
11		24.0660	32.25	10.84	43.09	60.00	-16.91	QP	
12		24.0660	21.51	10.84	32.35	50.00	-17.65	AVG	

## 8.7 ANTENNA APPLICATION

### 8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 8.7.2 Result

PASS.

- The EUT has an Internal Antenna for WIFI 2.4G, the antenna gain is 3 dBi.

Note:  Antenna uses a permanently attached antenna which is not replaceable.  
 Not using a standard antenna jack or electrical connector for antenna replacement  
 The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.



Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

\*\*\* End of Report \*\*\*