



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057  
Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM180700671006  
Page: 1 of 9

# RF Exposure Evaluation Report

**Application No.:** SZEM1807006710CR  
**Applicant:** Xiamen Huoshiquan Import & Export CO., LTD  
**Address of Applicant:** Room 703, No. 813-2 Xiahe Road, Siming District, XIAMEN China  
**Equipment Under Test (EUT):**  
**Product Name:** RC quadcopter  
**Model No.:** HS700, HS700D, HS700G, HS710, HS165, HS165G, HS165G, HS120D, HS120G, HS130D, HS130G, HS500, HS600, HS800, HS900, HS510, HS610, HS810, HS910, HS550, HS650, HS760, HS770, HS880, HS660, HS9001, CD200D, CD600, HS500G, HS600G, HS800G, HS900G, HS510G, HS550G, HS610G, HS650G, HS660G, HS760G, HS770G, HS880G, HS910G, HS500D, HS600D, HS800D, HS900D, HS510D, HS610D, HS810D, HS910D, HS650D, HS660D, HS760D, HS770D, HS880D, HS410, HS510, HS175, HS176, HS320, HS330 ♣

♣ Please refer to section 4.1 of this report which indicates which model was actually tested and which were electrically identical.

**FCC ID:** 2AJ55HOLYSTONEMJ  
**Standards:** 47 CFR Part 1.1307 (2016)  
 47 CFR Part 1.1310 (2016)  
**Date of Receipt:** 2018-07-26  
**Date of Test:** 2018-07-26 to 2018-09-04  
**Date of Issue:** 2018-09-12

<b>Test Result :</b>	<b>PASS*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



**SGS-CSTC Standards Technical Services Co., Ltd  
Shenzhen Branch.**

Report No.: SZEM180700671006  
Page: 2 of 9

## 2 Version

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
01		2018-09-12		Original

<b>Authorized for issue by:</b>				
				
		<hr/>		
		<b>Bill Chen /Project Engineer</b>		
				
		<hr/>		
		<b>Eric Fu /Reviewer</b>		



**SGS-CSTC Standards Technical Services Co., Ltd  
Shenzhen Branch.**

Report No.: SZEM180700671006  
Page: 3 of 9

**3 Contents**

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 VERSION .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 GENERAL INFORMATION .....</b>	<b>4</b>
4.1 GENERAL DESCRIPTION OF EUT .....	4
4.2 TEST LOCATION .....	6
4.3 TEST FACILITY .....	6
4.4 DEVIATION FROM STANDARDS .....	7
4.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	7
<b>5 RF EXPOSURE EVALUATION .....</b>	<b>8</b>
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	8
5.1.1 <i>Limits</i> .....	8
5.1.2 <i>Test Procedure</i> .....	8
4.1.3 EUT RF EXPOSURE EVALUATION .....	9



## 4 General Information

### 4.1 General Description of EUT

Power supply:	DC 7.4V			
Frequency Range:	UNII Band III	IEEE 802.11a	5745-5825	5
		IEEE 802.11n 20MHz	5745-5825	5
Data Modulation:	For 802.11a: OFDM(BPSK/QPSK/16QAM/64QAM) For 802.11n: OFDM(8PSK/QPSK/16QAM/64QAM)			
Antenna Type:	Monopole			
Antenna Gain:	Antenna 1 : 2dBi Antenna 2 : 2dBi Two antennas can not simultaneous transmission.			

Power supply:	RX: Rechargeable battery 7.4V 2800mAh ( Charge by USB )
Operation Frequency	2417MHz to 2466MHz
Modulation Type:	GFSK
Number of Channels:	50
Channel Spacing:	1MHz
Antenna Type:	Monopole
Antenna Gain:	Antenna 1 : 2dBi Antenna 2 : 2dBi Two antennas can not simultaneous transmission.

**Remark:**

The 5GHz camera needs to be used with the drone, 5GHz camera and drone can simultaneous transmission, 5GHz camera has an FCC ID: 2AJ55HOLYSTONEJX.



## SGS-CSTC Standards Technical Services Co., Ltd Shenzhen Branch.

Report No.: SZEM180700671006

Page: 5 of 9

### **Declaration of EUT Family Grouping:**

Model No.: HS700, HS700D, HS700G, HS710, HS165, HS165G, HS165G, HS120D, HS120G, HS130D, HS130G, HS500, HS600, HS800, HS900, HS510, HS610, HS810, HS910, HS550, HS650, HS760, HS770, HS880, HS660, HS9001, CD200D, CD600, HS500G, HS600G, HS800G, HS900G, HS510G, HS550G, HS610G, HS650G, HS660G, HS760G, HS770G, HS880G, HS910G, HS500D, HS600D, HS800D, HS900D, HS510D, HS610D, HS810D, HS910D, HS650D, HS660D, HS760D, HS770D, HS880D, HS410, HS510, HS175, HS176, HS320, HS330

Only the model HS700 was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only the colour, appearance, package and assort is different.



## SGS-CSTC Standards Technical Services Co., Ltd Shenzhen Branch.

Report No.: SZEM180700671006  
Page: 6 of 9

### 4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China  
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

### 4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



**SGS-CSTC Standards Technical Services Co., Ltd  
Shenzhen Branch.**

Report No.: SZEM180700671006

Page: 7 of 9

**4.4 Deviation from Standards**

None.

**4.5 Abnormalities from Standard Conditions**

None.

**4.6 Other Information Requested by the Customer**

None.



## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.





**SGS-CSTC Standards Technical Services Co., Ltd  
Shenzhen Branch.**

Report No.: SZEM180700671006  
Page: 9 of 9

**4.1.3 EUT RF Exposure Evaluation**

**For 2.4GHz**

Antenna 1 Gain: 2dBi

Antenna 2 Gain: 2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.59 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Lowest	2417	-10.4	0.09	0.00003	1.0	PASS

Note: Refer to report No. SZEM180700671002 for EUT test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

**For 5GHz**

Antenna 1 Gain: 2dBi

Antenna 2 Gain: 2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.59 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
Lowest	5745	12.75	18.84	0.006	1.0	PASS

Note: Refer to report No. SZEM180700671004 for EUT test Max Conducted Peak Output Power value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

So, Simultaneous transmission SAR test is not required, because the Max. sum of the MPE ratios is  $0.00003+0.006=0.00603<1$ .

- End of the Report -