

4 FCC §1.1310, § 2.1091- Maximum Permissible Exposure (MPE)

4.1 Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

4.2 RF Exposure Evaluation Result

MPE evaluation:

Mode	Frequency Range (MHz)	Antenna Gain		Target Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
GSM 850	824-849	4.07	2.553	22.5	177.8	20	0.0903	0.55
PCS 1900	1850-1910	5.44	3.499	20	100.0	20	0.0696	1
WCDMA Band V	824-849	4.07	2.553	23	199.5	20	0.1013	0.55
WCDMA Band II	1850-1910	5.44	3.499	23	199.5	20	0.1389	1
BLE	2402-2480	0.5	1.122	-1	0.794	20	0.0002	1

*Due to GSM not have GPRS and EDGE, so only one Averaging Time and the power calculate as below
 GSM 850: $31.5 - 9 = 22.5$ (dBm) and PCS 1900 = $29 - 9 = 20$ (dBm)

The BLE and WCDMA Band V can transmit simultaneously:

$$= S_{BLE}/S_{limit-BLE} + S_{WCDMA BAND V}/S_{limit-WCDMA BAND V} = 0.0002/1 + 0.1013/0.55 = 0.1844 < 1.0$$

Result: MPE evaluation meet 20 cm the requirement of standard.