

# FCC RF EXPOSURE EVALUATION REPORT

**Product Name:** Smart Thermostat  
**Trade Mark:** Hailin  
**Model No.:** BluStat  
**Add. Model No.:** N/A  
**Report Number:** 200303008RFC-2  
**Test Standards:** FCC 47 CFR Part 1 Subpart I  
**FCC ID:** 2AJ5K-BLUSTAT  
**Test Result:** PASS  
**Date of Issue:** June 17, 2020

Prepared for:

**Beijing Hailin Energy Saving Technology Inc**  
**Huilongguan International Information Industry Base, Changping**  
**District, Beijing,China**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F, Block A, Building 6, Baoneng Science and Technology Park,**  
**Qingxiang Road No.1, Longhua New District, Shenzhen, China**  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**


Prepared by: \_\_\_\_\_

*Tom*  
 Tony Kang  
 Project Engineer

Reviewed by: \_\_\_\_\_

*Kevin Liang*  
 Kevin Liang  
 Assistant Manager

Approved by: \_\_\_\_\_



Technical Director

Date: \_\_\_\_\_

June 17, 2020

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

**Version**

Version No.	Date	Description
V1.0	March 27, 2020	Original
V1.1	June 17, 2020	1. FCC ID change from 2AJ5K-BluStat to 2AJ5K-BLUSTAT 2. Update applicant information 3. Add MPE assess distance on page 8

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)<http://www.uttlab.com>UTTR-RF-FCCPART1-V1.0

## CONTENTS

<b>1. GENERAL INFORMATION</b>	<b>4</b>
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
1.4 OTHER INFORMATION	5
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	5
1.6 TEST LOCATION	5
1.7 TEST FACILITY	6
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
<b>2. EQUIPMENT LIST</b>	<b>6</b>
<b>3. MPE EVALUATION</b>	<b>7</b>
3.1 REFERENCE DOCUMENTS FOR EVALUATION	7
3.2 MPE COMPLIANCE REQUIREMENT	7
3.2.1 LIMITS	7
3.2.2 TEST PROCEDURE	7
3.3 MPE CALCULATION METHOD	7
3.4 MPE CALCULATION RESULTS	7
3.4.1 FOR WLAN	8
3.4.2 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	8
<b>APPENDIX 1 PHOTOS OF TEST SETUP</b>	<b>9</b>
<b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b>	<b>9</b>

## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

<b>Applicant:</b>	Beijing Hailin Energy Saving Technology Inc
<b>Address of Applicant:</b>	Huilongguan International Information Industry Base, Changping District, Beijing, China
<b>Manufacturer:</b>	Beijing Hailin Energy Saving Technology Inc
<b>Address of Manufacturer:</b>	Huilongguan International Information Industry Base, Changping District, Beijing, China

### 1.2 EUT INFORMATION

<b>Product Name:</b>	Smart Thermostat
<b>Model No.:</b>	BluStat
<b>Add. Model No.:</b>	N/A
<b>Trade Mark:</b>	Hailin
<b>DUT Stage:</b>	Production Unit
<b>Rated Voltage:</b>	AC 24V
<b>Classification of digital devices:</b>	Class B
<b>Highest Internal Frequency:</b>	2.462 GHz
<b>Sample Received Date:</b>	March 10, 2020
<b>Sample Tested Date:</b>	March 10, 2020 to March 27, 2020

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For 2.4 GHz ISM Band of Wi-Fi	
Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7
Number of Channels:	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20: 11
Channel Separation:	5 MHz
Antenna Type:	Integral Antenna
Antenna Gain:	2 dBi
Maximum Peak Power:	IEEE 802.11b: 16.62 dBm IEEE 802.11g: 19.66 dBm IEEE 802.11n-HT20: 18.59 dBm

### 1.4 OTHER INFORMATION

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11b	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz

### 1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

**FCC 47 CFR Part 1 Subpart I**

All test items have been performed and recorded as per the above standards

### 1.6 TEST LOCATION

All tests were performed at:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109  
Telephone: +86 (0) 755 2823 0888

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**



Fax: +86 (0) 755 2823 0886

---

## 1.7 TEST FACILITY

---

The test facility is recognized, certified, or accredited by the following organizations:

**CNAS-Lab Code: L9069**

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

**A2LA-Lab Certificate No.: 4312.01**

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**ISED Wireless Device Testing Laboratories**

CAB identifier: CN0032

**FCC Accredited Lab.**

Designation Number: CN1194

Test Firm Registration Number: 259480

---

## 1.8 DEVIATION FROM STANDARDS

None.

## 1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

## 1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 2. EQUIPMENT LIST

Please refer to the RF test report.

### 3. MPE EVALUATION

#### 3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES

#### 3.2 MPE COMPLIANCE REQUIREMENT

##### 3.2.1 Limits

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

##### Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

##### Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

**Note:** f = frequency in MHz; \* = Plane-wave equivalents power density.

##### 3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

#### 3.3 MPE CALCULATION METHOD

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

#### 3.4 MPE CALCULATION RESULTS

#### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.0

**Note:** For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

### 3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n and

#### 3.4.1.1 Antenna Type:

Chain 0: Integral Antenna

#### 3.4.1.2 Antenna Gain:

Chain 0: 2412MHz to 2462 MHz: 2 dBi

#### 3.4.1.3 Results for WLAN

Operating Mode	Freq.	Declared maximum conducted average output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
	(MHz)	(dBm)		(dBi)	(dBm)	(mW)	(mw/cm <sup>2</sup> )	
IEEE 802.11b	2412	13	2	2	17	50.1187	1	0.01
	2437	13	2	2	17	50.1187	1	0.01
	2462	13	2	2	17	50.1187	1	0.01
IEEE 802.11g	2412	9	2	2	13	19.9526	1	0.004
	2437	9	2	2	13	19.9526	1	0.004
	2462	9	2	2	13	19.9526	1	0.004
IEEE 802.11n-HT20	2412	9	2	2	13	19.9526	1	0.004
	2437	9	2	2	13	19.9526	1	0.004
	2462	9	2	2	13	19.9526	1	0.004

Remark: The MPE assessed distance was used 20cm

### 3.4.2 Simultaneous Multi-band Transmission MPE Analysis

N/A



## APPENDIX 1 PHOTOS OF TEST SETUP

N/A

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---