



← 100 mm →

↑ 60 mm ↓

Rear of Unit

| PIN | DEFINITION A PART | PIN | DEFINITION B PART |
|-----|--------------------|-----|-----------------------------|
| 1 | NC | 1 | Rear R+ Purple |
| 2 | NC | 2 | Rear R- Purple/Black Stripe |
| 3 | NC | 3 | Front R+ Grey |
| 4 | Perm. +12V Yellow | 4 | Front R- Grey/Black Stripe |
| 5 | Auto Antenna* Blue | 5 | Front L+ White |
| 6 | Illumination | 6 | Front L- White/Black Stripe |
| 7 | ACC Red | 7 | Rear L+ Green |
| 8 | GND Black | 8 | Rear L- Green/Black Stripe |

| Rear of Unit | | | | | |
|--------------|--------|-----|---|--------|-------|
| 1 | Rear R | Red | 2 | Rear L | White |

P/N:1270720014800

Model:Colombo ML110 BT

Warnings:
 Warranty void if this unit is damaged due to misuse or unauthorized service attempting.
 Before making any electrical connections disconnect the vehicle battery's negative terminal and carefully read the unit's Owner's Manual.
 Connect each pair of speaker leads only to a single pair of speakers (or speaker system) that has an impedance of at least 4 ohms, as well as 50-watt power handling capability. Never allow the uninsulated part of any speaker leads to touch a metal part of the vehicle.
 Connect speaker leads to input of external amplifiers ONLY if indicated in amplifier's manual, otherwise this unit's internal amplifier will be damaged.

This product was produced using lead free technology. Help keep the world clean! Dispose properly!

USB Output: 5V \approx 0.5A max

12V \ominus GROUND \approx 15A max

Made in China

FCC ID: 2AJ8C-COLOMBOML110

FCC STATEMENT
 This device complies with Part 15 of the FCC Rules.Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and
 (2) This device must accept any interference received, including interference that may cause undesired operation.