

FCC - TEST REPORTReport Number : **60.792.18.015.01R01** Date of Issue : November 16, 2018Model : **HG04705-US-TX**Product Type : **WIRELESS WEATHER STATION**Applicant : Lidl US Trading, LLCAddress : 3500 South Clark Street, Arlington, VA 22202, USAProduction Facility : PUTIAN DIOR INDUSTRIAL CO., LTD.Address : Linan Industrial Area, Xianyou County, Putian, Fujian, ChinaTest Result : **Positive** **Negative**Total pages
including
Appendices : 18

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval

1 Table of Contents

1 Table of Contents.....	2
2 Description of Equipment Under Test	3
3 Summary of Test Standards	4
4 Details about the Test Laboratory	5
4.1 Test Equipment Site List	6
4.2 Measurement System Uncertainty	7
5 Summary of Test Results.....	8
6 General Remarks	9
7 Emission Test Results	10
7.1 Spurious Radiated Emission	10
7.2 20dB Bandwidth.....	14
7.3 Transmission Time.....	15
8 Appendix A - General Product Information	17

2 Description of Equipment Under Test

Description of the Equipment Under Test

Product:	WIRELESS WEATHER STATION
Model no.:	HG04705-US-TX
FCC ID:	2AJ9O-HG4705TX
Rating:	3 VDC (2 x AA battery)
Frequency:	433.92MHz
Antenna gain:	0 dBi
Number of operated channel:	1
Modulation:	FSK



3 Summary of Test Standards

Test Standards

FCC Part 15 Subpart C 10-1-17 Edition Federal Communications Commission, PART 15 — Radio Frequency Devices, Subpart C — Unintentional Radiators

4 Details about the Test Laboratory

Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13 Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Shenzhen 518052, P.R.China
FCC Registration Number: 514049

Emission Tests	
Test Item	Test Site
FCC Part 15 Subpart C	
FCC Title 47 Part 15.205, 15.209 & 15.231(e) Radiated Emission	Site1
FCC Title 47 Part 15.207 Conduct Emission	NIL
FCC Title 47 Part 15.231(c) 20dB Bandwidth	Site 1
FCC Title 47 Part 15.247(e) Transmission Time	Site 1

4.1 Test Equipment Site List

Radiated emission Test – Site 1

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2019-7-6
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2019-6-28
Horn Antenna	Rohde & Schwarz	HF907	102294	2019-6-28
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2019-7-6
Signal Generator	Rohde & Schwarz	SMY01	839369/005	2019-7-6
Attenuator	Agilent	8491A	MY39264334	2019-7-6
3m Semi-anechoic chamber	TDK	9X6X6	----	2020-7-7
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

20dB Bandwidth, Transmission Time – Site 1

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	101030	2019-7-6

4.2 Measurement System Uncertainty

Measurement System Uncertainty Emissions

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.54dB
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-25000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted RF test	2.04dB

5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
FCC Title 47 Part 15.205, 15.209 & 15.231(e) Radiated Emission	10-13	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
FCC Title 47 Part 15.207 Conduct Emission (1)	NIL	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FCC Title 47 Part 15.231(c) 20dB Bandwidth	14	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
FCC Title 47 Part 15.247(e) Transmission Time	15	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark:

- 1) These requirements do not apply for equipment which employ battery power for operation and which do not operate from the AC power lines.

6 General Remarks

Remarks

All mode has been tested, only worst case has shown.

SUMMARY:

- All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

- The Equipment Under Test

- **Fulfills** the general approval requirements.


- **Does not** fulfill the general approval requirements.

Sample Received Date: November 1, 2018

Testing Start Date: November 2, 2018


Testing End Date: November 12, 2018

Reviewed by:



Hosea CHAN
EMC Project Engineer

Prepared by:



Eric LI
EMC Senior Project Engineer

7 Emission Test Results

7.1 Spurious Radiated Emission

EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Horizontal
 Comment: 3 VDC
 Remark: 9kHz to 5GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
216.940	20.96	46.00	-25.04	Peak
433.920	57.94	92.87	-34.93	Peak
867.918	36.76	72.87	-36.11	Peak
2603.500	43.28	74.00	-30.72	Peak
3037.500	44.98	74.00	-29.02	Peak
3471.500	46.51	74.00	-27.49	Peak

Duty cycle factor=-11.21
 Average value = Peak value + Duty cycle factor

Frequency MHz	PK Result @3m dB μ V/m	Duty Cycle Factor dB	AV Result @3m dB μ V/m	Limit dB μ V/m	Margin dB
216.940	20.96	/	/	46	-25.04
433.951	57.94	-11.21	46.73	72.87	-26.14
867.918	36.76	-11.21	25.55	52.87	-27.32
2603.500	43.28	-11.21	32.07	54	-21.93
3037.500	44.98	-11.21	33.77	54	-20.23
3471.500	46.51	-11.21	35.30	54	-18.70

Spurious Radiated Emission

EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Vertical
 Comment: 3 VDC
 Remark: 9kHz to 5GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency MHz	Result dBµV/m	Limit dBµV/m	Margin dB	Detector
216.940	31.77	46	-14.23	Peak
325.418	30.03	46	-15.97	Peak
433.920	71.53	92.87	-21.34	Peak
867.864	45.32	72.87	-27.55	Peak
2603.625	44.48	74	-29.52	Peak
3037.500	52.06	74	-21.94	Peak
3471.500	46.16	74	-27.84	Peak

Duty cycle factor=-11.21
 Average value = Peak value + Duty cycle factor

Frequency MHz	PK Result @3m dBµV/m	Duty Cycle Factor dB	AV Result @3m dBµV/m	Limit dBµV/m	Margin dB
216.940	31.77	/	/	46	-14.23
325.418	30.03	/	/	46	-15.97
433.920	71.53	-11.21	60.32	72.87	-12.55
867.864	45.32	-11.21	34.11	52.87	-18.76
2603.625	44.48	-11.21	33.27	54	-20.73
3037.500	52.06	-11.21	40.85	54	-13.15
3471.500	46.16	-11.21	34.95	54	-19.05


Spurious Radiated Emission

EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Vertical
 Comment: 3 VDC
 Remark: 9kHz to 5GHz


Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Duct Cycle Factor Calculation

a. Transmission period



b. Duration = 847.8ms




Spurious Radiated Emission


EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Vertical
 Comment: 3 VDC
 Remark: 9kHz to 5GHz

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

c. Pulse number in 100ms



d. Pulse width=509.57 μs




Calculation:
 Max. allowed $T_p=100\text{ms}$
 Number of pulses in 100ms=54
 Pulse width=509.57 μs
 $T_{on} = \text{Pulse width} * \text{Number of pulses in 100ms} = 27.5 \text{ ms}$
 Duty cycle factor= $20 * \log(T_{on}/T_p) = -11.2$

7.2 20dB Bandwidth

EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.231(c) 20dB Bandwidth
 Comment: 3 VDC

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed



Date: 12.NOV.2018 14:48:22

Bandwidth	Measured Value	Limit
20dB bandwidth	169.30 kHz	<= 1084.8 kHz
Limit=0.25%*Center Frequency=0.25%*433.92MHz=1084.8kHz		

7.3 Transmission Time

EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.231(e)
 Comment: 3 VDC

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency	Duration of each transmission	Limit	Silent period	Limit
433.92MHz	847.8ms	< 1s	56.25s	25.4s


Note: Silent period limit is 30 times the duration of the transmission but in no case less than 10 seconds
 Silent period= Transmitting period - Duration of each transmission
 = 57.101-0.8478 s
 = 56.25 s

Transmission Time

EUT: HG04705-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.231(e)
 Comment: 3 VDC


Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Duration of each transmission



Date: 12.NOV.2018 14:27:43

Transmitting period



Date: 12.NOV.2018 14:26:29

8 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT is 433.92MHz, the test separation distance is $\leq 5\text{mm}$ & $\leq 20\text{mm}$.

(Manufacturer specified the separation distance is: 20mm)

Step a.1)

>> Numeric threshold, $\text{mW} / 5 \text{ mm} * \sqrt{0.43392\text{GHz}} \leq 3.0$
Numeric threshold \leq **22.771mW**

Step a.2)


>> Numeric threshold, $\text{mW} / 20 \text{ mm} * \sqrt{0.43392\text{GHz}} \leq 3.0$
Numeric threshold \leq **91.084mW**

>> The power of EUT measured is: $-26.52\text{dBm} = 0.002\text{mW}$
Which is smaller than the Numeric threshold.
Therefore, the device is exempt from stand-alone SAR test requirements.

Appendix A - Conducted power

EUT: HG04705-US-TX
Op Condition: Operated, TX Mode
Comment: 3 VDC
Remark: NA

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed



Date: 12.NOV.2018 16:51:35