



No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170400319102

Page: 1 of 7

SAR Evaluation Report

Application No.: SZEM1704003191CR
Applicant: Lidl US Trading, LLC
Manufacturer: ATI Electronics (Shenzhen) Co.,LTD
Factory: ATI Electronics (Shenzhen) Co.,LTD
EUT Name: Sports In-Ear with Bluetooth True Wireless Stereo
Model No.: SIBT 16 A1
Trade Mark: Silvercrest
FCC ID: 2AJ9O-SIBT16A1
Standards: 47 CFR Part 1.1307 (2016)
47 CFR Part 2.1093 (2016)
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2017-04-13
Date of Test: 2017-04-17 to 2017-05-08
Date of Issue: 2017-05-10

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-05-10		Original

Authorized for issue by:			
Tested By			2017-05-10
	<hr/>		<hr/>
	Peter Geng /Project Engineer		Date
Checked By			2017-05-10
	<hr/>		<hr/>
	Eric Fu /Reviewer		Date



3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST LOCATION	5
4.4 TEST FACILITY	5
4.5 DEVIATION FROM STANDARDS	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 <i>Standard Requirement</i>	6
5.1.2 <i>Limits</i>	6
5.1.3 <i>EUT RF Exposure</i>	7



4 General Information

4.1 Client Information

Applicant:	Lidl US Trading, LLC
Address of Applicant:	3500 S. Clark Street, Arlington, Virginia 22202, United States
Manufacturer:	ATI Electronics (Shenzhen) Co.,LTD
Address of Manufacturer:	Floor 2, Block A, Floor 1-2, Block B, West of 4F complex building, no. 6 Plant, Tongfuyu Industrial Park, Fukeng, Guanlan Avenue, Longhua District, Shenzhen, 518810, China.
Factory:	ATI Electronics (Shenzhen) Co.,LTD
Address of Factory:	Floor 2, Block A, Floor 1-2, Block B, West of 4F complex building, no. 6 Plant, Tongfuyu Industrial Park, Fukeng, Guanlan Avenue, Longhua District, Shenzhen, 518810, China.

4.2 General Description of EUT

Product Name:	Sports In-Ear with Bluetooth True Wireless Stereo
Model No.:	SIBT 16 A1
Trade Mark:	Silvercrest
BT Version:	4.1+EDR
Operation Frequency:	2402MHz~2480MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Antenna Gain:	0dBi
Antenna Type:	Integral antenna
Power Supply	Left earbud: DC 3.7V 40mAh rechargeable battery; Right earbud: DC 3.7V 40mAh rechargeable battery both earbuds charged by a charging docking which has a DC 3.7V 380mAh rechargeable battery and charged from USB port
Cable:	USB charging line: 80cm, unshielded



4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion



5.1.3 EUT RF Exposure

For Left earbud

The Max Conducted Peak Output Power is 3.49dBm in highest channel(2.402GHz);

3.49dBm logarithmic terms convert to numeric result is nearly 2.23mW

According to the formula. calculate the test exclusion thresholds:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})}$$

General RF Exposure = $(2.23\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.691$ ①

SAR requirement:

S= 3.0 ② ;

① < ②.

So the SAR report is not required.

For Right earbud

The Max Conducted Peak Output Power is 3.76dBm in highest channel(2.402GHz);

3.76dBm logarithmic terms convert to numeric result is nearly 2.38mW

According to the formula. calculate the test exclusion thresholds:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})}$$

General RF Exposure = $(2.38\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.738$ ①

SAR requirement:

S= 3.0 ② ;

① < ②.

So the SAR report is not required.

For Both Bluetooth(Left earbud and Right earbud) transmit simultaneously:

According to the formula

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})/7.5} \text{ W/kg}$$

For Left earbud:

SAR test exclusion = $(2.23\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}/7.5} = 0.092 \text{ W/kg}$

For Right earbud:

SAR test exclusion = $(2.38\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}/7.5} = 0.098 \text{ W/kg}$

The total SAR test exclusion = $0.190 \text{ W/kg} < 1.6 \text{ W/kg}$

So the SAR report is not required.