

FCC Radio Test Report

FCC ID: 2AJ9Z-X11

Original Grant

Report No. : TB-FCC156188

Applicant : EMATIC LIMITED

Equipment Under Test (EUT)

EUT Name : ROCK X11

Model No. : ROCK X11

Series Model No. : N/A

Brand Name : EXTREM

Receipt Date : 2017-06-23

Test Date : 2017-06-24 to 2017-07-09

Issue Date : 2017-07-10

Standards : FCC Part 15: 2016, Subpart C(15.247)

Test Method : ANSI C63.10: 2013

Conclusions : PASS


In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC requirements

Test/Witness Engineer

: *DAN SU*

Approved& Authorized

: *Layla*



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

TB-RF-074-1.0

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	7
1.8 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	12
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	20
5.5 Test Data.....	20
6. RESTRICTED BANDS REQUIREMENT	41
6.1 Test Standard and Limit.....	41
6.2 Test Setup.....	41
6.3 Test Procedure.....	42
6.4 EUT Operating Condition	42
6.5 Test Data.....	42
7. NUMBER OF HOPPING CHANNEL	61
7.1 Test Standard and Limit.....	61
7.2 Test Setup.....	61
7.3 Test Procedure.....	61
7.4 EUT Operating Condition	61
7.5 Test Data.....	61
8. AVERAGE TIME OF OCCUPANCY.....	64
8.1 Test Standard and Limit.....	64
8.2 Test Setup.....	64

8.3 Test Procedure.....	64
8.4 EUT Operating Condition	64
8.5 Test Data.....	65
9. CHANNEL SEPARATION AND BANDWIDTH TEST	71
9.1 Test Standard and Limit.....	71
9.2 Test Setup.....	71
9.3 Test Procedure.....	71
9.4 EUT Operating Condition	71
9.5 Test Data.....	72
10. PEAK OUTPUT POWER TEST.....	84
10.1 Test Standard and Limit	84
10.2 Test Setup.....	84
10.3 Test Procedure.....	84
10.4 EUT Operating Condition	84
10.5 Test Data.....	85
11. ANTENNA REQUIREMENT.....	91
11.1 Standard Requirement.....	91
11.2 Antenna Connected Construction	91
11.3 Result.....	91

1. General Information about EUT

1.1 Client Information

Applicant : EMATIC LIMITED
Address : Unit 17, 9/F Tower A, New Mandarin Plaza NO, 14 Science Museum Rd, TST, Hong Kong, China
Manufacturer : EMATIC LIMITED
Address : Unit 17, 9/F Tower A, New Mandarin Plaza NO, 14 Science Museum Rd, TST, Hong Kong, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:		ROCK X11		
Models No.	:		ROCK X11		
Model Difference	:		N/A		
Product Description	Operation Frequency:	Bluetooth 4.1(EDR): 2402~2480 MHz			
	Number of Channel:	Bluetooth: 79 Channels See Note 2			
	Max Peak Output Power:	Bluetooth: 6.710 dBm(GFSK)			
	Antenna Gain:	1.15 dBi PIFA Antenna			
	Modulation Type:	GFSK (1 Mbps) π/4-DQPSK (2 Mbps) 8-DPSK (3 Mbps)			
Power Supply	: DC power supplied by AC/DC Adapter. DC Voltage supplied from Li-ion battery.				
Power Rating	: AC/DC Adapter(A138A-120150U-US2): Input: AC 100~240V 50/60Hz, 0.5A. Output: 5V/2.5A&9V/2A&12V/1.5A. DC 3.8V from 10000mA Li-ion battery.				
Connecting I/O Port(S)	: Please refer to the User's Manual				

Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) Channel List:


Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458

03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

(3) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

Charging+TX Mode



1.4 Description of Support Units

The EUT has been test as an independent unit.

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Charging + TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode($\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode($\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

TX Mode: GFSK (1 Mbps)
TX Mode: $\pi/4$ -DQPSK (2 Mbps)
TX Mode:8-DPSK (3 Mbps)

- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	*###3646633#*#*		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(c)& 15.209	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	99%OBW GFSK:861.2499kHz $\pi/4$ -DQPSK: 1165.60kHz 8-DPSK: 1168.80kHz

Note: N/A is an abbreviation for Not Applicable.

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.25, 2017	Mar. 24, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.24, 2017	Mar. 23, 2018
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.24, 2017	Mar. 23, 2018
Loop Antenna	Laplace instrument	RF300	0701	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.25, 2017	Mar. 24, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.24, 2017	Mar. 23, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 22, 2016	Jul. 21, 2017
Power Sensor	Anritsu	ML2411B	25406005	Jul. 22, 2016	Jul. 21, 2017

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard
FCC Part 15.207

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8m from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

4.4 EUT Operating Mode

Please refer to the description of test mode.


4.5 Test Data

Test data please refer the following pages.

EUT:	ROCK X11	Model Name :	ROCK X11				
Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60 Hz						
Terminal:	Line						
Test Mode:	Charging +TX Mode						
Remark:	Only worse case is reported						
<p>80.0 dBuV</p> <p>QP: —</p> <p>AVG: —</p> <p>peak</p> <p>Avg</p> <p>0.150 0.5 5 30.000 [MHz]</p>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV	dB	Detector
1		0.2740	28.14	9.59	37.73	60.99	-23.26
2		0.2740	12.44	9.59	22.03	50.99	-28.96
3 *		0.3620	26.57	9.60	36.17	58.68	-22.51
4		0.3620	12.73	9.60	22.33	48.68	-26.35
5		2.5220	22.20	9.63	31.83	56.00	-24.17
6		2.5220	13.17	9.63	22.80	46.00	-23.20
7		5.5500	19.44	9.77	29.21	60.00	-30.79
8		5.5500	12.04	9.77	21.81	50.00	-28.19
9		8.0580	20.30	9.93	30.23	60.00	-29.77
10		8.0580	13.10	9.93	23.03	50.00	-26.97
11		10.2580	19.88	10.07	29.95	60.00	-30.05
12		10.2580	12.76	10.07	22.83	50.00	-27.17


Emission Level= Read Level+ Correct Factor

EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Neutral		
Test Mode:	Charging +TX Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.2940	28.08	9.57	37.65	60.41	-22.76	QP
2		0.2940	16.62	9.57	26.19	50.41	-24.22	AVG
3		1.1220	24.20	9.59	33.79	56.00	-22.21	QP
4	*	1.1220	15.67	9.59	25.26	46.00	-20.74	AVG
5		2.2900	21.80	9.63	31.43	56.00	-24.57	QP
6		2.2900	14.58	9.63	24.21	46.00	-21.79	AVG
7		5.2580	27.45	9.96	37.41	60.00	-22.59	QP
8		5.2580	17.88	9.96	27.84	50.00	-22.16	AVG
9		7.2420	28.48	10.29	38.77	60.00	-21.23	QP
10		7.2420	18.24	10.29	28.53	50.00	-21.47	AVG
11		12.7739	27.82	10.45	38.27	60.00	-21.73	QP
12		12.7739	18.12	10.45	28.57	50.00	-21.43	AVG

Emission Level= Read Level+ Correct Factor

EUT:	ROCK X11	Model Name :	ROCK X11					
Temperature:	25°C	Relative Humidity:	55%					
Test Voltage:	AC 240V/60 Hz							
Terminal:	Line							
Test Mode:	Charging +TX Mode							
Remark:	Only worse case is reported							
								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.3060	30.19	9.57	39.76	60.08	-20.32	QP
2		0.3060	19.44	9.57	29.01	50.08	-21.07	AVG
3		0.4420	28.87	9.58	38.45	57.02	-18.57	QP
4		0.4420	18.51	9.58	28.09	47.02	-18.93	AVG
5 *		4.7420	29.52	9.86	39.38	56.00	-16.62	QP
6		4.7420	18.39	9.86	28.25	46.00	-17.75	AVG
7		5.2860	31.10	9.96	41.06	60.00	-18.94	QP
8		5.2860	20.13	9.96	30.09	50.00	-19.91	AVG
9		6.6220	32.04	10.22	42.26	60.00	-17.74	QP
10		6.6220	20.64	10.22	30.86	50.00	-19.14	AVG
11		11.1980	30.86	10.33	41.19	60.00	-18.81	QP
12		11.1980	20.42	10.33	30.75	50.00	-19.25	AVG

Emission Level= Read Level+ Correct Factor

EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 240V/60 Hz		
Terminal:	Neutral		
Test Mode:	Charging +TX Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV	dBuV	dB
1	*	0.4300	27.19	9.60	36.79	57.25	-20.46
2		0.4300	10.10	9.60	19.70	47.25	-27.55
3		1.1539	23.01	9.60	32.61	56.00	-23.39
4		1.1539	8.53	9.60	18.13	46.00	-27.87
5		1.8740	23.35	9.61	32.96	56.00	-23.04
6		1.8740	11.12	9.61	20.73	46.00	-25.27
7		6.6340	26.89	9.84	36.73	60.00	-23.27
8		6.6340	16.50	9.84	26.34	50.00	-23.66
9		9.1899	27.07	10.00	37.07	60.00	-22.93
10		9.1899	17.07	10.00	27.07	50.00	-22.93
11		11.7660	26.51	10.20	36.71	60.00	-23.29
12		11.7660	17.49	10.20	27.69	50.00	-22.31

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)


5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) The measuring distance of 0.8cm shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz


EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Over Detector
1		31.2893	41.85	-14.57	27.28	40.00	-12.72	peak
2		162.0414	50.35	-20.16	30.19	43.50	-13.31	peak
3		183.8439	55.92	-20.13	35.79	43.50	-7.71	peak
4	*	192.4185	57.17	-20.18	36.99	43.50	-6.51	peak
5		248.5518	46.99	-17.48	29.51	46.00	-16.49	peak
6		323.3204	45.84	-15.40	30.44	46.00	-15.56	peak


*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor




Above 1GHz(Only worse case is reported)

EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1	*	4803.685	30.19	13.44	43.63	54.00	-10.37
2		4805.157	44.39	13.45	57.84	74.00	-16.16

Emission Level= Read Level+ Correct Factor






EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2441MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		4881.433	43.98	13.90	57.88	74.00	-16.12 peak
2	*	4882.602	30.72	13.90	44.62	54.00	-9.38 AVG

Emission Level= Read Level+ Correct Factor




EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		4960.878	44.08	14.36	58.44	74.00	-15.56 peak
2	*	4961.365	30.82	14.38	45.20	54.00	-8.80 AVG


Emission Level= Read Level+ Correct Factor


EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX π /4-DQPSK Mode 2402MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1		4804.125	44.90	13.44	58.34	74.00	-15.66 peak
2	*	4805.345	30.67	13.45	44.12	54.00	-9.88 AVG


Emission Level= Read Level+ Correct Factor








EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX $\pi/4$ -DQPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1	*	4959.788	31.00	14.36	45.36	54.00	-8.64 AVG
2		4961.344	44.09	14.38	58.47	74.00	-15.53 peak


Emission Level= Read Level+ Correct Factor


EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX π /4-DQPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4959.548	44.42	14.36	58.78	74.00	-15.22 peak
2	*	4960.725	31.07	14.36	45.43	54.00	-8.57 AVG

Emission Level= Read Level+ Correct Factor












EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2480MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		4960.442	44.28	14.36	58.64	74.00	-15.36 peak
2	*	4961.326	30.84	14.38	45.22	54.00	-8.78 AVG

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.209


FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

Note: All restriction bands have been tested, only the worst case is reported.

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 1.5m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with AVG Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data


Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

(1) Radiation Test




EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	44.06	0.77	44.83	74.00	-29.17	peak
2		2390.000	31.86	0.77	32.63	54.00	-21.37	Avg
3	*	2402.000	81.99	0.82	82.81	Fundamental Frequency		Avg
4	X	2402.200	92.13	0.82	92.95	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor





EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX GFSK Mode 2480 MHz		
Remark:	Only worse case is reported		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor	Measure- ment dBuV/m	Limit dBuV/m	Over Detector
1	*	2479.800	87.61	1.15	88.76	Fundamental Frequency	AVG
2	X	2480.000	94.94	1.15	96.09	Fundamental Frequency	peak
3		2483.500	55.80	1.17	56.97	74.00	-17.03
4		2483.500	45.56	1.17	46.73	54.00	-7.27


Emission Level= Read Level+ Correct Factor














EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Ant. Pol.	Vertical		
Test Mode:	TX 8-DPSK Mode 2402MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	42.90	0.77	43.67	74.00	-30.33	peak
2		2390.000	31.96	0.77	32.73	54.00	-21.27	AVG
3	X	2402.100	98.98	0.82	99.80	Fundamental Frequency		peak
4	*	2402.100	85.93	0.82	86.75	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor









(2) Conducted Test





EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	GFSK Hopping Mode		
Remark:	Only worse case is reported		





EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX π /4-DQPSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		





EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	$\pi/4$ -DQPSK Hopping Mode		
Remark:	Only worse case is reported		



EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	TX 8-DPSK Mode 2402MHz/2480 MHz		
Remark:	Only worse case is reported		



EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode:	8-DPSK Hopping Mode		
Remark:	Only worse case is reported		




7. Number of Hopping Channel

7.1 Test Standard and Limit

- 6.1.1 Test Standard
FCC Part 15.247 (a)(1)
- 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

7.2 Test Setup



7.3 Test Procedure



- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.


7.4 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

7.5 Test Data

EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode		
Frequency Range	Test Mode	Quantity of Hopping Channel	Limit
2402MHz~2480MHz	GFSK	79	>15
	$\pi/4$ -DQPSK	79	
	8-DPSK	79	

GFSK Mode **$\pi/4$ -DQPSK Mode**




8. Average Time of Occupancy

8.1 Test Standard and Limit

- 8.1.1 Test Standard
FCC Part 15.247 (a)(1)
- 8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

8.2 Test Setup



8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

8.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / X) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$
$$\{\text{Period}\} = 0.4s * \{\text{Number of Hopping Frequency}\}$$

Note: X=2 or 4 or 6 (1DH1=2, 1DH3=4, 1DH5=6. 2DH1=2, 2DH3=4, 2DH5=6. 3DH1=2, 3DH3=4, 3DH5=6)

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

The EUT was set to the Hopping Mode by the Customer.


8.5 Test Data

EUT:	ROCK X11		Model Name :	ROCK X11		
Temperature:	25°C		Relative Humidity:	55%		
Test Voltage:	DC 3.8V					
Test Mode:	Hopping Mode (GFSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
1DH1	2441	0.420	134.40	31.60	400	PASS
1DH3	2441	1.715	272.00	31.60	400	PASS
1DH5	2441	2.9575	315.47	31.60	400	PASS

1DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79
1DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79
1DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79

GFSK Hopping Mode 1DH1

2441 MHz



Marker

Select Marker

1	2	3	4
---	---	---	---

Normal

Delta

Delta Pair (Tracking Ref)

Ref	Delta
-----	-------


Span Pair

Span	Center
------	--------

Off

More

1 of 2



EUT:	ROCK X11		Model Name :	ROCK X11					
Temperature:	25 °C		Relative Humidity:	55%					
Test Voltage:	DC 3.8V								
Test Mode:	Hopping Mode ($\pi/4$ -DQPSK)								
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result			
2DH1	2441	0.420	134.40	31.60	400	PASS			
2DH3	2441	1.6975	271.60	31.60	400	PASS			
2DH5	2441	2.9575	315.47	31.60	400	PASS			


2DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79


2DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79

2DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79

 $\pi/4$ -DQPSK Hopping Mode 2DH1

2441 MHz





EUT:	ROCK X11		Model Name :	ROCK X11					
Temperature:	25 °C		Relative Humidity:	55%					
Test Voltage:	DC 3.8V								
Test Mode:	Hopping Mode (8-DPSK)								
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result			
3DH1	2441	0.420	134.40	31.60	400	PASS			
3DH3	2441	1.7325	277.20	31.60	400	PASS			
3DH5	2441	2.9400	313.60	31.60	400	PASS			


2DH1 Total of Dwell= Pulse Time*(1600/2)*31.6/79


2DH3 Total of Dwell= Pulse Time*(1600/4)*31.6/79

2DH5 Total of Dwell= Pulse Time*(1600/6)*31.6/79

8-DPSK Hopping Mode 3DH1

2441 MHz





9. Channel Separation and Bandwidth Test

9.1 Test Standard and Limit


9.1.1 Test Standard

FCC Part 15.247

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	<=1 MHz (20dB bandwidth)	2400~2483.5
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

9.2 Test Setup




9.3 Test Procedure


- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Channel Separation: RBW=30 kHz, VBW=100 kHz.
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.


9.4 EUT Operating Condition


The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.


9.5 Test Data

















EUT:	ROCK X11	Model Name :	ROCK X11		
Temperature:	25°C	Relative Humidity:	55%		
Test Voltage:	DC 3.8V				
Test Mode:	Hopping Mode (GFSK)				
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)			
2402	1005.00	940.541			
2441	1005.00	937.779			
2480	1005.00	937.840			
GFSK Hopping Mode					
2402 MHz					
<p>Agilent</p> <p>Ref 20 dBm Atten 30 dB Mkr1 Δ 1.0050 MHz Peak Log 10 dB/Offst 1 dB -0.073 dB</p> <p>Marker Δ 1.005000 MHz -0.073 dB</p> <p>M1 S2 S3 LC AA</p> <p>Start 2.401 GHz #Res BW 100 kHz Stop 2.404 GHz #VBW 100 kHz #Sweep 7 ms (401 pts)</p>	<ul style="list-style-type: none">Peak SearchMeas ToolsNext PeakNext Pk RightNext Pk LeftMin SearchPk-Pk SearchMore 1 of 2				



EUT:	ROCK X11	Model Name :	ROCK X11
Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Test Mode:	Hopping Mode ($\pi/4$ -DQPSK)		
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)	
2402	1005.00	844.00	
2441	1005.00	836.67	
2480	1005.00	843.33	


 $\pi/4$ -DQPSK Hopping Mode**2402 MHz**



EUT:	ROCK X11	Model Name :	ROCK X11		
Temperature:	25°C	Relative Humidity:	55%		
Test Voltage:	DC 3.8V				
Test Mode:	Hopping Mode (8-DPSK)				
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)			
2402	1005.00	846.00			
2441	1005.00	851.33			
2480	1005.00	852.00			
8-DPSK Hopping Mode					
2402 MHz					
	<ul style="list-style-type: none">Peak SearchMeas ToolsNext PeakNext Pk RightNext Pk LeftMin SearchPk-Pk SearchMore 1 of 2				


8-DPSK Hopping Mode

2441 MHz



8-DPSK Hopping Mode

2480 MHz



10. Peak Output Power Test

10.1 Test Standard and Limit


10.1.1 Test Standard

FCC Part 15.247 (b) (1)

10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

10.2 Test Setup




10.3 Test Procedure


- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:
Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.
RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.


10.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.


10.5 Test Data










EUT:	ROCK X11	Model Name :	ROCK X11		
Temperature:	25°C	Relative Humidity:	55%		
Test Voltage:	DC 3.8V				
Test Mode:	TX Mode (8-DPSK)				
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)			
2402	6.130	21			
2441	5.809				
2480	5.318				
8-DPSK TX Mode					
2402 MHz					
					
					



11. Antenna Requirement

11.1 Standard Requirement

11.1.1 Standard

FCC Part 15.203

11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

11.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 1.15dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

11.3 Result

The EUT antenna is a PIFA Antenna. It complies with the standard requirement.

Antenna Type
<input type="checkbox"/> Permanent attached antenna
<input checked="" type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

-----END OF REPORT-----