



# RF Exposure Evaluation Report

**Equipment** : Araknis Networks 110-series Single-WAN Gigabit VPN Router with Wi-Fi

**Brand Name** : Araknis Networks

**Model No.** : AN-110-RT-2L1W-WIFI

**FCC ID** : 2AJAC-110WIFI

**Standard** : 47 CFR Part 2.1091

**Applicant** : Wirepath Home Systems. DBA SnapAV  
1800 Continental Blvd. Suite 200 Charlotte, NC  
28273 USA

**Manufacturer** : Wirepath Home Systems. DBA SnapAV  
1800 Continental Blvd. Suite 200 Charlotte, NC  
28273 USA

The product sample received on Jun. 02, 2017 and completely tested on Aug. 02, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091 and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Cliff Chang  
SPORTON INTERNATIONAL INC.





# TABLE OF CONTENTS

**1 GENERAL DESCRIPTION .....4**

1.1 EUT General Information .....4

1.2 Testing Location .....4

**2 MAXIMUM PERMISSIBLE EXPOSURE .....5**

2.1 Limit of Maximum Permissible Exposure .....5

2.2 MPE Calculation Method .....5

2.3 Calculated Result and Limit .....6

**PHOTOGRAPHS OF EUT V01**





# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)

Note:

The EUT can equip with external WWAN Dongle use.

The WWAN Dongle (FCC ID: QISE3372H-510) is for measurement only.

## 1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	3.67	27.32	30.99	31.5	1.41254	20	0.28115	1.00000
5.2G;D1D	6.51	24.26	30.77	31	1.25893	20	0.25058	1.00000
5.8G;D1D	6.51	24.99	31.50	32	1.58489	20	0.31546	1.00000

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz+WWAN Dongle (FCC ID: QISE3372H-510)

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
5.8G;D1D	6.51	24.99	31.50	32.00	1.58489	20	0.31546	1	0.31546
2.4G;G1D	3.67	27.32	30.99	31.50	1.41254	20	0.28115	1	0.28115
LTE(1909M)	3.36	29.15	32.51	33.00	1.99526	20	0.39714	1	0.39714
								Sum Ratio	0.99375
								Ratio Limit	1