



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
 Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
 Tel: +82-31-425-6200 / Fax: +82-31-424-0450
 www.kes.co.kr

Report No.:
 KES-RF-23T0039
 Page (46) of (84)


Mode: 802.11a_ANT 1
 Distance of measurement: 3 meter
 Channel: 64

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 398.82	45.81	Peak	H	-6.98	-	38.83	74.00	35.17
1 600.06	47.12	Peak	V	-6.03	-	41.09	74.00	32.91
6 660.92	40.95	Peak	V	8.69	-	49.64	68.23	18.59
6 894.91	38.90	Peak	H	9.26	-	48.16	68.23	20.07

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 351.32	42.04	Peak	H	7.01	-	49.05	74.00	24.95
5 352.41	41.34	Peak	V	7.01	-	48.35	74.00	25.65



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr


Mode: 802.11a_ANT 2
 Distance of measurement: 3 meter
 Channel: 52

- Spurious


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 393.50	49.17	Peak	H	-7.02	-	42.15	74.00	31.85
1 400.22	46.20	Peak	V	-6.97	-	39.23	74.00	34.77
1 597.40	49.83	Peak	H	-6.05	-	43.78	74.00	30.22
6 942.16	40.21	Peak	H	9.46	-	49.67	68.23	18.56
8 810.35	40.81	Peak	V	12.19	-	53.00	68.23	15.23

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4 692.12	41.39	Peak	H	4.64	-	46.03	74.00	27.97
4 742.68	40.22	Peak	V	4.87	-	45.09	74.00	28.91



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Report No.:
KES-RF-23T0039
Page (50) of (84)

Mode: 802.11a_ANT 2
Distance of measurement: 3 meter
Channel: 56

- **Spurious**

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 082.26	52.36	Peak	V	-9.43	-	42.93	74.00	31.07
1 324.91	45.73	Peak	H	-7.60	-	38.13	74.00	35.87
6 636.92	40.07	Peak	V	8.66	-	48.73	68.23	19.50
8 771.35	40.00	Peak	H	12.29	-	52.29	68.23	15.94

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
 Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
 Tel: +82-31-425-6200 / Fax: +82-31-424-0450
 www.kes.co.kr

Report No.:
 KES-RF-23T0039
 Page (52) of (84)


Mode: 802.11a_ANT 2
 Distance of measurement: 3 meter
 Channel: 64

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 134.29	55.70	Peak	V	-9.08	-	46.62	74.00	27.38
1 186.32	51.01	Peak	V	-8.74	-	42.27	74.00	31.73
1 504.75	47.45	Peak	H	-6.64	-	40.81	74.00	33.19
8 764.60	39.37	Peak	H	12.32	-	51.69	68.23	16.54
8 767.98	40.18	Peak	V	12.31	-	52.49	68.23	15.74

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
5 351.35	41.08	Peak	V	7.01	-	48.09	74.00	25.91
5 354.05	47.52	Peak	H	7.02	-	54.54	74.00	19.46
5 356.95	32.00	Average	H	7.03	-	39.03	54.00	14.97



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr


Mode: 802.11a_ANT 1
 Distance of measurement: 3 meter
 Channel: 100

- Spurious


Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1 050.39	44.73	Peak	H	-9.64	-	35.09	74.00	38.91
1 598.97	49.14	Peak	V	-6.04	-	43.10	74.00	30.90
6 938.41	40.13	Peak	V	9.44	-	49.57	74.00	24.43
10 998.03	40.82	Peak	H	16.06	-	56.88	74.00	17.12
11 002.91	29.58	Average	H	16.07	-	45.65	54.00	8.35

- Band edge

Frequency (MHz)	Level (dB μ V)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
5 469.36	44.04	Peak	V	7.01	-	51.05	68.23	17.18
5 469.96	47.75	Peak	H	7.01	-	54.76	68.23	13.47



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr



Note.

1. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact kes@kes.co.kr