

RF Exposure Evaluation Report

Product Name : Wireless module
Model No. : P5740-162
FCC ID : 2AJE7SMC-WEX07

Applicant : SMC Corporation

Address : 4-2-2, Kinunodai, Tsukubamirai-shi, Ibaraki-ken,, 300-2493 Japan

Date of Receipt : Apr. 29, 2021
Date of Declaration : Jul. 07, 2021
Report No. : 2140998R-E3082100013
Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Issued Date: Jul. 07, 2021

Report No.: 2140998R-E3082100013



Product Name	Wireless module	
Applicant	SMC Corporation	
Address	4-2-2, Kinunodai, Tsukubamirai-shi, Ibaraki-ken,, 300-2493 Japan	
Manufacturer	SMC Corporation	
Model No.	P5740-162	
FCC ID.	2AJE7SMC-WEX07	
Trade Name	SMC	
Applicable Standard	KDB 447498 D01 v06	<input checked="" type="checkbox"/> Minimum test separation distance \geq 20 cm <input type="checkbox"/> For low power devices
Test Result	Complied	

Documented By : Jinn Chen
 (Senior Adm. Specialist / Jinn Chen)

Tested By : wen Lee
 (Supervisor / Wen Lee)

Approved By : Tim Sung
 (Manager / Tim Sung)

Revision History

Report No.	Version	Description	Issued Date
2140998R-E3082100013	V1.0	Initial issue of report.	Jul. 07, 2021

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Wireless module
Trade Name	SMC
Model No.	P5740-162
FCC ID.	2AJE7SMC-WEX07
Frequency Range	2403MHz – 2481MHz
Channel Number	79
Type of Modulation	FHSS
Channel Control	Auto
Antenna Type	PCB Antenna / whip Antenna
Antenna Gain	Refer to the table “Antenna List”

1.2. Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	SMC	P5740-162	PCB Antenna	1.83 dBi for 2.4 GHz
2	SMC	P5740-164	whip Antenna	1.49 dBi for 2.4 GHz

2. RF Exposure Evaluation

2.1. Standard Applicable

According to KDB 447498 D01 (7.1), A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits.

2.2. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3. Test Result of RF Exposure Evaluation

Product : Wireless module
Test Item : RF Exposure Evaluation

Wireless 2.4G Peak Gain: 1.83dBi

Channel	Frequency	Conducted Peak Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mWc/m ²)	Pass/Fail
01	2403	13.58	22.803	0.0069	1	Pass

Note: The conducted output power is refer to report No.: 2140998R-E3032110109 from the DEKRA.