



**FCC Part 1 Subpart I
FCC Part 2 Subpart J
RSS 102 ISSUE 6**

RF EXPOSURE REPORT

FOR

HOUSEHOLD FOOD PREPARING MACHINE

MODEL NUMBER: VM0230, VM0231, VM0232, VM0233, VM0234

FCC ID: 2AJEHVM0230

IC: 21814-VM0230

REPORT NUMBER: R15203365-E2

ISSUE DATE: 2024-08-07

**Prepared for
VITA-MIX CORPORATION
8615 USHER RD.
CLEVELAND, OH 44138, UNITED STATES**

**Prepared by
UL LLC
12 LABORATORY DR.
RESEARCH TRIANGLE PARK, NC 27709 USA
TEL: (919) 549-1400**



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2024-04-30	Initial Issue	Charles Moody
V2	2024-08-07	Revised to Include RSS-102 and Updated Calculation	Charles Moody

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION	5
5. DECISION RULES AND MEASUREMENT UNCERTAINTY	5
5.1. <i>METROLOGICAL TRACEABILITY</i>	5
5.2. <i>DECISION RULES</i>	5
6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS)	6
6.1. <i>FCC RULES</i>	6
6.2. <i>ISED RULES</i>	7
6.3. <i>EQUATIONS</i>	8
7. RF EXPOSURE RESULTS.....	10

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Vita-Mix Corporation
8615 Usher Rd.
Cleveland, OH 44138, United States

EUT DESCRIPTION: Household Food Preparing Machine

MODEL: VM0230, VM0231, VM2032, VM0233, VM0234

SERIAL NUMBER: Non-Serialized

SAMPLE RECEIVED DATE: 2024-03-26, 2024-04-19

DATE TESTED: 2024-04-09 TO 2024-04-22

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies
RSS 102 ISSUE 6	Complies


UL LLC. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC. will constitute fraud and shall nullify the document.

Approved & Released For
UL LLC By:

Prepared By:



Michael Antola
Staff Engineer
Consumer, Medical and IT Segment
UL LLC

Charles Moody
Electrical Engineer
Consumer, Medical and IT Segment
UL LLC

2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 1.1310, 2.1091, 2.1093, KDB 447498 D01 v06, KDB 447498 D03 V01, IEEE Std C95.1-2005, and IEEE Std C95.3-2002, IC Safety Code 6 and RSS 102 Issue 6.

3. REFERENCES

Maximum circuit input power is excerpted from client documentation.

4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification # 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input type="checkbox"/>	Building: 12 Laboratory Dr RTP, NC 27709, U.S.A	US0067	2180C	825374
<input checked="" type="checkbox"/>	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A		27265	

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.2. DECISION RULES

For all tests where the applicable $U_{LAB} \leq U_{MAX}$ the Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2, where $U_{MAX} = 30\%$ (0.3) for RF Exposure evaluations. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

For all tests where the applicable $U_{LAB} > U_{MAX}$ the Decision Rule is based on Guarded Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.3.2, with a guard band equal to $(U_{LAB} - U_{MAX})$, where $U_{MAX} = 30\%$ (0.3) for RF Exposure evaluations. (Test results are adjusted by the value of the guard band to determine conformity with a specified requirement.)

6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS)

6.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Notes:

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

6.2. ISED RULES

For the purpose of this standard, Innovation, Science and Economic Development (ISED) has adopted the SAR and RF field strength limits established in Health Canada’s RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}

Note: *f* is frequency in MHz.

* Based on nerve stimulation (NS).

** Based on specific absorption rate (SAR).

6.3. EQUATIONS

POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * \text{D}^2)$$

Where

S = Power density in mW/cm²

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

DISTANCE

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in mW

DISTANCE CORRECTION

Distance correction factor to scale E-field reading from x meters to y meters is as follows:

$$\text{Correction Factor} = 20\log(x/y)$$

Where x is the initial measurement distance and y is the desired distance.

MAXIMUM E-FIELD STRENGTH (dBuV/m to V/m)

To convert from dBuV/m to V/m, the following equation was used:

$$V/m = 10^{[(dBuV/m - 120) / 20]}$$

MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

$$\text{Total EIRP} = (\text{EIRP1}) + (\text{EIRP2}) + \dots + (\text{EIRPn})$$

where

EIRPx = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

MIMO AND COLOCATED TRANSMITTERS (NON-IDENTICAL LIMIT FOR ALL TRANSMITTERS)

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as (Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

7. RF EXPOSURE RESULTS

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer.

Client Provided Data:

1. Maximum Circuit Input Power

(Single chain transmitters, and non-co-located transmitters)
 $=H5/(4*3.14*((C5)^2))$

Single Chain and non-co-located transmitters									
Band	Mode	Separ. Distance (cm)	Maximum Measured E-Field Strength (30m) (dBuV/m)	Maximum Measured E-Field Strength (3m) (dBuV/m)	EIRP (mW)	FCC PD (mW/cm ²)	ISED PD (W/m ²)	FCC PD Limit (mW/cm ²)	IC PD Limit (W/m ²)
13.56 MHz	VM0231	20.00	29.390	69.390	0.0026	0.000	0.000	0.979	2.000
13.56 MHz	VM0232	20.00	26.110	66.110	0.0012	0.000	0.000	0.979	2.000
13.56 MHz	VM0234	20.00	18.710	58.710	0.0002	0.000	0.000	0.979	2.000

Notes:

1. Maximum measured E-Field strength at 3 meters was converted to EIRP and compared to the FCC and ISED PD limits for 13.56MHz radios. The calculated PD for FCC and ISED are significantly below the PD limits.

END OF TEST REPORT