## FCC ID: 2AJEO-T10MR

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \*

 $[\,\,{\scriptstyle \checkmark}\,f(GHz)] \leqslant 3.0$  for 1-g SAR  $\,$  and  $\leqslant 7.5$  for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

| Transmit Frequency<br>(GHz) | Mode       | Max Conducted<br>Power (dBm) | tune up maximum<br>power(dBm) | Result calculation | 1-g SAR |
|-----------------------------|------------|------------------------------|-------------------------------|--------------------|---------|
| 2.402                       | GFSK       | 2.73                         | 5                             | 0.980              | 3       |
| 2.441                       | GFSK       | 3.12                         | 5                             | 0.988              | 3       |
| 2.480                       | GFSK       | 3.58                         | 5                             | 0.996              | 3       |
| 2.402                       | pi/4-DQPSK | 2.72                         | 5                             | 0.980              | 3       |
| 2.441                       | pi/4-DQPSK | 3.09                         | 5                             | 0.988              | 3       |
| 2.480                       | pi/4-DQPSK | 3.55                         | 5                             | 0.996              | 3       |
| 2.402                       | 8DPSK      | 2.91                         | 5                             | 0.980              | 3       |
| 2.441                       | 8DPSK      | 3.28                         | 5                             | 0.988              | 3       |
| 2.480                       | 8DPSK      | 3.74                         | 5                             | 0.996              | 3       |

BLE DTS

1M

| Transmit Frequency<br>(GHz) | Mode | Max Conducted<br>Power (dBm) | tune up maximum<br>power(dBm) | Result calculation | 1-g SAR |
|-----------------------------|------|------------------------------|-------------------------------|--------------------|---------|
| 2.402                       | GFSK | 3.11                         | 5                             | 0.980              | 3       |
| 2.441                       | GFSK | 3.38                         | 5                             | 0.988              | 3       |
| 2.480                       | GFSK | 3.79                         | 5                             | 0.996              | 3       |

2M

| Transmit Frequency<br>(GHz) | Mode | Max Conducted<br>Power (dBm) | tune up maximum<br>power(dBm) | Result calculation | 1-g SAR |
|-----------------------------|------|------------------------------|-------------------------------|--------------------|---------|
| 2.402                       | GFSK | 3.05                         | 5                             | 0.980              | 3       |
| 2.441                       | GFSK | 3.37                         | 5                             | 0.988              | 3       |
| 2.480                       | GFSK | 3.74                         | 5                             | 0.996              | 3       |

## Conclusion:

For the max result : 0.998≤ 3.0 for 1-g SAR extremity SAR, No SAR is required.

Signature:

Date: 2021.1.29

NAME AND TITLE (Please print or type): Lisa Wang/Manager COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China