

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AJFX-Z50

### EUT Specification

<b>EUT</b>	<b>Dash Cam</b>
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others: BLE: 2402-2480MHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	BLE: 5.09dBm (0.0032W) WIFI 2.4G: 14.91 dBm (0.0310W)
<b>Antenna gain (Max)</b>	2 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	<b>F/300</b>	<b>6</b>
1500-100000	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	<b>F/1500</b>	<b>6</b>
1500-100000	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/ cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	2412	14.88	14.88 ± 1	15.88	2	0.0122	1
	2437	14.72	14.72 ± 1	15.72	2	0.0118	1
	2462	14.66	14.66 ± 1	15.66	2	0.0116	1
802.11g	2412	14.50	14.50 ± 1	15.50	2	0.0112	1
	2437	14.34	14.34 ± 1	15.34	2	0.0108	1
	2462	14.40	14.40 ± 1	15.40	2	0.0109	1
802.11n (HT20)	2412	14.27	14.27 ± 1	15.27	2	0.0106	1
	2437	14.20	14.20 ± 1	15.20	2	0.0104	1
	2462	14.13	14.13 ± 1	15.13	2	0.0103	1
802.11n (HT40)	2422	14.89	14.89 ± 1	15.89	2	0.0122	1
	2437	14.91	14.91 ± 1	15.91	2	0.0123	1
	2452	14.75	14.75 ± 1	15.75	2	0.0119	1
BLE	2402	5.09	5.09 ± 1	6.09	2	0.0013	1
	2440	4.82	4.82 ± 1	5.82	2	0.0012	1
	2480	4.06	4.06 ± 1	5.06	2	0.0010	1