

Page 1 of 54

FCC Test Report

Report No.:AGC02294200806FE10

| FCC ID | ė | 2AJGMUV82 |
|---------------------|-----|--|
| PRODUCT DESIGNATION | | Two-way radio |
| BRAND NAME | © : | POFUNG,BAOFENG |
| MODEL NAME | | UV-82, UV82IC, P82UV, UV82X, UC82 Pro,UV-82 Plus, GT-5, UV-82HP, Mate82 |
| APPLICANT | : | PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY |
| DATE OF ISSUE | | Feb. 02, 2021 |
| STANDARD(S) | ċ | FCC Part 95 Rules |
| REPORT VERSION | : | V 1.0 |



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com

Web: http://cn.agc-cert.com/



Report Revise Record

| Report Version | Revise Time | Issued Date Valid Version | | Notes | |
|----------------|-------------|---------------------------|-------|-----------------|--|
| V1.0 | 1 | Feb. 02, 2021 | Valid | Initial release | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com

VERIFICATION OF COMPLIANCE

AGC

| Applicant | PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY |
|--------------------------|--|
| Address | 3/F FULOK BLDG 131-133 WING LOK ST SHEUNG WAN, Hong Kong |
| manufacturer | PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY |
| Address | 3/F FULOK BLDG 131-133 WING LOK ST SHEUNG WAN, Hong Kong |
| Factory | PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP COMPANY |
| Address | 3/F FULOK BLDG 131-133 WING LOK ST SHEUNG WAN, Hong Kong |
| Product Designation | Two-way radio |
| Brand Name | POFUNG, BAOFENG |
| Test Model | UV-82 |
| Series Model | UV82IC, P82UV, UV82X, UC82 Pro,UV-82 Plus, GT-5, UV-82HP, Mate82 |
| Difference Description | All the same except the model name. |
| Deviation | No any deviation from the test method |
| Condition of Test Sample | Normal |
| Date of Test | Nov. 01, 2020~Feb. 02, 2021 |
| Test Result | PASS |
| Report Template | AGCRT-US-PTT/RF |

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in TIA/EIA 603-E. The sample tested as described in this report is in compliance with the FCC Rules Part 95 requirements. The test results of this report relate only to the tested sample identified in this report.

Prepared By

Imim Aucorg

Donjon Huang (Project Engineer)

Feb. 02, 2021

Calvin Lin

Reviewed By

Calvin Liu (Reviewer)

Feb. 02, 2021

Approved By

Forrest Un

Forrest Lei Authorized Officer

Feb. 02, 2021

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agc-cert.com Web: http://cn.agc-cert.com/



TABLE OF CONTENTS

| | 1. GENERAL INFORMATION | 6 |
|------------|---|------|
| | 1.1 PRODUCT DESCRIPTION | 6 |
| | 1.2 RELATED SUBMITTAL(S) / GRANT (S) | |
| | 1.3 TEST METHODOLOGY | 8 |
| | 1.4 ADDRESS OF THE TEST LABORATORY | 8 |
| | 1.5 TEST FACILITY | |
| | 1.6 SPECIAL ACCESSORIES | |
| | 1.7 EQUIPMENT MODIFICATIONS | |
| | 1.8 ANTENNA REQUIREMENT错误!未定义 | .书签。 |
| | 2. SYSTEM TEST CONFIGURATION | |
| | 2.1 EUT CONFIGURATION | |
| | 2.2 EUT EXERCISE | 10 |
| | 2.3 CONFIGURATION OF TESTED SYSTEM | |
| | 2.4 MEASUREMENT UNCERTAINTY | |
| | 3. SUMMARY OF TEST RESULTS | |
| | 4. DESCRIPTION OF TEST MODES | |
| | 5. FREQUENCY TOLERANCE | |
| | 5.1 PROVISIONS APPLICABLE | 15 |
| | 5.2 MEASUREMENT PROCEDURE | |
| | 5.3 TEST SETUP BLOCK DIAGRAM | |
| | 5.4TEST RESULT | 17 |
| | 6. EMISSION BANDWIDTH | 19 |
| | 6.1 PROVISIONS APPLICABLE | 19 |
| | 6.2 MEASUREMENT PROCEDURE | |
| | 6.3 TEST SETUP BLOCK DIAGRAM | |
| | 6.4 MEASUREMENT RESULT | 22 |
| | 7. UNWANTED RADIATION | 25 |
| | 7.1 PROVISIONS APPLICABLE | 25 |
| | 7.2 MEASUREMENT PROCEDURE | |
| | 7.3 TEST SETUP BLOCK DIAGRAM | 27 |
| | 7.4 MEASUREMENT RESULTS: | 28 |
| | 7.5 EMISSION MASK PLOT | |
| | 8. AUDIO LOW PASS FILTER RESPONSE | 40 |
| | 8.1.PROVISIONS APPLICABLE | 40 |
| | 8.2.TEST PROCEDURE | 40 |
| Sta pre | amp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter approximation of AGC. The test results as the result of the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report apply only to the test report should be addressed to AGC by agc@agc-cert.com. | ults |
| Δ ## | ttestation of Global Compliance(Shenzhen)Co. Ltd | |



| 8.3 TEST CONFIGURATION | 40 |
|--------------------------------------|----|
| 8.4 TEST RESULT | |
| 9. MAXIMUMN TRANSMITTER POWER | |
| 9.1 PROVISIONS APPLICABLE | |
| 9.2 TEST PROCEDURE | |
| 9.3 TEST CONFIGURATION | |
| 9.4 TEST RESULT | |
| 10.SPURIOUS EMISSION ON ANTENNA PORT | |
| 10.1 PROVISIONS APPLICABLE | |
| 10.2 TEST PROCEDURE | |
| 10.3 TEST CONFIGURATION | |
| 10.4 TEST RESULT | |
| 11. MODULATION CHARACTERISTICS | |
| 11.1 PROVISIONS APPLICABLE | |
| 11.2 MEASUREMENT METHOD | |
| 11.3 MEASUREMENT RESULT | |
| APPENDIX I: PHOTOGRAPHS OF SETUP | |
| APPENDIX II: PHOTOGRAPHS OF EUT | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written exphorization of AGE". The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **Two-way radio** designed for voice communication. It is designed by way of utilizing the FM modulation achieves the system operating.

A major technical description of EUT is described as following:

| Communication Type | Voice/Tone only |
|--|---|
| Product Designation | Two-way radio |
| Test Model | UV-82 |
| Hardware Version | 82TS.V04 |
| Software Version | 82TS.V04 |
| Modulation | FM |
| Channel Separation | 12.5KHz |
| Emission Type | 11K0F3E |
| Emission Bandwidth | 10.59KHz |
| Maximum Transmitter Power | 35.88dBm-4W 26.93dBm-0.5W |
| Rated Output power | 4W/0.5W (It was fixed by the manufacturer, any individual can't arbitrarily change it.) |
| Antenna Designation | Inseparable |
| Antenna Gain | 1.5dBi |
| Power Supply | DC 7.4V by battery |
| Limiting Voltage | DC 6.29V~8.51V |
| Operation Frequency Range and Channel | GMRS: 462.5500MHz-462.7250MHz(4W) 462.5625MHz-462.7125MHz(4W) 467.5500MHz-467.7250MHz(4W) 467.5625MHz-467.7125MHz(0.5W) Test Channel : 4, 11, 19 and 27 channel |
| Frequency Tolerance | 1.091ppm |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the stand of the test results of the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day affective report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Channel List:

| CH. No | CH. Freq | Power | CH. No | CH. Freq | Power |
|--------|----------|-------|--------|----------|-------|
| 1 | 462.5625 | - 6 | 16 💿 | 462.5750 | 6 |
| 2 | 462.5875 | | 17 | 462.6000 | |
| 3 | 462.6125 | | 18 | 462.6250 | |
| 4 | 462.6375 | 4W | 19 | 462.6500 | 4W |
| 5 | 462.6625 | | 20 | 462.6750 | |
| 6 | 462.6875 | | 21 | 462.7000 | |
| 7 | 462.7125 | | 22 | 462.7250 | ® |
| 8 | 467.5625 | | 23 | 467.5500 | 0.5 |
| 9 💿 | 467.5875 | | 24 | 467.5750 | |
| 10 | 467.6125 | | 25 | 467.6000 | 0 |
| 11 | 467.6375 | 0.5W | 26 | 467.6250 | 4147 |
| 12 | 467.6625 | | 27 | 467.6500 | 4W |
| 13 | 467.6875 | | 28 | 467.6750 | |
| 14 | 467.7125 | 0 | 29 | 467.7000 | |
| 15 | 462.5500 | 4W | 30 | 467.7250 | |


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuerce of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com

Web: http://cn.agc-cert.com/





1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: **2AJGMUV82**, filing to comply with the FCC Part 95 requirements.

1.3 TEST METHODOLOGY.

FCC Part 95: Personal Radio Services
FCC Part 2: Frequency allocations and radio treaty matters, general rules and regulations.
TIA/EIA 603 E: March 2016: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

1.4 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories


A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Perturn/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.





IC-Registration No.: 24842

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

1.6 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the stand of the test results for the test results are apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day and the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com
 Web: http://cn.agc-cert.com/



2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System

EUT.

| C | ® | | -Cu o F | |
|-----------------------|---------------|---------------|--|------|
| Item | Equipment | Model No. | Identifier | Note |
| 1 | Two-way radio | UV-82 | FCC ID: 2AJGMUV82 | EUT |
| 2 | Adapter | 480-10050-E.S | Input: AC 100-240V 50/60Hz, 0.2A Output:: DC 10V 0.5A | AE |
| 3 | Charger | CHR-82 | Input: DC 10V 0.5A Output: DC 8.4V 0.5A | AE |
| 4 | Battery | BL-8 | DC 7.4V 2800mA | AE |
| 5 | Back clip | BC-82 | N/A | AE 💿 |

Table 2-1 Equipment Used in Tested System

Note: The battery is full-charged during the test

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand in the stand approver, or having been altered without authorization, or having not been stamped by the stand in the stand approver, or having been altered without authorization, or having not been stamped by the stand in the stand approver, or having been altered without authorization, or having not been stamped by the stand in the stand approver, or having been altered without authorization, or having not been stamped by the stand in the stand approver, or having been altered without authorization, or having not been stamped by the stand in the stand approver apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



2.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y $\pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB
- Uncertainty of total RF power, conducted, $Uc = \pm 0.8$ dB
- Uncertainty of spurious emissions, conducted, Uc = ±2.7dB
- Uncertainty of Occupied Channel Bandwidth: $Uc = \pm 2 \%$
- Uncertainty of Frequency: $Uc = \pm 2\%$
- Uncertainty of FM deviation: Uc=±2 %
- Uncertainty of Audio Level: Uc=±0.98dB
- Uncertainty of Modulation Limiting: Uc=0.42 %
- Uncertainty of Transient Frequency Behavior: Uc=6.8%

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the report is not permitted without the written authorization of AGE in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day and the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com



3. SUMMARY OF TEST RESULTS

| FCC 47 CFR Part 95 Test Cases | | | | | | |
|---|---|---------------------|--------|--|--|--|
| Test Item | Test Requirement | Test Method | Result | | | |
| Antenna Equipment | FCC CFR Part 95 | N/A | PASS | | | |
| Maximum Transmitter Power | FCC CFR Part 95.1767 FCC 47 CFR Part 2.1046(a) | ANSI/TIA-603-E-2016 | PASS | | | |
| Modulation Limit | FCC CFR Part 95.1775 FCC 47 CFR Part 2.1047(a)(b) | ANSI/TIA-603-E-2016 | PASS | | | |
| Audio Frequency Response | FCC CFR Part 95.1775 FCC 47 CFR Part 2.1047(a) | ANSI/TIA-603-E-2016 | PASS | | | |
| Audio Low Pass Filter Response | FCC 47 CFR Part 95.1775(e) | ANSI/TIA-603-E-2016 | PASS | | | |
| Emission Bandwidth | FCC CFR Part 95.1773 FCC 47 CFR Part 2.1049 | ANSI/TIA-603-E-2016 | PASS | | | |
| Emission Mask | FCC CFR Part 95.1779 | ANSI/TIA-603-E-2016 | PASS | | | |
| Transmitter Radiated Spurious Emission | FCC CFR Part 95.1779 FCC 47 CFR Part 2.1053 | ANSI/TIA-603-E-2016 | PASS | | | |
| Spurious Emission On Antenna Port | FCC CFR Part 95.1779 FCC 47 CFR Part 2.1051 | ANSI/TIA-603-E-2016 | N/A | | | |
| Frequency Stability | FCC CFR Part 95.1765 FCC 47 CFR Part 2.1055 (a)(1) | ANSI/TIA-603-E-2016 | PASS | | | |

1) N/A: In this whole report not application.

2) The EUT is Integral Antenna.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



LIST OF EQUIPMENTS USED

| | | | | S | |
|--------------------------------------|--------------|----------|--------------|---------------|---------------|
| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Due |
| TEST RECEIVER | R&S | ESCI | 10096 | Jun. 09, 2020 | Jun. 08, 2021 |
| EXA Signal Analyzer | KEYSIGHT | N9020A | MY53300860 | July 15, 2020 | July 14, 2021 |
| Horn antenna | SCHWARZBECK | BBHA9170 | 768 | Oct. 09, 2019 | Oct. 08, 2021 |
| preamplifier | ETS | 3117PA | 00225134 | Sep. 03, 2020 | Sep. 02, 2022 |
| Double-Ridged Waveguide Horn | ETS LINDGREN | 3117 | 00034609 | May. 17, 2019 | May. 16, 2021 |
| Broadband Preamplifier | SCHWARZBECK | BBV9718 | 9718-205 | Jun. 09, 2020 | Jun. 08, 2021 |
| Double-Ridged Waveguide Horn | ETS | 3117 | 00154520 | Oct. 26, 2019 | Oct. 25, 2021 |
| SIGNAL | AGILENT | E4421B | MY43351603 | Jun. 09, 2020 | Jun. 08, 2021 |
| ANTENNA | SCHWARZBECK | VULB9168 | VULB9168-494 | Jan. 09, 2019 | Jan. 08, 2021 |
| ANTENNA | SCHWARZBECK | VULB9168 | VULB9168-494 | Jan. 07, 2021 | Jan. 06, 2022 |
| ANTENNA | SCHWARZBECK | VULB9168 | D69250 | Sep.20, 2019 | Sep.19, 2021 |
| Modulation Domain Analyzer | НР | 53310A | 3121A02467 | Aug. 26, 2020 | Aug. 25, 2021 |
| Small environmental tester | ESPEC | SH-242 | 93008290 | Sep. 03, 2020 | Sep. 02, 2022 |
| RF Communication Test Set | HP | 8920B | US35010161 | Sep. 03, 2020 | Sep. 02, 202′ |
| Active loop antenna (9K-30MHz) | ZHINAN | ZN30900C | 18051 | Jun. 11, 2020 | Jun. 10, 2021 |
| Attenuator | Schaffner | 58-30-33 | ML030 | Oct. 26, 2020 | Oct. 25, 2021 |
| RF Cable | R&S | 1# | o | Each time | N/A |
| Fliter-UHF | Microwave | N25155M2 | 498705 | May. 11, 2020 | May. 10, 202 |

Note: 8920B can generate audio modulation frequency.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



4. DESCRIPTION OF TEST MODES

RF TEST MODES

The EUT (**Two-way radio**) has been tested under normal operating condition. (GMRS TX) are chosen for testing at each channel separation.

| NO. | TEST MODE DESCRIPTION | CHANNEL SEPARATION |
|-----|-----------------------|--------------------|
| 1 | GMRS TX CHANNEL 4 | 12.5 kHz |
| 2 | GMRS TX CHANNEL 11 | 12.5 kHz |
| 3 | GMRS TX CHANNEL 19 | 12.5 kHz |
| 4 | GMRS TX CHANNEL 27 | 12.5 kHz |

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, be test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



5. FREQUENCY TOLERANCE

5.1 PROVISIONS APPLICABLE

Standard Applicable [Part 95.1765]The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

FCC Part 95.1765,

GMRS: The carrier frequency of each GMRS transmitter transmitting an emission with an occupied bandwidth of 12.5 kHz or less must remain within 2.5 ppm

The carrier frequency of each GMRS transmitter transmitting an emission with an occupied bandwidth greater than 12.5 kHz must remain within 5 ppm

5.2 MEASUREMENT PROCEDURE

5.2.1 Frequency stability versus environmental temperature

- 1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz.Record this frequency as reference frequency.
- 3. Set the temperature of chamber to 50 °C. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- 4. Repeat step 2 with a 10[°]C decreased per stage until the lowest temperature -30[°]C is measured, record all measured frequencies on each temperature step.


5.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15℃ to 25℃. Otherwise, an environment chamber set for a temperature of 20℃ shall be used. The EUT shall be powered by DC 7.4V.
- 2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
- 3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGE, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



5.3 TEST SETUP BLOCK DIAGRAM



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com

Web: http://cn.agc-cert.com/



5.4TEST RESULT

| Environment | Power Supply | Reference Frequency | | | | Limit: |
|--------------------|--------------|---------------------|-------------|-------------|-------------|-----------------|
| Temperature (℃) | (V) | 462.6375MHz | 462.6500MHz | 467.6375MHz | 467.6500MHz | ppm |
| 50 | DC 7.4 | 0.849 | 0.653 | 0.743 | 0.375 | 8 |
| 40 | DC 7.4 | 0.906 | 0.659 | 0.982 | 0.361 | C.C |
| 30 | DC 7.4 | 0.807 | 0.916 | 0.599 | 0.423 | |
| 20 | DC 7.4 | 0.799 | 0.866 | 0.535 | 0.348 | 0 F1 |
| 10 | DC 7.4 | 0.922 | 0.903 | 0.817 | 0.833 | ±2.5for GMRS |
| 0 | DC 7.4 | 0.611 | 0.943 | 0.674 | 0.305 | Givirto |
| -10 | DC 7.4 | 0.569 | 0.802 | 0.605 | 0.784 | |
| -20 | DC 7.4 | 0.507 | 0.545 | 0.534 | 0.869 | |
| -30 | DC 7.4 | 0.686 | 1.068 | 0.913 | 0.458 | |
| Result | | | Pass | 0 | | |

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.4V)

(2) Frequency stability versus input voltage (Battery limiting voltage is 6.29V)

| Environment | Power Supply | - 6 | Reference | Frequency | | Limit: |
|--------------------|--------------|-------------|-------------|-------------|-------------|----------------|
| Temperature (℃) | (V) | 462.6375MHz | 462.6500MHz | 467.6375MHz | 467.6500MHz | ppm |
| 50 | DC 6.29 | 1.091 | 0.732 | 0.539 | 0.607 | |
| 40 | DC 6.29 | 0.930 | 0.869 | 0.527 | 0.991 | |
| 30 | DC 6.29 | 0.641 | 0.838 | 0.948 | 0.540 | |
| 20 | DC 6.29 | 0.646 | 1.036 | 1.065 | 0.476 | 0.51 |
| 10 | DC 6.29 | 0.842 | 0.974 | 0.769 | 0.770 | ±2.5fo GMRS |
| 0 | DC 6.29 | 0.610 | 0.658 | 0.532 | 0.775 | GIVING |
| -10 | DC 6.29 | 0.545 | 1.076 | 0.523 | 0.641 | |
| -20 | DC 6.29 | 0.728 | 0.756 | 0.754 | 0.510 | |
| -30 | DC 6.29 | 0.603 | 0.564 | 0.956 | 0.865 | 6 |
| Result | | | Pass | 8 | | 6 |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



| | Power Supply | | | | 8 | Limit: |
|-----------------------------------|--------------|-------------|-------------|-------------|-------------|-----------------|
| Environment Temperature (℃) | (V) | 462.6375MHz | 462.6500MHz | 467.6375MHz | 467.6500MHz | ppm |
| 50 | DC 8.51 | 0.604 | 1.013 | 1.015 | 0.825 | 0 |
| 40 | DC 8.51 | 0.843 | 0.834 | 0.750 | 0.567 | |
| 30 | DC 8.51 | 0.905 | 0.876 | 1.051 | 0.579 | 3 |
| 20 | DC 8.51 | 0.538 | 0.739 | 0.796 | 0.387 | |
| 10 | DC 8.51 | 0.754 | 0.982 | 0.990 | 0.350 | ±2.5for GMRS |
| 0 | DC 8.51 | 0.760 | 0.524 | 0.734 | 0.576 | GivirtS |
| -10 | DC 8.51 | 0.752 | 0.829 | 1.097 | 0.506 | |
| -20 | DC 8.51 | 0.727 | 0.741 | 0.540 | 0.558 | |
| -30 | DC 8.51 | 1.053 | 0.946 | 0.636 | 0.948 | |
| Result | | 0 | Pass | G | G © | |

(3) Frequency stability versus input voltage (Battery Fully Charged voltage is 8.51V)

Note: 1.Battery terminal voltage is declared and specified by the manufacturer.

2. All test values are in "ppm"

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Festing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



6. EMISSION BANDWIDTH

6.1 PROVISIONS APPLICABLE

FCC Part 95.1773: GMRS:

(a) Main channels. The authorized bandwidth is 20 kHz for GMRS transmitters operating on any of the 462 MHz main channels, or any of the 467 MHz main channels.

(b) Interstitial channels. The authorized bandwidth is 20 kHz for GMRS transmitters operating on any of the 462 MHz interstitial channels, and is 12.5 kHz for GMRS transmitters operating on any of the 467 MHz interstitial channels.

Occupied Bandwidth: The EUT was connected to the audio signal generator and the spectrum analyzer via the main RF connector, and through an appropriate attenuator. The EUT was controlled to transmit its maximum power. Then the bandwidth of 99% power can be measured by the spectrum analyzer.

6.2 MEASUREMENT PROCEDURE

1). The EUT was modulated by 2.5 KHz Sine wave audio signal, The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing).

2). Set SPA Center Frequency = fundamental frequency, RBW=300Hz.VBW= 1KHz, Span = 50 KHz.

3). Set SPA Max hold. Mark peak, -26 dB.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the report is not permitted without the written authorization of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day and a test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




6.3 TEST SETUP BLOCK DIAGRAM

Radiation method:

Radiated Below1GHz



Radiated Above 1 GHz




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd


 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com





Conduction method:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



6.4 MEASUREMENT RESULT


| Emission Bandwidth Measurement Result | | | | | | | | | | |
|---------------------------------------|--------------------|---------------------|-----------|--------|--|--|--|--|--|--|
| | | 12.5 KHz Channel Se | eparation | | | | | | | |
| Operating Frequency | Occupied Bandwidth | Emission Bandwidth | Limits | Result | | | | | | |
| 462.6375 MHz | 10.006 KHz | 10.59 KHz | 20 KHz | Pass | | | | | | |
| 467.6375 MHz | 9.973 KHz | 10.59 KHz | 12.5KHz | Pass | | | | | | |
| 462.6500 MHz | 10.005 KHz | 10.59 KHz | 20 KHz | Pass | | | | | | |
| 467.6500 MHz | 9.987 KHz | 10.58 KHz | 20 KHz | Pass | | | | | | |

Occupied bandwidth of 462.6375MHz-4W




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand in the stand of the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

AGC[®]




Occupied bandwidth of 467.6375MHz-0.5W

Occupied bandwidth of 462.6500MHz-4W



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

AGC[®]



Occupied bandwidth of 467.6500MHz-4W

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, be test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



7. UNWANTED RADIATION

7.1 PROVISIONS APPLICABLE

Standard Applicable [FCC Part 95.1779]

According to FCC section 95.1779, the unwanted emission should be attenuated below TP by at least 43+10 log(Transmit Power) dB.

7.2 MEASUREMENT PROCEDURE

Each GMRS transmitter type must be designed to comply with the applicable unwanted emissions limits in this section.

(a)Emission masks. Emission masks applicable to transmitting equipment in the GMRS are defined by the requirements in the following table. The numbers in the attenuation requirements column refer to rule paragraph numbers under paragraph (b) of this section.

| Emission types filter | Attenuation requirements |
|---|-----------------------------|
| A1D, A3E, F1D, G1D, F2D, F3E, G3E with audio filter | (1), (2), (7) |
| A1D, A3E, F1D, G1D, F3E, G3E without audio filter | (3), (4), (7) |
| H1D, J1D, R1D, H3E, J3E, R2E | (5), (6), (7) |

(1) Filtering noted for GMRS transmitters refers to the requirement in §95.1775(e).

- (2) Unwanted emission power may be measured as either mean power or peak envelope power, provided that the transmitter output power is measured the same way.
- (b) Attenuation requirements. The power of unwanted emissions must be attenuated below the transmitter output power in Watts (P) by at least:
- (1) 25 dB (decibels) on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.
- (2) 35 dB on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 250% of the authorized bandwidth.
- (3) 83 log (fd ÷ 5) dB on any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5 kHz up to and including 10 kHz.
- (4) 116 log (fd ÷ 6.1) dB or 50 + 10 log (P) dB, whichever is the lesser attenuation, on any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz), of more than 10 kHz up to and including 250% of the authorized bandwidth.
- (5) 25 dB on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 150% of the authorized bandwidth.
- (6) 35 dB on any frequency removed from the center of the authorized bandwidth by more than 150% up to and including 250% of the authorized bandwidth.
- (7) 43 + 10 log (P) dB on any frequency removed from the center of the authorized bandwidth by more than 250%.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Pestua/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



- (1) EUT was placed on a 0.8 or 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector.
- (2) A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
- (3)The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz,VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- (4)The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- (5)A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
- (6)The measurement results are obtained as described below: Power(EIRP)=PMea- PAg Pcl Ga The measurement results are amend as described below: Power(EIRP)=PMea- Pcl - Ga
- (7)This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi. (8)Test the EUT in the lowest channel, the middle channel the Highest channel

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bestrac/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.




7.3 TEST SETUP BLOCK DIAGRAM

SUBSTITUTION METHOD: (Radiated Emissions)

EUT BO CON Turntable) Test Receiver Test Receiver Turntable Test Receiver Turntable Test Receiver Turntable Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Test Receiver Turntable Controlles Antenna Tower Antenna Tower Antenna Tower Antenna Tower Turntable Controlles Controlles

Radiated Below1GHz

Radiated Above 1 GHz




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter aphroization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day Safter the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com





7.4 MEASUREMENT RESULTS:

the unwanted emission should be attenuated below TP by at least 43+10 log(Transmit Power) dB

Limit: At least 43+10 log (P) =43+10log (4) =46.01(dBc) 36.02-49.02= -13dBm At least 43+10 log (P) =43+10log (0.5) =39.99(dBc) 26.99-39.99= -13dBm

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the been stamped by the bedicated from given and the test results are presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day are are are are the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



FCC PART 95E 30 20 10 0 -10 -20 -evel[dBm] -30 -40 -50 -60 -70 -80 -90 -100 30M 100M 1G 12.75G Frequency[Hz]

Measurement Result for 12.5 KHz Channel Separation @ 462.6375MHz-4W-Horizontal

- Limit 🔹 Final Test ----- Horizontal

| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|------------|
| 1 | 1387.7888 | -35.77 | -39.22 | -13.00 | 26.22 | -3.45 | 103 | Horizontal |
| 2 | 3238.5989 | -31.00 | -27.29 | -13.00 | 14.29 | 3.71 | 340 | Horizontal |
| 3 | 3701.5952 | -28.55 | -24.14 | -13.00 | 11.14 | 4.41 | 36 | Horizontal |
| 4 | 4163.4163 | -40.72 | -36.39 | -13.00 | 23.39 | 4.33 | 46 | Horizontal |
| 5 | 5551.2301 | -48.68 | -39.57 | -13.00 | 26.57 | 9.11 | 27 | Horizontal |
| 6 | 7402.0402 | -53.42 | -40.15 | -13.00 | 27.15 | 13.27 | 55 | Horizontal |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the submitted resting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGS. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



FCC PART 95E 30 20 10 -10 -20 Level[dBm] -30 -40 -50 -60 -70 -80 -90 -100 30M 100M 1G 12.75G Frequency[Hz]

Measurement Result for 12.5 KHz Channel Separation @ 462.6375MHz-4W-Vertical

Limit # Final Test ---- Vertical

| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 925.3100 | -88.24 | -44.67 | -13.00 | 31.67 | 43.57 | 238 | Vertical |
| 2 | 1387.7888 | -41.65 | -40.24 | -13.00 | 27.24 | 1.41 | 294 | Vertical |
| 3 | 3238.5989 | -35.07 | -31.93 | -13.00 | 18.93 | 3.14 | 313 | Vertical |
| 4 | 3701.5952 | -26.79 | -23.64 | -13.00 | 10.64 | 3.15 | 313 | Vertical |
| 5 | 4163.4163 | -38.76 | -35.55 | -13.00 | 22.55 | 3.21 | 304 | Vertical |
| 6 | 5089.4089 | -42.51 | -38.22 | -13.00 | 25.22 | 4.29 | 359 | Vertical |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated restriction of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



FCC PART 95E 30 20 10 -10 -20 -evel[dBm] -30 -40 -50 -60 -70 -80 -90 -100 30M 100M 1G 12.75G Frequency[Hz]

Measurement Result for 12.5 KHz Channel Separation @ 462.6500MHz-4W-Horizontal

Limit # Final Test ---- Horizontal

| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|------------|
| 1 | 3238.5989 | -26.76 | -23.05 | -13.00 | 10.05 | 3.71 | 219 | Horizontal |
| 2 | 3701.5952 | -23.71 | -19.30 | -13.00 | 6.30 | 4.41 | 31 | Horizontal |
| 3 | 4164.5915 | -30.16 | -25.83 | -13.00 | 12.83 | 4.33 | 31 | Horizontal |
| 4 | 4626.4126 | -29.41 | -25.86 | -13.00 | 12.86 | 3.55 | 12 | Horizontal |
| 5 | 5089.4089 | -37.44 | -32.77 | -13.00 | 19.77 | 4.67 | 116 | Horizontal |
| 6 | 6940.2190 | -38.22 | -26.58 | -13.00 | 13.58 | 11.64 | 59 | Horizontal |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated restriction of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



FCC PART 95E 30 20 10 -10 -20 -evel[dBm] -30 -40 -50 -60 -70 -80 -90 -100 30M 100M 1G 12.75G Frequency[Hz]

Measurement Result for 12.5 KHz Channel Separation @ 462.6500MHz-4W-Vertical

Limit # Final Test ----- Vertical

| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 1387.7888 | -33.69 | -32.28 | -13.00 | 19.28 | 1.41 | 318 | Vertical |
| 2 | 3238.5989 | -29.50 | -26.36 | -13.00 | 13.36 | 3.14 | 346 | Vertical |
| 3 | 3701.5952 | -20.69 | -17.54 | -13.00 | 4.54 | 3.15 | 167 | Vertical |
| 4 | 4164.5915 | -34.32 | -31.11 | -13.00 | 18.11 | 3.21 | 252 | Vertical |
| 5 | 5089.4089 | -34.34 | -30.05 | -13.00 | 17.05 | 4.29 | 360 | Vertical |
| 6 | 6477.2227 | -43.96 | -32.34 | -13.00 | 19.34 | 11.62 | 17 | Vertical |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the submitted resting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGS. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



FCC PART 95E 30 20 10 -10 -20 -evel[dBm] -30 -40 -50 -60 -70 -80 -90 -100 30M 100M 1G 12.75G Frequency[Hz]

Measurement Result for 12.5 KHz Channel Separation @ 467.6500MHz-4W-Horizontal

Limit **#** Final Test — Horizontal


| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|------------|
| 1 | 1403.0653 | -32.53 | -35.94 | -13.00 | 22.94 | -3.41 | 107 | Horizontal |
| 2 | 1870.7621 | -38.04 | -38.48 | -13.00 | 25.48 | -0.44 | 351 | Horizontal |
| 3 | 3273.8524 | -21.30 | -17.52 | -13.00 | 4.52 | 3.78 | 324 | Horizontal |
| 4 | 3741.5492 | -23.62 | -19.16 | -13.00 | 6.16 | 4.46 | 343 | Horizontal |
| 5 | 4209.2459 | -27.98 | -23.76 | -13.00 | 10.76 | 4.22 | 23 | Horizontal |
| 6 | 5144.6395 | -29.50 | -24.26 | -13.00 | 11.26 | 5.24 | 239 | Horizontal |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated restriction of Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Measurement Result for 12.5 KHz Channel Separation @ 467.6500MHz-4W-Vertical



----- Limit # Final Test ----- Vertical


| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 935.9800 | -88.24 | -44.56 | -13.00 | 31.56 | 43.68 | 19 | Vertical |
| 2 | 1403.0653 | -32.96 | -31.44 | -13.00 | 18.44 | 1.52 | 360 | Vertical |
| 3 | 3273.8524 | -21.83 | -18.70 | -13.00 | 5.70 | 3.13 | 348 | Vertical |
| 4 | 3741.5492 | -25.82 | -22.65 | -13.00 | 9.65 | 3.17 | 169 | Vertical |
| 5 | 5144.6395 | -29.21 | -24.68 | -13.00 | 11.68 | 4.53 | 74 | Vertical |
| 6 | 6547.7298 | -38.36 | -26.66 | -13.00 | 13.66 | 11.70 | 19 | Vertical |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Fasting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Measurement Result for 12.5 KHz Channel Separation @ 467.6375MHz-0.5W-Horizontal




Limit * Final Test ---- Horizontal

| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|------------|
| 1 | 467.4700 | -69.70 | -33.99 | -13.00 | 20.99 | 35.71 | 141 | Horizontal |
| 2 | 1648.6649 | -41.03 | -43.13 | -13.00 | 30.13 | -2.10 | 351 | Horizontal |
| 3 | 3304.4054 | -26.50 | -22.67 | -13.00 | 9.67 | 3.83 | 351 | Horizontal |
| 4 | 3855.5356 | -32.20 | -27.61 | -13.00 | 14.61 | 4.59 | 341 | Horizontal |

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Fasting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





Measurement Result for 12.5 KHz Channel Separation @ 467.6375MHz-0.5W-Vertical

Limit # Final Test ---- Vertical


| NO. | Freq. [MHz] | Reading [dBm] | Level [dBm] | Limit [dBm] | Margin [dB] | Factor [dB] | Angle [°] | Polarity |
|-----|----------------|------------------|----------------|----------------|----------------|----------------|--------------|----------|
| 1 | 467.4700 | -69.23 | -33.30 | -13.00 | 20.30 | 35.93 | 230 | Vertical |
| 2 | 1403.0653 | -43.30 | -41.78 | -13.00 | 28.78 | 1.52 | 343 | Vertical |
| 3 | 3297.3547 | -29.33 | -26.21 | -13.00 | 13.21 | 3.12 | 351 | Vertical |
| 4 | 3844.9595 | -31.27 | -28.05 | -13.00 | 15.05 | 3.22 | 277 | Vertical |
| 5 | 4987.1737 | -43.70 | -39.82 | -13.00 | 26.82 | 3.88 | 359 | Vertical |

RESULT: PASS

Note:

- 1. Factor=Antenna Factor + Cable loss. (Below 1GHz)
- 2. Factor=Antenna Factor+ Cable loss-Pre-amplifier.(Above 1 GHz)
- 3. Margin=Limit-Level

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.





7.5 EMISSION MASK PLOT

Standard Applicable [FCC Part 95.1779] GMRS: Unwanted emissions shall be attenuated below the unmodulated carrier power in accordance with the following:

(1) At least 25 dB (decibels) on any frequency removed from the center of the authorized bandwidth by more than 50 %up to and including 100% of the authorized bandwidth.

(2) At least 35 dB on any frequency removed from the center of the authorized bandwidth by more than 100 % up to and including 250 % of the authorized bandwidth.

(3) At least 43 + 10 log10 (T) dB on any frequency removed from the center of the authorized bandwidth by more than 250 %.


The detailed procedure employed for Emission Mask measurements are specified as following:

- The transmitter shall be modulated by a 2.5 kHz audio signal,

- The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz.


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the selected "Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day affective in the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.






The Worst Emission Mask for channel 4 -4W-12.5K

The Worst Emission Mask for channel 11-4W-12.5K




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated festing/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and horization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.





The Worst Emission Mask for channel 19 -4W-12.5K

The Worst Emission Mask for channel 27-0.5W-12.5K



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated festing/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and horization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuence of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.



8. AUDIO LOW PASS FILTER RESPONSE 8.1.PROVISIONS APPLICABLE

§95.1775 GMRS modulation requirements

Audio filter. Each GMRS transmitter type must include audio frequency low pass filtering, unless it complies with the applicable paragraphs of §95.1779 (without filtering).

The filter must be between the modulation limiter and the modulated stage of the transmitter.

At any frequency (f in kHz) between 3 and 20 kHz, the filter must have an attenuation of at least 60 log (f/3) dB more than the attenuation at 1 kHz. Above 20 kHz, it must have an attenuation of at least 50 dB more than the attenuation at 1 kHz

8.2.TEST PROCEDURE

- (1) The DUT transmitter output port was connected to Modulation Analyzer.
- (2) Path loss for the measurement included.
- (3) Press 23.1SPCL on modulation analyzer to enable the external LO from SIgen.
- (4) Set the Sigen frequency to Fc + 1.5MHz, RF output level to 0dBm without modulation.
- (5) Transmit the radio and set the audio analyzer to 1 kHz audio frequency and 60% of the maximum deviation.
- (6) Up the amplitude by 20dB.
- (7) On DSA, get the reference point to 0dB.
- (8) Vary the frequency on audio analyzer from 3 kHz to 30 kHz, record the audio tone from DSA.

8.3 TEST CONFIGURATION

RF Communication Test set

ion Audio output Transmitter Under Test EUT

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphorization of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



8.4 TEST RESULT

TEST CHANNEL: 11

| Audio | Response | Limit | |
|-----------|-------------|--------|--|
| Frequency | Attenuation | (dB) | Audio Frequency Low Pass Filter Response |
| (kHz) | (dB) | | |
| 1 | 0 | / | -5.00 |
| 3 | -2.01 | 0.00 | ₽ ,1500 |
| 4 | -9.73 | -7.50 | |
| 5 | -16.97 | -13.31 | 99 -15.00 -25.00 -35.00 |
| 6 | -23.31 | -18.06 | ¥ -35.00 |
| 7 | -30.50 | -22.08 | |
| 8 | -35.68 | -25.56 | ž -55.00 |
| 9 | -39.88 | -28.63 | -65.00 |
| 10 | -44.73 | -31.37 | 1 10 100 Audio Frequency (kHz) |
| 15 | -56.71 | -41.94 | Response Attenuation (dB) |
| 20 | -63.58 | -50.00 | |
| 30 | -62.88 | -50.00 | |
| 50 | -61.69 | -50.00 | |
| 70 | -62.47 | -50.00 | |

Note: All the modes had been tested, but only the worst data recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Fasting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



9. MAXIMUMN TRANSMITTER POWER 9.1 PROVISIONS APPLICABLE

FCC Part 95.1767 For GMRS, the maximum permissible transmitter output power effective radiated power (e.r.p.) as follows.

This section contains transmitting power limits for GMRS stations. The maximum transmitting power depends on which channels are being used and the type of station.

(a)462/467 MHz main channels. The limits in this paragraph apply to stations transmitting on any of the 462 MHz main channels or any of the 467 MHz main channels. Each GMRS transmitter type must be capable of operating within the allowable power range. GMRS licensees are responsible for ensuring that their GMRS stations operate in compliance with these limits.

(1)The transmitter output power of mobile, repeater and base stations must not exceed 50 Watts.

(2)The transmitter output power of fixed stations must not exceed 15 Watts.

(b)462 MHz interstitial channels. The effective radiated power (ERP) of mobile, hand-held portable and base stations transmitting on the 462 MHz interstitial channels must not exceed 5 Watts.

(c)467 MHz interstitial channels. The effective radiated power (ERP) of hand-held portable units

transmitting on the 467 MHz interstitial channels must not exceed 0.5 Watt. Each GMRS transmitter type capable of transmitting on these channels must be designed such that the ERP does not exceed 0.5 Watt.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand in spectrum of the stand in the report is not permitted without the written authorization of AGE in the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day authorization of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



9.2 TEST PROCEDURE

- (1)EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made. The radiated emission measurements of all transmit frequencies in all channels were measured with peak detector
- (2)A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver
- (3)The EUT is then put into continuously transmitting mode at its maximum power level during the test.Set Test Receiver or Spectrum RBW=100kHz,VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
- (4)The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
- (5)A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
- The measurement results are obtained as described below: Power(EIRP)=PMea- PAg Pcl Ga The measurement results are amend as described below:

Power(EIRP)=PMea- Pcl - Ga

- (6)This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
- (7)ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.
- (8)Test the EUT in the lowest channel, the middle channel the Highest channel


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the store of t



9.3 TEST CONFIGURATION

Effective Radiated Power


Radiated Below1GHz




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written aphroization of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

Radiated Above 1 GHz

AGC[®]





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuer of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com



9.4 TEST RESULT

The maximum Power (CP) for UHF is

Analog: 4W/0.5W for 12.5 KHz Channel Separation

Calculation Formula: CP = R + A + L

* Note:

CP: The final Conducted Power

R : The reading value from spectrum analyzer

A : The attenuation value of the used attenuator

L: The loss of all connection cables

ERP RESULT:

| Frequency | Reading Level | Antenna | S.G. | Cable Loss | Ant.Gain | Emission Level | Emission Level | Limit | Margin |
|---------------------------|------------------|--------------|-------|---------------|----------|-------------------|-------------------|-------|--------|
| (MHz) | (dBuv/m) | Polarization | (dBm) | (dB) | (dBi) | (dBm) | (W) | (W) | (W) |
| ChannelSeparation:12.5KHz | | | | | | | | 6 | |
| 462.6375 | 104.87 | V | 29.64 | 0.38 | 6.6 | 35.86 | 3.85 | 5 | 1.15 |
| 462.6375 | 104.75 | Н | 29.52 | 0.38 | 6.6 | 35.74 | 3.75 | 5 | 1.25 |
| 462.6500 | 104.84 | V | 29.61 | 0.38 | 6.6 | 35.83 | 3.83 | 50 | 46.17 |
| 462.6500 | 104.8 | ◎ H | 29.57 | 0.38 | 6.6 | 35.79 | 3.79 💿 | 50 | 46.21 |
| 467.6500 | 104.89 | V | 29.66 | 0.38 | 6.6 | 35.88 | 3.87 | 50 | 46.13 |
| 467.6500 | 104.77 | н | 29.54 | 0.38 | 6.6 | 35.76 | 3.77 | 50 | 46.23 |
| 467.6375 | 95.94 | V | 20.71 | 0.38 | 6.6 | 26.93 | 0.49 | 0.5 | 0.01 |
| 467.6375 | 95.88 | Н | 20.65 | 0.38 | 6.6 | 26.87 | 0.49 | 0.5 🛛 | 0.01 |

NOTE:

Calculation Formula:

Emission Level(dBm) = S.G.(dBm)- Cable Loss(dB)+ Ant.Gain(dBi)

The Ant. Gain including the correct factor 2.15.

Margin(dB) = Limit(dBm)- Emission Level(dBm)

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stead restro/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGS. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



10.SPURIOUS EMISSION ON ANTENNA PORT

10.1 PROVISIONS APPLICABLE

Please refer to FCC 47 CFR 2.1051, 2.1057 & 95.1779 for specification details. Emissions shall be attenuated below the mean output power of the transmitter as follows:

| FCC Rules | Attenuation Limit (dBc) |
|-----------|-----------------------------|
| § 95.1779 | At least 43 + 10 log (P) dB |

43 +10 log (Pwatts)

Note: In general, the worse case attenuation requirement shown above was applied.

Calculation: Limit (dBm) =EL-43-10log10 (TP)

EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is P(dBm)

Limit (dBm) = P(dBm)-43-10 log (Pwatts) = -13dBm

10.2 TEST PROCEDURE

- 1. The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation.
- 2. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to show any out of band emission up to 10th . Harmonic for the lower and the highest frequency range.
- 3. Set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz, while set RBW=1MHz.VBW=3MHz from the 1GHz to 10th Harmonic.
- 4. The audio input was set the unmodulated carrier, the resulting picture is print out for each channel separation.

10.3 TEST CONFIGURATION



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand in spectrum of the stand in the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



10.4 TEST RESULT

Not applicable Note: The product is a non-detachable antenna, no need to evaluate this test.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Pesting/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written approver, and the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issuerce of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



11. MODULATION CHARACTERISTICS 11.1 PROVISIONS APPLICABLE

According to [FCC Part 95.1775, Part 2.1047(a)], for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

Part 95.1775(a) A GMRS unit that transmits emission type F3E must not exceed a peak frequency deviation of plus orminus 2.5 kHz, and the audio frequency response must not exceed 3.125 kHz.

Part 2.1047(a) A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of100 to 5000Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing thefrequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shallbe submitted.

11.2 MEASUREMENT METHOD

11.2.1 Modulation Limit

- (1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1KHz using this level as a reference (0dB) and vary the input level from –20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- (2). Repeat step 1 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

11.2.2 Audio Frequency Response

- Personal Radio Service stations that transmit voice emissions may also transmit audible or subaudible tones or other signals for the purpose of selective calling and/or receiver squelch activation. These tones and signals are ancillary to voice communications and are considered to be included within the voice emission types, e.g., A3E, F3E, and G3E.
- (a) Tones that are audible (having a frequency higher than 300 Hertz), must last no longer than 15 seconds at one time.
- (b) Tones that are subaudible (having a frequency of 300 Hertz or less), may be transmitted continuously during a communication session.
 - (1). Configure the EUT as shown in figure 1.
 - (2). Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0 dB).
 - (3). Vary the Audio frequency from 100 Hz to 10 KHz and record the frequency deviation.
 - (4). Audio Frequency Response = 20log10 (Deviation of test frequency/Deviation of 1 KHz reference).






11.3 MEASUREMENT RESULT

TEST CHANNEL: 11

(A). MODULATION LIMIT:

| Modulation Level (dB) | Peak Freq. Deviation At 300 Hz | Peak Freq. Deviation At 1000 Hz | Peak Freq. Deviation At 1500 Hz | Peak Freq. Deviation At 3000 Hz |
|-----------------------------|--------------------------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| -20 | 0.15 | 0.47 | 0.69 | 1.01 |
| -15 | 0.32 | 0.58 | 0.85 | 1.26 |
| -10 | 0.41 | 0.69 | 0.99 | 1.37 |
| -5 | 0.5 | 1.05 | 1.14 | 1.49 |
| 0 | 0.85 | 1.21 | 1.36 | 1.58 |
| +5 | 0.91 | 1.24 | 1.44 | 1.77 |
| +10 | 1.03 | 1.32 | 1.52 | 1.85 |
| +15 | 1.26 | 1.35 | 1.71 | 1.97 |
| +20 | 1.24 | 1.34 | 1.69 | 1.95 |



Note: 1.All the modes had been tested, but only the worst data recorded in the report. 2. The data unit evaluated in this report is "KHz"

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the stand of the stand of the test results of the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day affective report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.




(B). AUDIO FREQUENCY RESPONSE:


462.6500MHz @ 12.5 KHz Channel Separations-4W

| Frequency (Hz) | Deviation (KHz) | Audio Frequency Response(dB) | |
|----------------|-----------------|---------------------------------|--|
| 100 | | | |
| 200 | | - 0 | |
| 300 | 0.09 | -26.44 | |
| 400 | 0.16 | -21.45 | |
| 500 | 0.65 | -9.27 | |
| 600 | 0.85 | -6.94 | |
| 700 | 1.12 | -4.54 | |
| 800 | 1.52 | -1.89 | |
| 900 | 1.65 | -1.18 | |
| 1000 | 1.89 | 0.00 | |
| 1200 | 2.11 | 0.96 | |
| 1400 | 2.15 | 1.12 | |
| 1600 | 2.32 | 1.78 | |
| 1800 | 2.48 | 2.36 | |
| 2000 | 2.96 | 3.90 | |
| 2400 | 3.15 | 4.44 | |
| 2500 | 3.19 | 4.55 | |
| 2800 | 3.23 | 4.65 | |
| 3000 | 3.25 | 4.71 | |
| 3200 | 2.74 | 3.23 | |
| 3600 | 2.69 | 3.07 | |
| 4000 | 2.47 | 2.32 | |
| 4500 | 2.13 | 1.04 | |
| 5000 | 1.47 | -2.18 | |
| 5500 | 1.13 | -4.47 | |
| 6000 | 0.43 | -12.86 | |
| 6500 | 0.32 | -15.43 | |
| 7000 | 0.14 | -22.61 | |
| 7500 | 0.05 | -31.55 | |
| 9000 | | - | |
| 10000 | | - Ci - 0 | |
| 14000 | - | - ~C | |
| 18000 | -6 - 0 | | |
| 20000 | | | |
| 30000 | · · · | <u>-C</u> | |

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the step of the destination of the stamp. The test results are presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Frequency Response Result



Note: All the modes had been tested, but only the worst data recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the bedicated resting/inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGE. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com



APPENDIX I: PHOTOGRAPHS OF SETUP RADIATED EMISSION TEST SETUP



RADIATED EMISSION ABOVE 1G TEST SETUP




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the submitted restriction of AGE the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15day after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agc-cert.com





APPENDIX II: PHOTOGRAPHS OF EUT

Please refer to the project number: AGC02294200806AP01

----END OF REPORT----

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Festiva/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter approximation of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc-cert.com.



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. The non-CMA report issued by AGC is only permitted to be used by the client as internal reference use and shall not be used for public demonstration purpose.

5. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

6. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

7. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

9. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

10. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the Bedicated Perturn/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the writter authorization of AGC, the test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issues of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc@agc~cert.com.