Applicant/Grantee								
FCC ID:		2AJIC-HB300N						
Section 15.212 Modular Transmitters								
Reques	t for Modula	r Approval 🛛 Requ	uest for Limited Modular Approval					
		Requirements	EUT Conditions	Comply (Y/N)				
Single Modular Approval Requirements								
1	transmitte shielding. tuning cap external to elements.	elements of the modular r must have their own The physical crystal and acitors may be located o the shielded radio	Shi elding Case	Y				
2	The modular transmitter must have buffered modulation/ data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.		Internal buffer	Y .				
3		ar transmitter must have wer supply regulation.	Internal regulator	Y				
4	The modul comply with transmission sections 15 15.204(c). be perman a "unique" connection and the and cable). The installation 15.203 is not can approvals uthis section	ar transmitter must in the antenna and on system requirements of 5.203, 15.204(b) and The antenna must either ently attached or employ antenna coupler (at all is between the module tenna, including the e "professional" provision of Section of applicable to modules ply to limited modular under paragraph (b) of n.	Confirmed	Y				
5	tested in a configuration to be inside testing for requirement transmitted powered, if AC line confound in Sepower lines connections.	ar transmitter must be stand-alone on, i.e., the module must de another device during compliance with Part 15 ats. Unless the module will be battery to must comply with the aducted requirements action 15.207. AC or DC and data input/output acted to the module must a ferrites; unless they will	Confirmed	Y				

.

		10.00	
	be marketed with the module (see		
	Section 15.27(a)). The length of		
	these lines shall be the length		
	typical of actual use or, if that		
	length is unknown, at least 10		
	centimeters to insure that there is		
	1		
	no coupling between the case of the		
	module and supporting equipment.		
	Any accessories, peripherals, or		
	support equipment connected to the		
	module during testing shall be		
			i
	unmodified and commercially		
	available (see Section 15.31(i)).		
6	The modular transmitter must be	Confirmed	Υ
•		San and the second	:
1	equipped with either a permanently		
	affixed label or must be capable of		
	electronically displaying its FCC		
1	identification number.		
1	(A) If using a permanently affixed label,		
	the modular transmitter must be labeled		
	with its own FCC identification number,		
1	•		
	and, if the FCC identification number is		}
1	not visible when the module is installed		
,			
1	inside another device, then the outside of		
İ	the device into which the module is		
	installed must also display a label referring		
	to the endosed module. This exterior label		
	can use wording such as the following:		
	"Contains Transmitter Module		[
			İ
	FCC ID: XYZMODEL1" or "Contains FCC ID:		
	XYZMODEL1." Any similar wording		
	that expresses the same meaning may be		
	used. The Grantee may either provide such		ì
	a label, an example of which must be		
	induded in the application for equipment		
	authorization, or, must provide adequate		
	instructions along with the module which		
	explain this requirement. In the latter		
	case, a copy of these instructions must be		
	induded in the application for equipment		
	authorization.		
	(B) If the modular transmitter uses an	İ	
	electronic display of the FCC identification		
	number, the information must be readily		
	accessible and visible on the modular		
	transmitter or on the device in which it is		
	installed. If the module is installed inside		
	another device, then the outside of the		
1	· · · · · · · · · · · · · · · · · · ·		
	device into which the module is installed		
	must display a label referring to the	İ	
	end osed module. This exterior label can		
	use wording such as the following:		
	"Contains FCC certified transmitter		
	module(s)." Any similar wording that		
	expresses the same meaning may be used.		
	The user manual must include instructions		
	on how to access the electronic display. A	ļ	
	copy of these instructions must be included		

	in the application for equipment authorization		
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Confirmed	Y
8	The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	Confirmed	Y

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, e.g., shielding, minimum signaling amplitude, buffered modulation/ data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

Derrick Lee / Manager

HB Wireless Communication Technology

Tel: 886227926009 Fax: 886227939328

E-mail: DerrickLee@hong-bo.com.tw