## FCC ID: 2AJIV-EF1010

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

## BR+EDR:

Antenna Type: PCB Antenna Antenna Gain:2.95dBi

| Modulation    | Channel<br>Freq.<br>(GHz) | Conduct<br>ed<br>power<br>(dBm) | Conducte<br>d power<br>(mW) | Tune-up<br>power<br>(dBm) | Max<br>tune-up<br>power<br>(dBm) | Max<br>tune-up<br>power<br>(mW) | Distance<br>(mm) | Result<br>calculatio<br>n | 1g SAR<br>Exclusion<br>threshold | SAR test exclusion |
|---------------|---------------------------|---------------------------------|-----------------------------|---------------------------|----------------------------------|---------------------------------|------------------|---------------------------|----------------------------------|--------------------|
| GFSK          | 2.402                     | 5.25                            | 3.350                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.234                     | 3.00                             | YES                |
|               | 2.441                     | 5.2                             | 3.311                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.244                     | 3.00                             | YES                |
|               | 2.480                     | 5.42                            | 3.483                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.254                     | 3.00                             | YES                |
| π/4-<br>DQPSK | 2.402                     | 5.45                            | 3.508                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.234                     | 3.00                             | YES                |
|               | 2.441                     | 5.38                            | 3.451                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.244                     | 3.00                             | YES                |
|               | 2.480                     | 5.58                            | 3.614                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.254                     | 3.00                             | YES                |
| 8DPSK         | 2.402                     | 5.33                            | 3.412                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.234                     | 3.00                             | YES                |
|               | 2.441                     | 5.18                            | 3.296                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.244                     | 3.00                             | YES                |
|               | 2.480                     | 5.58                            | 3.614                       | 5±1                       | 6.0                              | 3.981                           | <5               | 1.254                     | 3.00                             | YES                |

Conclusion:

Signature:

For the max result: 1.254≤ 3.0 for 1-g SAR, No SAR is required.

NAME AND TITLE (Please print or type): Alex /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Date: 2022-04-26