

TEST REPORT

CREATIVE LABS PTE. LTD. Applicant:

31 International Business Park #03-01, Singapore Address:

609921

Equipment Type: Sound Blaster Katana SE

Model Name: MF8415

Brand Name: CREATIVE

FCC ID: 2AJIV-MF8415

47 CFR Part 2.1091 **Test Standard:** KDB 447498 D04 v01

Sample Arrival Date: Feb. 01, 2023

Test Date: Feb. 01, 2023 - Feb. 11, 2023

Date of Issue: Apr. 21, 2023

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie zhu Checked by: Xiong Lining Approved by: Tolan Tu

(Testing Director)

Julie zhu

Liong Li Wing

Tolan la



Revision History

VersionIssue DateRevisions ContentRev. 01Apr. 21, 2023Initial Issue

TABLE OF CONTENTS

1	GENER	RAL INFORMATION	3
	1.1	Test Laboratory	3
	1.2	Test Location	3
2	PRODU	JCT INFORMATION	4
	2.1	Applicant Information	4
	2.2	Manufacturer Information	4
	2.3	General Description for Equipment under Test (EUT)	4
	2.4	Ancillary Equipment	4
	2.5	Technical Information	4
3	SUMMA	ARY OF TEST RESULT	5
	3.1	Test Standards	5
4	DEVICE	E CATEGORY AND LEVELS LIMITS	6
5	ASSES	SMENT RESULT	8
	5.1	Output Power	8
	5.2	Tune-up power	8
	5.3	RF Exposure Evaluation Result	8
	5.4	Conclusion	8



GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.		
Addross	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road,		
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China		
Phone Number	+86 755 6685 0100		

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.		
	☑ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi		
	Road, Nanshan District, Shenzhen, Guangdong Province, P. R.		
Location	China		
Location	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park,		
	No. 1008, Songbai Road, Yangguang Community, Xili Sub-district,		
	Nanshan District, Shenzhen, Guangdong Province, P. R. China		
Accreditation	The laboratory is a testing organization accredited by FCC as a		
Certificate	accredited testing laboratory. The designation number is CN1196.		



2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	CREATIVE LABS PTE. LTD.
Address	31 International Business Park #03-01, Singapore 609921

2.2 Manufacturer Information

Manufacturer	CREATIVE LABS PTE. LTD.		
Address	31 International Business Park #03-01, Singapore 609921		

2.3 General Description for Equipment under Test (EUT)

EUT Name	Sound Blaster Katana SE			
Model Name Under Test	MF8415			
Series Model Name	N/A			
Description of Model	1/4			
name differentiation	N/A			
Hardware Version	Thanos2-MF			
Software Version	V230418			
Dimensions (Approx.)	N/A			
Weight (Approx.)	N/A			

2.4 Ancillary Equipment

Note: Not applicable.

2.5 Technical Information

Network and Wireless	Bluetooth
connectivity	Diuetootii

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Bluetooth			
Frequency Range	Bluetooth	2400 ~ 2483.5 MHz		
Antenna Type	Bluetooth	PCB Antenna		
Exposure Category	General Population/Uncontrolled Exposure			
EUT Stage	Mobile Device			

Tel: +86-755-66850100 E-mail: qc@baluntek.com Page No. 4 / 9

Web: www.titcgroup.com Template No.: TRP-FCC-Mobile (2022-08-15)



3 SUMMARY OF TEST RESULT

3.1 Test Standards

No. Identity		Document Title			
1 47 CFR Part 2.1091		Radiofrequency radiation exposure evaluation: mobile devices			
2	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01			

Note: This model has two structures of boards, which are used to control the power on and off. Structure A: there is MM32F chip, and there is no R5F chip. Structure B: There is an R5F chip, but there is no MM32F chip, which has no effect on RF performance.



4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Device:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP20cm in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{\text{th }}(\text{mW}) = ERP_{20 \text{ cm }}(\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B.1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula (B.2).



$$P_{\text{th (mW)}} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\,\mathrm{cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

					Dis	stance	(mm)				
		5	10	15	20	25	30	35	40	45	50
(z)	300	39	65	88	110	129	148	166	184	201	217
(MHz)	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
Frequency	1900	3	12	26	44	66	92	122	157	195	236
edn	2450	3	10	_ 22	38	59	83	111	143	179	219
Fr	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169



5 ASSESSMENT RESULT

5.1 Output Power

GFSK	π/4-DQPSK	8-DPSK					
3.50	3.42	3.48					
Antenna Gain (dBi) 1.85							
EIRP (dBm) 5.35 5.27 5.33							
_	5.35	1.85					

Note: This table listed the worst case power value, please refer to BL-SZ2310712-601 report for more details.

5.2 Tune-up power

Mode	Peak Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)	
Bluetooth	[2.00,4.00]	[4.00,6.00]	[1.85,3.85]	

Note1: ERP= EIRP -2.15dB.

Note2: According KDB 447498 D04, used the greater of maximun Peak power and ERP to compare with the threshold value Pth.

5.3 RF Exposure Evaluation Result

Evolution mode	Maximum power	Maximum power	Distance	Threshold Power	Verdict
	(dBm)	(mw)	(cm)	(mW)	
Bluetooth	4	2.51	20	3060.00	Pass

5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.



Statement

- 1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
- 2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
- 3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
- 4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
- 5. The test data and results are only valid for the tested samples provided by the customer.
- 6. This report shall not be partially reproduced without the written permission of the laboratory.
- 7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

-- END OF REPORT--