

Appendix A: Effective (Isotropic) Radiated Power Output Data

Test Result

Band	Channel	PCL	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GSM850	128	5	33.97	26.82	38.45	PASS
GSM850	190	5	34.15	27	38.45	PASS
GSM850	251	5	34.36	27.21	38.45	PASS
GSM1900	512	0	29.91	29.91	33.00	PASS
GSM1900	661	0	30.52	30.52	33.00	PASS
GSM1900	810	0	30.35	30.35	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
GPRS850	128	5	1	34.00	26.85	38.45	PASS
GPRS850	128	5	2	31.13	23.98	38.45	PASS
GPRS850	128	5	3	28.97	21.82	38.45	PASS
GPRS850	128	5	4	26.70	19.55	38.45	PASS
GPRS850	190	5	1	34.17	27.02	38.45	PASS
GPRS850	190	5	2	31.24	24.09	38.45	PASS
GPRS850	190	5	3	29.09	21.94	38.45	PASS
GPRS850	190	5	4	26.84	19.69	38.45	PASS
GPRS850	251	5	1	34.40	27.25	38.45	PASS
GPRS850	251	5	2	31.23	24.08	38.45	PASS
GPRS850	251	5	3	29.05	21.9	38.45	PASS
GPRS850	251	5	4	26.81	19.66	38.45	PASS
GPRS1900	512	0	1	29.87	29.87	33.00	PASS
GPRS1900	512	0	2	27.80	27.8	33.00	PASS
GPRS1900	512	0	3	26.05	26.05	33.00	PASS
GPRS1900	512	0	4	23.97	23.97	33.00	PASS
GPRS1900	661	0	1	30.63	30.63	33.00	PASS
GPRS1900	661	0	2	28.02	28.02	33.00	PASS
GPRS1900	661	0	3	26.22	26.22	33.00	PASS
GPRS1900	661	0	4	24.15	24.15	33.00	PASS
GPRS1900	810	0	1	30.49	30.49	33.00	PASS
GPRS1900	810	0	2	27.84	27.84	33.00	PASS
GPRS1900	810	0	3	26.03	26.03	33.00	PASS
GPRS1900	810	0	4	23.95	23.95	33.00	PASS

Band	Channel	PCL	Slot	Conducted Power (dBm)	ERP/EIRP (dBm)	ERP/EIRP Limit (dBm)	Verdict
EGPRS850	128	8	1	25.99	18.84	38.45	PASS
EGPRS850	128	8	2	24.61	17.46	38.45	PASS
EGPRS850	128	8	3	22.42	15.27	38.45	PASS
EGPRS850	128	8	4	19.74	12.59	38.45	PASS
EGPRS850	190	8	1	26.44	19.29	38.45	PASS
EGPRS850	190	8	2	25.15	18	38.45	PASS
EGPRS850	190	8	3	22.79	15.64	38.45	PASS
EGPRS850	190	8	4	20.28	13.13	38.45	PASS
EGPRS850	251	8	1	25.98	18.83	38.45	PASS
EGPRS850	251	8	2	24.68	17.53	38.45	PASS
EGPRS850	251	8	3	22.43	15.28	38.45	PASS
EGPRS850	251	8	4	19.85	12.7	38.45	PASS
EGPRS1900	512	2	1	25.74	25.74	33.00	PASS
EGPRS1900	512	2	2	23.98	23.98	33.00	PASS
EGPRS1900	512	2	3	21.40	21.4	33.00	PASS
EGPRS1900	512	2	4	18.22	18.22	33.00	PASS
EGPRS1900	661	2	1	26.28	26.28	33.00	PASS
EGPRS1900	661	2	2	24.71	24.71	33.00	PASS
EGPRS1900	661	2	3	22.27	22.27	33.00	PASS
EGPRS1900	661	2	4	19.33	19.33	33.00	PASS
EGPRS1900	810	2	1	25.63	25.63	33.00	PASS
EGPRS1900	810	2	2	24.03	24.03	33.00	PASS
EGPRS1900	810	2	3	21.48	21.48	33.00	PASS
EGPRS1900	810	2	4	18.41	18.41	33.00	PASS

Remark: EIRP (dBm) = Conducted power (dBm) + Antenna Gain (dBi). (For GSM1900)

ERP (dBm) = EIRP (dBm) - 2.15 (dB). (For GSM850)


Appendix B: Peak-to-Average Ratio(CCDF)

Test Result

Band	Channel	PCL	Result(dB)	Limit(dB)	Verdict
GSM850	190	5	2.64	13	PASS
EGPRS850	190	8	5.73	13	PASS
GSM1900	661	0	2.75	13	PASS
EGPRS1900	661	2	5.58	13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





Appendix C: 26dB Bandwidth and Occupied Bandwidth

Test Result

Band	Channel	PCL	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM850	128	5	0.24221	0.3097	---	PASS
GSM850	190	5	0.24418	0.3082	---	PASS
GSM850	251	5	0.24318	0.3106	---	PASS
EGPRS850	128	8	0.24411	0.3070	---	PASS
EGPRS850	190	8	0.24478	0.3067	---	PASS
EGPRS850	251	8	0.24371	0.3106	---	PASS
GSM1900	512	0	0.24433	0.3147	---	PASS
GSM1900	661	0	0.24126	0.3152	---	PASS
GSM1900	810	0	0.24298	0.3095	---	PASS
EGPRS1900	512	2	0.24659	0.3112	---	PASS
EGPRS1900	661	2	0.24180	0.3030	---	PASS
EGPRS1900	810	2	0.24275	0.3069	---	PASS

Test Graphs







Appendix D: Band Edge

Test Result

Band	Channel	PCL	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM850	128	5	823.98	-24.40	-13	PASS
GSM850	251	5	849.02	-23.38	-13	PASS
EGPRS850	128	8	823.98	-32.79	-13	PASS
EGPRS850	251	8	849.00	-33.01	-13	PASS
GSM1900	512	0	1850.00	-26.93	-13	PASS
GSM1900	810	0	1910.00	-27.13	-13	PASS
EGPRS1900	512	2	1849.99	-19.86	-13	PASS
EGPRS1900	810	2	1910.01	-21.08	-13	PASS

Test Graphs






Appendix E: Conducted Spurious Emission

Test Result

Band	Channel	PCL	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM850	128	5	0.009~0.15MHz	0.01	-55.74	-33	PASS
GSM850	128	5	0.15~30MHz	0.15	-43.61	-13	PASS
GSM850	128	5	30~1000MHz	969.35	-45.12	-13	PASS
GSM850	128	5	1000~10000MHz	2472.4	-27.5	-13	PASS
GSM850	190	5	0.009~0.15MHz	0.01	-56.42	-33	PASS
GSM850	190	5	0.15~30MHz	0.16	-43.13	-13	PASS
GSM850	190	5	30~1000MHz	952.47	-43.58	-13	PASS
GSM850	190	5	1000~10000MHz	1673.2	-27.99	-13	PASS
GSM850	251	5	0.009~0.15MHz	0.01	-55.12	-33	PASS
GSM850	251	5	0.15~30MHz	0.17	-43.14	-13	PASS
GSM850	251	5	30~1000MHz	705.22	-45.83	-13	PASS
GSM850	251	5	1000~10000MHz	2546.5	-26.85	-13	PASS
GSM1900	512	0	0.009~0.15MHz	0.01	-59.21	-43	PASS
GSM1900	512	0	0.15~30MHz	0.15	-43.64	-23	PASS
GSM1900	512	0	30~1000MHz	838.04	-45.31	-13	PASS
GSM1900	512	0	1000~18000MHz	16547.07	-22.24	-13	PASS
GSM1900	661	0	0.009~0.15MHz	0.01	-57.45	-43	PASS
GSM1900	661	0	0.15~30MHz	0.16	-46.68	-23	PASS
GSM1900	661	0	30~1000MHz	847.87	-46	-13	PASS
GSM1900	661	0	1000~18000MHz	17009.47	-22.88	-13	PASS
GSM1900	810	0	0.009~0.15MHz	0.01	-58.32	-43	PASS
GSM1900	810	0	0.15~30MHz	0.15	-43.75	-23	PASS
GSM1900	810	0	30~1000MHz	754.46	-46.02	-13	PASS
GSM1900	810	0	1000~18000MHz	16949.97	-22.15	-13	PASS

Remark: All channel and all modulation had been tested, but only the worst case data displayed in this report.

Test Graphs





JianYan Testing Group Shenzhen Co., Ltd.


No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Project No.: JYTSZR2308042







Appendix F: Frequency Stability

Test Result

Reference Frequency: GSM850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	-6.36	-0.007602	±2.5	Pass
	-20	-7.20	-0.008606		
	-10	-7.85	-0.009383		
	0	-6.68	-0.007985		
	10	-9.27	-0.011081		
	20	-7.04	-0.008415		
	30	-6.13	-0.007327		
	40	-9.33	-0.011152		
	50	-5.81	-0.006945		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-13.53	-0.016173	±2.5	Pass
	3.85	-3.94	-0.004710		
	4.40	-6.62	-0.007913		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS850 Middle channel=190 Frequency=836.6MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	6.78	0.008104	±2.5	Pass
	-20	7.30	0.008726		
	-10	9.07	0.010842		
	0	4.26	0.005092		
	10	10.27	0.012276		
	20	5.71	0.006825		
	30	5.29	0.006323		
	40	4.62	0.005522		
	50	11.11	0.013280		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	11.56	0.013818	±2.5	Pass
	3.85	6.42	0.007674		
	4.40	7.46	0.008917		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: PCS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (℃)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	15.05	0.008005	Within authorized band for PCS 1900	Pass
	-20	8.23	0.004378		
	-10	9.33	0.004963		
	0	8.04	0.004277		
	10	5.00	0.002660		
	20	-1.65	-0.000878		
	30	-1.23	-0.000654		
	40	3.91	0.002080		
	50	-2.00	-0.001064		
Voltage					
Temperature (℃)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	-5.91	-0.003144	Within authorized band for PCS 1900	Pass
	3.85	4.04	0.002149		
	4.40	5.62	0.002989		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Reference Frequency: EGPRS1900 Middle channel=661 Frequency=1880MHz					
Temperature					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	12.85	0.006835	Within authorized band for PCS 1900	Pass
	-20	12.69	0.006750		
	-10	17.95	0.009548		
	0	4.23	0.002250		
	10	-3.94	-0.002096		
	20	5.55	0.002952		
	30	7.62	0.004053		
	40	15.30	0.008138		
	50	6.62	0.003521		
Voltage					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	3.45	2.52	0.001340	Within authorized band for PCS 1900	Pass
	3.85	0.74	0.000394		
	4.40	6.42	0.003415		
Remark: All channel had been tested, but only the worst case data displayed in this report.					

Appendix G: Modulation Characteristics

Test Result

Band	Channel	Result	Verdict
GSM850	190	PASS	PASS
EGPRS850	190	PASS	PASS
GSM1900	661	PASS	PASS
EGPRS1900	661	PASS	PASS

Remark: All channel had been tested, but only the worst case data displayed in this report.

Test Graphs

