



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Shanghai SmartPeak Technology Co.,Ltd.

Block 2, No.20 Xuhongzhong Rd, Xuhui District, Shanghai, China

FCC ID: 2AJMSP1000

Report Type: Original Report	Product Type: POS Terminal
Test Engineer: Hope Zhang	<i>Hope Zhang</i>
Report Number: RSHA1219001-00D	
Report Date: 2019-01-07	
Reviewed By: Oscar Ye RF Leader	<i>Oscar Ye</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §15.247 (I) & §1.1310 & §2.1093 - RF EXPOSURE	14
MEASUREMENT RESULT	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
CORRECTED FACTOR & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	22
APPLICABLE STANDARD	22
EUT SETUP	22
EMI TEST RECEIVER SETUP.....	23
TEST PROCEDURE	23
CORRECTED AMPLITUDE & MARGIN CALCULATION	23
TEST RESULTS SUMMARY	23
TEST DATA	24
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	60
APPLICABLE STANDARD	60
TEST PROCEDURE	60

TEST DATA	61
FCC §15.247(d) – BAND EDGE.....	64
APPLICABLE STANDARD	64
TEST PROCEDURE	64
TEST DATA	64
FCC §15.247(e) - POWER SPECTRAL DENSITY	69
APPLICABLE STANDARD	69
TEST PROCEDURE	69
TEST DATA	69

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Shanghai SmartPeak Technology Co.,Ltd.
Tested Model	P1000
Product Type	POS Terminal
Dimension	170mm(L)*82mm(W)*56mm(H)
Power Supply	DC 5V from adapter and DC 7.4V from battery

Adapter information:

Model: ASSA65w-050200

Input: AC 100-240V, 50/60Hz 0.45A

Output: DC 5.0V, 2.0A

**All measurement and test data in this report was gathered from production sample serial number: 20181219001.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2018-12-19)*

Objective

This report is prepared on behalf of Shanghai SmartPeak Technology Co.,Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 22H24E27 PCB, Part 90 PCB and Part 15.225 DXX submissions with FCC ID: 2AJMSP1000.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
18	2438	38	2478
19	2440	39	2480

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test software: The EUT was tested in the engineering mode


Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	Channel	Power Level
802.11b	1 Mbps	Low	19
		Middle	19
		High	19
802.11g	6 Mbps	Low	13
		Middle	13
		High	13
802.11n-HT20	MCS0	Low	10
		Middle	10
		High	10
BLE	1Mbps	/	Software default


Note: For Wi-Fi mode, the value of power level increases 4, the power attenuates 1dB.

Duty Cycle:


802.11b Mode Middle Channel




802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



BLE Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100.00	/	/	0.00
802.11g	100.00	/	/	0.00
802.11n-HT20	100.00	/	/	0.00
BLE	68.05%	0.426	2.35	1.67

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	0.8	EUT	Adapter

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2018-11-12	2019-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2016-12-26	2019-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2018-08-15	2019-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2018-08-27	2019-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
A.H.Systems, inc	Amplifier	2641-1	466	2018-09-11	2019-09-10
EM Electronics Corporation	Amplifier	EM18G40G	060726	2018-03-22	2019-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2018-08-05	2019-08-04
Narda	Attenuator	10dB	010	2018-08-15	2019-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2018-08-15	2019-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2018-08-15	2019-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2018-11-12	2019-11-11
Agilent	Power Meter	N1912A	MY5000492	2018-11-18	2019-11-17
Agilent	Power Sensor	N1921A	MY54210024	2018-11-18	2019-11-17
Narda	Attenuator	10dB	010	2018-08-15	2019-08-14
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
SmartPeak	RF Cable	SmartPeakC01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2018-11-30	2019-11-29
Rohde & Schwarz	LISN	ENV216	3560655016	2018-11-30	2019-11-29
BACL	Auto test Software	BACL-EMC	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2018-01-10	2019-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2018-08-15	2019-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (I) & §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For Wi-Fi:

Please refer to SAR Report:RSH181219050-20

For BLE:

For worst case:

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE	2402-2480	-2.00	0.63	5.0	0.2	3.0	Yes

Result: So the standalone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a FPC antenna for Wi-Fi and Bluetooth, and the antenna gain is 1.50 dBi, which is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Corrected Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V)} - \text{Corrected Amplitude (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	20.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa


The testing was performed by Hope Zhang on 2018-12-29.

Test Result: Compliant.

For Wi-Fi Mode:


EUT operation mode: Transmitting in 802.11g mode high channel (worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Comment
0.170	52.07	QP	9.000	L1	16.04	64.96	12.89	Compliance
0.170	35.35	AV	9.000	L1	16.04	54.96	19.61	Compliance
0.570	40.91	QP	9.000	L1	16.03	56.00	15.09	Compliance
0.570	28.36	AV	9.000	L1	16.03	46.00	17.64	Compliance
0.785	36.62	QP	9.000	L1	15.93	56.00	19.38	Compliance
0.785	22.97	AV	9.000	L1	15.93	46.00	23.03	Compliance
1.900	35.73	QP	9.000	L1	15.85	56.00	20.27	Compliance
1.900	22.16	AV	9.000	L1	15.85	46.00	23.84	Compliance
2.750	36.17	QP	9.000	L1	15.85	56.00	19.83	Compliance
2.750	24.06	AV	9.000	L1	15.85	46.00	21.94	Compliance
25.750	37.79	QP	9.000	L1	16.48	60.00	22.21	Compliance
25.750	30.22	AV	9.000	L1	16.48	50.00	19.78	Compliance

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Comment
0.180	48.05	QP	9.000	N	16.05	64.49	16.44	Compliance
0.180	32.26	AV	9.000	N	16.05	54.49	22.23	Compliance
0.350	38.85	QP	9.000	N	16.08	58.96	20.11	Compliance
0.350	23.12	AV	9.000	N	16.08	48.96	25.84	Compliance
0.550	36.58	QP	9.000	N	16.08	56.00	19.42	Compliance
0.550	21.99	AV	9.000	N	16.08	46.00	24.01	Compliance
2.850	32.40	QP	9.000	N	15.90	56.00	23.60	Compliance
2.850	19.13	AV	9.000	N	15.90	46.00	26.87	Compliance
3.400	32.85	QP	9.000	N	15.89	56.00	23.15	Compliance
3.400	17.28	AV	9.000	N	15.89	46.00	28.72	Compliance
25.850	37.92	QP	9.000	N	16.26	60.00	22.08	Compliance
25.850	30.83	AV	9.000	N	16.25	50.00	19.17	Compliance

Note:

- 1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Margin (dB) = Limit (dBµV) – Corrected Amplitude (dBµV)

For BLE Mode:


EUT operation mode: Transmitting in high channel (worst case)

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Comment
0.170	50.13	QP	9.000	L1	16.04	64.96	14.83	Compliance
0.170	32.19	AV	9.000	L1	16.04	54.96	22.77	Compliance
0.560	40.81	QP	9.000	L1	16.04	56.00	15.19	Compliance
0.560	27.87	AV	9.000	L1	16.04	46.00	18.13	Compliance
1.050	34.43	QP	9.000	L1	15.88	56.00	21.57	Compliance
1.050	22.51	AV	9.000	L1	15.88	46.00	23.49	Compliance
2.500	36.07	QP	9.000	L1	15.85	56.00	19.93	Compliance
2.500	24.91	AV	9.000	L1	15.85	46.00	21.09	Compliance
5.550	30.28	QP	9.000	L1	15.89	60.00	29.72	Compliance
5.550	20.74	AV	9.000	L1	15.89	50.00	29.26	Compliance
25.650	37.11	QP	9.000	L1	16.48	60.00	22.89	Compliance
25.650	29.69	AV	9.000	L1	16.48	50.00	20.31	Compliance

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Comment
0.170	50.29	QP	9.000	N	16.06	64.96	14.67	Compliance
0.170	40.42	AV	9.000	N	16.06	54.96	14.54	Compliance
0.350	38.65	QP	9.000	N	16.08	58.96	20.31	Compliance
0.350	26.48	AV	9.000	N	16.08	48.96	22.48	Compliance
0.550	36.30	QP	9.000	N	16.08	56.00	19.70	Compliance
0.550	22.08	AV	9.000	N	16.08	46.00	23.92	Compliance
3.250	32.32	QP	9.000	N	15.89	56.00	23.68	Compliance
3.250	17.66	AV	9.000	N	15.89	46.00	28.34	Compliance
8.600	27.59	QP	9.000	N	15.96	60.00	32.41	Compliance
8.600	17.59	AV	9.000	N	15.96	50.00	32.41	Compliance
25.700	38.16	QP	9.000	N	16.25	60.00	21.84	Compliance
25.700	29.99	AV	9.000	N	16.25	50.00	20.01	Compliance

Note:

- 1) Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	Detector	Duty Cycle	Measurement method
30 MHz - 1000 MHz	120 kHz	/	QP	/	QP
Above 1GHz	1MHz	3 MHz	PK	/	PK
	1MHz	3 MHz	RMS	≥98%	Ave
	1MHz	1/T	PK	<98%	Ave

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	24.1-24.8 °C
Relative Humidity:	48-50 %
ATM Pressure:	101.0-101.2kPa

The testing was performed by Hope Zhang from 2018-12-22 to 2019-01-04.

Test Result: Compliant.


EUT operation mode: Transmitting

For Wi-Fi Mode:

Spurious Emission Test:

30MHz-1GHz:

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case high channel of 802.11g mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	QuasiPeak (dBµV/m)	Height (cm)	Polar (H/V)				
30.019207	19.58	101.0	V	264.0	-3.9	40.00	20.42
38.360950	13.76	199.0	V	64.0	-9.6	40.00	26.24
118.562400	11.52	198.0	H	341.0	-11.4	43.50	31.98
143.092100	10.42	198.0	H	347.0	-12.1	43.50	33.08
179.801050	8.99	199.0	V	315.0	-13.6	43.50	34.51
251.541350	10.33	198.0	H	95.0	-12.0	46.00	35.67

1GHz-18GHz:

802.11b Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1238.000000	---	21.95	150.0	H	260.0	-9.1	54.00	32.05
1238.000000	31.76	---	150.0	H	260.0	-9.1	74.00	42.24
3067.200000	---	28.97	200.0	H	278.0	-1.5	54.00	25.03
3067.200000	39.60	---	200.0	H	278.0	-1.5	74.00	34.40
4824.000000	---	33.39	200.0	V	206.0	1.9	54.00	20.61
4824.000000	42.55	---	200.0	V	206.0	1.9	74.00	31.45
7236.000000	46.15	---	200.0	V	149.0	9.0	74.00	27.85
7236.000000	---	37.04	200.0	V	149.0	9.0	54.00	16.96
10856.600000	---	41.02	100.0	H	75.0	13.3	54.00	12.98
10856.600000	51.44	---	100.0	H	75.0	13.3	74.00	22.56
17561.400000	---	46.46	150.0	V	98.0	17.3	54.00	7.54
17561.400000	57.87	---	150.0	V	98.0	17.3	74.00	16.13

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1221.000000	---	21.93	150.0	V	2.0	-9.2	54.00	32.07
1221.000000	32.33	---	150.0	V	2.0	-9.2	74.00	41.67
3046.800000	---	27.89	200.0	V	165.0	-1.6	54.00	26.11
3046.800000	37.67	---	200.0	V	165.0	-1.6	74.00	36.33
4874.000000	---	32.25	100.0	V	281.0	1.9	54.00	21.75
4874.000000	40.95	---	100.0	V	281.0	1.9	74.00	33.05
7311.000000	47.30	---	150.0	V	0.0	9.2	74.00	26.70
7311.000000	---	38.27	150.0	V	0.0	9.2	54.00	15.73
10656.000000	---	42.05	150.0	V	330.0	13.0	54.00	11.95
10656.000000	51.82	---	150.0	V	330.0	13.0	74.00	22.18
17507.000000	---	46.54	200.0	H	185.0	17.2	54.00	7.46
17507.000000	57.00	---	200.0	H	185.0	17.2	74.00	17.00

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1357.000000	---	22.84	200.0	V	89.0	-8.4	54.00	31.16
1357.000000	31.69	---	200.0	V	89.0	-8.4	74.00	42.31
2999.200000	37.86	---	150.0	H	63.0	-1.6	74.00	36.14
2999.200000	---	29.74	150.0	H	63.0	-1.6	54.00	24.26
4924.000000	---	32.83	200.0	V	3.0	2.0	54.00	21.17
4924.000000	41.94	---	200.0	V	3.0	2.0	74.00	32.06
7386.000000	---	38.33	100.0	V	266.0	9.4	54.00	15.67
7386.000000	48.03	---	100.0	V	266.0	9.4	74.00	25.97
10428.200000	---	42.92	200.0	V	164.0	12.7	54.00	11.08
10428.200000	52.27	---	200.0	V	164.0	12.7	74.00	21.73
17622.600000	---	47.29	150.0	H	5.0	17.3	54.00	6.71
17622.600000	56.70	---	150.0	H	5.0	17.3	74.00	17.30

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV /m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1360.400000	31.99	---	100.0	H	175.0	-8.4	74.00	42.01
1360.400000	---	22.53	100.0	H	175.0	-8.4	54.00	31.47
3040.000000	38.25	---	150.0	H	5.0	-1.6	74.00	35.75
3040.000000	---	28.74	150.0	H	5.0	-1.6	54.00	25.26
4824.000000	---	32.45	100.0	V	39.0	1.9	54.00	21.55
4824.000000	40.89	---	100.0	V	39.0	1.9	74.00	33.11
7236.000000	---	37.17	200.0	V	287.0	9.0	54.00	16.83
7236.000000	46.07	---	200.0	V	287.0	9.0	74.00	27.93
10897.400000	---	40.80	100.0	H	191.0	13.3	54.00	13.20
10897.400000	51.21	---	100.0	H	191.0	13.3	74.00	22.79
17476.400000	---	46.83	200.0	V	68.0	17.1	54.00	7.17
17476.400000	56.92	---	200.0	V	68.0	17.1	74.00	17.08

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1380.800000	---	22.49	200.0	H	191.0	-8.3	54.00	31.51
1380.800000	31.66	---	200.0	H	191.0	-8.3	74.00	42.34
2968.600000	---	30.05	150.0	V	0.0	-1.8	54.00	23.95
2968.600000	37.73	---	150.0	V	0.0	-1.8	74.00	36.27
4874.000000	---	32.30	150.0	V	196.0	1.9	54.00	21.70
4874.000000	41.08	---	150.0	V	196.0	1.9	74.00	32.92
7311.000000	---	38.27	150.0	V	358.0	9.2	54.00	15.73
7311.000000	47.25	---	150.0	V	358.0	9.2	74.00	26.75
10387.400000	---	42.14	150.0	V	0.0	12.7	54.00	11.86
10387.400000	51.68	---	150.0	V	0.0	12.7	74.00	22.32
17639.600000	---	47.22	100.0	V	349.0	17.3	54.00	6.78
17639.600000	57.24	---	100.0	V	349.0	17.3	74.00	16.76

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1221.000000	---	22.32	200.0	H	277.0	-9.2	54.00	31.68
1221.000000	32.00	---	200.0	H	277.0	-9.2	74.00	42.00
3091.000000	---	28.81	150.0	V	142.0	-1.5	54.00	25.19
3091.000000	40.47	---	150.0	V	142.0	-1.5	74.00	33.53
4924.000000	---	32.77	200.0	V	110.0	2.0	54.00	21.23
4924.000000	41.57	---	200.0	V	110.0	2.0	74.00	32.43
7386.000000	---	38.53	150.0	V	245.0	9.4	54.00	15.47
7386.000000	47.86	---	150.0	V	245.0	9.4	74.00	26.14
11254.400000	---	42.60	150.0	V	239.0	13.2	54.00	11.40
11254.400000	53.11	---	150.0	V	239.0	13.2	74.00	20.89
17459.400000	---	45.98	200.0	H	190.0	17.0	54.00	8.02
17459.400000	56.22	---	200.0	H	190.0	17.0	74.00	17.78

802.11n-HT20 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel : 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1251.600000	32.35	---	150.0	V	121.0	-9.0	74.00	41.65
1251.600000	---	22.55	150.0	V	121.0	-9.0	54.00	31.45
3019.600000	39.07	---	200.0	H	359.0	-1.6	74.00	34.93
3019.600000	---	28.54	200.0	H	359.0	-1.6	54.00	25.46
4824.000000	---	32.35	200.0	V	308.0	1.9	54.00	21.65
4824.000000	41.37	---	200.0	V	308.0	1.9	74.00	32.63
7236.000000	46.26	---	100.0	V	0.0	9.0	74.00	27.74
7236.000000	---	38.29	100.0	V	0.0	9.0	54.00	15.71
10846.400000	---	41.66	100.0	V	105.0	13.3	54.00	12.34
10846.400000	51.27	---	100.0	V	105.0	13.3	74.00	22.73
17551.200000	---	46.59	150.0	V	154.0	17.2	54.00	7.41
17551.200000	56.95	---	150.0	V	154.0	17.2	74.00	17.05

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1343.400000	---	22.64	200.0	H	121.0	-8.5	54.00	31.36
1343.400000	32.28	---	200.0	H	121.0	-8.5	74.00	41.72
3033.200000	---	28.87	150.0	V	239.0	-1.6	54.00	25.13
3033.200000	38.84	---	150.0	V	239.0	-1.6	74.00	35.16
4874.000000	41.02	---	100.0	V	260.0	1.9	74.00	32.98
4874.000000	---	32.88	100.0	V	260.0	1.9	54.00	21.12
7311.000000	---	38.08	200.0	V	238.0	9.2	54.00	15.92
7311.000000	47.70	---	200.0	V	238.0	9.2	74.00	26.30
10380.600000	---	40.96	150.0	V	142.0	12.7	54.00	13.04
10380.600000	51.81	---	150.0	V	142.0	12.7	74.00	22.19
17445.800000	---	46.45	100.0	V	292.0	16.9	54.00	7.55
17445.800000	57.25	---	100.0	V	292.0	16.9	74.00	16.75

High Channel : 2462MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1272.000000	---	22.43	100.0	V	227.0	-8.9	54.00	31.57
1272.000000	31.27	---	100.0	V	227.0	-8.9	74.00	42.73
3094.400000	---	29.94	150.0	H	319.0	-1.5	54.00	24.06
3094.400000	39.77	---	150.0	H	319.0	-1.5	74.00	34.23
4924.000000	---	32.02	100.0	V	68.0	2.0	54.00	21.98
4924.000000	41.87	---	100.0	V	68.0	2.0	74.00	32.13
7386.000000	---	38.64	100.0	V	1.0	9.4	54.00	15.36
7386.000000	48.49	---	100.0	V	1.0	9.4	74.00	25.51
10758.000000	---	42.35	200.0	H	0.0	13.1	54.00	11.65
10758.000000	51.64	---	200.0	H	0.0	13.1	74.00	22.36
17537.600000	---	46.75	200.0	V	68.0	17.2	54.00	7.25
17537.600000	56.94	---	200.0	V	68.0	17.2	74.00	17.06

18GHz-25GHz:


Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case high channel of 802.11g mode in Z-axis of orientation was recorded

Horizontal



Date: 4.JAN.2019 15:39:15

Horizontal



Date: 4.JAN.2019 15:55:36

Fundamental Test & Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)

Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

802.11b Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	108.52	---	200.0	V	190.0	6.1	/	/
2412.000000	---	101.68	200.0	V	190.0	6.1	/	/
2412.000000	106.19	---	150.0	H	92.0	6.1	/	/
2412.000000	---	99.30	150.0	H	92.0	6.1	/	/
2390.000000	46.8	---	100.0	V	38.0	6.0	74.0	27.2
2390.000000	---	39.6	100.0	V	38.0	6.0	54.0	14.4
Middle Channel: 2437MHz								
2437.000000	109.04	---	150.0	V	349.0	6.2	/	/
2437.000000	---	101.94	150.0	V	349.0	6.2	/	/
2437.000000	106.99	---	100.0	H	237.0	6.2	/	/
2437.000000	---	99.85	100.0	H	237.0	6.2	/	/
High Channel: 2462MHz								
2462.000000	108.55	---	200.0	V	18.00	6.2	/	/
2462.000000	---	101.68	200.0	V	18.00	6.2	/	/
2462.000000	106.37	---	200.0	H	345.00	6.2	/	/
2462.000000	---	99.62	200.0	H	345.00	6.2	/	/
2483.500000	52.15	---	150.0	V	218.00	6.3	74.00	21.85
2483.500000	---	46.19	150.0	V	218.00	6.3	54.0	7.81

802.11g Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	106.62	---	150.0	V	297.0	6.1	/	/
2412.000000	---	90.32	150.0	V	297.0	6.1	/	/
2412.000000	104.39	---	200.0	H	313.0	6.1	/	/
2412.000000	---	87.94	200.0	H	313.0	6.1	/	/
2390.000000	67.73	---	100.0	V	293.0	6.0	74	6.27
2390.000000	---	51.06	100.0	V	293.0	6.0	54	2.94
Middle Channel: 2437MHz								
2437.000000	106.33	---	150.0	V	255.0	6.2	/	/
2437.000000	---	93.19	150.0	V	255.0	6.2	/	/
2437.000000	104.32	---	100.0	H	271.0	6.2	/	/
2437.000000	---	90.97	100.0	H	271.0	6.2	/	/
High Channel: 2462MHz								
2462.000000	106.19	---	100.0	V	311.00	6.20	/	/
2462.000000	---	92.97	100.0	V	311	6.2	/	/
2462.000000	103.78	---	150.0	H	238.00	6.20	/	/
2462.000000	---	90.72	150.0	H	238	6.2	/	/
2483.500000	---	48.79	150.0	V	0	6.3	54	5.21
2483.500000	61.13	---	150.0	V	335	6.3	74	12.87

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2412.000000	101.66	---	150.0	V	262.0	6.1	/	/
2412.000000	---	89.45	150.0	V	262.0	6.1	/	/
2412.000000	99.35	---	200.0	H	194.0	6.1	/	/
2412.000000	---	87.32	200.0	H	194.0	6.1	/	/
2390.000000	63.08	---	200.0	V	201.0	6.0	74	10.92
2390.000000	---	51.44	200.0	V	201.0	6.0	54	2.56
Middle Channel: 2437MHz								
2437.000000	100.69	---	250.0	V	340.0	6.2	/	/
2437.000000	---	88.79	250.0	V	340.0	6.2	/	/
2437.000000	98.55	---	200.0	H	14.0	6.2	/	/
2437.000000	---	86.50	200.0	H	14.0	6.2	/	/
High Channel: 2462MHz								
2462.000000	100.08	---	250.00	V	164.00	6.2	/	/
2462.000000	---	87.81	250.00	V	164.00	6.2	/	/
2462.000000	97.80	---	200.00	H	223.00	6.2	/	/
2462.000000	---	85.66	200.00	H	223.00	6.2	/	/
2483.500000	---	50.81	150.00	V	344.00	6.3	54	3.19
2483.500000	63.43	---	150.00	V	344.00	6.3	74	10.57

For BLE Mode:

Spurious Emission Test:

30MHz-1GHz

(The worst case **high channel of operation in the Z axis of orientation** was recorded)



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBμV/m)	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polar (H/V)				
31.106837	19.33	101.0	V	137.0	-4.7	40.00	20.67
39.886100	15.27	101.0	V	96.0	-10.6	40.00	24.73
109.708050	9.54	101.0	H	271.0	-13.1	43.50	33.96
130.650800	11.17	199.0	H	19.0	-11.6	43.50	32.33
212.090000	10.30	101.0	H	45.0	-12.3	43.50	33.20
286.162900	11.40	101.0	V	193.0	-10.9	46.00	34.60

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
2040.400000	35.50	---	200.0	H	62.0	-5.7	74.00	38.50
2040.400000	---	26.38	200.0	H	62.0	-5.7	54.00	27.62
3597.600000	39.42	---	100.0	V	138.0	-0.5	74.00	34.58
3597.600000	---	33.63	100.0	V	138.0	-0.5	54.00	20.37
4804.000000	42.42	---	200.0	V	255.0	1.8	74.00	31.58
4804.000000	---	33.28	200.0	V	255.0	1.8	54.00	20.72
7206.000000	---	37.64	150.0	V	174.0	8.9	54.00	16.36
7206.000000	46.93	---	150.0	V	174.0	8.9	74.00	27.07
9217.800000	50.42	---	150.0	H	244.0	11.6	74.00	23.58
9217.800000	---	41.48	150.0	H	244.0	11.6	54.00	12.52
14763.200000	55.00	---	100.0	V	314.0	14.1	74.00	19.00
14763.200000	---	45.09	100.0	V	314.0	14.0	54.00	8.91
17507.000000	---	47.86	150.0	H	110.0	17.2	54.00	6.14
17507000000	56.91	---	150.0	H	110.0	17.6	74.00	17.09

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	23.47	100.0	V	116.0	-7.2	54.00	30.53
1595.000000	32.76	---	100.0	V	116.0	-7.2	74.00	41.24
3060.400000	---	28.58	150.0	V	84.0	-1.5	54.00	25.42
3060.400000	38.82	---	150.0	V	84.0	-1.5	74.00	35.18
4880.000000	---	32.17	100.0	V	240.0	1.9	54.00	21.83
4880.000000	41.43	---	100.0	V	240.0	1.9	74.00	32.57
7320.000000	---	37.89	150.0	V	260.0	9.2	54.00	16.11
7320.000000	47.93	---	150.0	V	260.0	9.2	74.00	26.07
10373.800000	---	41.11	100.0	H	355.0	12.7	54.00	12.89
10373.800000	51.76	---	100.0	H	355.0	12.7	74.00	22.24
17544.400000	---	47.83	100.0	V	67.0	17.2	54.00	6.17
17544.400000	56.79	---	100.0	V	67.0	17.2	74.00	17.21

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1323.000000	---	21.44	100.0	H	164.0	-8.6	54.00	32.56
1323.000000	30.56	---	100.0	H	164.0	-8.6	74.00	43.44
3145.400000	---	28.13	150.0	V	196.0	-1.4	54.00	25.87
3145.400000	38.71	---	150.0	V	196.0	-1.4	74.00	35.29
4960.000000	---	31.67	100.0	V	303.0	2.0	54.00	22.33
4960.000000	40.53	---	100.0	V	303.0	2.0	74.00	33.47
7440.000000	---	38.30	150.0	V	239.0	9.6	54.00	15.70
7440.000000	47.13	---	150.0	V	239.0	9.6	74.00	26.87
10904.200000	---	41.40	100.0	V	291.0	13.3	54.00	12.60
10904.200000	50.11	---	100.0	V	291.0	13.3	74.00	23.89
17530.800000	---	46.88	150.0	H	11.0	17.2	54.00	7.12
17530.800000	57.26	---	150.0	H	11.0	17.2	74.00	16.74

18GHz-25GHz


(The worst case **high channel of operation in the Z axis of orientation** was recorded)

Horizontal



Date: 4.JAN.2019 16:14:05

Vertical



Date: 4.JAN.2019 16:33:21

Fundamental Test & Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)


Note:

- 1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
- Corrected Amplitude (dBµV /m) = Corrected Factor (dB/m) + Reading (dBµV)
- Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV /m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2402.000000	93.32	---	150.0	V	3.0	6.0	/	/
2402.000000	---	84.51	150.0	V	3.0	6.0	/	/
2402.000000	90.92	---	100.0	H	271.0	6.0	/	/
2402.000000	---	82.48	100.0	H	271.0	6.0	/	/
2390.000000	---	39.89	150.0	V	161.0	6.0	54	14.11
2390.000000	48.72	---	150.0	V	161.0	6.0	74	25.28
Middle Channel: 2440MHz								
2440.000000	92.41	---	250.0	V	36.0	6.2	/	/
2440.000000	---	83.21	250.0	V	36.0	6.2	/	/
2440.000000	90.01	---	100.0	H	37.0	6.2	/	/
2440.000000	---	80.86	100.0	H	37.0	6.2	/	/
High Channel: 2480MHz								
2480.000000	93.22	---	100.0	V	122.0	6.3	/	/
2480.000000	---	84.24	100.0	V	122.0	6.3	/	/
2480.000000	90.84	---	200.0	H	196.0	6.3	/	/
2480.000000	---	81.84	200.0	H	196.0	6.3	/	/
2483.500000	45.62	---	200.0	V	351.0	6.3	74	19.61
2483.500000	---	36.66	200.0	V	351.0	6.3	54	7.34

Conducted Spurious Emissions at Antenna Port


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	24.1-24.5 °C
Relative Humidity:	48-50 %
ATM Pressure:	101.0-101.2kPa


The testing was performed by Hope Zhang from 2018-12-21 to 2018-12-22.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
1	2412	9.08	≥0.5
6	2437	9.08	≥0.5
11	2462	8.60	≥0.5
802.11g Mode			
1	2412	16.47	≥0.5
6	2437	16.47	≥0.5
11	2462	16.47	≥0.5
802.11n-HT20 Mode			
1	2412	17.74	≥0.5
6	2437	17.56	≥0.5
11	2462	17.68	≥0.5
BLE Mode			
0	2402	0.733	≥0.5
19	2440	0.745	≥0.5
39	2480	0.745	≥0.5


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3


The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW \geq DTS bandwidth.
2. Set VBW \geq 3 x RBW.
3. Set span \geq 3 x RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data

Environmental Conditions

Temperature:	24.1 °C
Relative Humidity:	50 %
ATM Pressure:	101.2kPa


The testing was performed by Hope Zhang on 2018-12-22.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)	Result
802.11b Mode					
Low	2412	17.70	14.48	30	Pass
Middle	2437	17.29	13.31	30	Pass
High	2462	17.71	13.67	30	Pass
802.11g Mode					
Low	2412	18.61	11.33	30	Pass
Middle	2437	18.49	11.15	30	Pass
High	2462	18.79	11.41	30	Pass
802.11n-HT20 Mode					
Low	2412	15.85	8.64	30	Pass
Middle	2437	15.97	8.91	30	Pass
High	2462	15.79	8.52	30	Pass
BLE Mode					
Low	2402	-2.95	/	30	Pass
Middle	2440	-3.50	/	30	Pass
High	2480	-2.73	/	30	Pass


BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	24.1-24.8 °C
Relative Humidity:	48-50 %
ATM Pressure:	101.0-101.2kPa

The testing was performed by Hope Zhang from 2018-12-21 to 2018-12-22.

Test Result: Compliant.

EUT operation mode: Transmitting


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side



BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	24.1-24.8 °C
Relative Humidity:	48-50 %
ATM Pressure:	101.0-101.2kPa


The testing was performed by Hope Zhang from 2018-12-21 to 2018-12-22.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-8.37	≤8
Middle	2437	-8.19	≤8
High	2462	-7.30	≤8
802.11g mode			
Low	2412	-9.68	≤8
Middle	2437	-9.72	≤8
High	2462	-10.54	≤8
802.11n-HT20 mode			
Low	2412	-9.85	≤8
Middle	2437	-11.09	≤8
High	2462	-9.48	≤8
BLE mode			
Low	2402	-18.48	≤8
Middle	2440	-18.93	≤8
High	2480	-18.29	≤8


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



***** END OF REPORT *****