

## RF Exposure Requirements

---

Product Description: Bluetooth speaker

Model No.: KH-A1, KH-A2, KH-A3, KH-A5, KH-A7, KH-A8, KH-19, KH-J06, KH-J07, KH-J08, KH-J09, KH-J10, KH-J11, KH-J12, KH-J13, KH-J15, KH-J16, KH-J17, KH-J18, KH-J19

FCC ID: 2AJMUKH-A1

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2402-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 1.05dBm

Tune-Up output power: 1.5dBm

RF channel transmit frequency: 2402 MHz

Result: 0.44

Limit: 3.0

The exclusion thresholds is  $0.44 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.