

# SPOT CHECK REPORT

---

**FCC ID:** XMR2022EM060KGL  
**Applicant:** Quectel Wireless Solutions Co., Ltd  
**Product:** LTE-A Cat 6 M.2 Module  
**Model No.:** EM060K-GL  
**Brand Name:** Quectel  
**FCC Rule(s):** Part 96  
**Result:** Complies  
**Received Date:** 2023-09-22  
**Test Date:** 2023-09-25 ~ 2023-10-10

**Reviewed By:**

\_\_\_\_\_  
Sunny Sun

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.26-2015. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

Report No.	Version	Description	Issue Date	Note
2309RSU052-U5	V01	Initial Report	2023-10-26	Valid

Note: This report is prepared for FCC Class II permissive supplement to FCC ID: XMR2022EM060KGL adding a new antenna & modify the tune up power and related data.

---

## CONTENTS

Description	Page
<b>1. General Information</b> .....	<b>5</b>
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Testing Facility .....	5
1.4. Product Information.....	6
1.5. Radio Specification .....	6
1.6. Description of Available Antennas.....	7
1.7. Test Methodology .....	7
<b>2. Test Configuration</b> .....	<b>8</b>
2.1. Test System Connection Diagram.....	8
2.2. Test Environment Condition .....	8
<b>3. Measuring Instrument</b> .....	<b>9</b>
<b>4. Decision Rules and Measurement Uncertainty</b> .....	<b>10</b>
4.1. Decision Rules .....	10
4.2. Measurement Uncertainty.....	10
<b>5. Test Result</b> .....	<b>11</b>
5.1. Summary.....	11
5.2. Equivalent Isotropically Radiated Power Measurement .....	12
5.2.1. Test Limit .....	12
5.2.2. Test Procedure .....	12
5.2.3. Test Setting .....	12
5.2.4. Test Setup .....	13
5.2.5. Test Result .....	13
5.3. Radiated Spurious Emissions Measurement.....	14
5.3.1. Test Limit .....	14
5.3.2. Test Procedure .....	14
5.3.3. Test Setting .....	14
5.3.4. Test Setup .....	14
5.3.5. Test Result .....	15
<b>Appendix A - Test Result</b> .....	<b>16</b>
A.2 Equivalent Isotropically Radiated Power Test Result .....	16
A.6 Radiated Spurious Emissions Test Result .....	20
<b>Appendix B - Test Setup Photograph</b> .....	<b>21</b>

**Appendix C - EUT Photograph .....22**



#### 1.4. Product Information

Product Name	LTE-A Cat 6 M.2 Module
Model No.	EM060K-GL
Brand Name	Quectel
IMEI	Conducted sample: 867228050091049 Radiated sample: 857228050091213
3GPP Specification	WCDMA Band II/IV/V LTE FDD Band 2, 4, 5, 7, 12, 13, 14, 17, 25, 26, 30, 66, 71 LTE TDD Band 38, 41, 42, 43, 46, 48
GNSS Specification	GPS, GLONASS, Bei Dou, Galileo
Temperature Operating Range	-25 ~ 75 °C
Power Supply Rating	3.135 ~ 4.4Vdc, typical 3.7Vdc
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

#### 1.5. Radio Specification

E-UTRA Specification	
TX & Rx Frequency Range	Band 42/43/48: 3550 ~ 3700 MHz
Modulation	UL up to 16QAM & DL up to 64QAM
Device Type	End User Device
Power Class	3

### 1.6. Description of Available Antennas

Technology	Frequency Range (MHz)	Antenna Type	Max Peak Gain (dBi)
LTE Band 2	1850 ~ 1910	Dipole PIFA	0.25
LTE Band 4	1710 ~ 1755		1.47
LTE Band 5	824 ~ 849		1.10
LTE Band 7	2500 ~ 2570		2.40
LTE Band 12	699 ~ 716		1.30
LTE Band 13	777 ~ 787		1.30
LTE Band 14	788 ~ 798		1.30
LTE Band 17	704 ~ 716		1.30
LTE Band 25	1850 ~ 1915		0.25
LTE Band 26	814 ~ 849		1.30
LTE Band 30	2305 ~ 2315		-3.00
LTE Band 38	2570 ~ 2620		2.40
LTE Band 41	2496 ~ 2690		2.40
LTE Band 42	3450 ~ 3550		-1.80
LTE Band 43	3700 ~ 3800		0.60
LTE Band 48	3550 ~ 3700		0.60
LTE Band 66	1710 ~ 1780		1.47
LTE Band 71	663 ~ 698		1.22

Note 1: All antenna information (Antenna type and Peak Gain) is provided by the manufacturer.

Note 2: The typical antennas used to calculate the ERP (EIRP).


### 1.7. Test Methodology

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.26:2015
- FCC CFR 47 Part Part 96
- FCC KDB 971168 D01 v03r01: Power Meas License Digital Systems
- FCC KDB 971168 D02 v02r01: Misc Rev Approv License Devices
- FCC KDB 412172 D01 v01r01: Determining ERP and EIRP
- FCC KDB 940660 D01 v03 Part 96 CBRS Eqpt

## 2. Test Configuration

### 2.1. Test System Connection Diagram



### 2.2. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20% ~ 75%RH



### 3. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2024-05-15	WZ-AC2
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2024-09-17	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2024-05-23	WZ-AC2
Thermohygrometer	Mingle	ETH529	MRTSUE06170	1 year	2023-11-27	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2023-10-13	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2024-05-07	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2024-04-20	WZ-AC2
Horn Antenna	ETS	3117	MRTSUE06257	1 year	2024-09-23	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2023-11-05	WZ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06640	1 year	2024-01-12	WZ-AC2
Preamplifier	EMCI	EMC051845SE	MRTSUE06987	1 year	2024-09-07	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11038	1 year	2023-11-01	WZ-AC2
Communication Tester	R&S	CMW500	MRTSUE06243	1 year	2024-09-27	SIP-SR1
Communication Tester	R&S	CMW500	MRTSUE06243	1 year	2023-10-08	SIP-SR1
Thermohygrometer	testo	622	MRTSUE06629	1 year	2024-01-03	SIP-SR1
Communication Tester	R&S	CMW500	MRTSUE06881	1 year	2024-05-23	SIP-SR1
DC POWER MODULE	Keysight	N6743B	MRTSUE06905	N/A	N/A	SIP-SR1
DC POWER MODULE	Keysight	N6743B	MRTSUE06906	N/A	N/A	SIP-SR1
Signal Analyzer	Keysight	N9021B	MRTSUE06915	1 year	2023-12-28	SIP-SR1
Temperature Chamber	BAOYT	BYG-80CL	MRTSUE06932	1 year	2024-02-12	SIP-SR1
Shielding Room	MIX-BEP	SIP-SR1	MRTSUE06948	N/A	N/A	SIP-SR1

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_MF 7802	2.03C	RE Antenna & Turntable

## 4. Decision Rules and Measurement Uncertainty

### 4.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 4.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

Radiated Spurious Emissions	
The maximum measurement uncertainty is evaluated as:	
Coaxial:	9kHz~30MHz: 2.59dB
Coplanar:	9kHz~30MHz: 2.60dB
Horizontal:	30MHz~200MHz: 3.85dB
	200MHz~1GHz: 4.36dB
	1GHz~40GHz: 4.98dB
Vertical:	30MHz~200MHz: 4.06dB
	200MHz~1GHz: 5.28dB
	1GHz~40GHz: 4.91dB
Output Power	
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ):	
1.5dB	

## 5. Test Result

### 5.1. Summary

FCC Part Section(s)	Test Description	Test Condition	Test Result
96.41(b)	Equivalent Isotropic Radiated Power	Conducted	Pass
2.1053, 96.41(e)	Spurious Emissions	Radiated	Pass

**Notes:**

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

## 5.2. Equivalent Isotropically Radiated Power Measurement

### 5.2.1. Test Limit

The maximum effective isotropic radiated power (EIRP) End User Device is 23dBm/10MHz

### 5.2.2. Test Procedure

ANSI C63.26-2015 - Section 5.2.4.4.2 & 5.2.5.5

### 5.2.3. Test Setting

When the fundamental condition for average power measurements cannot be realized (i.e., the EUT can not be configured to transmit at full-power on a continuous basis (i.e., duty cycle < 98%) and the instrumentation cannot be configured to measure only during active full-power transmissions), then the following procedure can be used if the EUT duty cycle is constant (i.e., duty cycle variations are less than or equal to  $\pm 2\%$ ).

- a) Set span to 2 × to 3 × the OBW.
- b) Set RBW = 1% to 5% of the OBW.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Set number of measurement points in sweep  $\geq 2 \times$  span / RBW.
- e) Sweep time:
  - 1) Set = auto-couple, or
  - 2) Set  $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$  for single sweep (automation-compatible) measurement.
- f) Detector = power averaging (rms).
- g) Set sweep trigger to “free run.”
- h) Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time.
- i) Using the marker function to identify the maximum PSD.
- j) Add  $10 \log (1/\text{duty cycle})$  to the measured power level to compute the average power during continuous transmission. For example, add  $[10 \log (1/0.25)] = 6 \text{ dB}$  if the duty cycle is a constant 25%.

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation (1) as follows:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T \tag{1}$$

where


ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as  $P_{\text{Meas}}$ , e.g., dBm or dBW)

$P_{\text{Meas}}$  measured transmitter output power or PSD, in dBm or dBW

$G_T$  gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

For devices utilizing multiple antennas, see 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

#### 5.2.4. Test Setup



#### 5.2.5. Test Result

Refer to Appendix A.1.

### 5.3. Radiated Spurious Emissions Measurement

#### 5.3.1. Test Limit

Out of band emissions: The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

$E \text{ (dB}\mu\text{V/m)} = \text{EIRP (dBm)} - 20 \log D + 104.8$ ; where D is the measurement distance in meters. The emission limit equal to 55.3dB $\mu$ V/m.

#### 5.3.2. Test Procedure


ANSI C63.26-2015 - Section 5.2.7 & 5.5

#### 5.3.3. Test Setting


1. RBW = 1MHz
2. VBW  $\geq 3 \times$  RBW
3. Sweep time  $\geq 10 \times$  (number of points in sweep)  $\times$  (transmission symbol period)
4. Detector = Peak
5. Trace mode = max hold
6. The trace was allowed to stabilize

#### 5.3.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



**5.3.5. Test Result**

Refer to Appendix A.2.

## Appendix A - Test Result

### A.2 Equivalent Isotropically Radiated Power Test Result

Test Site	SIP-SR1	Test Engineer	Yoniter Yang
Test Date	2023-09-25 ~ 2023-10-10	Test Band	Band 42/43/48

Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Output Power (dBm/10MHz)	EIRP (dBm/10MHz)	Limit (dBm/10MHz)
QPSK						
3552.50	5	1	0	21.37	21.97	<23.00
3625.00				21.15	21.75	<23.00
3697.50				21.28	21.88	<23.00
3555.00	5	1	12	21.41	22.01	<23.00
3625.00				21.19	21.79	<23.00
3695.00				21.29	21.89	<23.00
3557.50	5	1	24	21.37	21.97	<23.00
3625.00				21.14	21.74	<23.00
3692.50				21.24	21.84	<23.00
3560.00	5	25	0	20.09	20.69	<23.00
3625.00				19.79	20.39	<23.00
3690.00				19.79	20.39	<23.00
3552.50	10	1	0	21.36	21.96	<23.00
3625.00				20.12	20.72	<23.00
3697.50				21.29	21.89	<23.00
3555.00	10	1	24	21.34	21.94	<23.00
3625.00				21.15	21.75	<23.00
3695.00				21.24	21.84	<23.00
3557.50	10	1	49	21.35	21.95	<23.00
3625.00				21.19	21.79	<23.00
3692.50				21.23	21.83	<23.00
3560.00	10	50	0	19.98	20.58	<23.00
3625.00				20.03	20.63	<23.00
3690.00				19.88	20.48	<23.00

Note: The EIRP (dBm/10MHz) = Output Power (dBm/10MHz) + Antenna Gain (dBi)



Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Output Power (dBm/10MHz)	EIRP (dBm/10MHz)	Limit (dBm/10MHz)
<b>QPSK</b>						
3552.50	15	1	0	21.29	21.89	<23.00
3625.00				21.08	21.68	<23.00
3697.50				21.28	21.88	<23.00
3555.00	15	1	37	21.34	21.94	<23.00
3625.00				21.13	21.73	<23.00
3695.00				21.24	21.84	<23.00
3557.50	15	1	74	21.39	21.99	<23.00
3625.00				21.25	21.85	<23.00
3692.50				21.31	21.91	<23.00
3560.00	15	75	0	18.73	19.33	<23.00
3625.00				18.45	19.05	<23.00
3690.00				18.77	19.37	<23.00
3552.50	20	1	0	21.36	21.96	<23.00
3625.00				21.08	21.68	<23.00
3697.50				21.23	21.83	<23.00
3555.00	20	1	49	21.35	21.95	<23.00
3625.00				21.14	21.74	<23.00
3695.00				21.15	21.75	<23.00
3557.50	20	1	99	21.45	22.05	<23.00
3625.00				21.26	21.86	<23.00
3692.50				21.16	21.76	<23.00
3560.00	20	100	0	18.29	18.89	<23.00
3625.00				17.41	18.01	<23.00
3690.00				17.40	18.00	<23.00
Note: The EIRP (dBm/10MHz) = Output Power (dBm/10MHz) + Antenna Gain (dBi)						

Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Output Power (dBm)	EIRP (dBm)	Limit (dBm)
<b>QPSK</b>						
3552.50	5	1	0	21.37	21.97	N/A
3625.00				21.15	21.75	N/A
3697.50				21.28	21.88	N/A
3555.00	5	1	12	21.41	22.01	N/A
3625.00				21.19	21.79	N/A
3695.00				21.29	21.89	N/A
3557.50	5	1	24	21.37	21.97	N/A
3625.00				21.14	21.74	N/A
3692.50				21.24	21.84	N/A
3560.00	5	25	0	20.38	20.98	N/A
3625.00				20.16	20.76	N/A
3690.00				20.28	20.88	N/A
3552.50	10	1	0	21.36	21.96	N/A
3625.00				20.12	20.72	N/A
3697.50				21.29	21.89	N/A
3555.00	10	1	24	21.34	21.94	N/A
3625.00				21.15	21.75	N/A
3695.00				21.24	21.84	N/A
3557.50	10	1	49	21.35	21.95	N/A
3625.00				21.19	21.79	N/A
3692.50				21.23	21.83	N/A
3560.00	10	50	0	20.37	20.97	N/A
3625.00				20.22	20.82	N/A
3690.00				20.31	20.91	N/A
Note: The EIRP (dBm) = Output Power (dBm) + Antenna Gain (dBi)						

Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Output Power (dBm)	EIRP (dBm)	Limit (dBm)
<b>QPSK</b>						
3552.50	15	1	0	21.29	21.89	N/A
3625.00				21.08	21.68	N/A
3697.50				21.28	21.88	N/A
3555.00	15	1	37	21.34	21.94	N/A
3625.00				21.13	21.73	N/A
3695.00				21.24	21.84	N/A
3557.50	15	1	74	21.39	21.99	N/A
3625.00				21.25	21.85	N/A
3692.50				21.31	21.91	N/A
3560.00	15	75	0	20.36	20.96	N/A
3625.00				20.19	20.79	N/A
3690.00				20.29	20.89	N/A
3552.50	20	1	0	21.36	21.96	N/A
3625.00				21.08	21.68	N/A
3697.50				21.23	21.83	N/A
3555.00	20	1	49	21.35	21.95	N/A
3625.00				21.14	21.74	N/A
3695.00				21.15	21.75	N/A
3557.50	20	1	99	21.45	22.05	N/A
3625.00				21.26	21.86	N/A
3692.50				21.16	21.76	N/A
3560.00	20	100	0	20.39	20.99	N/A
3625.00				20.18	20.78	N/A
3690.00				20.26	20.86	N/A
Note: The EIRP (dBm) = Output Power (dBm) + Antenna Gain (dBi)						

**A.6 Radiated Spurious Emissions Test Result**

Test Site	WZ-AC2	Test Engineer	Carl Jiang
Test Date	2023-09-29 ~ 2023-09-30	Test Band	LTE Band 42/43/48, 1RB, QPSK

Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB/m)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
Middle Channel							
7477.000	31.2	12.1	43.3	55.3	-12.0	Peak	Horizontal
9653.000	32.0	13.6	45.6	55.3	-9.7	Peak	Horizontal
7247.500	34.2	11.3	45.5	55.3	-9.8	Peak	Vertical
9950.500	31.9	13.9	45.8	55.3	-9.5	Peak	Vertical

Note: Measure Level (dB $\mu$ V/m) = Reading Level (dB $\mu$ V) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

## **Appendix B - Test Setup Photograph**

Refer to "2309RSU052-UT" file.

## Appendix C - EUT Photograph

Refer to "2309RSU052-UE" file.