



FCC RADIO TEST REPORT

FCC ID : 2AJN7-TP00128AUC
Equipment : Notebook Computer
Brand Name : Lenovo
Model Name : TP00128A
Applicant : LC Future Center Limited Taiwan Branch
7F., No. 780, Bei'an Rd., Zhongshan Dist., Taipei City 104, Taiwan
Manufacturer : LCFC (HeFei) Electronics Technology Co., Ltd.
No. 3188-1, Yungu Road (Hefei Export Processing Zone),
Hefei Economics & Technology Development Area, Anhui, CHINA
Standard : FCC 47 CFR Part 2, 96

Equipment: Foxconn T99W175 tested inside of Lenovo Notebook Computer.

The product was received on Jun. 03, 2021 and testing was started from Jun. 09, 2021 and completed on Jun. 26, 2021. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Product Specification of Equipment Under Test	5
1.3 Modification of EUT	5
1.4 Testing Location	6
1.5 Applied Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration	8
2.4 Frequency List of Low/Middle/High Channels.....	8
3 Radiated Test Items	10
3.1 Measuring Instruments.....	10
3.2 Test Setup	10
3.3 Test Result of Radiated Test.....	11
3.4 Radiated Spurious Emission	12
4 List of Measuring Equipment.....	13
5 Uncertainty of Evaluation	14
Appendix A. Test Results of Radiated Test	
Appendix B. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FG0N0620-02G	01	Initial issue of report	Jun. 30, 2021
FG0N0620-02G	02	1. Add remark description in summary of test result 2. Revise product feature of equipment under test	Sep. 29, 2021
FG0N0620-02G	03	Revise Antenna Information	Oct. 04, 2021



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	§2.1046	Conducted Output Power	Not Required	-
-	§96.41	Peak-to-Average Ratio	Not Required	-
-	§96.41	Effective Isotropic Radiated Power	Not Required	-
-	§2.1049 §96.41	Occupied Bandwidth	Not Required	-
-	§2.1051 §96.41	Conducted Band Edge Measurement	Not Required	-
-	§2.1051 §96.41	Conducted Spurious Emission	Not Required	-
-	§2.1055	Frequency Stability for Temperature & Voltage	Not Required	-
3.4	§2.1051 §96.41	Radiated Spurious Emission	Pass	Under limit 6.54 dB at 7362.000 MHz

Note:

1. This is a variant report by adding antenna manufacturer. All the test cases were performed on original report which can be referred to Sporton Report Number FG0N0620G. Based on the original report, the test cases were verified.
2. The Maximum EIRP power does not exceed the original grant.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sheng Kuo

Report Producer: Dara Chiu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Notebook Computer
Brand Name	Lenovo
Model Name	TP00128A
FCC ID	2AJN7-TP00128AUC
EUT supports Radios application	WCDMA/HSPA/LTE/5G NR/GNSS/NFC/UWB WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer.
2. Equipment: Foxconn T99W175 tested inside of Lenovo Notebook Computer.

WWAN Antenna Information				
MIMO 2 Antenna	Manufacturer	JYT/NVC	Peak gain (dBi)	-5.61
	Part number	JYAAE0155HR	Type	PIFA

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	3552.5 MHz ~ 3697.5 MHz
Rx Frequency	3552.5 MHz ~ 3697.5 MHz
Bandwidth	5 MHz / 10 MHz / 15 MHz / 20 MHz
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan
Test Site No.	Sporton Site No.
	03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature	22.3~26.4°C
Relative Humidity	58~66%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW3786

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ ANSI / TIA-603-E
- ♦ FCC 47 CFR Part 2, 96
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v03
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in Tablet Type (three orthogonal panels, X, Y, Z) and Notebook Type. The worst cases (Y plane) were recorded in this report.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel			
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H	
Radiated Spurious Emission	48	-	-				v	v					v			v	v	v
Remark	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																	

Test Items	Band	Bandwidth (MHz)										Modulation				RB #			Test Channel				
		20+20	20+15	15+20	20+10	10+20	20+5	5+20	15+15	15+10	10+15	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H		
Radiated Spurious Emission	48_CA	v									-	-	-	v				v			v	v	v
Remark	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.																						

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

2.4 Frequency List of Low/Middle/High Channels

LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560.0	3625.0	3690.0
15	Channel	55315	55990	56665
	Frequency	3557.5	3625.0	3692.5
10	Channel	55290	55990	56690
	Frequency	3555.0	3625.0	3695.0
5	Channel	55265	55990	56715
	Frequency	3552.5	3625.0	3697.5



LTE Band 48 Channel and Frequency List_CA					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
20 + 20	PCC	Channel	55340	55891	56442
		Frequency	3560	3615.1	3670.2
	SCC	Channel	55538	56089	56640
		Frequency	3579.8	3634.9	3690
20 + 15	PCC	Channel	55340	55916	56491
		Frequency	3560.0	3617.6	3675.1
	SCC	Channel	55511	56087	56662
		Frequency	3577.1	3634.7	3692.2
15 + 20	PCC	Channel	55318	55893	56469
		Frequency	3557.8	3615.3	3672.9
	SCC	Channel	55489	56064	56640
		Frequency	3574.9	3632.4	3690.0
20 + 10	PCC	Channel	55340	55941	56541
		Frequency	3560.0	3620.1	3680.1
	SCC	Channel	55484	56085	56685
		Frequency	3574.4	3634.5	3694.5
10 + 20	PCC	Channel	55295	55896	56496
		Frequency	3555.5	3615.6	3675.6
	SCC	Channel	55439	56040	56640
		Frequency	3569.9	3630.0	3690.0
20 + 5	PCC	Channel	55340	55965	56590
		Frequency	3560.0	3622.5	3685.0
	SCC	Channel	55457	56082	56707
		Frequency	3571.7	3634.2	3696.7
5 + 20	PCC	Channel	55273	55898	56523
		Frequency	3553.3	3615.8	3678.3
	SCC	Channel	55390	56015	56640
		Frequency	3565.0	3627.5	3690.0


3 Radiated Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz to 18GHz



For radiated emissions above 18GHz



3.3 Test Result of Radiated Test

Please refer to Appendix A.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



3.4 Radiated Spurious Emission

3.4.1 Description of Radiated Spurious Emission Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz .

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
ERP (dBm) = EIRP - 2.15
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is -40dBm/MHz



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jul. 14, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Jul. 13, 2021	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	37059 & 01	30MHz~1GHz	Oct. 11, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Oct. 10, 2021	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 11, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Oct. 10, 2021	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Nov. 23, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Nov. 22, 2021	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1212	1GHz~18GHz	May 18, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	May 17, 2022	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	00993	18GHz~40GHz	Nov. 19, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Nov. 18, 2021	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170980	18GHz~40GHz	Jan. 11, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Jan. 10, 2022	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 24, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Mar. 23, 2022	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY57280120	1GHz~26.5GHz	Jul. 20, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Jul. 19, 2021	Radiation (03CH12-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz~18GHz	Dec. 05, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Dec. 04, 2021	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz~40GHz	Dec. 11, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Jan. 15, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Jan. 14, 2022	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMB100A	101107	100kHz~40GHz	Dec. 04, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Dec. 03, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 11, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Dec. 10, 2021	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 22, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Feb. 21, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 22, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Feb. 21, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-12SS	SN2	1.2GHz Low Pass Filter	Mar. 17, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080-1200-15000-60SS	SN1	1.2GHz High Pass Filter	Mar. 17, 2021	Jun. 09, 2021 ~ Jun. 26, 2021	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN2	3GHz High Pass Filter	Jul. 14, 2020	Jun. 09, 2021 ~ Jun. 26, 2021	Jul. 13, 2021	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 09, 2021 ~ Jun. 26, 2021	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jun. 09, 2021 ~ Jun. 26, 2021	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 09, 2021 ~ Jun. 26, 2021	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Jun. 09, 2021 ~ Jun. 26, 2021	N/A	Radiation (03CH12-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.07 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.21 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.80 dB
---	---------



Appendix A. Test Results of Radiated Test

LTE Band 48

LTE Band 48 / 20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	7102	-52.82	-40	-12.82	-48.86	-62.78	1.78	11.74	H
	10653	-58.47	-40	-18.47	-56.06	-66.90	2.47	10.90	H
	14204	-54.86	-40	-14.86	-57.71	-63.70	2.87	11.71	H
	21307	-55.03	-40	-15.03	-76.84	-71.75	1.98	18.70	H
	24859	-52.52	-40	-12.52	-77.28	-68.53	2.07	18.07	H
	28411	-51.16	-40	-11.16	-76.47	-68.41	2.32	19.56	H
									H
	7102	-54.95	-40	-14.95	-50.6	-64.91	1.78	11.74	V
	10653	-58.89	-40	-18.89	-56.23	-67.32	2.47	10.90	V
	14204	-55.41	-40	-15.41	-57.99	-64.25	2.87	11.71	V
	21307	-55.03	-40	-15.03	-76.71	-71.75	1.98	18.70	V
	24859	-51.56	-40	-11.56	-77.53	-67.57	2.07	18.07	V
	28411	-49.23	-40	-9.23	-76.36	-66.48	2.32	19.56	V
									V
Middle	7232	-49.04	-40	-9.04	-45.21	-58.72	1.85	11.53	H
	10848	-57.61	-40	-17.61	-55.49	-65.94	2.57	10.90	H
	14464	-55.71	-40	-15.71	-58.31	-63.94	2.85	11.09	H
	18077	-54.09	-40	-14.09	-72.03	-70.32	1.76	17.98	H
	21696	-54.95	-40	-14.95	-76.35	-71.74	1.99	18.78	H
	25314	-52.03	-40	-12.03	-77.23	-68.63	2.14	18.74	H
									H
	7232	-56.47	-40	-16.47	-52.37	-66.16	1.85	11.53	V
	10848	-57.64	-40	-17.64	-55.31	-65.97	2.57	10.90	V
	14464	-56.10	-40	-16.10	-57.87	-64.34	2.85	11.09	V
	18077	-54.63	-40	-14.63	-71.64	-70.86	1.76	17.98	V
	21696	-54.69	-40	-14.69	-76.08	-71.48	1.99	18.78	V
	25314	-50.41	-40	-10.41	-76.08	-67.01	2.14	18.74	V
									V



LTE Band 48 / 20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	7362	-46.54	-40	-6.54	-42.52	-55.95	1.92	11.32	H
	11043	-58.32	-40	-18.32	-56.56	-66.64	2.63	10.95	H
	14724	-54.58	-40	-14.58	-58.23	-63.38	2.91	11.72	H
	18399	-55.38	-40	-15.38	-73.65	-71.43	1.87	17.92	H
	22084	-55.51	-40	-15.51	-77.41	-72.30	2.08	18.87	H
	25770	-51.65	-40	-11.65	-77.54	-68.67	2.03	19.05	H
									H
	7362	-53.22	-40	-13.22	-49.02	-62.63	1.92	11.32	V
	11043	-58.35	-40	-18.35	-56.43	-66.67	2.63	10.95	V
	14724	-55.74	-40	-15.74	-57.72	-64.54	2.91	11.72	V
	18399	-56.02	-40	-16.02	-73.41	-72.07	1.87	17.92	V
	22084	-55.05	-40	-15.05	-76.95	-71.84	2.08	18.87	V
	25770	-50.66	-40	-10.66	-77.73	-67.68	2.03	19.05	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 48C

LTE Band 48C / 20MHz+20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	7140	-53.10	-40	-13.10	-49.2	-62.98	1.80	11.68	H
	10705	-58.33	-40	-18.33	-56	-66.73	2.50	10.90	H
	14279	-55.28	-40	-15.28	-58.05	-63.95	2.86	11.53	H
	21418	-55.34	-40	-15.34	-76.87	-72.09	1.95	18.70	H
	24981	-52.28	-40	-12.28	-77.04	-68.47	2.08	18.27	H
	28556	-50.98	-40	-10.98	-76.21	-68.20	2.31	19.53	H
									H
	7140	-59.42	-40	-19.42	-55.17	-69.30	1.80	11.68	V
	10705	-58.45	-40	-18.45	-55.88	-66.85	2.50	10.90	V
	14279	-55.64	-40	-15.64	-57.98	-64.31	2.86	11.53	V
	21418	-55.35	-40	-15.35	-76.82	-72.10	1.95	18.70	V
	24981	-50.66	-40	-10.66	-76.57	-66.85	2.08	18.27	V
	28556	-49.08	-40	-9.08	-76.18	-66.30	2.31	19.53	V
									V
Middle	7250	-55.10	-40	-15.10	-51.24	-64.75	1.86	11.50	H
	10870	-57.58	-40	-17.58	-55.49	-65.90	2.58	10.90	H
	14498	-55.17	-40	-15.17	-57.74	-63.32	2.85	11.00	H
	18122	-54.05	-40	-14.05	-72.04	-70.25	1.77	17.98	H
	21751	-55.62	-40	-15.62	-77.04	-72.41	2.01	18.80	H
	25370	-51.83	-40	-11.83	-77.11	-68.50	2.15	18.82	H
									H
	7250	-58.76	-40	-18.76	-54.65	-68.41	1.86	11.50	V
	10870	-57.77	-40	-17.77	-55.48	-66.09	2.58	10.90	V
	14498	-55.97	-40	-15.97	-57.64	-64.12	2.85	11.00	V
	18122	-54.95	-40	-14.95	-72.02	-71.15	1.77	17.98	V
	21751	-55.14	-40	-15.14	-76.55	-71.93	2.01	18.80	V
	25370	-49.69	-40	-9.69	-76.26	-66.36	2.15	18.82	V
									V



LTE Band 48C / 20MHz+20MHz / QPSK									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Highest	7360	-52.00	-40	-12.00	-47.98	-61.41	1.91	11.32	H
	11040	-58.08	-40	-18.08	-56.32	-66.39	2.63	10.95	H
	14718	-54.16	-40	-14.16	-57.77	-62.95	2.91	11.70	H
	18399	-55.18	-40	-15.18	-73.45	-71.23	1.87	17.92	H
	22073	-55.01	-40	-15.01	-76.85	-71.80	2.08	18.87	H
	25758	-51.73	-40	-11.73	-77.6	-68.75	2.04	19.05	H
									H
	7360	-55.98	-40	-15.98	-51.77	-65.39	1.91	11.32	V
	11040	-58.37	-40	-18.37	-56.44	-66.68	2.63	10.95	V
	14718	-55.81	-40	-15.81	-57.78	-64.60	2.91	11.70	V
	18399	-56.17	-40	-16.17	-73.56	-72.22	1.87	17.92	V
	22073	-55.00	-40	-15.00	-76.84	-71.79	2.08	18.87	V
	25758	-50.27	-40	-10.27	-77.33	-67.29	2.04	19.05	V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.