



FCC RADIO TEST REPORT

FCC ID : 2AJN7-TP00141A
Equipment : Notebook Computer
Brand Name : Lenovo
Model Name : TP00141A
Applicant : LC Future Center Limited Taiwan Branch
7F., No.780, Beian Rd., Zhongshan Dist., Taipei
104, Taiwan
Manufacturer : LCFC (HeFei) Electronics Technology Co., Ltd.
No. 3188-1, Yungu Road (Hefei Export
Processing Zone), Hefei Economics &
Technology Development Area, Anhui, CHINA
Standard : FCC 47 CFR Part 2, 90(R)

Equipment: Quectel EM05-G tested inside of Lenovo Notebook Computer.

The product was received on Dec. 07, 2021 and testing was performed from Dec. 17, 2021 and completed on Jan. 21, 2022. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory



Table of Contents

History of this test report.....3
Summary of Test Result.....4
1 General Description5
 1.1 Product Feature of Equipment Under Test.....5
 1.2 Product Specification of Equipment Under Test.....5
 1.3 Modification of EUT5
 1.4 Testing Site.....6
 1.5 Applied Standards6
2 Test Configuration of Equipment Under Test7
 2.1 Test Mode.....7
 2.2 Connection Diagram of Test System.....7
 2.3 Support Unit used in test configuration and system8
 2.4 Frequency List of Low/Middle/High Channels8
3 Conducted Test Items.....9
 3.1 Measuring Instruments9
 3.2 Conducted Output Power Measurement and ERP10
4 Radiated Test Items11
 4.1 Measuring Instruments11
 4.2 Radiated Spurious Emission13
5 List of Measuring Equipment.....14
6 Uncertainty of Evaluation.....16
Appendix A. Test Results of Conducted Test
Appendix B. Test Results of Radiated Test
Appendix C. Test Setup Photographs



History of this test report

Report No.	Version	Description	Issued Date
FG1D0801C	01	Initial issue of report	Jan. 14, 2022
FG1D0801C	02	1. Adding Radiated Spurious Emission test data 2. Revise remark in section 2.1 3. Revise List of Measuring Equipment	Jan. 25, 2022



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
	§90.542 (a)(7)	Effective Radiated Power	Pass	-
-	-	Peak-to-Average Ratio	-	See Note
-	§2.1049	Occupied Bandwidth	-	See Note
-	§2.1053 §90.543 (e)(2)	Conducted Band Edge Measurement	-	See Note
-	§2.1051 §90.210 (n)	Emission Mask	-	See Note
-	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	-	See Note
-	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	-	See Note
4.2	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	Pass	Under limit 2.80 dB at 1584.000 MHz

Note: The module (Model: EM05-G) makes no difference after verifying output power, this report reuses test data from the module report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sheng Kuo

Report Producer: Cindy Liu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Notebook Computer
Brand Name	Lenovo
Model Name	TP00141A
FCC ID	2AJN7-TP00141A
Sample 1	EUT with ICT Antenna
Sample 2	EUT with Speed Antenna
EUT supports Radios application	WCDMA/HSPA/LTE/GNSS
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer.
2. Equipment: Quectel EM05-G tested inside of Lenovo Notebook Computer.

WWAN Antenna Information				
Main Antenna	Manufacturer	ICT	Peak gain (dBi)	0.70
	Part number	DC33001XA00	Type	PIFA
	Manufacturer	Speed	Peak gain (dBi)	0.90
	Part number	DC33001X900	Type	PIFA

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx Frequency	790.5 MHz ~ 795.5 MHz
Rx Frequency	760.5 MHz ~ 765.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	24.39 dBm
Type of Modulation	QPSK / 16QAM

1.3 Modification of EUT

No modifications are made to the EUT during all test items.



1.4 Testing Site

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333
Test Site No.	Sporton Site No.
	TH03-HY
Test Engineer	Benjamin Lin
Temperature (°C)	23.5~25
Relative Humidity (%)	49.4~52

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010
Test Site No.	Sporton Site No.
	03CH12-HY (TAF Code: 3786)
Test Engineer	Jack Cheng, Lance Chiang and Chuan Chu
Temperature (°C)	21.6~26.2°C
Relative Humidity (%)	56~68%
Remark	The Radiated Spurious Emission test item subcontracted to Sporton International Inc. Wensan Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ ANSI C63.26-2015
- ◆ FCC 47 CFR Part 2, Part 90(R)
- ◆ ANSI / TIA-603-E
- ◆ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ◆ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ◆ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.


2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	v	v	-	-	v	v	-	v	v	v	v	v	v
E.R.P	14	-	-	v	v	-	-	v	v	-	Max. Power					
Radiated Spurious Emission	14	-	-	v	v	-	-	v		-	v			v	v	v
Remark	<ol style="list-style-type: none"> The mark "v" means that this configuration is chosen for testing The mark "-" means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. Radiated spurious emission main test with Sample1, and spot check LTE Band 14 with Sample 2. 															

2.2 Connection Diagram of Test System





2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

2.4 Frequency List of Low/Middle/High Channels

LTE Band 14 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5


3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power Measurement and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.1.1 Test Setup


For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.2 Radiated Spurious Emission

4.2.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jan. 04, 2021	Dec. 20, 2021~ Dec. 31, 2021	Jan. 03, 2022	Radiation (03CH12-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 07, 2021	Jan. 20, 2022~ Jan. 21, 2022	Sep. 06, 2022	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	37059 & 01	30MHz~1GHz	Oct. 09, 2021	Dec. 20, 2021~ Jan. 21, 2022	Oct. 08, 2022	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D & N-6-06	35414 & AT-N0602	30MHz~1GHz	Oct. 09, 2021	Dec. 20, 2021~ Jan. 21, 2022	Oct. 08, 2022	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Oct. 25, 2021	Dec. 20, 2021~ Dec. 31, 2021	Oct. 24, 2022	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1212	1GHz~18GHz	May 18, 2021	Dec. 20, 2021~ Jan. 21, 2022	May 17, 2022	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-1328	1GHz~18GHz	Dec. 03, 2021	Jan. 20, 2022~ Jan. 21, 2022	Dec. 02, 2022	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 24, 2021	Dec. 20, 2021~ Jan. 21, 2022	Mar. 23, 2022	Radiation (03CH12-HY)
Preamplifier	Aglient	8449B	3008A02375	1GHz~26.5GHz	May 25, 2021	Dec. 20, 2021~ Jan. 21, 2022	May 24, 2022	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	17100018000 54002	1GHz~18GHz	Jun. 16, 2021	Dec. 20, 2021~ Dec. 31, 2021	Jun. 15, 2022	Radiation (03CH12-HY)
Preamplifier	E-INSTRUME NT TECH LTD.	ERA-100M-18G-5 6-01-A70	EC1900270	1GHz-18GHz	Dec. 27, 2021	Jan. 20, 2022~ Jan. 21, 2022	Dec. 26, 2022	Radiation (03CH12-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Jan. 15, 2021	Dec. 20, 2021~ Dec. 31, 2021	Jan. 14, 2022	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 15, 2021	Jan. 20, 2022~ Jan. 21, 2022	Oct. 14, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz~30MHz	Mar. 11, 2021	Dec. 20, 2021~ Dec. 31, 2021	Mar. 10, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY9837/4PE	9kHz~30MHz	Mar. 11, 2021	Jan. 20, 2022~ Jan. 21, 2022	Mar. 10, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30MHz~18GHz	Dec. 10, 2021	Dec. 20, 2021~ Jan. 21, 2022	Dec. 09, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30MHz~40GHz	Feb. 22, 2021	Dec. 20, 2021~ Jan. 21, 2022	Feb. 21, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30MHz~40GHz	Feb. 22, 2021	Dec. 20, 2021~ Jan. 21, 2022	Feb. 21, 2022	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15539/4	30MHz~18GHz	Feb. 22, 2021	Jan. 20, 2022~ Jan. 21, 2022	Feb. 21, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-12SS	SN2	1.2GHz Low Pass Filter	Mar. 17, 2021	Dec. 20, 2021~ Jan. 21, 2022	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080-12 00-15000-60SS	SN1	1.2GHz High Pass Filter	Mar. 17, 2021	Dec. 20, 2021~ Jan. 21, 2022	Mar. 16, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-2700-30 00-18000-60ST	SN2	3GHz High Pass Filter	Jul. 12, 2021	Dec. 20, 2021~ Jan. 21, 2022	Jul. 11, 2022	Radiation (03CH12-HY)
Filter	Wainwright	WHKX8-5872.5-6 750-18000-40ST	SN2	6.75GHz High Pass Filter	Mar. 17, 2021	Jan. 20, 2022~ Jan. 21, 2022	Mar. 16, 2022	Radiation (03CH12-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303B	TP140349	N/A	Sep. 30, 2021	Dec. 20, 2021~ Jan. 21, 2022	Sep. 29, 2022	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 20, 2021~ Jan. 21, 2022	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Dec. 20, 2021~ Jan. 21, 2022	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Dec. 20, 2021~ Jan. 21, 2022	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Dec. 20, 2021~ Jan. 21, 2022	N/A	Radiation (03CH12-HY)
Base Station (Measure)	Anritsu	MT8821C	6262025341	N/A	Oct. 05, 2021	Dec. 17, 2021	Oct. 04, 2022	Conducted (TH03-HY)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.10 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.39 dB
---	---------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power & ERP)

LTE Band 14 Maximum Average Power [dBm] (GT - LC = 0.9 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
10	1	0	QPSK		24.39		23.14	0.2061
10	1	25			23.81			
10	1	49			24.05			
10	25	0			23.06			
10	25	12			22.88			
10	25	25			22.97			
10	50	0			22.87			
10	1	0	16-QAM		22.66		21.65	0.1462
10	1	25			22.90			
10	1	49			22.83			
10	25	0			21.98			
10	25	12			22.08			
10	25	25			22.07			
10	50	0			22.04			
Limit	ERP < 3W			Result			Pass	

LTE Band 14 Maximum Average Power [dBm] (GT - LC = 0.9 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	ERP (dBm)	ERP (W)
5	1	0	QPSK	24.35	24.30	24.31	23.1	0.2042
5	1	12		23.71	23.81	23.81		
5	1	24		24.00	24.00	24.00		
5	12	0		22.98	23.05	23.04		
5	12	7		22.86	22.79	22.78		
5	12	13		22.96	22.97	22.89		
5	25	0		22.77	22.87	22.85		
5	1	0	16-QAM	22.59	22.60	22.58	21.65	0.1462
5	1	12		22.86	22.90	22.86		
5	1	24		22.77	22.75	22.79		
5	12	0		21.97	21.93	21.95		
5	12	7		22.08	21.98	22.08		
5	12	13		22.01	22.04	22.07		
5	25	0		21.96	21.95	21.96		
Limit	ERP < 3W			Result			Pass	



Appendix B. Test Results of Radiated Test

<Sample 1>

LTE Band 14

LTE Band 14 / 5MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1576	-48.10	-42.15	-5.95	-57.83	-53.44	0.90	8.39	H
	2368	-37.49	-13	-24.49	-51.63	-44.73	1.12	10.52	H
	3152	-55.29	-13	-42.29	-71.41	-63.51	1.30	11.66	H
									H
									H
									H
	1576	-48.35	-42.15	-6.20	-57.55	-53.69	0.90	8.39	V
	2368	-37.68	-13	-24.68	-51.59	-44.92	1.12	10.52	V
	3152	-54.49	-13	-41.49	-71.03	-62.71	1.30	11.66	V
									V
									V
									V
Middle	1584	-46.06	-42.15	-3.91	-55.72	-51.43	0.90	8.42	H
	2376	-39.19	-13	-26.19	-53.27	-46.44	1.12	10.53	H
	3160	-54.28	-13	-41.28	-70.42	-62.52	1.30	11.68	H
									H
									H
									H
	1584	-47.32	-42.15	-5.17	-56.51	-52.69	0.90	8.42	V
	2376	-41.17	-13	-28.17	-55.06	-48.42	1.12	10.53	V
	3160	-53.30	-13	-40.30	-69.88	-61.54	1.30	11.68	V
									V
									V
									V



Highest	1584	-44.95	-42.15	-2.80	-54.61	-50.32	0.90	8.42	H
	2384	-41.39	-13	-28.39	-55.42	-48.65	1.12	10.54	H
	3176	-54.14	-13	-41.14	-70.32	-62.41	1.30	11.72	H
									H
									H
									H
									H
	1584	-47.87	-42.15	-5.72	-57.06	-53.24	0.90	8.42	V
	2384	-42.97	-13	-29.97	-56.87	-50.23	1.12	10.54	V
	3176	-53.46	-13	-40.46	-70.10	-61.73	1.30	11.72	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 14 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1576	-47.08	-42.15	-4.93	-56.81	-52.42	0.90	8.39	H
	2368	-37.69	-13	-24.69	-51.83	-44.93	1.12	10.52	H
	3152	-55.13	-13	-42.13	-71.25	-63.35	1.30	11.66	H
									H
									H
									H
									H
	1576	-48.88	-42.15	-6.73	-58.08	-54.22	0.90	8.39	V
	2368	-38.96	-13	-25.96	-52.87	-46.20	1.12	10.52	V
	3152	-54.31	-13	-41.31	-70.85	-62.53	1.30	11.66	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



<Sample 2>

LTE Band 14

LTE Band 14 / 5MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1576	-54.46	-42.15	-12.31	-64.19	-59.80	0.90	8.39	H
	2368	-54.00	-13	-41.00	-68.14	-61.24	1.12	10.52	H
	3152	-54.20	-13	-41.20	-70.32	-62.42	1.30	11.66	H
									H
									H
									H
									H
	1576	-49.02	-42.15	-6.87	-58.22	-54.36	0.90	8.39	V
	2368	-50.77	-13	-37.77	-64.68	-58.01	1.12	10.52	V
	3152	-53.12	-13	-40.12	-69.66	-61.34	1.30	11.66	V
									V
									V
									V
									V
Middle	1584	-55.25	-42.15	-13.10	-64.91	-60.62	0.90	8.42	H
	2376	-48.36	-13	-35.36	-62.44	-55.61	1.12	10.53	H
	3160	-53.44	-13	-40.44	-69.58	-61.68	1.30	11.68	H
									H
									H
									H
	1584	-50.86	-42.15	-8.71	-60.05	-56.23	0.90	8.42	V
	2376	-56.19	-13	-43.19	-70.08	-63.44	1.12	10.53	V
	3160	-50.77	-13	-37.77	-67.35	-59.01	1.30	11.68	V
									V
									V
									V



Highest	1584	-54.47	-42.15	-12.32	-64.13	-59.84	0.90	8.42	H
	2384	-54.82	-13	-41.82	-68.85	-62.08	1.12	10.54	H
	3176	-54.04	-13	-41.04	-70.22	-62.31	1.30	11.72	H
									H
									H
									H
									H
	1584	-53.93	-42.15	-11.78	-63.12	-59.30	0.90	8.42	V
	2384	-49.83	-13	-36.83	-63.73	-57.09	1.12	10.54	V
	3176	-52.45	-13	-39.45	-69.09	-60.72	1.30	11.72	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 14 / 10MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1576	-56.21	-42.15	-14.06	-65.94	-61.55	0.90	8.39	H
	2368	-52.37	-13	-39.37	-66.51	-59.61	1.12	10.52	H
	3152	-55.21	-13	-42.21	-71.33	-63.43	1.30	11.66	H
									H
									H
									H
									H
	1576	-54.34	-42.15	-12.19	-63.54	-59.68	0.90	8.39	V
	2368	-51.44	-13	-38.44	-65.35	-58.68	1.12	10.52	V
	3152	-53.88	-13	-40.88	-70.42	-62.10	1.30	11.66	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.