

Report No.: SEWA2309000114RG01

Rev.:

75 of 87 Page:

Field Strength of Spurious Radiation

Test Band = LTE Band 66_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO	Frequency	Reading	Factor	V [[4] [] (==]	Level	Limit	Margin	Height	Angle	Delevity			
NO.	[MHz]	[dBµV]	[dB]	AF[dB/m]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3404.1800	42.75	-46.28	29.43	-69.36	-13.00	56.36	211	25	Horizontal			
2	5106.2700	40.88	-45.36	32.94	-66.81	-13.00	53.81	132	252	Horizontal			
3	6808.3600	40.36	-44.16	35.85	-63.21	-13.00	50.21	154	283	Horizontal			
4	8510.4500	38.23	-41.59	37.56	-61.06	-13.00	48.06	148	207	Horizontal			
5	10212.5400	34.24	-39.45	38.81	-61.65	-13.00	48.65	197	60	Horizontal			
6	11914.6300	31.33	-37.18	38.88	-62.23	-13.00	49.23	183	29	Horizontal			

Final	Final Data List												
NO.	Frequency	Reading	Factor	Λ Γ[dD/ma]	Level	Limit	Margin	Height	Angle	Delevity			
NO.	[MHz]	[dBµV]	[dB]	AF[dB/m]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3404.1800	42.76	-46.28	29.43	-69.35	-13.00	56.35	233	357	Vertical			
2	5106.2700	41.32	-45.36	32.94	-66.37	-13.00	53.37	215	359	Vertical			
3	6808.3600	41.00	-44.16	35.85	-62.57	-13.00	49.57	145	352	Vertical			
4	8510.4500	37.85	-41.59	37.56	-61.44	-13.00	48.44	196	4	Vertical			
5	10212.5400	34.33	-39.45	38.81	-61.56	-13.00	48.56	258	59	Vertical			
6	11914.6300	31.22	-37.18	38.88	-62.34	-13.00	49.34	142	210	Vertical			





Report No.: SEWA2309000114RG01

Rev.:

76 of 87 Page:

Test Band = LTE Band 66_ TM1 **Test Channel = Mid Channel**

Final	Final Data List												
NO	Frequency	Reading	Factor	Λ Γ[dD/ma]	Level	Limit	Margin	Height	Angle	Delevity			
NO.	[MHz]	[dBµV]	[dB]	AF[dB/m]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3454.1800	42.70	-46.27	29.48	-69.35	-13.00	56.35	222	359	Horizontal			
2	5181.2700	41.22	-45.30	32.98	-66.36	-13.00	53.36	302	350	Horizontal			
3	6908.3600	40.39	-44.05	35.97	-62.95	-13.00	49.95	159	296	Horizontal			
4	8635.4500	37.85	-41.46	37.81	-61.06	-13.00	48.06	192	29	Horizontal			
5	10362.5400	34.42	-39.04	38.85	-61.03	-13.00	48.03	184	43	Horizontal			
6	12089.6300	32.45	-37.37	39.04	-61.14	-13.00	48.14	170	360	Horizontal			

Final	Final Data List												
NO.	Frequency	Reading	Factor	A E[dD/m]	Level	Limit	Margin	Height	Angle	Delority			
NO.	[MHz]	[dBµV]	[dB]	AF[dB/m]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3454.1800	42.47	-46.27	29.48	-69.58	-13.00	56.58	298	104	Vertical			
2	5181.2700	40.68	-45.30	32.98	-66.90	-13.00	53.90	122	313	Vertical			
3	6908.3600	39.31	-44.05	35.97	-64.03	-13.00	51.03	263	29	Vertical			
4	8635.4500	37.41	-41.46	37.81	-61.50	-13.00	48.50	210	60	Vertical			
5	10362.5400	33.99	-39.04	38.85	-61.46	-13.00	48.46	140	330	Vertical			
6	12089.6300	31.23	-37.37	39.04	-62.36	-13.00	49.36	172	283	Vertical			





Report No.: SEWA2309000114RG01

Rev.:

77 of 87 Page:

Test Band = LTE Band 66_ TM1 **Test Channel = High Channel**

Final	Final Data List												
NO	Frequency	Reading	Factor	V [[4] [/==]	Level	Limit	Margin	Height	Angle	Delevity			
NO.	[MHz]	[dBµV]	[dB]	AF[dB/m]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3504.1800	43.24	-46.25	29.52	-68.75	-13.00	55.75	263	4	Horizontal			
2	5256.2700	41.16	-45.17	32.94	-66.34	-13.00	53.34	215	329	Horizontal			
3	7008.3600	40.21	-43.61	36.10	-62.56	-13.00	49.56	148	360	Horizontal			
4	8760.4500	37.37	-41.42	38.02	-61.30	-13.00	48.30	188	329	Horizontal			
5	10512.5400	34.28	-38.76	38.97	-60.77	-13.00	47.77	192	4	Horizontal			
6	12262.6300	32.68	-37.44	39.11	-60.91	-13.00	47.91	200	222	Horizontal			

Final	Final Data List												
NO.	Frequency	Reading	Factor	Λ Γ[dD/m]	Level	Limit	Margin	Height	Angle	Delevity			
NO.	[MHz]	[dBµV]	[dB]	AF[dB/m]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	3504.1800	42.64	-46.25	29.52	-69.35	-13.00	56.35	245	88	Vertical			
2	5256.2700	41.49	-45.17	32.94	-66.01	-13.00	53.01	133	344	Vertical			
3	7008.3600	40.60	-43.61	36.10	-62.17	-13.00	49.17	261	134	Vertical			
4	8760.4500	37.81	-41.42	38.02	-60.86	-13.00	47.86	100	286	Vertical			
5	10512.5400	34.05	-38.76	38.97	-61.00	-13.00	48.00	184	74	Vertical			
6	12262.6300	31.49	-37.44	39.11	-62.10	-13.00	49.10	199	120	Vertical			





Report No.: SEWA2309000114RG01

Rev.: 01

Page: 78 of 87

Test Band = UL CA Band 2A-66A_ TM1 Test Channel = Low Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3404.18	51.32	-111.74	-60.42	-13.00	47.42	263	264	Horizontal				
2	3702.18	49.18	-111.07	-61.89	-13.00	48.89	241	331	Horizontal				
3	5106.27	49.24	-106.94	-57.70	-13.00	44.70	176	314	Horizontal				
4	5553.27	48.53	-106.36	-57.83	-13.00	44.83	265	314	Horizontal				
5	6808.36	48.03	-101.99	-53.96	-13.00	40.96	284	247	Horizontal				
6	7404.36	47.75	-100.78	-53.03	-13.00	40.03	178	264	Horizontal				

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3404.18	50.13	-111.74	-61.61	-13.00	48.61	263	49	Vertical				
2	3702.18	49.80	-111.07	-61.27	-13.00	48.27	365	360	Vertical				
3	5106.27	48.83	-106.94	-58.11	-13.00	45.11	251	215	Vertical				
4	5553.27	49.11	-106.36	-57.25	-13.00	44.25	174	231	Vertical				
5	6808.36	49.04	-101.99	-52.95	-13.00	39.95	189	280	Vertical				
6	7404.36	49.35	-100.78	-51.43	-13.00	38.43	265	81	Vertical				





Report No.: SEWA2309000114RG01

Rev.: 79 of 87 Page:

Test Band = UL CA Band 2A-66A_ TM1 **Test Channel = Mid Channel**

Final	Data List								
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Polarity
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polatily
1	3454.18	50.78	-111.64	-60.86	-13.00	47.86	263	63	Horizontal
2	3742.18	52.53	-110.86	-58.33	-13.00	45.33	251	3	Horizontal
3	5181.27	48.82	-106.84	-58.02	-13.00	45.02	174	360	Horizontal
4	5613.27	50.69	-106.14	-55.45	-13.00	42.45	262	360	Horizontal
5	6908.36	47.76	-101.69	-53.93	-13.00	40.93	284	352	Horizontal
6	7484.36	47.29	-100.43	-53.14	-13.00	40.14	176	130	Horizontal

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	3454.18	50.91	-111.64	-60.73	-13.00	47.73	214	360	Vertical				
2	3742.18	50.57	-110.86	-60.29	-13.00	47.29	175	262	Vertical				
3	5181.27	50.57	-106.84	-56.27	-13.00	43.27	265	181	Vertical				
4	5613.27	50.34	-106.14	-55.80	-13.00	42.80	251	358	Vertical				
5	6908.36	47.73	-101.69	-53.96	-13.00	40.96	148	359	Vertical				
6	7484.36	48.45	-100.43	-51.98	-13.00	38.98	188	360	Vertical				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, Gregory or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are referred for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, **Cercibil CARD Procheck/Pages com**

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86–512) 62992980 www.sgsgroup.com.cn t (86–512) 62992980 sgs.china@sgs.com



Report No.: SEWA2309000114RG01

Rev.: 01 Page: 80 of 87

Test Band = UL CA Band 2A-66A_ TM1 Test Channel = High Channel

Final	Data List								
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity
1	3504.18	50.80	-111.52	-60.72	-13.00	47.72	263	211	Horizontal
2	3782.18	54.05	-110.66	-56.61	-13.00	43.61	241	163	Horizontal
3	5256.27	51.16	-106.73	-55.57	-13.00	42.57	176	99	Horizontal
4	5673.27	51.10	-105.88	-54.78	-13.00	41.78	262	99	Horizontal
5	7008.36	48.90	-101.63	-52.73	-13.00	39.73	362	163	Horizontal
6	7564.36	48.78	-100.01	-51.23	-13.00	38.23	241	194	Horizontal

Final	Data List								
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity
1	3504.18	50.75	-111.52	-60.77	-13.00	47.77	265	360	Vertical
2	3782.18	52.54	-110.66	-58.12	-13.00	45.12	241	162	Vertical
3	5256.27	50.45	-106.73	-56.28	-13.00	43.28	176	98	Vertical
4	5673.27	49.14	-105.88	-56.74	-13.00	43.74	294	16	Vertical
5	7008.36	47.83	-101.63	-53.80	-13.00	40.80	186	351	Vertical
6	7564.36	49.49	-100.01	-50.52	-13.00	37.52	247	340	Vertical





Report No.: SEWA2309000114RG01

81 of 87

Rev.: 01

Page:

Test Band = UL CA Band 5A-66A_ TM1
Test Channel = Low Channel

Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1649.18	41.68	-94.97	-53.29	-13.00	40.29	262	11	Horizontal			
2	2473.77	41.00	-91.42	-50.42	-13.00	37.42	251	17	Horizontal			
3	3298.36	50.56	-111.65	-61.09	-13.00	48.09	174	276	Horizontal			
4	3404.18	51.80	-111.74	-59.94	-13.00	46.94	186	309	Horizontal			
5	5106.27	49.19	-106.94	-57.75	-13.00	44.75	102	359	Horizontal			
6	6808.36	50.28	-101.99	-51.71	-13.00	38.71	109	357	Horizontal			

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1649.18	42.50	-94.97	-52.47	-13.00	39.47	263	309	Vertical			
2	2473.77	41.21	-91.42	-50.21	-13.00	37.21	241	109	Vertical			
3	3298.36	51.15	-111.65	-60.50	-13.00	47.50	177	163	Vertical			
4	3404.18	51.90	-111.74	-59.84	-13.00	46.84	156	359	Vertical			
5	5106.27	49.45	-106.94	-57.49	-13.00	44.49	366	358	Vertical			
6	6808.36	50.59	-101.99	-51.40	-13.00	38.40	354	360	Vertical			





Report No.: SEWA2309000114RG01

Rev.: 01 Page: 82 of 87

Test Band = UL CA Band 5A-66A_ TM1 Test Channel = Mid Channel

Final	Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Polarity				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	1664.18	40.77	-94.93	-54.16	-13.00	41.16	162	224	Horizontal				
2	2496.27	40.91	-91.26	-50.35	-13.00	37.35	241	172	Horizontal				
3	3328.36	51.64	-111.69	-60.05	-13.00	47.05	176	197	Horizontal				
4	3454.18	52.29	-111.64	-59.35	-13.00	46.35	284	248	Horizontal				
5	5181.27	49.19	-106.84	-57.65	-13.00	44.65	196	360	Horizontal				
6	6908.36	47.07	-101.69	-54.62	-13.00	41.62	254	248	Horizontal				

Final	Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	1664.18	41.84	-94.93	-53.09	-13.00	40.09	263	164	Vertical				
2	2496.27	40.95	-91.26	-50.31	-13.00	37.31	241	80	Vertical				
3	3328.36	51.47	-111.69	-60.22	-13.00	47.22	176	3	Vertical				
4	3454.18	51.15	-111.64	-60.49	-13.00	47.49	284	358	Vertical				
5	5181.27	49.39	-106.84	-57.45	-13.00	44.45	175	230	Vertical				
6	6908.36	48.11	-101.69	-53.58	-13.00	40.58	265	360	Vertical				





Report No.: SEWA2309000114RG01

Rev.: 01 Page: 83 of 87

Test Band = UL CA Band 5A-66A_ TM1 Test Channel = Mid Channel

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1679.18	41.00	-94.89	-53.89	-13.00	40.89	263	108	Horizontal			
2	2518.77	40.81	-91.20	-50.39	-13.00	37.39	251	2	Horizontal			
3	3358.36	51.52	-111.71	-60.19	-13.00	47.19	174	358	Horizontal			
4	3504.18	50.29	-111.52	-61.23	-13.00	48.23	186	358	Horizontal			
5	5256.27	51.52	-106.73	-55.21	-13.00	42.21	264	360	Horizontal			
6	7008.36	47.79	-101.63	-53.84	-13.00	40.84	188	245	Horizontal			

Final	Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	1679.18	40.71	-94.89	-54.18	-13.00	41.18	263	131	Vertical				
2	2518.77	41.34	-91.20	-49.86	-13.00	36.86	241	33	Vertical				
3	3358.36	50.91	-111.71	-60.80	-13.00	47.80	178	111	Vertical				
4	3504.18	51.12	-111.52	-60.40	-13.00	47.40	264	291	Vertical				
5	5256.27	51.85	-106.73	-54.88	-13.00	41.88	265	360	Vertical				
6	7008.36	48.22	-101.63	-53.41	-13.00	40.41	214	47	Vertical				





Report No.: SEWA2309000114RG01

Rev.: 01

Page: 84 of 87

Test Band = UL CA Band 13A-66A_ TM1 Test Channel = Low Channel

Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1559.68	41.20	-95.17	-53.97	-13.00	40.97	263	282	Horizontal			
2	2332.5	46.79	-92.24	-45.45	-13.00	32.45	163	133	Horizontal			
3	3119.36	51.45	-111.58	-60.13	-13.00	47.13	176	0	Horizontal			
4	3454.18	50.06	-111.64	-61.58	-13.00	48.58	284	295	Horizontal			
5	5181.27	49.76	-106.84	-57.08	-13.00	44.08	175	131	Horizontal			
6	6908.36	49.48	-101.69	-52.21	-13.00	39.21	268	131	Horizontal			

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1559.68	40.11	-95.17	-55.06	-13.00	42.06	263	3	Vertical			
2	2339.52	40.96	-92.21	-51.25	-13.00	38.25	251	360	Vertical			
3	3119.36	50.61	-111.58	-60.97	-13.00	47.97	174	10	Vertical			
4	3454.18	51.57	-111.64	-60.07	-13.00	47.07	162	249	Vertical			
5	5181.27	49.37	-106.84	-57.47	-13.00	44.47	284	357	Vertical			
6	6908.36	48.14	-101.69	-53.55	-13.00	40.55	186	297	Vertical			





Report No.: SEWA2309000114RG01

Rev.: 01

Page: 85 of 87

Test Band = UL CA Band 13A-66A_ TM1 Test Channel = Mid Channel

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1559.68	41.58	-95.17	-53.59	-13.00	40.59	251	358	Horizontal			
2	2339.52	47.53	-92.21	-44.68	-13.00	31.68	142	145	Horizontal			
3	3119.36	52.79	-111.58	-58.79	-13.00	45.79	263	248	Horizontal			
4	3454.18	49.69	-111.64	-61.95	-13.00	48.95	284	181	Horizontal			
5	5181.27	48.97	-106.84	-57.87	-13.00	44.87	176	115	Horizontal			
6	6908.36	47.79	-101.69	-53.90	-13.00	40.90	244	198	Horizontal			

Final	Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	1559.68	41.06	-95.17	-54.11	-13.00	41.11	263	40	Vertical				
2	2339.52	40.70	-92.21	-51.51	-13.00	38.51	241	353	Vertical				
3	3119.36	51.23	-111.58	-60.35	-13.00	47.35	176	312	Vertical				
4	3454.18	50.57	-111.64	-61.07	-13.00	48.07	284	328	Vertical				
5	5181.27	50.71	-106.84	-56.13	-13.00	43.13	188	162	Vertical				
6	6908.36	48.45	-101.69	-53.24	-13.00	40.24	263	296	Vertical				





Report No.: SEWA2309000114RG01

Rev.: Page: 86 of 87

Test Band = UL CA Band 13A-66A_ TM1 **Test Channel = High Channel**

Final Data List												
NO.	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority			
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity			
1	1564.68	39.98	-95.16	-55.18	-13.00	42.18	263	322	Horizontal			
2	2347	50.56	-92.18	-41.62	-13.00	28.62	241	133	Horizontal			
3	3129.36	51.30	-111.55	-60.25	-13.00	47.25	176	198	Horizontal			
4	3504.18	50.12	-111.52	-61.40	-13.00	48.40	284	0	Horizontal			
5	5256.27	50.67	-106.73	-56.06	-13.00	43.06	169	198	Horizontal			
6	7008.36	47.92	-101.63	-53.71	-13.00	40.71	362	357	Horizontal			

Final	Final Data List												
NO	Frequency	Reading	Factor	Level	Limit	Margin	Height	Angle	Dolority				
NO.	[MHz]	[dBµV]	[dB]	[dBm]	[dBm]	[dB]	[cm]	[°]	Polarity				
1	1564.68	41.40	-95.16	-53.76	-13.00	40.76	263	324	Vertical				
2	2347.02	40.69	-92.18	-51.49	-13.00	38.49	241	269	Vertical				
3	3129.36	50.70	-111.55	-60.85	-13.00	47.85	176	229	Vertical				
4	3504.18	50.51	-111.52	-61.01	-13.00	48.01	284	0	Vertical				
5	5256.27	49.63	-106.73	-57.10	-13.00	44.10	196	2	Vertical				
6	7008.36	47.55	-101.63	-54.08	-13.00	41.08	266	7	Vertical				

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & AMP. The basic equation with a sample calculation is as follows:

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier (dB)

Level = Reading Level + AF + Factor -95.26

Margin = Limit – Level



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-C



Report No.: SEWA2309000114RG01

Rev.: 01

Page: 87 of 87

Frequency Stability

Test Result

Band	Bandwidth	Modulation	Channel	RB Configure	Voltag e [Vdc]	Temperatur e (°C)	Deviation (Hz)	Deviation (ppm)	Verdic t
Band66	20MHz	QPSK	132322	100RB#0	VL	NT	-0.70	-0.000401	PASS
Band66	20MHz	QPSK	132322	100RB#0	VN	NT	-0.40	-0.000229	PASS
Band66	20MHz	QPSK	132322	100RB#0	VH	NT	-0.70	-0.000401	PASS

Band	Bandwidth	Modulation	Channel	RB Configure	Voltag e [Vdc]	Temperatur e (°C)	Deviation (Hz)	Deviation (ppm)	Verdic t
Band66	20MHz	QPSK	132322	100RB#0	NV	-30	-1.30	-0.000745	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	-20	-0.70	-0.000401	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	-10	-0.60	-0.000344	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	0	-0.70	-0.000401	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	10	0.70	0.000401	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	20	-2.40	-0.001375	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	30	-1.80	-0.001032	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	40	0.20	0.000115	PASS
Band66	20MHz	QPSK	132322	100RB#0	NV	50	-0.70	-0.000401	PASS

---End of Attachment---

