


TEST REPORT

Application No.: BTEK240726008AE
Applicant: Shenzhen Sincodynamic Technology Co.,Ltd
Address of Applicant: No.1 Changguang Industrial Park, No.40 Aoxin Road, Baoan Community, Yuanshan St., Henggang, Shenzhen, 518115 China
Manufacturer: Shenzhen Sincodynamic Technology Co.,Ltd
Address of Manufacturer: No.1 Changguang Industrial Park, No.40 Aoxin Road, Baoan Community, Yuanshan St., Henggang, Shenzhen, 518115 China
Equipment Under Test (EUT):
EUT Name: ANC Bluetooth Headphone
Test Model.: BSBTH30BK
Adding Model(s): BSBTH30BL,BSBTH30BKWH,BSSONICHOPBK,BSSONICHOPNV, BSSONICHOPWH,P3-ANC
Trade Mark: /
FCC ID: 2AJ08-BSBTH30
Standard(s) : 47 CFR Part 2 Subpart J Section 2.1093
447498 D01 General RF Exposure Guidance v06
Date of Receipt: 2024-07-26
Date of Test: 2024-07-27 to 2024-08-07
Date of Issue: 2024-08-08

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Lion Cai/ Approved & Authorized
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
V0		2024-08-08		Original

Authorized for issue by:				
		Zora . Huang		
		Zora Huang/Project Engineer		
		June Li		
		June Li/Reviewer		

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



2 Contents

	Page
1 Cover Page.....	1
2 Contents	3
3 General Information	4
3.1 Details of E.U.T.	4
3.2 Description of Support Units	4
3.3 Test Location	4
3.4 Deviation from Standards	4
3.5 Abnormalities from Standard Conditions	4
4 Test Requirement	5
4.1 Assessment Result	5



General Information

3.1 Details of E.U.T.

Power supply:	Input:5V $\pm$ 1A Battery:3.7V $\pm$ 200mAh 0.74wh
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.3
Modulation Type:	GFSK, π /4DQPSK,8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Antenna Type:	PCB Antenna
Antenna Gain:	-0.58 dBi
Sample No.:	BTEK240726008AE-01
Remark: The information in this section is provided by the applicant or manufacturer, BANTEK is not liable to the accuracy, suitability, reliability or/and integrity of the information.	

Model No.: BSBTH30BK,BSBTH30BL,BSBTH30BKWH,BSSONICHOPBK,BSSONICHOPNV,BSSONICHOPWH,P3-ANC

Only the model Sound BSBTH30BK was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions of other models are identical for the above models, with only difference on Model No.

3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
/	/	/	/

3.3 Test Location

All tests were performed at:

Shenzhen BANTEK Testing Co., Ltd.,

A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518103

Tel:0755-2334 4200 Fax: 0755-2334 4200

FCC Registration Number: 264293

Designation Number: CN1356

No tests were sub-contracted.

3.4 Deviation from Standards

None

3.5 Abnormalities from Standard Conditions

None



4 Test Requirement

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(b)

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

4.1 Assessment Result

☒ Passed ☐ Not Applicable

Type	Frequency (MHz)	Conducted Power (dBm)	Maximum Tune-up (dBm)	Calculating data	Limit	Result
GFSK	2402	3.72	4.00	0.0007	3.0	Pass
$\pi/4$ DQPSK	2402	5.94	6.00	0.0010	3.0	Pass
8DPSK	2402	6.37	6.50	0.0012	3.0	Pass

Note: The exposure evaluation safety distance is 5mm.

- End of the Report -

