

FCC ID : 2AJOF-ATOM500-TX

1. RF EXPOSURE

1.1. The Requirement

System operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See Section 15.247 and Section 15.407

1.2. Limit For Maximum Permissible Exposure (MPE)

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time $ E ^2, H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

F = frequency in MHz, * Plane-wave equivalent power density

1.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the antenna is 2.5 dBi, the RF power density can be obtained.

1.4.TEST RESULTS

Maximum measured transmitter power

Directional gain= $2.5+10\log 2=5.51$

For 5G WIFI

The test was performed with 802.11A						
Channel	Frequency (MHz)	Ave output power ANT 1(dBm)	Ave output power ANT 2 (dBm)	Ave output power ANT 1(mW)	Ave output power ANT 2 (mW)	Limits dBm / W
Low	5180	15.19	15.14	33.04	32.66	24 dBm/0.25 W
High	5240	15.43	15.67	34.91	36.90	24 dBm/0.25 W
Low	5745	12.97	12.94	19.82	19.68	30 dBm / 1 W
High	5825	11.62	11.22	14.52	13.24	30 dBm / 1 W

The test was performed with 802.11N20						
Channel	Frequency (MHz)	Ave output power ANT 1(dBm)	Ave output power ANT 2 (dBm)	Ave output Total power (dBm)	Ave output Total power (mW)	Limits dBm
Low	5180	16.55	16.66	19.62	91.53	24 dBm
High	5240	16.83	16.96	19.91	97.85	24 dBm
Low	5745	12.57	12.84	15.72	37.30	30 dBm
High	5825	11.75	11.66	14.72	29.62	30 dBm

Operation Mode	Channel Number	Channel Frequency (MHz)	Antenna Gain (Numeric)	Power Density At 20cm (mW/cm ²)			Power Density Limit (mW/cm ²)	Test Results
				Ant 1	Ant 2	Sum		
802.11a	38	5180	1.778	0.011	0.011	--	1.000	Pass
	46	5240	1.778	0.012	0.013	--	1.000	Pass
	149	5745	1.778	0.007	0.007	--	1.000	Pass
	165	5825	1.778	0.006	0.004	--	1.000	Pass
802.11n 20M	38	5180	1.778	0.016	0.017	0.033	1.000	Pass
	46	5240	1.778	0.017	0.018	0.035	1.000	Pass
	149	5745	1.778	0.007	0.007	0.014	1.000	Pass
	165	5825	1.778	0.006	0.006	0.012	1.000	Pass

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.

1.5.FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, Human proximity to the antenna shall not be less than 20cm(8 inches) during normal operation. Proposed RF exposure safety information to include in User's Manual.